

CPC**COOPERATIVE PATENT CLASSIFICATION****F23D****BURNERS** (generating combustion products of high pressure or high velocity [F23R](#))**Guidance heading:****F23D 1/00****Burners for combustion of pulverulent fuel** (disposition of burners [F23C](#))**F23D 1/005**

- . {burning a mixture of pulverulent fuel delivered as a slurry, i.e. comprising a carrying liquid (preparing slurries [F23K 1/02](#)) }

F23D 1/02

- . Vortex burners, e.g. for cyclone-type combustion apparatus

F23D 1/04

- . Burners producing cylindrical flames without centrifugal action

F23D 1/06

- . Burners producing sheet flames

Guidance heading: Combustion of a liquid**F23D 3/00****Burner using capillary action****F23D 3/02**

- . Wick burners

F23D 3/04

- .. with flame spreaders ([F23D 3/12](#) takes precedence)

F23D 3/06

- .. Inverted wick burners, e.g. for illumination

F23D 3/08

- .. characterised by shape, construction, or material, of wick

F23D 3/10

- .. Blue-flame burners

F23D 3/12

- ... with flame spreaders

F23D 3/14

- ... with mixing of air and fuel vapour in a chamber before the flame

F23D 3/16

- .. using candles ([candles per se C11C](#))

F23D 3/18

- .. Details of wick burners

F23D 3/20

- ... Flame spreaders

F23D 3/22

- ... Devices for mixing evaporated fuel with air

F23D 3/24

- ... Carriers for wicks

F23D 3/26

- Safety devices thereon

F23D 3/28

- ... Wick-adjusting devices

F23D 3/30

- directly engaging with the wick

F23D 3/32

- engaging with a tube carrying the wick

F23D 3/34

- Wick stop devices; Wick-fixing devices

F23D 3/36

- ... Devices for trimming wicks

F23D 3/38

- ... Devices for replacement of wicks

F23D 3/40

- . the capillary action taking place in one or more rigid porous bodies

F23D 5/00**Burners in which liquid fuel evaporates in the combustion space, with or without**

chemical conversion of evaporated fuel

- F23D 5/02 . the liquid forming a pool, e.g. bowl-type evaporators, dish-type evaporators
- F23D 5/04 . . Pot-type evaporators, i.e. using a partially-enclosed combustion space
- F23D 5/045 . . . {with forced draft }
- F23D 5/06 . the liquid forming a film on one or more plane or convex surfaces
- F23D 5/08 . . on cascaded surfaces
- F23D 5/10 . . on grids
- F23D 5/12 . Details
- F23D 5/123 . . {Inserts promoting evaporation }
- F23D 5/126 . . {Catalytic elements }
- F23D 5/14 . . Maintaining predetermined amount of fuel in evaporator
- F23D 5/16 . . Safety devices
- F23D 5/18 . . Preheating devices

F23D 7/00 Burners in which drops of liquid fuel impinge on a surface**F23D 9/00 Burners in which a stream of liquid fuel impinges intermittently on a hot surface****F23D 11/00 Burners using a direct spraying action of liquid droplets or vaporised liquid into the combustion space (spraying in general [B05B](#) , [B05D](#))**

- F23D 11/001 . {spraying nozzle combined with forced draft fan in one unit (nozzles per se [F23D 11/38](#)) }
- F23D 11/002 . {spraying nozzle arranged within furnace openings (refractory bricks or blocks specially shaped for burner openings [F23M 5/025](#)) }
- F23D 11/004 . . {for producing radiant heat }
- F23D 11/005 . {with combinations of different spraying or vaporising means }
- F23D 11/007 . . {combination of means covered by sub-groups [F23D 11/10](#) and [F23D 11/24](#) }
- F23D 11/008 . . {combination of means covered by sub-groups [F23D 5/00](#) and [F23D 11/00](#) }
- F23D 11/02 . the combustion space being a chamber substantially at atmospheric pressure
- F23D 11/04 . the spraying action being obtained by centrifugal action
- F23D 11/06 . . using a horizontal shaft
- F23D 11/08 . . using a vertical shaft
- F23D 11/10 . the spraying being induced by a gaseous medium, e.g. water vapour
- F23D 11/101 . . {medium and fuel meeting before the burner outlet }
- F23D 11/102 . . . {in an internal mixing chamber }

- F23D 11/103 {with means creating a swirl inside the mixing chamber }
- F23D 11/104 . . . {intersecting at a sharp angle, e.g. Y-jet atomiser }
- F23D 11/105 . . . {at least one of the fluids being submitted to a swirling motion }
- F23D 11/106 . . {medium and fuel meeting at the burner outlet }
- F23D 11/107 . . . {at least one of both being subjected to a swirling motion }
- F23D 11/108 . . {medium and fuel intersecting downstream of the burner outlet }
- F23D 11/12 . . characterised by the shape or arrangement of the outlets from the nozzle
- F23D 11/14 . . . with a single outlet, e.g. slit
- F23D 11/16 . . in which an emulsion of water and fuel is sprayed
- F23D 11/18 . . the gaseous medium being water vapour generated at the nozzle
- F23D 11/20 . . . the water vapour being superheated
- F23D 11/22 . . the gaseous medium being vaporised fuel, e.g. for a soldering lamp, {or other gaseous fuel }

- F23D 11/24 . by pressurisation of the fuel before a nozzle through which it is sprayed by a substantial pressure reduction into a space
- F23D 11/26 . . with provision for varying the rate at which the fuel is sprayed
- F23D 11/28 . . . with flow-back of fuel at the burner, e.g. using by-pass
- F23D 11/30 . . . with return feed of uncombusted sprayed fuel to reservoir

- F23D 11/32 . by electrostatic means

- F23D 11/34 . by ultrasonic means {or other kinds of vibrations }
- F23D 11/345 . . {with vibrating atomiser surfaces }

- F23D 11/36 . Details {e.g. burner cooling means, noise reduction means }
- F23D 11/38 . . Nozzles (nozzles in general [B05B](#)) ; Cleaning devices therefor
- F23D 11/383 . . . {with swirl means }
- F23D 11/386 . . . {Nozzle cleaning }
- F23D 11/40 . . Mixing tubes [or chambers]; Burner heads
- F23D 11/402 . . . {Mixing chambers downstream of the nozzle }
- F23D 11/404 . . . {Flame tubes (not forming part of the burner [F23M 9/06](#)) }
- F23D 11/406 . . . {Flame stabilising means, e.g. flame holders }
- F23D 11/408 . . . {Flow influencing devices in the air tube }
- F23D 11/42 . . Starting devices ([igniting F23Q](#))
- F23D 11/44 . . Preheating devices; Vaporising devices ([vaporising devices per se F23K 5/22](#))
- F23D 11/441 . . . { Vaporizing devices incorporated with burners }
- F23D 11/443 {heated by the main burner flame }
- F23D 11/445 {the flame and the vaporiser not coming into direct contact }
- F23D 11/446 {heated by an auxiliary flame }
- F23D 11/448 {heated by electrical means }
- F23D 11/46 . . Devices on the vaporiser for controlling the feeding of the fuel

- F23D 14/00** **Burners for combustion of a gas, e.g. of a gas stored under pressure as a liquid**

- F23D 14/02 . Premix gas burners, i.e. in which gaseous fuel is mixed with combustion air upstream of the combustion zone
- F23D 14/04 . . induction type, e.g. Bunsen burner, ({atmospheric or aerated gas burner })
- F23D 14/045 . . . {with a plurality of burner bars assembled together, e.g. in a grid-like arrangement }
- F23D 14/06 . . . with radial outlets at the burner head
- F23D 14/065 {with injector axis inclined to the burner head axis }
- F23D 14/08 . . . with axial outlets at the burner head
- F23D 14/085 {with injector axis inclined to the burner head axis }
- F23D 14/10 . . . with elongated tubular burner head
- F23D 14/105 [N. with injector axis parallel to the burner head axis]

- F23D 14/12 . Radiant burners
- F23D 14/125 . . {heating a wall surface to incandescence }
- F23D 14/14 . . using screens or perforated plates
- F23D 14/145 . . . {the burner plate being a screen }
- F23D 14/16 . . using permeable blocks
- F23D 14/18 . . using catalysis for flameless combustion

- F23D 14/20 . Non-premix gas burners, i.e. in which gaseous fuel is mixed with combustion air on arrival at the combustion zone ([F23D 14/30 to F23D 14/44 take precedence](#))
- F23D 14/22 . . with separate air and gas feed ducts, e.g. with ducts running parallel or crossing each other
- F23D 14/24 . . . at least one of the fluids being submitted to a swirling motion

- F23D 14/26 . with provision for a retention flame ([pilot flame igniters F23Q 9/00](#))

- F23D 14/28 . in association with a gaseous fuel source, e.g. acetylene generator, or a container for liquefied gas

- F23D 14/30 . Inverted burners, e.g. for illumination

- F23D 14/32 . using a mixture of gaseous fuel and pure oxygen or oxygen-enriched air ([F23D 14/38 takes precedence](#))

- F23D 14/34 . Burners specially adapted for use with means for pressurising the gaseous fuel or the combustion air ([F23D 14/38 takes precedence](#))
- F23D 14/36 . . in which the compressor and burner form a single unit

- F23D 14/38 . Torches, e.g. for cutting, brazing, welding or heating ({ nozzles for torches [F23D 14/52](#) })
- F23D 14/40 . . for welding ([F23D 14/44 takes precedence](#))
- F23D 14/42 . . for cutting ([F23D 14/44 takes precedence](#))
- F23D 14/44 . . for use under water

- F23D 14/46 . Details {e.g. noise reduction means }
- F23D 14/465 . . {for torches ([F23D 14/52 takes precedence](#)) }

- F23D 14/48 . . . Nozzles ({injectors for mixing devices [F23D 14/64](#) }; for spraying or coating [B05B](#))
- F23D 14/50 . . . Cleaning devices therefor
- F23D 14/52 . . . for torches; for blow-pipes
- F23D 14/54 for cutting or welding metal
- F23D 14/56 . . . for spreading the flame over an area, e.g. for desurfacing of solid material, for surface hardening, for heating workpieces, (scarfing by applying flames [B23K 7/00](#))
- F23D 14/58 . . . characterised by the shape or arrangement of the outlet or outlets from the nozzle, e.g. of annular configuration
- F23D 14/583 {of elongated shape, e.g. slits }
- F23D 14/586 {formed by a set of sheets, strips, ribbons or the like }
- F23D 14/60 . . . Devices for simultaneous control of gas and combustion air (regulation of combustion in general [F23N](#))
- F23D 14/62 . . . Mixing devices; Mixing tubes
- F23D 14/64 . . . with injectors
- F23D 14/66 . . . Preheating the combustion air or gas
- F23D 14/68 . . . Treating the combustion air or gas, e.g. by filtering, by moistening (in general [B01](#))
- F23D 14/70 . . . Baffles or like flow-disturbing devices
- F23D 14/72 . . . Safety devices, e.g. operative in case of failure of gas supply (protection or supervision of pipe-line systems [F17D 5/00](#))
- F23D 14/725 . . . {Protection against flame failure by using flame detection devices (pilot flame igniters with interlock with main fuel supply [F23Q 9/08](#)) }
- F23D 14/74 . . . Preventing flame lift-off ([F23D 14/70](#) takes precedence)
- F23D 14/76 . . . Protecting flame and burner parts
- F23D 14/78 . . . Cooling burner parts
- F23D 14/80 . . . Selection of a non-toxic gas
- F23D 14/82 . . . Preventing flashback or blowback ([F23D 14/70](#) takes precedence; {by use of a retention flame [F23D 14/26](#) }; in gas feed lines [A62C 4/02](#))
- F23D 14/825 {using valves }
- F23D 14/84 . . . Flame spreading or otherwise shaping ([F23D 14/70](#) takes precedence)

Guidance heading: Other burners

F23D 17/00 Burners for combustion conjointly or alternatively of gaseous or liquid or pulverulent fuel

- F23D 17/002 . {gaseous or liquid fuel }
- F23D 17/005 . {gaseous or pulverulent fuel }
- F23D 17/007 . {liquid or pulverulent fuel }

F23D 21/00 Burners not otherwise provided for { Note : combinations of spraying or vaporising means covered by sub-groups [F23D 5/00](#) and [F23D 21/00](#) are classified in [F23D 11/008](#) }

- F23D 21/005 . { specially adapted for use in particular heating operations }

F23D 23/00 **Assemblies of two or more burners** (gas burners with provision for a retention flame [F23D 14/26](#); disposition of burners [F23C](#) ; for industrial furnaces [F27](#))

F23D 99/00 **Subject matter not provided for in other groups of this subclass**

- F23D 99/003 . { specially adapted for use in particular heating operations }
- F23D 99/006 .. { for heating liquids, e.g. for vaporising, for concentrating }

Guidance heading:

F23D 2200/00 **Burners for fluid fuel**

Guidance heading:

F23D 2201/00 **Burners adapted for particulate solid or pulverulent fuels**

- F23D 2201/10 . Nozzle tips
- F23D 2201/101 .. tiltable
- F23D 2201/20 . Fuel flow guiding devices
- F23D 2201/30 . Wear protection

F23D 2202/00 **Liquid fuel burners**

F23D 2203/00 **Gaseous fuel burners**

- F23D 2203/002 . Radiant burner mixing tubes
- F23D 2203/005 . Radiant burner heads
- F23D 2203/007 . Mixing tubes, air supply regulation
- F23D 2203/10 . Flame diffusing means
- F23D 2203/101 .. characterised by surface shape
- F23D 2203/1012 ... tubular
- F23D 2203/1015 ... spherical
- F23D 2203/1017 ... curved
- F23D 2203/102 .. using perforated plates
- F23D 2203/1023 ... with specific free passage areas
- F23D 2203/1026 ... with slotshaped openings
- F23D 2203/103 .. using screens
- F23D 2203/104 .. Grids, e.g. honeycomb grids

| | | |
|---------------------|-------|--|
| F23D 2203/105 | . . | Porous plates |
| F23D 2203/1055 | . . . | with a specific void range |
| F23D 2203/106 | . . | Assemblies of different layers |
| F23D 2203/107 | . . | coated with catalysts |
| F23D 2203/108 | . . | with stacked sheets or strips forming the outlets |
| F23D 2204/00 | | Burners adapted for simultaneous or alternative combustion having more than one fuel supply |
| F23D 2204/10 | . . | gaseous and liquid fuel |
| F23D 2204/20 | . . | gaseous and pulverulent fuel |
| F23D 2204/30 | . . | liquid and pulverulent fuel |
| F23D 2205/00 | | Assemblies of two or more burners, irrespective of fuel type |
| F23D 2206/00 | | Burners for specific applications |
| F23D 2206/0005 | . . | Liquid fuel burners adapted for use in locomotives |
| F23D 2206/001 | . . | Liquid fuel burners adapted for use in automobile steam boilers |
| F23D 2206/0015 | . . | Gas burners for use in retort furnaces |
| F23D 2206/0021 | . . | Gas burners for use in furnaces of the reverberatory, muffle or crucible type |
| F23D 2206/0026 | . . | Vapour burners adapted for use in illumination devices |
| F23D 2206/0031 | . . | Liquid fuel burners adapted for use in welding lamps |
| F23D 2206/0036 | . . . | Liquid fuel burners adapted for use in welding and cutting metals |
| F23D 2206/0042 | . . | Vapour burners for illumination by radiation, with vaporiser heated by an auxiliary flame |
| F23D 2206/0047 | . . | Vapour burners for illumination by radiation, with vaporiser heated by the main flame |
| F23D 2206/0052 | . . | Vapour burners for illumination by radiation, with vaporiser heated by conduction |
| F23D 2206/0057 | . . | Liquid fuel burners adapted for use in illumination and heating |
| F23D 2206/0063 | . . . | Catalytic burners adapted for use in illumination and heating |
| F23D 2206/0068 | . . | Gas burners for illumination with slot type nozzles |
| F23D 2206/0073 | . . | Gas burners for illumination with Argand nozzles |
| F23D 2206/0078 | . . | Gas burners adapted for use in lamps with preheated air |
| F23D 2206/0084 | . . | Gas burners adapted for use in ceiling and wagon lamps |

| | |
|---------------------|--|
| F23D 2206/0089 | . Gas burners for illumination using acetylene as a fuel |
| F23D 2206/0094 | . Gas burners adapted for use in illumination and heating |
| F23D 2206/10 | . Turbines |
| F23D 2207/00 | Ignition devices associated with burner |
| F23D 2208/00 | Control devices associated with burners |
| F23D 2208/005 | . Controlling air supply in radiant gas burners |
| F23D 2208/10 | . Sensing devices |
| F23D 2209/00 | Safety arrangements |
| F23D 2209/10 | . Flame flashback |
| F23D 2209/20 | . Flame lift-off / stability |
| F23D 2209/30 | . Purging |
| F23D 2210/00 | Noise abatement |
| F23D 2210/101 | . using noise dampening material |
| F23D 2211/00 | Thermal dilatation prevention or compensation |
| F23D 2212/00 | Burner material specifications |
| F23D 2212/005 | . Radiant gas burners made of specific materials, e.g. rare earths |
| F23D 2212/10 | . ceramic |
| F23D 2212/101 | .. Foam, e.g. reticulated |
| F23D 2212/103 | .. Fibres |
| F23D 2212/105 | .. Particles |
| F23D 2212/20 | . metallic |
| F23D 2212/201 | .. Fibres |
| F23D 2212/203 | .. Particles |
| F23D 2213/00 | Burner manufacture specifications |
| F23D 2214/00 | Cooling |

F23D 2700/00**TBD**

- F23D 2700/001 . Air supply for wick burners
- F23D 2700/002 . Wick burners without flame spreaders or burner hood
- F23D 2700/003 . Wick burners with flame spreaders or burner hood
- F23D 2700/004 . Inverted wick burners, wick burners using preheated air
- F23D 2700/005 . Wick burners using alcohol as a fuel
- F23D 2700/006 . Wick burners using oil as a fuel
- F23D 2700/009 . Details of blue flame wick burners
- F23D 2700/01 . Blue flame burners without flame spreader or burner hood
- F23D 2700/011 . Blue flame burners with flame spreader or burner hood without a bead at the wick carrying tube
- F23D 2700/012 . Blue flame burners with flame spreader or burner hood with a bead at the wick carrying tube
- F23D 2700/013 . Blue flame burners with flame on one side only without a bead at the wick carrying tube
- F23D 2700/014 . Blue flame burners with flame on one side only and a bead at the wick carrying tube
- F23D 2700/015 . Tubes carrying the wick
- F23D 2700/016 . Safety devices for wick carrying tubes
- F23D 2700/017 . Wick adjusting devices directly engaging the wick
- F23D 2700/018 . Wick adjusting devices engaging the tube carrying the wick
- F23D 2700/019 . Wick stop devices and wick fixing devices
- F23D 2700/02 . Devices for mounting the wick to the carrier
- F23D 2700/021 . Burners in which the gas produced in the wick is not burned instantaneously
- F23D 2700/022 . Burners using carburetted gas
- F23D 2700/023 . Gasifying and evaporating devices
- F23D 2700/024 . Nozzles and cleaning devices therefor
- F23D 2700/025 . Mixing tubes and burner heads
- F23D 2700/026 . Preheating devices, starting devices

- F23D 2700/027 . Vaporisers with devices for controlling the feeding of the fuel
- F23D 2700/03 . Alcohol vapour burners
- F23D 2700/031 . Vapour burners where the vaporiser is heated by an auxiliary flame
- F23D 2700/032 . Vapour burners where the vaporiser is heated by the main flame itself
- F23D 2700/033 . Vapour burners where the vaporiser is heated by conduction

- F23D 2900/00 Special features of, or arrangements for burners using fluid fuels or solid fuels suspended in a carrier gas**

- F23D 2900/00001 . local catalytic coatings applied to burner surfaces
- F23D 2900/00002 . Cleaning burner parts, e.g. burner tips
- F23D 2900/00003 . Fuel or fuel-air mixtures flow distribution devices upstream of the outlet
- F23D 2900/00004 . Burners specially adapted for generating high luminous flames, e.g. yellow for fuel-rich mixtures
- F23D 2900/00006 . Liquid fuel burners using pure oxygen or O₂-enriched air as oxidant ([for gaseous fuels F23D 14/32](#))
- F23D 2900/00008 . Burner assemblies with diffusion and premix modes, i.e. dual mode burners
- F23D 2900/00011 . Burner with means for propagating the flames along a wall surface
- F23D 2900/00012 . Liquid or gas fuel burners with flames spread over a flat surface, either premix or non-premix type, e.g. "Flächenbrenner"
- F23D 2900/00013 . . with means for spreading the flame in a fan or fishtail shape over a melting bath
- F23D 2900/00014 . Pilot burners specially adapted for ignition of main burners in furnaces or gas turbines
- F23D 2900/00015 . Pilot burners specially adapted for low load or transient conditions, e.g. for increasing stability
- F23D 2900/00016 . Preventing or reducing deposit build-up on burner parts, e.g. from carbon
- F23D 2900/00017 . Assembled burner modules
- F23D 2900/00018 . Means for protecting parts of the burner, e.g. ceramic lining outside of the flame tube
- F23D 2900/00019 . Outlet manufactured from knitted fibres
- F23D 2900/01001 . Pulverised solid fuel burner with means for swirling the fuel-air mixture
- F23D 2900/03081 . Catalytic wick burners
- F23D 2900/03082 . Wick made of specific material, e.g. ceramic

- F23D 2900/05001 . Burner using gel type fuel
- F23D 2900/05002 . Use of porous members to convert liquid fuel into vapor
- F23D 2900/11001 . Impinging-jet injectors or jet impinging on a surface
- F23D 2900/11002 . Liquid fuel burners with more than one nozzle
- F23D 2900/11101 . Pulverising gas flow impinging on fuel from pre-filming surface, e.g. lip atomizers
- F23D 2900/11401 . Flame intercepting baffles forming part of burner head
- F23D 2900/11402 . Airflow diaphragms at burner nozzle
- F23D 2900/11403 . Flame surrounding tubes in front of burner nozzle
- F23D 2900/14 . Special features of gas burners
- F23D 2900/14001 . . Sealing or support of burner plate borders
- F23D 2900/14002 . . of premix or non premix types, specially adapted for the combustion of low heating value (LHV) gas
- F23D 2900/14003 . . with more than one nozzle
- F23D 2900/14004 . . with radially extending gas distribution spokes
- F23D 2900/14005 . . Rotary gas burner
- F23D 2900/14021 . . Premixing burners with swirling or vortices creating means for fuel or air
- F23D 2900/14041 . . Segmented or straight line assembly of burner bars
- F23D 2900/14042 . . Star shaped assembly of burner bars or arms
- F23D 2900/14061 . . for cooking ranges having a coated burner cap
- F23D 2900/14062 . . for cooking ranges having multiple flame rings
- F23D 2900/14063 . . for cooking ranges having one flame ring fed by multiple venturis
- F23D 2900/14064 . . Burner heads of non circular shape
- F23D 2900/1412 . . for radiant burners
- F23D 2900/14121 . . . with radiation intensifying means
- F23D 2900/14122 . . . with extra radiation grids, e.g. strips or rods
- F23D 2900/14123 . . . with radiation intensifying perforated plates
- F23D 2900/14124 . . . cooperating with refractory wall surfaces
- F23D 2900/14125 . . . with extra radiation screens, e.g. wires, threads or gauzes
- F23D 2900/14181 . . . Catalytic type with carbon containing radiating surface
- F23D 2900/14241 . . Post-mixing with swirling means
- F23D 2900/14381 . . Single operating member opening and closing fuel and oxidant supply valves in torches
- F23D 2900/14481 . . Burner nozzles incorporating flow adjusting means
- F23D 2900/14482 . . Burner nozzles incorporating a fluidic oscillator
- F23D 2900/14581 . . with outlets consisting of a bed of irregular particles, e.g. glass
- F23D 2900/14582 . . with outlets consisting of layers of spherical particles
- F23D 2900/14641 . . with gas distribution manifolds or bars provided with a plurality of nozzles

- F23D 2900/14642 . . with jet mixers with more than one gas injection nozzles or orifices for a single mixing tube
- F23D 2900/14681 . . Adding steam or water vapor to primary or secondary combustion air
- F23D 2900/14701 . . Swirling means inside the mixing tube or chamber to improve premixing

- F23D 2900/21 . Burners specially adapted for a particular use
- F23D 2900/21001 . . for use in blast furnaces
- F23D 2900/21002 . . for use in car heating systems
- F23D 2900/21003 . . for heating or re-burning air or gas in a duct
- F23D 2900/21004 . . for use in gas fed fireplaces
- F23D 2900/21005 . . for flame deposition, e.g. FHD, flame hydrolysis deposition
- F23D 2900/21006 . . for heating a catalyst in a car
- F23D 2900/21007 . . for producing soot, e.g. nano particle soot