

CPC**COOPERATIVE PATENT CLASSIFICATION****B60S****SERVICING, CLEANING, REPAIRING, SUPPORTING, LIFTING, OR MANOEUVRING OF VEHICLES, NOT OTHERWISE PROVIDED FOR****NOTE**

Attention is drawn to the Note following the title of class B60.

B60S 1/00

Cleaning of vehicles (by apparatus not integral with vehicle [B60S 3/00](#); cleaning in general [B08B](#); de-icing of aircraft [B64D](#); heating arrangements specially adapted for transparent or reflecting areas [H05B 3/84](#))

- B60S 1/02 . Cleaning windscreens, windows or optical devices {(wind deflectors specially adapted for preventing soiling of windows or windscreens [B60J 1/2002](#))}
- B60S 1/023 . . {including defroster or demisting means}
- B60S 1/026 . . . {using electrical means}
- B60S 1/04 . . Wipers or the like, e.g. scrapers
- B60S 1/0402 . . . {completely or partially concealed in a cavity}
- B60S 1/0405 {the cavity being equipped with a movable cover}
- B60S 1/0408 . . . {Means for influencing the aerodynamic quality of wipers, e.g. clip-on wind deflectors ([B60S 1/32](#) takes precedence)}
- B60S 1/0411 . . . {the windscreens, windows or optical devices being movable with respect to fixed wipers}
- B60S 1/0413 . . . {Modular wiper assembly}
- B60S 1/0416 {including other vehicle fittings}
- B60S 1/0419 {the support structure being integrally molded}
- B60S 1/0422 {having a separate transverse element}
- B60S 1/0425 {characterised by the attachment of the wiper shaft holders to the transverse element}
- B60S 1/0427 {characterised by the attachment of the wiper motor holder to the transverse element}
- B60S 1/043 . . . {Attachment of the wiper assembly to the vehicle}
- B60S 1/0433 {Attachement of a wiper modular assembly to the vehicle}
- B60S 1/0436 {Attachement of separate wiper shaft holders to the vehicle ([B60S 1/0425](#) takes precedence)}
- B60S 1/0438 {Attachement of separate wiper motor assembly to the vehicle}
- B60S 1/0441 {characterised by the attachment means}
- B60S 1/0444 {comprising vibration or noise absorbing means}
- B60S 1/0447 {non-screw fixation, (e.g. snap-in, bayonet-type..)}
- B60S 1/045 {having a pre-attachment device (i.e. to hold elements in position during mounting)}
- B60S 1/0452 . . . {Position of the wipers relative to the vehicle}

B60S 1/0455	{Device for lifting the wipers off the screen in its parking position or at extremes of wipe}
B60S 1/0458	{Arrangement wherein the windscreen frame cooperates with the wipers}
B60S 1/0461	{Arrangement of the side pillars}
B60S 1/0463	{Arrangement of the cow}
B60S 1/0466	{Arrangement of wipers on openable windows}
B60S 1/0469	{Devices for assisting the wiper positioning on the vehicle}
B60S 1/0472	{Arrangement of the wipers on right or left-hand drive vehicles}
B60S 1/0475	...	{Cleaning of wiper blades}
B60S 1/0477	{Arrangement for deicing or for removing debris from wiper blades (heated wiper blade B60S 1/3805)}
B60S 1/048	{with a heating device for the wiper parking position}
B60S 1/0483	{the cleaning device being separated from the vehicle (renovating blade rubbers B60S 2001/3846)}
B60S 1/0486	{the cleaning device being integrated with the vehicle}
B60S 1/0488	...	{Wiper arrangement for crash protection or impact absorption}
B60S 1/0491	...	{Additional elements being fixed on wipers or parts of wipers not otherwise provided for, e.g. covers, antennae or lights}
B60S 1/0494	...	{Wipers actuated by wind force only}
B60S 1/0497	...	{Wiper units as items separate from vehicle, e.g. for emergency use or retro-fittable}
B60S 1/06	...	characterised by the drive (producing other than swinging movement B60S 1/44)
B60S 1/08	electrically driven {(conjoint control of windscreen wiper motor and liquid supply of windscreen washer B60S 1/482 ; conjoint control of windscreen wiper motor and means for cleaning parts o parts other than windscreens or front windows B60S 1/56 , B60S 1/58 , B60S 1/606)}
B60S 1/0803	{Intermittent control circuits}
B60S 1/0807	{using electronic control means, e.g. tubes, semiconductors (B60S 1/0818 , B60S 1/0896 take precedence)}
B60S 1/0811	{combined with mechanical control means, e.g. thermal relays}
B60S 1/0814	{using several drive motors; motor synchronisation circuits}
B60S 1/0818	{including control systems responsive to external conditions, e.g. by detection of moisture, dirt or the like}
B60S 1/0822	{ characterized by the arrangement or type of detection means}
B60S 1/0825	{ Capacitive rain sensor}
B60S 1/0829	{ Oscillator-resonator rain sensor}
B60S 1/0833	{ Optical rain sensor}
B60S 1/0837	{ with a particular arrangement of the optical elements}
B60S 1/084	{ including a hologram}
B60S 1/0844	{ including a camera}
B60S 1/0848	{ Cleaning devices for cameras on vehicle}
B60S 1/0851	{ Resistive rain sensor}
B60S 1/0855	{ Ultrasonic rain sensor}
B60S 1/0859	{ Other types of detection of rain, e.g. by measuring friction or rain}

		drop impact}
B60S 1/0862	{ including additional sensors (vehicle speed sensors B60S 1/0896)}
B60S 1/0866	{ including a temperature sensor (heating devices for windshield B60H)}
B60S 1/087	{ including an ambient light sensor (control of vehicle lights B60Q)}
B60S 1/0874	{ characterized by the position of the sensor on the windshield}
B60S 1/0877	{ at least part of the sensor being positioned between layers of the windshield}
B60S 1/0881	{ characterized by the attachment means on the windshield}
B60S 1/0885	{ the sensor being integrated in a rear-view mirror module}
B60S 1/0888	{ characterized by the attachment of the elements in a unit}
B60S 1/0892	{ Testing and production of rain sensors}
B60S 1/0896	{including control systems responsive to a vehicle driving condition, e.g. speed}
B60S 1/10	pneumatically driven
B60S 1/105	{with means for stopping or setting the wipers at their limit of movement}
B60S 1/12	hydraulically driven
B60S 1/125	{with means for stopping or setting the wipers at their limit of movement}
B60S 1/14	personally driven
B60S 1/16	Means for transmitting drive
B60S 1/163	{with means for stopping or setting the wipers at their limit of movement}
B60S 1/166	{characterised by the combination of a motor-reduction unit and a mechanism for converting rotary into oscillatory movement}
B60S 1/18	mechanically {(B60S 1/166 takes precedence)}
B60S 1/185	{with means for stopping or setting the wipers at their limit of movement}
B60S 1/20	by cable drives; by flexible shafts
B60S 1/22	by rotary cams
B60S 1/24	by rotary cranks
B60S 1/245	{with particular rod arrangements between the motor driven axle and the wiper arm axle}
B60S 1/26	by toothed gearing
B60S 1/28	...	characterised by a plurality of wipers (B60S 1/06 takes precedence)
B60S 1/30	arranged both outside and inside
B60S 1/32	...	characterised by constructional features of wiper blade arms {or blades}
B60S 1/34	Wiper arms; Mountings therefor {(wiper arms provided with liquid spreading means B60S 1/522 ; with gas spreading means B60S 1/544)}
B60S 1/3402	{with means for obtaining particular wiping patterns (by varying the effective length of the angularly oscillating arm B60S 1/365)}
B60S 1/3404	{the wiper blades being moved substantially parallel with themselves}
B60S 1/3406	{the wiper blades being rotated with respect to the wiper arms around an axis perpendicular to the wiped field (B60S 1/3404 takes precedence)}

B60S 1/3409	{the wiper arms consisting of two or more articulated elements}
B60S 1/3411	{with means for varying wiper-blade pressure on windshield during operation}
B60S 1/3413	{with means for holding the arm off the glass in an intermediate position between the working position and the fully folded back position}
B60S 1/3415	{with means for supplying cleaning fluid to windscreen cleaners, e.g. washers (arrangement of nozzles B60S 1/52)}
B60S 1/3418	{with means for additionally adjusting the wiper arm working position with respect to the surface to be wiped}
B60S 1/342	{with means for temporarily uncoupling the wiper arm from the drive}
B60S 1/3422	{ Means arranged in the wiper structure to lift the arm at extremes of wipe (means arranged on the vehicle body B60S 1/0455)}
B60S 1/3425	{ Constructional aspects of the arm}
B60S 1/3427	{ Arm piece, link piece and mounting head formed as one element}
B60S 1/3429	{ Arm pieces}
B60S 1/3431	{ Link pieces}
B60S 1/3434	{ Manufacturing details thereof}
B60S 1/3436	{ Mounting heads}
B60S 1/3438	{ Manufacturing details thereof}
B60S 1/344	{ Flat-type mounting heads}
B60S 1/3443	{ Wiper shafts}
B60S 1/3445	{ Joints between elements}
B60S 1/3447	{ the elements being an arm piece and a link piece}
B60S 1/345	{ the elements being a link piece and a mounting head}
B60S 1/3452	{ the joint being a snap fit pivot joint}
B60S 1/3454	{ the joint being at end of mounting head furthest away from blade}
B60S 1/3456	{ Locks or stays for holding arms in fully folded back position}
B60S 1/3459	{ the element being a mounting head and a shaft}
B60S 1/3461	{ with means to adjust the orientation of the head relative to shaft}
B60S 1/3463	{ Means to press blade onto screen}
B60S 1/3465	{ with coil springs}
B60S 1/3468	{ Mountings therefor}
B60S 1/347	{ with adjustment means to adjust wiping pressure (during wiping B60S 1/3411)}
B60S 1/3472	{ with adjustment means to keep wiping pressure constant (varying wiping pressure B60S 1/3411)}
B60S 1/3475	{ with blade or leaf springs}
B60S 1/3477	{ with elastomeric or rubber springs}
B60S 1/3479	{ Means to cover the wiper parts}
B60S 1/3481	{ for mounting head}
B60S 1/3484	{ integral with arm or link piece}
B60S 1/3486	{ Means to allow blade to follow curvature of the screen (i.e. rotation along longitudinal axis of the arm)}

B60S 1/3488	{ Means for mounting wiper arms onto the vehicle}
B60S 1/349	{ Means for mounting the wiper bearing to the vehicle body}
B60S 1/3493	{ Means for mounting the wiper shaft in the wiper bearing}
B60S 1/3495	{ Means for mounting the drive mechanism to the wiper shaft}
B60S 1/3497	{ Additional means for guiding the blade other than the arm or blade joint}
B60S 1/36	Variable-length arms
B60S 1/365	{the effective length being automatically varied during angular oscillation of the arm}
B60S 1/38	Wiper blades {(provided with liquid spreading means B60S 1/524 ; provided with gas spreading means B60S 1/546)}
B60S 1/3801	{characterised by a blade support harness consisting of several articulated elements (B60S 1/3803 , B60S 1/3806 take precedence)}
B60S 1/3803	{heated wiper blades}
B60S 1/3805	{electrically}
B60S 1/3806	{ Means, or measures taken, for influencing the aerodynamic quality of the wiper blades}
B60S 1/3808	{ Spoiler integral with the squeegee}
B60S 1/381	{ Spoilers mounted on the squeegee or on the vertebra}
B60S 1/3848	{ Flat-type wiper blade, i.e. without harness}
B60S 1/3849	{ Connectors therefor; Connection to wiper arm; Attached to blade}
B60S 1/3851	{ Mounting of connector to blade assembly}
B60S 1/3853	{ Snap-fit, e.g. elastic connection}
B60S 1/3855	{ by welding, gluing or the like}
B60S 1/3856	{ Gripping the blade}
B60S 1/3858	{ with protrusions cooperating with holes}
B60S 1/386	{ made in two halves}
B60S 1/3862	{ Transport of liquid there through}
B60S 1/3863	{ Connectors having a spoiler}
B60S 1/3865	{ Connectors having an integral pivot pin for connection with the wiper arm}
B60S 1/3867	{ pin formed on the interior of side walls}
B60S 1/3868	{ pin formed on the exterior of side walls}
B60S 1/387	{ the connector being suitable for receiving different types of adapter}
B60S 1/3872	{ without connector, e.g. connection to wiper arm via squeegee or vertebra}
B60S 1/3874	{ with a reinforcing vertebra}
B60S 1/3875	{ rectangular section}
B60S 1/3877	{ embedded in the squeegee}
B60S 1/3879	{ placed in side grooves in the squeegee}
B60S 1/3881	{ in additional element, e.g. spoiler}
B60S 1/3882	{ C-shape section}
B60S 1/3884	{ Wire-shaped section}
B60S 1/3886	{ End caps}

B60S 1/3887	{ Mounting of end caps}
B60S 1/3889	{ cooperating with holes in the vertebra}
B60S 1/3891	{ with locking device}
B60S 1/3893	{ cooperating with holes in the squeegee}
B60S 1/3894	{ having a particular shape}
B60S 1/3896	{ with openings at the longitudinal extremities}
B60S 1/40	Connections between blades and arms
B60S 1/4003	{ Multi-purpose connections for two or more kinds of arm ends}

NOTE

Multi-aspect classification is applied for technical subjects relating to the arms and covered by subgroups [B60S 1/4006](#) to [B60S 1/40J](#)

B60S 1/4006	{ for arms provided with a hook-shaped end}
B60S 1/4009	{ comprising a detachable intermediate element mounted on the hook-shaped end}
B60S 1/4016	{ the element being provided with retention means co-operating with the hook-shaped end of the arm}
B60S 1/4019	{ the retention means being protrusions or holes}
B60S 1/4038	{ for arms provided with a channel-shaped end}
B60S 1/4041	{ the channel-shaped end comprising a pivot pin mounted between the side walls}
B60S 1/4045	{ comprising a detachable intermediate element mounted on the channel-shaped end}
B60S 1/4048	{ the element being provided with retention means co-operating with the channel-shaped end of the arm}
B60S 1/4064	{ the channel-shaped end being provided with protrusions on, or holes in, the side walls to create a pivot}
B60S 1/4067	{ for arms provided with a side pin}
B60S 1/407	{ with means provided on the arm for locking the side pin}
B60S 1/4074	{ with means provided on the blade for locking the side pin}
B60S 1/4077	{ characterised by the connecting part of, or an intermediate element mounted on, the wiper blade (means for locking the side pin B60S 1/4074)}
B60S 1/4083	{ for arms provided with a flat end}
B60S 1/4087	{ the end being provided with protrusions or holes}
B60S 1/42	resilient
B60S 1/44	...	the wiper blades having other than swinging movement, e.g. rotary {(the wiper blade support member, e.g. arm, having a swinging movement B60S 1/32)}
B60S 1/46	..	using liquid; Windscreen washers
B60S 1/48	...	Liquid supply therefor
B60S 1/481	{the operation of at least part of the liquid supply being controlled by electric means (electrical washing liquid warming-up means B60S 1/488)}
B60S 1/482	{combined with the operation of windscreen wipers}
B60S 1/483	{using a supply pump driven by the windscreen-wiper motor}
B60S 1/485	{including control systems responsive to external conditions, e.g. by

		detection of moisture, dirt or the like}
B60S 1/486	{including control systems responsive to a vehicle driving condition, e.g. speed}
B60S 1/487	{the liquid being heated (nozzles provided with heating means B60S 1/52)}
B60S 1/488	{electrically}
B60S 1/50	Arrangement of reservoir
B60S 1/52	Arrangement of nozzles; {Liquid spreading means}(nozzles per se B05B)
B60S 1/522	{moving liquid spreading means, e.g. arranged in wiper arms}
B60S 1/524	{arranged in wiper blades}
B60S 1/526	{according to vehicle movement characteristics, e.g. speed, or climatic conditions, e.g. wind}
B60S 1/528	{the spreading means being moved between a rest position and a working position (B60S 1/526 takes precedence)}
B60S 1/54	..	using gas, e.g. hot air
B60S 1/542	...	{using wiping devices}
B60S 1/544	...	{moving gas spreading means, e.g. arranged in wiper arms}
B60S 1/546	{arranged in wiper blades}
B60S 1/548	{according to vehicle movement characteristics, e.g. speed, or climatic conditions, e.g. wind}
B60S 1/56	..	specialy adapted for cleaning other parts or devices than front windows or windscreens {(rear-view mirror arrangements mounted on vehicle exterior including cleaning devices B60R 1/0602)}
B60S 1/563	...	{for registration, licensing or like devices}
B60S 1/566	...	{including wiping devices (B60S 1/563 , B60S 1/583 take precedence)}
B60S 1/58	...	for rear windows
B60S 1/583	{including wiping devices}
B60S 1/586	{including defroster or demisting means}
B60S 1/60	...	for signalling devices, e.g. reflectors
B60S 1/603	{the operation of at least a part of the cleaning means being controlled by electric means}
B60S 1/606	{combined with the operation of windscreen or front window cleaning means}
B60S 1/62	.	Other vehicle fittings for cleaning
B60S 1/64	..	for cleaning vehicle interiors, e.g. built-in vacuum cleaners
B60S 1/66	..	for cleaning vehicle exterior
B60S 1/68	...	for freeing wheels or tyres from foreign matter, e.g. wheel scrapers
B60S 1/685	{for two-wheeled vehicles}
B60S 3/00		Vehicle cleaning apparatus not integral with vehicles (cleaning in general B08B ; cleaning peculiar to waterborne vessels B63B 57/00 , B63B 59/00 ; ground equipment for cleaning aircraft B64F 5/00 ; { multistage treatment applied to waste water from vehicle wash installations C02F 9/00 })
B60S 3/002	.	{Vehicle drying apparatus}

- B60S 3/004 . {Conveyers for vehicle cleaning apparatus}
- B60S 3/006 . {specially adapted for railway vehicles ([B60S 3/008](#) takes precedence)}
- B60S 3/008 . {for interiors of land vehicles}
- B60S 3/04 . for exteriors of land vehicles {([B60S 3/002](#), [B60S 3/004](#) take precedence; specially adapted for railway vehicles [B60S 3/006](#))}
- B60S 3/041 . . {specially adapted for two-wheeled vehicles}
- B60S 3/042 . . {Wheel cleaning devices (integral with vehicle [B60S 1/00](#))}
- B60S 3/044 . . {Hand-held cleaning arrangements with liquid or gas distributing means ([B60S 3/045](#) takes precedence)}
- B60S 3/045 . . {Other hand-held cleaning arrangements, e.g. with sponges, brushes, scrapers or the like ([brushes per se](#) [A46B](#))}
- B60S 3/047 . . . {using liquid or gas distributing means ([B60S 3/048](#) takes precedence)}
- B60S 3/048 . . . {with rotary or vibratory bodies contacting the vehicle}
- B60S 3/06 . . with rotary bodies contacting the vehicle {(hand-held [B60S 3/048](#))}
- B60S 3/063 . . . {the axis of rotation being approximately vertical}
- B60S 3/066 . . . {the axis of rotation being approximately horizontal}

- B60S 5/00** **Servicing, maintaining, repairing or refitting of vehicles** ({collecting or removing exhaust gases in workshops [B08B 15/002](#); straightening vehicle body parts [B21D 1/12](#), [B21D 1/14](#)}; vehicles adapted to carry a workshop for servicing or maintenance [B60P 3/14](#); servicing rail locomotives [B61K](#)); {registering or indicating the working of vehicles [G07C 5/00](#); testing of vehicles [G01M 17/00](#); arrangements for electrical testing [G01R 31/00](#); devices for monitoring or checking brake systems [B60T 17/22](#); filling or draining lubricant [F01M 11/04](#); means for collecting, retaining, or draining-off lubricant [F16N 31/00](#); draining of lubricant from gearing [F16H 57/0406](#); assembly or repair of springs or dampers [F16F 9/3271](#); tool, instrument or work supports or storage means used in association with vehicles [B25H 5/00](#)}
- B60S 5/02 . Supplying fuel to vehicles; General disposition of plant in filling stations (apparatus for transferring measured quantities of petrol, oil, or the like from storage space to vehicles [B67D](#))
- B60S 5/04 . Supplying air for tyre inflation (arrangement of tyre inflating devices on vehicles [B60C 23/00](#); tyre pressure gauges [G01L 17/00](#); { pumps actuated by muscle power [F04B 33/00](#)})
- B60S 5/043 . . {characterised by the inflation control means or the drive of the air pressure system}
- B60S 5/046 . . . {using electrical or electronical means}
- B60S 5/06 . Supplying batteries to, or removing batteries from, vehicles (circuit arrangements for charging batteries [H02J 7/00](#))

- B60S 9/00** **Ground-engaging vehicle fittings for supporting, lifting, or manoeuvring the vehicle, wholly or in part, e.g. built-in jacks** { props for vehicle draw bars [B60D 1/66](#); anti-theft devices acting on vehicle jacking means [B60R 25/001](#)}; (lifting devices in general [B66F](#), supports in general [F16M](#))

- B60S 9/02 . for only lifting or supporting
- B60S 9/04 .. mechanically
- B60S 9/06 ... of screw-and-nut type
- B60S 9/08 the screw axis being substantially vertical
- B60S 9/10 .. by fluid pressure
- B60S 9/12 ... of telescopic type

- B60S 9/14 . for both lifting and manoeuvring
- B60S 9/16 .. for operating only on one end of vehicle ([B60S 9/205](#) takes precedence)
- B60S 9/18 ... mechanically
- B60S 9/20 ... with fluid-pressure lift
- B60S 9/205 .. Power driven manoeuvring fittings, e.g. reciprocally driven steppers or rotatably driven cams ([vehicles with ground-engaging propulsion means, e.g. walking members, B62D 57/02](#))
- B60S 9/21 ... comprising a rotatably driven auxiliary wheel or endless track, e.g. driven by ground wheel ([track vehicles with additional or alternative ground wheels B62D 55/02, B62D 55/04; auxiliary drives from a ground wheel B60K 25/08](#))
- B60S 9/215 driven by an auxiliary motor

- B60S 9/22 . Means for attaching lifting, supporting, or manoeuvring devices to vehicles ([for separate devices B60S 11/00](#))

- B60S 11/00 Vehicle modifications for receiving separate lifting, supporting, or manoeuvring devices**

- B60S 13/00 Vehicle-manoevring devices separate from the vehicle (vehicle lifting {e.g. liftable turntables} or pushing devices [B66F](#); {workshop equipment [B25H](#)})**

- B60S 13/02 . Turntables; Traversers ([incorporated in vehicle-storing garages \[E04H\]\(#\); {rotary display stands \[A47F 5/02\]\(#\)}](#))

- B60S 2001/00 Cleaning of vehicles (by apparatus not integral with vehicle [B60S 3/00](#); cleaning in general [B08B](#); de-icing of aircraft [B64D](#); heating arrangements specially adapted for transparent or reflecting areas [H05B 3/84](#))**

- B60S 2001/02 . Cleaning windcreens, windows or optical devices [{\(wind deflectors specially adapted for preventing soiling of windows or windcreens \[B60J 1/2002\]\(#\)\)}](#)
- B60S 2001/04 .. Wipers or the like, e.g. scrapers
- B60S 2001/32 ... characterised by constructional features of wiper blade arms [{or blades}](#)
- B60S 2001/38 Wiper blades [{\(provided with liquid spreading means \[B60S 1/524\]\(#\); provided with gas spreading means \[B60S 1/546\]\(#\)\)}](#)
- B60S 2001/3812 Means of supporting or holding the squeegee or blade rubber
- B60S 2001/3813 characterised by a support harness consisting of several articulated elements

B60S 2001/3815	characterised by the joint between elements
B60S 2001/3817	characterised by a backing strip to aid mounting of squeegee in support
B60S 2001/3818	the backing strip being a channel-like element, e.g. not continuous
B60S 2001/382	the backing strip being an essentially planar reinforcing strip, e.g. vertebra
B60S 2001/3822	characterised by additional means to prevent longitudinal sliding of squeegee in support, e.g. clips
B60S 2001/3824	the blade or squeegee pivoting about an axis parallel to blade longitudinal axis
B60S 2001/3825	the squeegee mounted directly to or in wiper blade arm
B60S 2001/3827	characterised by the squeegee or blade rubber or wiping element
B60S 2001/3829	characterised by the material of the squeegee or coating thereof
B60S 2001/3831	cleaning by scrubbing or abrasive action
B60S 2001/3832	cleaning by rigid or semi-rigid scraping elements, e.g. for removing ice
B60S 2001/3834	equipped with brush-like elements
B60S 2001/3836	characterised by cross-sectional shape
B60S 2001/3837	with more than one wiping edge or lip
B60S 2001/3839	with longitudinally split squeegee, with squeegee parts
B60S 2001/3841	Squeegee modifications to prevent longitudinally sliding of squeegee in support structure
B60S 2001/3843	equipped with removable cover or protective elements
B60S 2001/3844	equipped with means to indicate wear or usage of blade
B60S 2001/3846	Devices for renewing or renovating blade wiping edges, e.g. cutters
B60S 2001/3898	method for manufacturing wiper blades
B60S 2001/40	Connections between blades and arms
B60S 2001/4006	{ for arms provided with a hook-shaped end}
B60S 2001/4009	{ comprising a detachable intermediate element mounted on the hook-shaped end}
B60S 2001/4012	the element being provided with bearing surfaces on its side walls
B60S 2001/4016	{ the element being provided with retention means co-operating with the hook-shaped end of the arm}
B60S 2001/4022	the element being provided with a locking element movable thereon
B60S 2001/4025	the element being able to receive pivot pins of different diameters
B60S 2001/4029	the element being able to receive arms of different widths
B60S 2001/4032	the element being able to receive arms with hooks of different radiuses
B60S 2001/4035	the connection being covered by a removable cover mounted on the blade
B60S 2001/4038	{ for arms provided with a channel-shaped end}
B60S 2001/4045	{ comprising a detachable intermediate element mounted on the channel-shaped end}
B60S 2001/4048	{ the element being provided with retention means co-operating with the channel-shaped end of the arm}

B60S 2001/4051	the intermediate element engaging the side walls of the arm
B60S 2001/4054	the intermediate element engaging the back part of the arm
B60S 2001/4058	comprising a separate locking element, e.g. in addition to an intermediate element
B60S 2001/4061	covered by a removable cover mounted on the blade
B60S 2001/4067	{ for arms provided with a side pin}
B60S 2001/4077	{ characterised by the connecting part of, or an intermediate element mounted on, the wiper blade (means for locking the side pin B60S 1/4074)}
B60S 2001/408	the connecting part or the intermediate element being provided with holes for different diameters of pivoting pin
B60S 2001/409	characterised by the arm or connecting part mounted on the arm presenting a shaped opening for bearing the pivot axis
B60S 2001/4093	characterised by the mounting of the pivot on the main yoke of the blade
B60S 2001/4096	Connections between arm and blade not using a cylindrical pivot axis on the blade