

CPC**COOPERATIVE PATENT CLASSIFICATION****F04C****ROTARY-PISTON, OR OSCILLATING-PISTON,
POSITIVE-DISPLACEMENT MACHINES FOR LIQUIDS ([engines F03C](#));
ROTARY-PISTON, OR OSCILLATING-PISTON,
POSITIVE-DISPLACEMENT PUMPS****NOTE**

Attention is drawn to the notes preceding class F01 especially as regards the definitions of "machines", "pumps", "positive displacement", "rotary-piston machines", "oscillating-piston machines", "rotary piston", "co-operating members", "movement of co-operating members", "teeth or tooth-equivalents" and "internal axis".

F04C 2/00

Rotary-piston machines or pumps (with non-parallel axes of co-operating members [F04C 3/00](#); with the working-chamber walls at least partly resiliently deformable [F04C 5/00](#); with fluid ring or the like [F04C 7/00](#); rotary-piston pumps specially adapted for elastic fluids [F04C 18/00](#); rotary-piston machines or pumps in which the working-fluid is exclusively displaced by, or exclusively displaces, one or more reciprocating pistons [F04B](#))

NOTE

Group [F04C 2/30](#) takes precedence over groups [F04C 2/02](#) to [F04C 2/28](#)

F04C 2/02

- . of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents

F04C 2/025

- .. {the moving and the stationary member having co-operating elements in spiral form}

F04C 2/04

- .. of internal axis type

F04C 2/045

- ... { having a C-shaped piston}

F04C 2/06

- .. of other than internal-axis type

F04C 2/063

- ... with coaxially-mounted members having continuously-changing circumferential spacing between them

F04C 2/067

- having cam-and-follower type drive

F04C 2/07

- having crankshaft-and-connecting-rod type drive

F04C 2/073

- having pawl-and-ratchet type drive

F04C 2/077

- having toothed-gearing type drive

F04C 2/08

- . of intermeshing-engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing

F04C 2/082

- .. {Details specially related to intermeshing engagement type machines or pumps}

F04C 2/084

- ... {Toothed wheels}

F04C 2/086

- ... {Carter}

- F04C 2/088 . . . { Elements in the toothed wheels or the carter for relieving the pressure of fluid imprisoned in the zones of engagement}
- F04C 2/10 . . of internal-axis type with the outer member having more teeth or tooth-equivalents, e.g. rollers, than the inner member
- F04C 2/101 . . . {with a crescent-shaped filler element, located between the inner and outer intermeshing members}
- F04C 2/102 . . . {the two members rotating simultaneously around their respective axes}
- F04C 2/103 . . . {one member having simultaneously a rotational movement about its own axis and an orbital movement}
- F04C 2/104 {having an articulated driving shaft}
- F04C 2/105 {Details concerning timing or distribution valves}
- F04C 2/106 {Spool type distribution valves}
- F04C 2/107 . . . with helical teeth
- F04C 2/1071 {the inner and outer member having a different number of threads and one of the two being made of elastic materials, e.g. Moineau type}
- F04C 2/1073 {where one member is stationary while the other member rotates and orbits}
- F04C 2/1075 {Construction of the stationary member}
- F04C 2/1076 {where one member orbits or wobbles relative to the other member which rotates around a fixed axis}
- F04C 2/1078 {where one member rotates and both members are allowed to orbit or wobble}
- F04C 2/113 . . . the inner member carrying rollers intermeshing with the outer member
- F04C 2/12 . . of other than internal-axis type
- F04C 2/123 . . . {with radially or approximately radially from the rotor body extending tooth-like elements, co-operating with recesses in the other rotor, e.g. one tooth}
- F04C 2/126 . . . {with radially from the rotor body extending elements, not necessarily co-operating with corresponding recesses in the other rotor, e.g. lobes, Roots type}
- F04C 2/14 . . . with toothed rotary pistons
- F04C 2/16 with helical teeth, e.g. chevron-shaped, screw type {(for non-parallel axes of movement [F04C 3/00](#))}
- F04C 2/165 {having more than two rotary pistons with parallel axes}
- F04C 2/18 . . . with similar tooth forms ([F04C 2/16](#) takes precedence)
- F04C 2/20 . . . with dissimilar tooth forms ([F04C 2/16](#) takes precedence)
- F04C 2/22 . of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth-equivalents than the outer member
- F04C 2/24 . of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions
- F04C 2/26 . . of internal-axis type
- F04C 2/28 . . of other than internal-axis type
- F04C 2/30 . having the characteristics covered by two or more groups [F04C 2/02](#), [F04C 2/08](#), [F04C 2/22](#), [F04C 2/24](#) or having the characteristics covered by one of these groups together with some other type of movement between co-operating members

- F04C 2/32 .. having both the movement defined in groups [F04C 2/02](#) and relative reciprocation between co-operating members
- F04C 2/321 ... { with vanes hinged to the inner member and reciprocating with respect to the inner member }
- F04C 2/322 ... { with vanes hinged to the outer member and reciprocating with respect to the outer member }
- F04C 2/324 ... with vanes hinged to the inner member and reciprocating with respect to the outer member
- F04C 2/328 and hinged to the outer member
- F04C 2/332 ... with vanes hinged to the outer member and reciprocating with respect to the inner member
- F04C 2/336 and hinged to the inner member
- F04C 2/34 .. having the movement defined in groups [F04C 2/08](#) or [F04C 2/22](#) and relative reciprocation between the co-operating members
- F04C 2/344 ... with vanes reciprocating with respect to the inner member
- F04C 2/3441 {the inner and outer member being in contact along one line or continuous surface substantially parallel to the axis of rotation}
- F04C 2/3442 {the surfaces of the inner and outer member, forming the working space, being surfaces of revolution}
- F04C 2/3443 {with a separation element located between the inlet and outlet opening}
- F04C 2/3445 {the vanes having the form of rollers, slippers or the like}
- F04C 2/3446 {the inner and outer member being in contact along more than one line or surface}
- F04C 2/3447 {the vanes having the form of rollers, slippers or the like}
- F04C 2/3448 {with axially movable vanes}
- F04C 2/348 the vanes positively engaging, with circumferential play, an outer rotatable member
- F04C 2/352 the vanes being pivoted on the axis of the outer member
- F04C 2/356 ... with vanes reciprocating with respect to the outer member
- F04C 2/3562 {the inner and outer member being in contact along one line or continuous surface substantially parallel to the axis of rotation}
- F04C 2/3564 {the surfaces of the inner and outer member, forming the working space, being surfaces of revolution}
- F04C 2/3566 {the inner and outer member being in contact along more than one line or surface}
- F04C 2/3568 {with axially movable vanes}
- F04C 2/36 .. having both the movements defined in groups [F04C 2/22](#) and [F04C 2/24](#)
- F04C 2/38 .. having the movement defined in group [F04C 2/02](#) and having a hinged member ([F04C 2/32](#) takes precedence)
- F04C 2/39 ... with vanes hinged to the inner as well as to the outer member
- F04C 2/40 .. having the movement defined in group [F04C 2/08](#) or [F04C 2/22](#) and having a hinged member
- F04C 2/44 ... with vanes hinged to the inner member
- F04C 2/46 ... with vanes hinged to the outer member

F04C 3/00 Rotary-piston machines or pumps, with non-parallel axes of movement of

co-operating members, e.g. of screw type (with the working-chamber walls at least partly resiliently deformable [F04C 5/00](#); rotary-piston pumps with non-parallel axes of movement of co-operating members specially adapted for elastic fluids [F04C 18/48](#))

- F04C 3/02 . the axes being arranged at an angle of 90 degrees
- F04C 3/04 . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
- F04C 3/06 . the axes being arranged otherwise than at an angle of 90 degrees
- F04C 3/08 . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
- F04C 3/085 . . . {the axes of cooperating members being on the same plane}
- F04C 5/00 Rotary-piston machines or pumps with the working-chamber walls at least partly resiliently deformable** (such pumps specially adapted for elastic fluids [F04C 18/00](#))
- F04C 7/00 Rotary-piston machines or pumps with fluid ring or the like** (such pumps specially adapted for elastic fluids [F04C 19/00](#))
- F04C 9/00 Oscillating-piston machines or pumps** (such pumps specially adapted for elastic fluids [F04C 21/00](#))
- F04C 9/002 . {the piston oscillating around a fixed axis}
- F04C 9/005 . {the piston oscillating in the space, e.g. around a fixed point (rotary-piston machines or pumps with non-parallel axes of movement between co-operating members [F04C 3/00](#))}
- F04C 9/007 . {the points of the moving element describing approximately an alternating movement in axial direction with respect to the other element}
- F04C 11/00 Combinations of two or more machines or pumps, each being of rotary-piston or oscillating-piston type** (combinations of such pumps specially adapted for elastic fluids [F04C 23/00](#)); **Pumping installations** ([F04C 13/00](#) takes precedence; specially adapted for elastic fluids [F04C 23/00](#); fluid gearing F16H)

NOTE

Multi-stage engines, motors, pumps or compressors with stages connected in series or in parallel are not considered as having complementary function

- F04C 11/001 . {of similar working principle}
- F04C 11/003 . . {having complementary function}
- F04C 11/005 . {of dissimilar working principle}
- F04C 11/006 . . {having complementary function}

- F04C 11/008
 - . {Enclosed motor pump units}
- F04C 13/00**
Adaptations of machines or pumps for special use, e.g. for extremely high pressures (of pumps specially adapted for elastic fluids [F04C 25/00](#))
- F04C 13/001
 - . {Pumps for particular liquids}
- F04C 13/002
 - .. {for homogeneous viscous liquids}
- F04C 13/004
 - ... {with means for fluidising or diluting the material being pumped}
- F04C 13/005
 - . { Removing contaminants, deposits or scale from the pump; Cleaning}
- F04C 13/007
 - . {Venting; Gas and vapour separation during pumping (preventing vapour lock in fuel pumps [F02M 37/20](#), in centrifugal pumps [F04D 9/00](#))}
- F04C 13/008
 - . {Pumps for submersible use, i.e. down-hole pumping}
- F04C 14/00**
Control of, monitoring of, or safety arrangements for, machines, pumps or pumping installations (of pumps or pumping installations specially adapted for elastic fluids [F04C 28/00](#))
- F04C 14/02
 - . specially adapted for several machines or pumps connected in series or in parallel
- F04C 14/04
 - . specially adapted for reversible machines or pumps
- F04C 14/06
 - . specially adapted for stopping, starting, idling or no-load operation
- F04C 14/065
 - .. { Capacity control using a multiplicity of units or pumping capacities, e.g. multiple chambers, individually switchable or controllable}
- F04C 14/08
 - . characterised by varying the rotational speed
- F04C 14/10
 - . characterised by changing the positions of the inlet or outlet openings with respect to the working chamber
- F04C 14/12
 - .. using sliding valves
- F04C 14/14
 - .. using rotating valves
- F04C 14/16
 - .. using lift valves
- F04C 14/18
 - . characterised by varying the volume of the working chamber (by changing the positions of inlet or outlet openings [F04C 14/10](#))
- F04C 14/185
 - .. { by varying the useful pumping length of the cooperating members in the axial direction}
- F04C 14/20
 - .. by changing the form of the inner or outer contour of the working chamber
- F04C 14/22
 - .. by changing the eccentricity between cooperating members
- F04C 14/223
 - ... {using a movable cam}
- F04C 14/226
 - {by pivoting the cam around an eccentric axis}
- F04C 14/24
 - . characterised by using valves regulating pressure or flow rate, e.g. discharge valves, { unloading valves}([F04C 14/10](#) takes precedence)
- F04C 14/26
 - .. using bypass channels

F04C 14/265 . . . {being obtained by displacing a lateral sealing face}

F04C 14/28 . Safety arrangements; Monitoring

F04C 15/00 **Component parts, details or accessories of machines, pumps or pumping installations, not provided for in groups [F04C 2/00](#) to [F04C 14/00](#) (of pumps specially adapted for elastic fluids [F04C 18/00](#) to [F04C 29/00](#))**

F04C 15/0003 . {Sealing arrangements in rotary-piston machines or pumps (sealing in general [F16J](#))}

F04C 15/0007 . . {Radial sealings for working fluid}

F04C 15/0011 . . . {of rigid material}

F04C 15/0015 . . . {of resilient material}

F04C 15/0019 . . . {Radial sealing elements specially adapted for intermeshing-engagement type machines or pumps, e.g. gear machines or pumps}

F04C 15/0023 . . {Axial sealings for working fluid}

F04C 15/0026 . . . {Elements specially adapted for sealing of the lateral faces of intermeshing-engagement type machines or pumps, e.g. gear machines or pumps}

F04C 15/003 . . {Sealings for working fluid between radially and axially moving parts}

F04C 15/0034 . . { for other than the working fluid, i.e. the sealing arrangements are not between working chambers of the machine}

F04C 15/0038 . . . {Shaft sealings specially adapted for rotary-piston machines or pumps}

F04C 15/0042 . {Systems for the equilibration of forces acting on the machines or pump (interstice adjustment other than by fluid pressure [F01C 21/102](#))}

F04C 15/0046 . . {Internal leakage control}

F04C 15/0049 . . { Equalization of pressure pulses (silencing for compressors [F04C 29/06](#))}

F04C 15/0053 . {Venting means for starting}

F04C 15/0057 . {Driving elements, brakes, couplings, transmission specially adapted for machines or pumps (brakes, couplings, transmissions per se [F16](#), [B60](#))}

F04C 15/0061 . . {Means for transmitting movement from the prime mover to driven parts of the pump, e.g. clutches, couplings, transmissions}

F04C 15/0065 . . . {for eccentric movement}

F04C 15/0069 . . . {Magnetic couplings}

F04C 15/0073 . . . {Couplings between rotors and input or output shafts acting by interengaging or mating parts, i.e. positive coupling of rotor and shaft}

F04C 15/0076 . . {Fixing rotors on shafts, e.g. by clamping together hub and shaft}

F04C 15/008 . . {Prime movers}

F04C 15/0084 . . { Brakes, braking assemblies}

F04C 15/0088 . {Lubrication (of machines or engines in general [F01M](#))}

F04C 15/0092 . . {Control systems for the circulation of the lubricant}

F04C 15/0096 . {Heating; Cooling (of machines or engines in general [F01P](#))}

F04C 15/06 . Arrangements for admission or discharge of the working fluid, e.g. constructional

features of the inlet or outlet

- F04C 15/062 .. {Arrangements for supercharging the working space (similar arrangements for internal combustion engines [F02B 33/00](#), [F02B 37/00](#))}
- F04C 15/064 .. {with inlet and outlet valves specially adapted for rotary or oscillating piston machines or pumps}
- F04C 15/066 ... {of the non-return type}
- F04C 15/068 {of the elastic type, e.g. reed valves}

F04C 18/00

Rotary-piston pumps specially adapted for elastic fluids (with fluid ring or the like [F04C 19/00](#); rotary-piston pumps in which the working-fluid is exclusively displaced by one or more reciprocating pistons [F04B](#))

NOTE

Group [F04C 18/30](#) takes precedence over groups [F04C 18/02](#) to [F04C 18/28](#) and [F04C 18/48](#) to [F04C 18/56](#).

- F04C 18/02 . of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents
- F04C 18/0207 .. {both members having co-operating elements in spiral form}
- F04C 18/0215 ... {where only one member is moving}
- F04C 18/0223 {with symmetrical double wraps}
- F04C 18/023 ... {where both members are moving}
- F04C 18/0238 {with symmetrical double wraps}
- F04C 18/0246 ... {Details concerning the involute wraps or their base, e.g. geometry}
- F04C 18/0253 { Details concerning the base}
- F04C 18/0261 { Details of the ports, e.g. location, number, geometry}
- F04C 18/0269 { Details concerning the involute wraps}
- F04C 18/0276 { Different wall heights}
- F04C 18/0284 { Details of the wrap tips}
- F04C 18/0292 { Ports or channels located in the wrap}
- F04C 18/04 .. of internal-axis type
- F04C 18/045 ... { having a C-shaped piston}
- F04C 18/06 .. of other than internal-axis type
- F04C 18/063 ... with coaxially-mounted members having continuously-changing circumferential spacing between them
- F04C 18/067 having cam-and-follower type drive
- F04C 18/07 having crankshaft-and-connecting-rod type drive
- F04C 18/073 having pawl-and-ratchet type drive
- F04C 18/077 having toothed-gearing type drive
- F04C 18/08 . of intermeshing-engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
- F04C 18/082 .. {Details specially related to intermeshing engagement type pumps}
- F04C 18/084 ... {Toothed wheels}

F04C 18/086	...	{Carter}
F04C 18/088	...	{ Elements in the toothed wheels or the carter for relieving the pressure of fluid imprisoned in the zones of engagement}
F04C 18/10	..	of internal-axis type with the outer member having more teeth or tooth equivalents, e.g. rollers, than the inner member
F04C 18/103	...	{with a crescent shaped filler element, located between the inner and outer intermeshing elements}
F04C 18/107	...	with helical teeth
F04C 18/1075	{the inner and outer member having a different number of threads and one of the two being made of elastic material, e.g. Moineau type}
F04C 18/113	...	the inner member carrying rollers intermeshing with the outer member
F04C 18/12	..	of other than internal-axis type
F04C 18/123	...	{with radially or approximately radially from the rotor body extending tooth-like elements, co-operating with recesses in the other rotor, e.g. one tooth}
F04C 18/126	...	{with radially from the rotor body extending elements, not necessarily co-operating with corresponding recesses in the other rotor, e.g. lobes, Roots type}
F04C 18/14	...	with toothed rotary pistons
F04C 18/16	with helical teeth, e.g. chevron-shaped, screw type {(for non-parallel axes of movement F04C 18/48)}
F04C 18/165	{having more than two rotary pistons with parallel axes}
F04C 18/18	with similar tooth forms (F04C 18/16 takes precedence)
F04C 18/20	with dissimilar tooth forms (F04C 18/16 takes precedence)
F04C 18/22	.	of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth equivalents than the outer member
F04C 18/24	.	of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions
F04C 18/26	..	of internal-axis type
F04C 18/28	..	of other than internal-axis type
F04C 18/30	.	having the characteristics covered by two or more of groups F04C 18/02 , F04C 18/08 , F04C 18/22 , F04C 18/24 , F04C 18/48 , or having the characteristics covered by one of these groups together with some other type of movement between co-operating members
F04C 18/32	..	having both the movement defined in group F04C 18/02 and relative reciprocation between the co-operating members
F04C 18/321	...	{ with vanes hinged to the inner member and reciprocating with respect to the inner member}
F04C 18/322	...	{ with vanes hinged to the outer member and reciprocating with respect to the outer member}
F04C 18/324	...	with vanes hinged to the inner member and reciprocating with respect to the outer member
F04C 18/328	and hinged to the outer member
F04C 18/332	...	with vanes hinged to the outer member and reciprocating with respect to the inner member
F04C 18/336	and hinged to the inner member

- F04C 18/34 .. having the movement defined in group [F04C 18/08](#) or [F04C 18/22](#) and relative reciprocation between the co-operating members
- F04C 18/344 ... with vanes reciprocating with respect to the inner member
- F04C 18/3441 {the inner and outer member being in contact along one line or continuous surface substantially parallel to the axis of rotation}
- F04C 18/3442 {the surfaces of the inner and outer member, forming the inlet and outlet opening}
- F04C 18/3443 {with a separation element located between the inlet and outlet opening}
- F04C 18/3445 {the vanes having the form of rollers, slippers or the like}
- F04C 18/3446 {the inner and outer member being in contact along more than one line or surface}
- F04C 18/3447 {the vanes having the form of rollers, slippers or the like}
- F04C 18/3448 {with axially movable vanes}
- F04C 18/348 the vanes positively engaging, with circumferential play, an outer rotatable member
- F04C 18/352 the vanes being pivoted on the axis of the outer member
- F04C 18/356 ... with vanes reciprocating with respect to the outer member
- F04C 18/3562 {the inner and outer member being in contact along one line or continuous surfaces substantially parallel to the axis of rotation}
- F04C 18/3564 {the surfaces of the inner and outer member, forming the working space, being surfaces of revolution}
- F04C 18/3566 {the inner and outer member being in contact along more than line or surface}
- F04C 18/3568 {with axially movable vanes}
- F04C 18/36 .. having both the movement defined in groups [F04C 18/22](#) and [F04C 18/24](#)
- F04C 18/38 .. having the movement defined in group [F04C 18/02](#) and having a hinged member ([F04C 18/32](#) takes precedence)
- F04C 18/39 ... with vanes hinged to the inner as well as to the outer member
- F04C 18/40 .. having the movement defined in group [F04C 18/08](#) or [F04C 18/22](#) and having a hinged member
- F04C 18/44 ... with vanes hinged to the inner member
- F04C 18/46 ... with vanes hinged to the outer member
- F04C 18/48 . Rotary-piston pumps with non-parallel axes of movement of co-operating members
- F04C 18/50 .. the axes being arranged at an angle of 90 degrees
- F04C 18/52 ... of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
- F04C 18/54 .. the axes being arranged otherwise than at an angle of 90 degrees
- F04C 18/56 ... of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
- F04C 18/565 {the axes of cooperating members being on the same plane}
- F04C 19/00 Rotary-piston pumps with fluid ring or the like, specially adapted for elastic fluids**
- F04C 19/001 . {General arrangements, plants, flowsheets}

- F04C 19/002 . {with rotating outer members}
- F04C 19/004 . {Details concerning the operating liquid, e.g. nature, separation, cooling, cleaning, control of the supply}
- F04C 19/005 . {Details concerning the admission or discharge}
- F04C 19/007 . . {Port members in the form of side plates}
- F04C 19/008 . . {Port members in the form of conical or cylindrical pieces situated in the centre of the impeller}

F04C 21/00 Oscillating-piston pumps specially adapted for elastic fluids

- F04C 21/002 . {the piston oscillating around a fixed axis}
- F04C 21/005 . {the piston oscillating in the space, e.g. around a fixed point (rotary-piston pumps with non-parallel axes of rotation between co-operating members [F04C 18/48](#))}
- F04C 21/007 . {the points of the moving element describing approximately an alternating movement in axial direction with respect to the other element}

F04C 23/00 Combinations of two or more pumps, each being of rotary-piston or oscillating-piston type, specially adapted for elastic fluids; Pumping installations specially adapted for elastic fluids; Multi-stage pumps specially adapted for elastic fluids ([F04C 25/00](#) takes precedence)

NOTE

Multi-stage pumps or compressors with stages connected in series or in parallel are not considered as having complementary function

- F04C 23/001 . {of similar working principle}
- F04C 23/003 . . {having complementary function}
- F04C 23/005 . {of dissimilar working principle}
- F04C 23/006 . . {having complementary function}
- F04C 23/008 . {Hermetic pumps}

NOTE

Multi-stage steam engines, motors, pumps or compressors with stages connected in series or in parallel are not considered as having complementary function

- F04C 23/02 . Pumps characterised by combination with or adaptation to specific driving engines or motors ([predominant aspects of the engines or motors, see the relevant classes](#))

F04C 25/00 Adaptations of pumps for special use of pumps for elastic fluids

- F04C 25/02 . for producing high vacuum ([sealing arrangements F04C 27/00](#); [silencing F04C 29/06](#))

F04C 27/00 Sealing arrangements in rotary-piston pumps specially adapted for elastic fluids

- F04C 27/001 . {Radial sealings for working fluid}
- F04C 27/002 . . {of rigid material}
- F04C 27/003 . . {of resilient material}
- F04C 27/004 . . {Radial sealing elements specially adapted for intermeshing-engagement type pumps, e.g. gear pumps}
- F04C 27/005 . {Axial sealings for working fluid}
- F04C 27/006 . . {Elements specially adapted for sealing of the lateral faces of intermeshing-engagement type pumps, e.g. gear pumps}
- F04C 27/007 . {Sealings for working fluid between radially and axially moving parts}
- F04C 27/008 . { for other than working fluid, i.e. the sealing arrangements are not between working chambers of the machine}
- F04C 27/009 . . {Shaft sealings specially adapted for pumps}
- F04C 27/02 . Liquid sealing for high-vacuum pumps {or for compressors}

F04C 28/00 Control of, monitoring of, or safety arrangements for, pumps or pumping installations specially adapted for elastic fluids

- F04C 28/02 . specially adapted for several pumps connected in series or in parallel
- F04C 28/04 . specially adapted for reversible pumps
- F04C 28/06 . specially adapted for stopping, starting, idling or no-load operation
- F04C 28/065 . . { Capacity control using a multiplicity of units or pumping capacities, e.g. multiple chambers, individually switchable or controllable}
- F04C 28/08 . characterised by varying the rotational speed
- F04C 28/10 . characterised by changing the positions of the inlet or outlet openings with respect to the working chamber
- F04C 28/12 . . using sliding valves
- F04C 28/125 . . . {with sliding valves controlled by the use of fluid other than the working fluid}
- F04C 28/14 . . using rotating valves
- F04C 28/16 . . using lift valves
- F04C 28/18 . characterised by varying the volume of the working chamber ([by changing the positions of inlet or outlet openings F04C 28/10](#))
- F04C 28/185 . . { by varying the useful pumping length of the cooperating members in the axial direction}
- F04C 28/20 . . by changing the form of the inner or outer contour of the working chamber

- F04C 28/22 . . . by changing the eccentricity between cooperating members
- F04C 28/24 . . characterised by using valves regulating pressure or flow rate, e.g. discharge valves { unloading valves}(F04C 28/10 takes precedence)
- F04C 28/26 . . . using bypass channels
- F04C 28/265 . . . {being obtained by displacing a lateral sealing face}
- F04C 28/28 . . Safety arrangements; Monitoring
- F04C 29/00** **Component parts, details or accessories of pumps or pumping installations, not provided for in groups F04C 18/00 to F04C 28/00**
- F04C 29/0007 . . {Injection of a fluid in the working chamber for sealing, cooling and lubricating (sealing only F04C 27/00; lubrication only F04C 29/02; cooling F02B 47/02, F02D 21/00, F02M 25/00)}
- F04C 29/0014 . . . {with control systems for the injection of the fluid}
- F04C 29/0021 . . {Systems for the equilibration of forces acting on the pump}(interstice adjustment other than by fluid pressure F01C 21/102)
- F04C 29/0028 . . . {Internal leakage control}
- F04C 29/0035 . . . {Equalization of pressure pulses (silencing F04C 29/06)}
- F04C 29/0042 . . {Driving elements, brakes, couplings, transmissions specially adapted for pumps (brakes, couplings, transmissions per se F16, B60)}
- F04C 29/005 . . . {Means for transmitting movement from the prime mover to driven parts of the pump, e.g. clutches, couplings, transmissions}
- F04C 29/0057 . . . {for eccentric movement}
- F04C 29/0064 . . . {Magnetic couplings}
- F04C 29/0071 . . . {Couplings between rotors and input or output shafts acting by interengaging or mating parts, i.e. positive coupling of rotor and shaft}
- F04C 29/0078 . . . {Fixing rotors on shafts, e.g. by clamping together hub and shaft}
- F04C 29/0085 . . . {Prime movers}
- F04C 29/0092 . . {Removing solid or liquid contaminants from the gas under pumping, e.g. by filtering or deposition; Purging; Scrubbing; Cleaning}
- F04C 29/02 . . Lubrication (of machines or engines in general F01M); Lubricant separation (separation in general B01D)
- F04C 29/021 . . . {Control systems for the circulation of the lubricant}
- F04C 29/023 . . . {Lubricant distribution through a hollow driving shaft (F04C 29/025 takes precedence)}
- F04C 29/025 . . . {using a lubricant pump}
- F04C 29/026 . . . {Lubricant separation}
- F04C 29/028 . . . {Means for improving or restricting lubricant flow}
- F04C 29/04 . . Heating; Cooling (of machines or engines in general F01P); Heat insulation (heat insulation in general F16L 59/00)
- F04C 29/042 . . . {by injecting a fluid (injection of fluid for sealing, cooling or lubrication F04C 29/0007)}

- F04C 29/045 .. {of the electric motor in hermetic pumps}
- F04C 29/047 .. { Cooling of electronic devices installed inside the pump housing, e.g. inverters}

WARNING

[N: WARNING this group is pending a reorganisation, see also [F04C 29/04](#)

- F04C 29/06 . Silencing (gas-flow silencers or exhaust apparatus for machines or engines in general F01N)

WARNING

{ WARNING Subgroups [F04C 29/061](#) to [F04C 29/068](#) pending a reorganisation, see also [F04C 29/06](#)}

- F04C 29/061 .. { Silencers using overlapping frequencies, e.g. Helmholtz resonators}
- F04C 29/063 .. { Sound absorbing materials}
- F04C 29/065 .. { Noise dampening volumes, e.g. muffler chambers}
- F04C 29/066 ... { with means to enclose the source of noise}
- F04C 29/068 .. { the silencing means being arranged inside the pump housing}
- F04C 29/12 . Arrangements for admission or discharge of the working fluid, e.g. constructional features of the inlet or outlet
- F04C 29/122 .. {Arrangements for supercharging the working space (similar arrangements for internal combustion engines [F02B 33/00](#), [F02B 37/00](#))}
- F04C 29/124 .. {with inlet and outlet valves specially adapted for rotary or oscillating piston pumps}
- F04C 29/126 ... {of the non-return type}
- F04C 29/128 {of the elastic type, e.g. reed valves}

F04C 2210/00**Fluid**

- F04C 2210/10 . working
- F04C 2210/1005 .. Air
- F04C 2210/1011 .. Amine
- F04C 2210/1016 .. Blood
- F04C 2210/1022 .. C3HmFn
- F04C 2210/1027 .. CO2
- F04C 2210/1033 .. Concrete
- F04C 2210/1038 .. Cooking oil
- F04C 2210/1044 .. Fuel
- F04C 2210/105 .. Helium (He)
- F04C 2210/1055 .. Hydrogen (H2)
- F04C 2210/1061 .. LPG
- F04C 2210/1066 .. Nitrogen (N2)

F04C 2210/1072	..	Oxygen (O2)
F04C 2210/1077	..	Steam
F04C 2210/1083	..	Urea
F04C 2210/1088	..	Vegetable oil
F04C 2210/1094	..	Water
F04C 2210/12	.	auxiliary
F04C 2210/122	..	Nitrogen (N2)
F04C 2210/124	..	Sodium (Na)
F04C 2210/126	..	Tin
F04C 2210/128	..	Water
F04C 2210/14	.	Lubricant
F04C 2210/142	..	Ester
F04C 2210/145	..	PAG
F04C 2210/147	..	Water
F04C 2210/20	.	liquid, i.e. incompressible
F04C 2210/201	..	DME
F04C 2210/203	..	Fuel
F04C 2210/205	..	Ink
F04C 2210/206	..	Oil
F04C 2210/208	..	Water
F04C 2210/22	.	gaseous, i.e. compressible
F04C 2210/221	..	Air
F04C 2210/222	..	Carbon dioxide (CO2)
F04C 2210/224	..	Hydrogen (H2)
F04C 2210/225	..	Nitrogen (N2)
F04C 2210/227	..	Steam
F04C 2210/228	..	Vapour
F04C 2210/24	.	mixed, e.g. two-phase fluid
F04C 2210/242	..	Steam
F04C 2210/245	..	Vapour
F04C 2210/247	..	Water
F04C 2210/26	.	Refrigerants with particular properties, e.g. HFC- 134a
F04C 2210/261	..	Carbon dioxide (CO2)
F04C 2210/263	..	HFO1234YF
F04C 2210/265	..	Ammoniac (NH3)
F04C 2210/266	..	Propane
F04C 2210/268	..	R32

- F04C 2210/40 . Properties
- F04C 2210/42 . . magnetic or ferromagnetic; Ferrofluids
- F04C 2210/44 . . Viscosity
- F04C 2210/60 . Condition
- F04C 2210/62 . . Purity

F04C 2220/00 Application

- F04C 2220/10 . Vacuum
- F04C 2220/12 . . Dry running
- F04C 2220/20 . Pumps with means for separating and evacuating the gaseous phase
- F04C 2220/22 . for very low temperatures, i.e. cryogenic
- F04C 2220/24 . for metering throughflow
- F04C 2220/26 . for step-by-step output movement
- F04C 2220/28 . for pulsed fluid flow
- F04C 2220/30 . Use in a chemical vapor deposition (CVD) process or in a similar process
- F04C 2220/40 . Pumps with means for venting areas other than the working chamber, e.g. bearings, gear chambers, shaft seals
- F04C 2220/50 . Pumps with means for introducing gas under pressure for ballasting

F04C 2230/00 Manufacture

NOTE

Manufacture comprises also treatment, assembly or disassembly methods, repairing, handling or the like.

- F04C 2230/10 . by removing material
- F04C 2230/101 . . by electrochemical methods
- F04C 2230/102 . . by spark erosion methods
- F04C 2230/103 . . using lasers
- F04C 2230/20 . essentially without removing material
- F04C 2230/21 . . by casting
- F04C 2230/22 . . by sintering
- F04C 2230/23 . . by permanently joining parts together

F04C 2230/231	... by welding
F04C 2230/24	.. by extrusion
F04C 2230/25	.. by forging
F04C 2230/26	.. by rolling
F04C 2230/27	.. by hydroforming
F04C 2230/40	. Heat treatment
F04C 2230/41	.. Hardening; Annealing
F04C 2230/60	. Assembly methods
F04C 2230/601	.. Adjustment
F04C 2230/602	.. Gap; Clearance
F04C 2230/603	.. Centering; Aligning
F04C 2230/604	.. Mounting devices for pumps or compressors
F04C 2230/605	.. Balancing
F04C 2230/70	. Disassembly methods
F04C 2230/80	. Repairing methods
F04C 2230/85	. Methods for improvement by repair or exchange of parts
F04C 2230/90	. Improving properties of machine parts
F04C 2230/91	.. Coating
F04C 2230/92	.. Surface treatment
F04C 2240/00	Components
F04C 2240/10	. Stators
F04C 2240/102	.. with means for discharging condensate or liquid separated from the gas pumped
F04C 2240/20	. Rotors
F04C 2240/30	. Casings or housings
F04C 2240/40	. Electric motor
F04C 2240/401	.. Linear motor
F04C 2240/402	.. Plurality of electronically synchronised motors
F04C 2240/403	.. with inverter for speed control
F04C 2240/45	. Hybrid prime mover
F04C 2240/50	. Bearings
F04C 2240/51	.. for cantilever assemblies
F04C 2240/52	.. for assemblies with supports on both sides
F04C 2240/54	.. Hydrostatic or hydrodynamic bearing assemblies specially adapted for rotary

	positive displacement pumps or compressors
F04C 2240/56	.. Bearing bushings or details thereof
F04C 2240/60	. Shafts
F04C 2240/601	.. Shaft flexion
F04C 2240/603	.. with internal channels for fluid distribution, e.g. hollow shaft
F04C 2240/605	.. Shaft sleeves or details thereof
F04C 2240/70	. Use of multiplicity of similar components; Modular construction
F04C 2240/80	. Other components
F04C 2240/801	.. Wear plates
F04C 2240/802	.. Liners
F04C 2240/803	.. Electric connectors or cables; Fittings therefor
F04C 2240/804	.. Accumulators for refrigerant circuits
F04C 2240/805	.. Fastening means, e.g. bolts
F04C 2240/806	.. Pipes for fluids; Fittings therefor
F04C 2240/807	.. Balance weight, counterweight
F04C 2240/808	.. Electronic circuits (e.g. inverters) installed inside the machine
F04C 2240/809	.. Lubricant sump
F04C 2240/81	.. Sensor, e.g. electronic sensor for control or monitoring
F04C 2240/811	.. Actuator for control, e.g. pneumatic, hydraulic, electric
F04C 2250/00	Geometry
F04C 2250/10	. of the inlet or outlet
F04C 2250/101	.. of the inlet
F04C 2250/102	.. of the outlet
F04C 2250/20	. of the rotor
F04C 2250/201	.. conical shape
F04C 2250/30	. of the stator
F04C 2250/301	.. compression chamber profile defined by a mathematical expression or by parameters
F04C 2270/00	Control; Monitoring or safety arrangements
F04C 2270/01	. Load
F04C 2270/015	.. Controlled or regulated
F04C 2270/02	. Power
F04C 2270/025	.. Controlled or regulated
F04C 2270/03	. Torque

F04C 2270/035	..	Controlled or regulated
F04C 2270/04	.	Force
F04C 2270/041	..	Controlled or regulated
F04C 2270/042	..	radial
F04C 2270/0421	...	Controlled or regulated
F04C 2270/0422	...	centrifugal
F04C 2270/04225	Controlled or regulated
F04C 2270/044	..	axial
F04C 2270/0445	...	Controlled or regulated
F04C 2270/05	.	Speed
F04C 2270/051	..	Controlled or regulated
F04C 2270/052	..	angular
F04C 2270/0525	...	Controlled or regulated
F04C 2270/054	..	linear
F04C 2270/0545	...	Controlled or regulated
F04C 2270/06	.	Acceleration
F04C 2270/065	..	Controlled or regulated
F04C 2270/07	.	Electric current
F04C 2270/075	..	Controlled or regulated
F04C 2270/08	.	Amplitude of electric current
F04C 2270/085	..	Controlled or regulated
F04C 2270/09	.	Electric current frequency
F04C 2270/095	..	Controlled or regulated
F04C 2270/10	.	Voltage
F04C 2270/105	..	Controlled or regulated
F04C 2270/11	.	Magnetic flux
F04C 2270/115	..	Controlled or regulated
F04C 2270/12	.	Vibration
F04C 2270/125	..	Controlled or regulated
F04C 2270/13	.	Noise
F04C 2270/135	..	Controlled or regulated
F04C 2270/14	.	Pulsations
F04C 2270/145	..	Controlled or regulated
F04C 2270/15	.	Resonance

F04C 2270/155	..	Controlled or regulated
F04C 2270/16	.	Wear
F04C 2270/165	..	Controlled or regulated
F04C 2270/17	.	Tolerance; Play; Gap
F04C 2270/175	..	Controlled or regulated
F04C 2270/18	.	Pressure
F04C 2270/185	..	Controlled or regulated
F04C 2270/19	.	Temperature
F04C 2270/195	..	Controlled or regulated
F04C 2270/20	.	Flow
F04C 2270/205	..	Controlled or regulated
F04C 2270/21	.	Pressure difference
F04C 2270/215	..	Controlled or regulated
F04C 2270/22	.	Temperature difference
F04C 2270/225	..	Controlled or regulated
F04C 2270/23	.	Working cycle timing control
F04C 2270/24	.	Level of liquid, e.g. lubricant or cooling liquid
F04C 2270/40	.	Conditions across a pump or machine
F04C 2270/42	.	Conditions at the inlet of a pump or machine
F04C 2270/44	.	Conditions at the outlet of a pump or machine
F04C 2270/46	.	Conditions in the working chamber
F04C 2270/48	.	Conditions of a reservoir linked to a pump or machine
F04C 2270/50	.	Conditions before a throttle
F04C 2270/52	.	Conditions after a throttle
F04C 2270/54	.	Conditions in a control cylinder/piston unit
F04C 2270/56	.	Number of pump/machine units in operation
F04C 2270/58	.	Valve parameters
F04C 2270/585	..	Controlled or regulated
F04C 2270/60	.	Prime mover parameters

- F04C 2270/605
 - .. Controlled or regulated
- F04C 2270/70
 - . Safety, emergency conditions or requirements
- F04C 2270/701
 - .. Cold start
- F04C 2270/72
 - .. preventing reverse rotation
- F04C 2270/78
 - . Warnings
- F04C 2270/782
 - .. Sound
- F04C 2270/784
 - .. Light
- F04C 2270/80
 - . Diagnostics
- F04C 2270/86
 - . Detection
- F04C 2270/90
 - . Remote control, e.g. wireless, via LAN, by radio, or by a wired connection from a central computer
- F04C 2280/00**
 - Arrangements for preventing or removing deposits or corrosion**
- F04C 2280/02
 - . Preventing solid deposits in pumps, e.g. in vacuum pumps with chemical vapour deposition (CVD) processes
- F04C 2280/04
 - . Preventing corrosion