

CPC**COOPERATIVE PATENT CLASSIFICATION****B67C****CLEANING, FILLING WITH LIQUIDS OR SEMILIQUIDS, OR EMPTYING, OF BOTTLES, JARS, CANS, CASKS, BARRELS, OR SIMILAR CONTAINERS, NOT OTHERWISE PROVIDED FOR; FUNNELS****B67C 3/00**

Bottling liquids or semiliquids; Filling jars or cans with liquids or semiliquids using bottling or like apparatus; Filling casks or barrels with liquids or semiliquids (filling containers with liquids or semiliquids using apparatus other than bottling or like apparatus [B65B 3/00](#))

B67C 3/001

. {Cleaning of filling devices }

B67C 3/002

.. {using cups or dummies to be placed under the filling heads }

B67C 3/004

... {permanently attached to the filling machine and movable between a rest and a working position }

B67C 3/005

.. { Cleaning outside parts of filling devices }

B67C 3/007

. {Applications of control, warning or safety devices in filling machinery ([flow-control B67C 3/28](#)) }

B67C 3/008

. { Bottling or like apparatus specially adapted to be transported, e.g. positioned on a truck or in a container }

B67C 3/02

. Bottling liquids or semiliquids; Filling jars or cans with liquids or semiliquids using bottling or like apparatus

B67C 3/023

.. { Filling multiple liquids in a container ([B67C 3/208](#) takes precedence) }

B67C 3/026

... { Filling the liquids simultaneously }

B67C 3/04

.. without applying pressure

B67C 3/045

... { Apparatus specially adapted for filling bottles with hot liquids }

B67C 3/06

.. using counterpressure, i.e. filling while the container is under pressure

B67C 3/065

... {Filling siphons, e.g. carbonating beverages during filling (siphons [B67D 1/0456](#)) }

B67C 3/08

... and subsequently lowering the counterpressure

B67C 3/10

... preliminary filling with inert gases, e.g. carbon dioxide

B67C 3/12

... Pressure-control devices

B67C 3/14

... specially adapted for filling with hot liquids

B67C 3/16

.. using suction

B67C 3/18

.. using siphoning arrangements

B67C 3/20

.. with provision for metering the liquids to be introduced, e.g. when adding syrups ([measuring volume, or volume flow, in general G01F](#))

B67C 3/202

... {by weighing }

B67C 3/204

... {using dosing chambers }

B67C 3/206

... {using arrangements of cylinders and pistons ([B67C 3/208](#) takes precedence) }

B67C 3/208

... {specially adapted for adding small amounts of additional liquids, e.g. syrup }

B67C 3/22	..	Details
B67C 3/222	...	{Head-space air removing devices, e.g. by inducing foam }
B67C 3/223	{by squeezing the container elastically }
B67C 3/225	...	{ Means for filling simultaneously, e.g. in a rotary filling apparatus or multiple rows of containers }
B67C 3/24	...	Devices for supporting or handling bottles (transport or storing devices in general B65G)
B67C 3/242	{engaging with bottle necks (B67C 3/26 takes precedence) }
B67C 3/244	{Bottle lifting devices actuated by jacks, e.g. hydraulic, pneumatic (B67C 3/242 takes precedence) }
B67C 3/246	{Bottle lifting devices actuated by cams (B67C 3/242 takes precedence) }
B67C 3/248	{Bottle lifting devices actuated by threads B67C 3/242 takes precedence }
B67C 3/26	...	Filling-heads; Means for engaging filling-heads with bottle necks
B67C 3/2608	{comprising anti-dripping means }
B67C 3/2611	{to prevent dripping from sources other than the filling product, e.g. deflectors for vapours condensed on the outer surface of the filling device }
B67C 3/2614	{specially adapted for counter-pressure filling }
B67C 3/2617	{the liquid valve being opened by mechanical or electrical actuation }
B67C 3/262	{and the filling operation stopping when the liquid rises to a level at which it closes a vent opening }
B67C 3/2622	{and the filling operation stopping when probes, e.g. electrical or optical probes, sense the wanted liquid level (level control in general G01F) }
B67C 3/2625	{the liquid valve being opened automatically when a given counter-pressure is obtained in the container to be filled }
B67C 3/2628	{and the filling operation stopping when the liquid rises to a level at which it closes a vent opening }
B67C 3/2631	{and the filling operation stopping when probes, e.g. electrical or optical probes, sense the wanted liquid level (level control in general G01F) }
B67C 3/2634	{specially adapted for vacuum or suction filling }
B67C 3/2637	{comprising a liquid valve opened by relative movement between the container and the filling head }
B67C 3/264	{and the filling operation being carried out manually }
B67C 3/2642	{specially adapted for sterilising prior to filling }
B67C 3/28	...	Flow-control devices, e.g. using valves ({ B67C 3/2617 , B67C 3/2625 , B67C 3/2637 take precedence }; valves in general F16K)
B67C 3/281	{Profiled valve bodies for smoothing the flow at the outlet of the filling nozzle }
B67C 3/282	{ related to filling level control (B67C 3/2617 , B67C 3/2625 take precedence) }
B67C 3/283	{ using pressure sensing means }
B67C 3/284	{ using non-liquid contact sensing means (B67C 3/283 takes precedence) }
B67C 3/285	{ using liquid contact sensing means (B67C 3/283 takes precedence) }
B67C 3/286	{ related to flow rate control, i.e. controlling slow and fast filling phases }

B67C 3/287 { related to flow control using predetermined or real-time calculated parameters }
B67C 3/288 { using master-slave controls }
B67C 3/30	. Filling of barrels or casks
B67C 3/32	.. using counterpressure, i.e. filling while the container is under pressure
B67C 3/34	.. Devices for engaging filling-heads with filling-apertures
B67C 7/00	Concurrent cleaning, filling, and closing of bottles; Processes or devices for at least two of these operations
B67C 7/0006	. {Conveying; Synchronising }
B67C 7/0013	.. {Synchronising }
B67C 7/002	.. {General lay-out of bottle-handling machines }
B67C 7/0026	.. {the containers travelling along a linear path }
B67C 7/0033	... {the operation being performed batch-wise }
B67C 7/004	.. {the containers travelling along a circular path }
B67C 7/0046	... {Infeed and outfeed devices }
B67C 7/0053 {using grippers (for supporting bottle necks during filling B67C 3/242) }
B67C 7/0073	. {Sterilising, aseptic filling and closing (B67C 3/2642 takes precedence) }
B67C 7/008	.. {comprising a cleaning step between two closing steps }
B67C 7/0086	.. {Sterilisation being restricted to the area of application of the closure }
B67C 7/0093	. {Lever action devices operated by hand or foot }
B67C 9/00	Devices for emptying bottles, not otherwise provided for {during preparation of alcoholic beverages except beer C12G 1/00 }
B67C 11/00	Funnels, e.g. for liquids (filter funnels B01D 23/28; volume flow-meters G01F)
B67C 11/02	. without discharge valves
B67C 11/04	. with non-automatic discharge valves
B67C 11/06	. with automatic discharge valves
B67C 11/063	.. { for preventing spilling or dripping }
B67C 11/066	.. { for preventing overflow of the filled container }
B67C 2003/00	Bottling liquids or semiliquids; Filling jars or cans with liquids or semiliquids using bottling or like apparatus; Filling casks or barrels with liquids or semiliquids (filling containers with liquids or semiliquids using apparatus other than bottling or like apparatus B65B 3/00)
B67C 2003/02	. Bottling liquids or semiliquids; Filling jars or cans with liquids or semiliquids using bottling or like apparatus

B67C 2003/22	..	Details
B67C 2003/221	...	Automatic exchange of components
B67C 2003/226	...	Additional process steps or apparatuses related to filling with hot liquids, e.g. after-treatment
B67C 2003/227	...	Additional apparatus related to blow-moulding of the containers, e.g. a complete production line forming filled containers from preforms
B67C 2003/228	...	Aseptic features
B67C 2003/26	...	Filling-heads; Means for engaging filling-heads with bottle necks
B67C 2003/2602	Details of vent-tubes
B67C 2003/2605	Piston-like check valves
B67C 2003/2645	Means to avoid overfilling by preventing gas returning from the container into the filling tank via the liquid valve, e.g. mesh screens
B67C 2003/2648	Inflatable gaskets for sealingly engaging bottle necks or bodies
B67C 2003/2651	The liquid valve being carried by the vent tube
B67C 2003/2654	specially adapted for bottom filling, e.g. the liquid valve being located at the lowest part of the vent tube
B67C 2003/2657	specially adapted for filling cans
B67C 2003/266	Means for centering the container with the filling head
B67C 2003/2662	with means for detecting the presence of a container
B67C 2003/2665	Means for locking the filling head in a given position once engaged by a container
B67C 2003/2668	Means for adapting the filling head to various sizes of containers
B67C 2003/2671	Means for preventing foaming of the liquid
B67C 2003/2674	by creating a conical shaped flow directed to the container wall at the container neck height
B67C 2003/2677	by means of a deflector
B67C 2003/268	by means of a flow channel integral with the filling nozzle
B67C 2003/2682	by creating a conical shaped flow directed to the container wall just above the container bottom
B67C 2003/2685	Details of probes
B67C 2003/2688	Means for filling containers in defined atmospheric conditions
B67C 2003/2691	by enclosing one container in a chamber
B67C 2003/2694	by enclosing a set of containers in a chamber
B67C 2003/2697	by enclosing the container partly in a chamber
B67C 2007/00		Concurrent cleaning, filling, and closing of bottles; Processes or devices for at least two of these operations
B67C 2007/0006	.	{Conveying; Synchronising }
B67C 2007/006	..	Devices particularly adapted for container filling
B67C 2007/0066	..	Devices particularly adapted for container closing
B67C 2011/00		Funnels, e.g. for liquids (filter funnels B01D 23/28; volume flow-meters G01F)
B67C 2011/02	.	without discharge valves

- B67C 2011/022 . . for draining oil from engines
- B67C 2011/025 . . . with integral tool for opening the draining plug
- B67C 2011/027 . . for filling oil into engines

- B67C 2011/20 . comprising closures, e.g. stoppers, caps or lids

- B67C 2011/30 . comprising venting means

- B67C 2011/40 . comprising level indicating means