

CPC**COOPERATIVE PATENT CLASSIFICATION****H05G**

X-RAY TECHNIQUE (apparatus for radiation diagnosis [A61B 6/00](#); X-ray therapy [A61N](#) ; testing by X-rays [G01N](#) ; apparatus for X-ray photography [G03B](#) ; filters, conversion screens, microscopes [G21K](#) ; X-ray tubes [H01J 35/00](#); TV systems having X-ray input [H04N 5/321](#))

WARNING

The following IPC group is not used in the CPC scheme. [H05G 1/61](#) covered by [H05G 1/60](#)

H05G 1/00

X-ray apparatus involving X-ray tubes; circuits therefor

H05G 1/02

. Constructional details

H05G 1/025

.. { Means for cooling the X-ray tube or the generator }

H05G 1/04

.. Mounting the X-ray tube within a closed housing

H05G 1/06

... X-ray tube and at least part of the power supply apparatus being mounted within the same housing

H05G 1/08

. Electrical details

H05G 1/085

.. { Circuit arrangements particularly adapted for X-ray tubes having a control grid }

H05G 1/10

.. Power supply arrangements for feeding the X-ray tube { supply circuits with converters in general [H02M](#) ; supply circuits for emitters and amplifiers [H04B 1/16](#) to [H04B 1/1623](#) }

H05G 1/12

... with dc or rectified single-phase ac { or double-phase }

H05G 1/14

... with single-phase low-frequency ac { also when a rectifier element is in series with the X-ray tube }

H05G 1/16

.... Reducing the peak-inverse voltage

H05G 1/18

... with polyphase ac of low frequency { rectified }

H05G 1/20

... with high-frequency ac; with pulse trains { (pulse generators in general [H03K 3/00](#), [H03K 4/00](#)) }

H05G 1/22

... with single pulses

H05G 1/24

.... Obtaining pulses by using energy storage devices (pulse generators [H03K](#)) { current and voltage pulse generators [H03K 3/53](#) }

H05G 1/26

.. Measuring, controlling, protecting (measuring electric values [G01R](#) ; measuring X-ray intensity [G01T](#))

H05G 1/265

... { Measurements of current, voltage or power }

H05G 1/28

... Measuring or recording actual exposure time; Counting number of exposures; Measuring required exposure time

H05G 1/30

... Controlling

H05G 1/32

.... supply voltage of the X-ray apparatus or tube (regulating supply without reference to operating characteristics of the apparatus [G05F](#)) { voltage regulation in general [G05F](#) }

H05G 1/34

.... anode current, heater current, heater voltage of X-ray tube (regulating supply without reference to operating characteristics of the apparatus [G05F](#))

-) { [current regulation in general G05F](#) }
- H05G 1/36 temperature of anode; brightness of image { [power \(electrical temperature regulating in general G05D 23/19 \)](#) }
- H05G 1/38 exposure time { [time switches in general H01H 43/00 and subgroups](#) }
- H05G 1/40 using adjustable time-switch
- H05G 1/42 using arrangements for switching when a predetermined dose of radiation has been applied, e.g. in which the switching instant is determined by measuring the electrical energy supplied to the tube
- H05G 1/44 in which the switching instant is determined by measuring the amount of radiation directly { [dosimetry in general G01T 1/02](#) }
- H05G 1/46 Combined control of different quantities, e.g. exposure time as well as voltage or current
- H05G 1/48 Compensating the voltage drop occurring at the instant of switching-on of the apparatus ([regulating supply without reference to the operating characteristics of the apparatus G05F](#)) { [voltage regulation in general G05F](#) }
- H05G 1/50 Passing the tube current only during a restricted portion of the voltage waveform
- H05G 1/52 target size or shape; direction of electron beam, e.g. in tubes with one anode and more than one cathode
- H05G 1/54 Protecting { [or lifetime prediction](#) } ([overload protection combined with control H05G 1/46](#))
- H05G 1/56 . . . Switching-on; Switching-off
- H05G 1/58 . . . Switching arrangements for changing-over from one mode of operation to another, e.g. from radioscopy to radiography, from radioscopy to irradiation { [or from one tube voltage to an other](#) }
- H05G 1/60 . . . Circuit arrangements for obtaining a series of X-ray photographs or for X-ray cinematography
- H05G 1/62 . . . Circuit arrangements for obtaining X-ray photography at predetermined instants in the movement of an object, e.g. X-ray stroboscopy
- H05G 1/64 . . . Circuit arrangements for X-ray apparatus incorporating image intensifiers

WARNING

[Material provisionally in 97DP27; image intensifiers H01J 31/00](#)

- H05G 1/66 . . . Circuit arrangement for X-ray tubes with target movable relatively to the anode
- H05G 1/68 . . . Circuit arrangements for Lilienfield tubes; Circuit arrangements for gas-filled X-ray tubes
- H05G 1/70 . . . Circuit arrangements for X-ray tubes with more than one anode; Circuit arrangements for apparatus comprising more than one X ray tube { [or more than one cathode \(H05G 1/58 takes precedence \)](#) }

H05G 2/00 Apparatus or processes specially adapted for producing X-rays, not involving X-ray tubes, e.g. involving generation of a plasma (X-ray lasers H01S 4/00; plasma technique in general H05H)

- H05G 2/001 . { [X-ray radiation generated from plasma \(plasma for generation of electrons to be accelerated towards an anode H01J 35/00 \)](#) }
- H05G 2/003 . . { [being produced from a liquid or gas](#) }
- H05G 2/005 . . . { [containing a metal as principal radiation generating component](#) }

- H05G 2/006 . . . { details of the ejection system, e.g. constructional details of the nozzle }
- H05G 2/008 . . { involving a beam of energy, e.g. laser or electron beam in the process of exciting the plasma }