

CPC**COOPERATIVE PATENT CLASSIFICATION****F02F**

CYLINDERS, PISTONS OR CASINGS, FOR COMBUSTION ENGINES; ARRANGEMENTS OF SEALINGS IN COMBUSTION ENGINES (specially adapted for rotary-piston or oscillating-piston internal-combustion engines [F02B](#) ; specially adapted for gas-turbine plants [F02C](#) ; specially adapted for jet-propulsion plants [F02K](#))

NOTE

Attention is drawn to the notes preceding class [F01](#) .

In considering the relationship between class [F16](#) and subclass [F02F](#) , class [F16](#) will take precedence unless the subject-matter is specific to combustion engines.

F02F 1/00

Cylinders; Cylinder heads (in general [F16J](#))

[F02F 1/002](#)

. { Integrally formed cylinders and cylinder heads }

[F02F 1/004](#)

. { Cylinder liners ([F02F 1/08](#) , [F02F 1/16](#) take precedence) }

[F02F 1/02](#)

. having cooling means (cylinder heads [F02F 1/26](#))

[F02F 1/04](#)

.. for air cooling

[F02F 1/045](#)

... { Attachment of cylinders to crankcase }

[F02F 1/06](#)

... Shape or arrangement of cooling fins; Finned cylinders

[F02F 1/065](#)

.... { with means for directing or distributing cooling medium }

[F02F 1/08](#)

.... running-liner and cooling-part of cylinder being different parts or of different material

[F02F 1/10](#)

.. for liquid cooling

[F02F 1/102](#)

... { Attachment of cylinders to crankcase }

[F02F 1/108](#)

... { Siamese-type cylinders, i.e. cylinders cast together }

[F02F 1/12](#)

... Preventing corrosion of liquid-swept surfaces

[F02F 1/14](#)

... Cylinders with means for directing, guiding or distributing liquid stream

[F02F 1/16](#)

... Cylinder liners of wet type

[F02F 1/163](#)

.... { the liner being midsupported }

[F02F 1/166](#)

.... { Spacer decks }

[F02F 1/18](#)

. Other cylinders

[F02F 1/183](#)

.. { Oval or square cylinders }

[F02F 1/186](#)

.. { for use in engines with two or more pistons reciprocating within same cylinder (such engines per se [F02B 75/28](#)) }

[F02F 1/20](#)

.. characterised by constructional features providing for lubrication

[F02F 1/22](#)

.. characterised by having ports in cylinder wall for scavenging or charging

[F02F 1/24](#)

. Cylinder heads

- F02F 1/242 .. { Arrangement of spark plugs or injectors }
- F02F 1/243 .. { Cylinder heads and inlet or exhaust manifolds integrally cast together }
- F02F 1/26 .. having cooling means
- F02F 1/28 ... for air cooling
- F02F 1/30 Finned cylinder heads
- F02F 1/305 { the cylinder heads being of side valve type }
- F02F 1/32 the cylinder heads being of overhead valve type
- F02F 1/34 with means for directing or distributing cooling medium ([F02F 1/32](#) takes precedence)
- F02F 1/36 ... for liquid cooling
- F02F 1/365 { the cylinder heads being of side valve type }
- F02F 1/38 the cylinder heads being of overhead valve type
- F02F 1/40 Cylinder heads with means for directing, guiding, or distributing liquid stream ([F02F 1/38](#) takes precedence)
- F02F 1/42 .. Shape or arrangement of intake or exhaust channels in cylinder heads
- F02F 1/4214 ... { specially adapted for four or more valves per cylinder }
- F02F 1/4221 { particularly for three or more inlet valves (mechanisms for driving such valves [F01L 1/265](#)) }
- F02F 1/4228 ... { Helically-shaped channels } ([F02B 31/00](#) takes precedence)]
- F02F 1/4235 ... { of intake channels }
- F02F 1/4242 { with a partition wall inside the channel }
- F02F 1/425 { with a separate deviation element inside the channel }
- F02F 1/4257 { with an intake liner }
- F02F 1/4264 ... { of exhaust channels }
- F02F 1/4271 { with an exhaust liner }
- F02F 1/4285 ... { of both intake and exhaust channel }
- F02F 1/4292 { with liners ([F02F 1/4257](#) , [F02F 1/4271](#) take precedence) }

F02F 3/00 **Pistons (in general [F16J](#))**

- F02F 3/0015 . { Multi-part pistons }
- F02F 3/0023 .. { the parts being bolted or screwed together }
- F02F 3/003 .. { the parts being connected by casting, brazing, welding or clamping }
- F02F 3/0069 .. { the crown and skirt being interconnected by the gudgeon pin }
- F02F 3/0076 . { the inside of the pistons being provided with ribs or fins }
- F02F 3/0084 . { the pistons being constructed from specific materials }
- F02F 3/0092 .. { the material being steel-plate }
- F02F 3/02 . having means for accomodating or controlling heat expansion
- F02F 3/022 .. { the pistons having an oval circumference or non-cylindrical shaped skirts, e.g. oval ([F02F 3/025](#) , [F02F 3/027](#) take precedence) }
- F02F 3/025 .. { having circumferentially slotted piston skirts, e.g. T-slots }
- F02F 3/027 .. { the skirt wall having cavities }

- F02F 3/04 . . having expansion-controlling inserts
- F02F 3/042 . . . { the inserts consisting of reinforcements in the skirt interconnecting separate wall parts, e.g. rods or strips }
- F02F 3/045 . . . { the inserts being located in the crown }
- F02F 3/047 . . . { the inserts being located around the gudgeon pin bearings }
- F02F 3/06 . . . the inserts having bimetallic effect
- F02F 3/08 . . . the inserts being ring-shaped

- F02F 3/10 . having surface coverings ([F02F 3/02](#) takes precedence)
- F02F 3/105 . . { the coverings forming a double skirt }
- F02F 3/12 . . on piston heads
- F02F 3/14 . . . within combustion chambers

- F02F 3/16 . having cooling means
- F02F 3/18 . . the means being a liquid or solid coolant, e.g. sodium, in a closed chamber in piston
- F02F 3/20 . . the means being a fluid flowing through or along piston
- F02F 3/22 . . . the fluid being liquid
- F02F 3/225 { the liquid being directed into blind holes }

- F02F 3/24 . having means for guiding gases in cylinders, e.g. for guiding scavenging charge in two-stroke engines

- F02F 3/26 . having combustion chamber in piston head ([the surface thereof being covered F02F 3/14](#))

- F02F 3/28 . Other pistons with specially-shaped head
- F02F 3/285 . . { the head being provided with an insert located in or on the combustion-gas-swept surface }

- F02F 5/00** **Piston rings, e.g. associated with piston crown** { not used see [F16J 9/00](#) }

- F02F 7/00** **Casings, e.g. crankcases** ([engine casings in general F16M](#)) { or frames }

- F02F 7/0002 . { Cylinder arrangements }
- F02F 7/0004 . . { Crankcases of one-cylinder engines }
- F02F 7/0007 . . { Crankcases of engines with cylinders in line }
- F02F 7/0009 . . { Crankcases of opposed piston engines }
- F02F 7/0012 . . { Crankcases of V-engines }
- F02F 7/0014 . . { Crankcases of W-, deldic, or quadratic engines, or the like }
- F02F 7/0017 . . { Crankcases of radial engines }
- F02F 7/0019 . . { Cylinders and crankshaft not in one plane (deaxation) }

- F02F 7/0021 . { Construction }
- F02F 7/0024 . . { Casings for larger engines }
- F02F 7/0026 . . . { Casings for horizontal engines }

- F02F 7/0029 .. { Space-frames }
- F02F 7/0031 .. { Construction kit principle ([modular engines](#))}
- F02F 7/0034 .. { Built from sheet material and welded casings }
- F02F 7/0036 .. { Casings for two-stroke engines with scavenging conduits }
- F02F 7/0039 .. { Casings for small engines, especially with crankcase pumps }

- F02F 7/0043 . { Arrangements of mechanical drive elements }
- F02F 7/0046 .. { Shape of casings adapted to facilitate fitting or dismantling of engine parts }
- F02F 7/0048 .. { Tunnel-type frames }
- F02F 7/0051 .. { Crankcase pump engines }
- F02F 7/0053 .. { Crankshaft bearings fitted in the crankcase }
- F02F 7/0058 .. { Longitudinally or transversely separable crankcases }

- F02F 7/006 . { Camshaft or pushrod housings ([oil sumps F01M 11/0004](#))}

- F02F 7/0065 . { Shape of casings for other machine parts and purposes, e.g. utilisation purposes, safety }
- F02F 7/0068 .. { Adaptations for other accessories }
- F02F 7/007 .. { Adaptations for cooling }
- F02F 7/0073 .. { Adaptations for fitting the engine, e.g. front-plates or bell-housings }
- F02F 7/008 .. { Sound insulation ([see also F02B 77/13](#))}

- F02F 7/0082 . { Mounting of engine casings }

- F02F 7/0085 . { Materials for constructing engines or their parts }
- F02F 7/0087 .. { Ceramic materials }

- F02F 7/0095 . { Constructing engine casings ([welded casings F02F 7/0034](#))}

- F02F 11/00** **Arrangements of sealings in combustion engines** ([piston rings F02F 5/00](#) { not used, see [F16J 9/00](#) } ; sealings per se [F16J](#))

- F02F 11/002 . { involving cylinder heads }
- F02F 11/005 . { involving cylinder liners }
- F02F 11/007 . { involving rotary applications }

- F02F 2001/00** **Cylinders; Cylinder heads** ([in general F16J](#))

- F02F 2001/006 . having a ring at the inside of a liner or cylinder for preventing the deposit of carbon oil particles, e.g. oil scrapers

- F02F 2001/008 . Stress problems, especially related to thermal stress

- F02F 2001/02 . having cooling means ([cylinder heads F02F 1/26](#))
- F02F 2001/10 .. for liquid cooling

F02F 2001/104	...	using an open deck, i.e. the water jacket is open at the block top face
F02F 2001/106	...	using a closed deck, i.e. the water jacket is not open at the block top face
F02F 2001/24	.	Cylinder heads
F02F 2001/241	..	specially adapted to pent roof shape of the combustion chamber
F02F 2001/244	..	Arrangement of valve stems in cylinder heads
F02F 2001/245	...	the valve stems being orientated at an angle with the cylinder axis
F02F 2001/246	and orientated radially from the combustion chamber surface
F02F 2001/247	...	the valve stems being orientated in parallel with the cylinder axis
F02F 2001/248	..	Methods for avoiding thermal stress-induced cracks in the zone between valve seat openings
F02F 2001/249	..	with flame plate, e.g. insert in the cylinder head used as a thermal insulation between cylinder head and combustion chamber
F02F 2001/42	..	Shape or arrangement of intake or exhaust channels in cylinder heads
F02F 2001/4207	...	Arrangements with one conduit connected with two valves; Arrangements connecting one valve with two conduits
F02F 2001/4264	...	{ of exhaust channels }
F02F 2001/4278	Exhaust collectors
F02F 2003/00	Pistons (in general F16J)	
F02F 2003/0007	.	Monolithic pistons; One piece constructions; Casting of pistons
F02F 2003/0015	.	{ Multi-part pistons }
F02F 2003/003	..	{ the parts being connected by casting, brazing, welding or clamping }
F02F 2003/0038	...	by brazing
F02F 2003/0046	...	by crimping
F02F 2003/0053	...	by soldering
F02F 2003/0061	...	by welding
F02F 2007/00	Casings, e.g. crankcases (engine casings in general F16M) { or frames }	
F02F 2007/0021	.	{ Construction }
F02F 2007/0041	..	Fixing Bolts
F02F 2007/0043	.	{ Arrangements of mechanical drive elements }
F02F 2007/0053	..	{ Crankshaft bearings fitted in the crankcase }
F02F 2007/0056	...	using bearing beams, i.e. bearings interconnected by a beam or multiple beams
F02F 2007/006	.	{ Camshaft or pushrod housings (oil sumps F01M 11/0004) }
F02F 2007/0063	..	Head bolts; Arrangements of cylinder head bolts
F02F 2007/0065	.	{ Shape of casings for other machine parts and purposes, e.g. utilisation purposes, safety }
F02F 2007/0073	..	{ Adaptations for fitting the engine, e.g. front-plates or bell-housings }

- F02F 2007/0075 . . . Front covers
- F02F 2007/0078 . . . Covers for belt transmissions
- F02F 2007/0085 . { **Materials for constructing engines or their parts** }
- F02F 2007/009 . . Hypereutectic aluminum, e.g. aluminum alloys with high SI content
- F02F 2007/0092 . . Transparent materials
- F02F 2007/0097 . for large diesel engines
- F02F 2200/00 Manufacturing**
- F02F 2200/02 . Riveting
- F02F 2200/04 . Forging of engine parts
- F02F 2200/06 . Casting ([casting of pistons F02F 2003/0007](#))
- F02F 2200/08 . . using a lost model, e.g. foam casting
- F02F 2200/11 . using wrought materials, e.g. wrought steels
- F02F 2547/00**