

CPC**COOPERATIVE PATENT CLASSIFICATION****H03H****IMPEDANCE NETWORKS, e.g. RESONANT CIRCUITS; RESONATORS**

(measuring, testing [G01R](#); arrangements for producing a reverberation or echo sound [G10K 15/08](#) ; impedance networks or resonators consisting of distributed impedances, e.g. of the waveguide type, [H01P](#); control of amplification, e.g. bandwidth control of amplifiers, [H03G](#); tuning resonant circuits, e.g. tuning coupled resonant circuits, [H03J](#); networks for modifying the frequency characteristics of communication systems [H04B](#))

NOTE

This subclass covers :

networks comprising lumped impedance elements;

networks comprising distributed impedance elements together with lumped impedance elements;

networks comprising electromechanical or electro-acoustic elements;

networks simulating reactances and comprising discharge tubes or semiconductor devices;

constructions of electromechanical resonators.

In this subclass, the following expression is used with the meaning indicated:
"passive elements" means resistors, capacitors, inductors, mutual inductors or diodes.

Attention is drawn to the Notes following the titles of class [B81](#) and subclass [B81B](#) relating to "micro-structural devices" and "micro-structural systems".

In this subclass, main groups with a higher number take precedence.

H03H 1/00

Constructional details of impedance networks whose electrical mode of operation is not specified or applicable to more than one type of network ([constructional details of electromechanical transducers H03H 9/00](#))

H03H 1/0007

. { of radio frequency interference filters }

H03H 1/02

. of RC networks, e.g. integrated networks

H03H 2/00

Networks using elements or techniques not provided for in groups [H03H 3/00](#) to [H03H 21/00](#)

H03H 2/001

. { comprising magnetostatic wave network elements }

H03H 2/003

. { comprising optical fibre network elements (optical elements per se [G02B](#) , [G02F](#) ; transmission systems using light waves [H04B 10/00](#)) }

H03H 2/005

. { Coupling circuits between transmission lines or antennas and transmitters, receivers or amplifiers }

- H03H 2/006 . . { Transmitter or amplifier output circuits }
- H03H 2/008 . . { Receiver or amplifier input circuits }

H03H 3/00 Apparatus or processes specially adapted for the manufacture of impedance networks, resonating circuits, resonators

- H03H 3/007 . for the manufacture of electromechanical resonators or networks
- H03H 3/0072 . . { of micro-electro-mechanical resonators or networks (micro-membranes or micro-beams [B81B 3/00M2](#) ; manufacture of micro-structural devices in general [B81C](#)) }
- H03H 3/0073 . . . { Integration with other electronic structures }
- H03H 3/0075 . . . { Arrangements or methods specially adapted for testing micro-electro-mechanical resonators or networks }
- H03H 3/0076 . . . { for obtaining desired frequency or temperature coefficients }
- H03H 3/0077 { by tuning of resonance frequency }
- H03H 3/0078 { involving adjustment of the transducing gap }
- H03H 3/013 . . for obtaining desired frequency or temperature coefficient ({ [H03H 3/0076](#) } [H03H 3/04](#) , [H03H 3/10](#) take precedence)
- H03H 3/02 . . for the manufacture of piezo-electric or electrostrictive resonators or networks ([H03H 3/08](#) takes precedence)
- H03H 3/04 . . . for obtaining desired frequency or temperature coefficient
- H03H 3/06 . . for the manufacture of magnetostrictive resonators or networks
- H03H 3/08 . . for the manufacture of resonators or networks using surface acoustic waves
- H03H 3/10 . . . for obtaining desired frequency or temperature coefficient

H03H 5/00 One-port networks comprising only passive electrical elements as network components

- H03H 5/003 . { comprising distributed impedance elements together with lumped impedance elements }
- H03H 5/006 . { comprising simultaneously tunable inductance and capacitance }
- H03H 5/02 . without voltage- or current-dependent elements
- H03H 5/10 . . comprising at least one element with prescribed temperature coefficient
- H03H 5/12 . with at least one voltage- or current-dependent element

H03H 7/00 Multiple-port networks comprising only passive electrical elements as network components (receiver input circuits [H04B 1/18](#) ; networks simulating a length of communication cable [H04B 3/40](#))

- H03H 7/002 . { Gyration }
- H03H 7/004 . { Capacitive coupling circuits not otherwise provided for }
- H03H 7/01 . Frequency selective two-port networks

H03H 7/0107	..	{ Non-linear filters }
H03H 7/0115	..	{ comprising only inductors and capacitors (H03H 7/075 , H03H 7/09 , H03H 7/12 , H03H 7/13 take precedence) }
H03H 7/0123	..	{ comprising distributed impedance elements together with lumped impedance elements }
H03H 7/0138	..	{ Electrical filters or coupling circuits }
H03H 7/0146	...	{ Coupling circuits between two tubes, not otherwise provided for }
H03H 7/0153	..	{ Electrical filters; Controlling thereof }
H03H 7/0161	...	{ Bandpass filters (H03H 7/12 takes precedence) }
H03H 7/0169	{ Intermediate frequency filters }
H03H 7/0176	{ without magnetic core }
H03H 7/0184	{ with ferromagnetic core }
H03H 7/03	..	comprising means for compensation of loss
H03H 7/06	..	including resistors (H03H 7/075 , H03H 7/09 , H03H 7/12 , H03H 7/13 take precedence)
H03H 7/065	...	Parallel T-filters
H03H 7/07	...	Bridged T-filters
H03H 7/075	..	Ladder networks, e.g. electric wave filters
H03H 7/09	..	Filters comprising mutual inductance
H03H 7/12	..	Bandpass or bandstop filters with adjustable bandwidth and fixed centre frequency (H03H 7/09 takes precedence; automatic control of bandwidth in amplifiers H03G 5/16)
H03H 7/13	..	using electro-optic elements
H03H 7/17	..	{ Structural details of sub-circuits of frequency selective networks }

WARNING

not complete, pending reorganisation, see provisionally also [H03H 7/01](#) A, [H03H 7/0123](#) to [H03H 7/07](#) , [H03H 7/09](#) to [H03H 7/13](#) and [H03H 7/42](#)

H03H 7/1708	...	{ Comprising bridging elements, i.e. elements in a series path without own reference to ground and spanning branching nodes of another series path (H03H 7/07 takes precedence) }
H03H 7/1716	...	{ Comprising foot-point elements }
H03H 7/1725	{ Element to ground being common to different shunt paths, i.e. Y-structure }
H03H 7/1733	{ Element between different shunt or branch paths (H03H 7/425 takes precedence) }
H03H 7/1741	...	{ Comprising typical LC combinations, irrespective of presence and location of additional resistors (when resistors are present, also classify in H03H 7/06 to H03H 7/07) }
H03H 7/175	{ Series LC in series path (H03H 7/1783 takes precedence) }
H03H 7/1758	{ Series LC in shunt or branch path (H03H 7/1791 takes precedence) }
H03H 7/1766	{ Parallel LC in series path (H03H 7/1783 takes precedence) }
H03H 7/1775	{ Parallel LC in shunt or branch path (H03H 7/1791 takes precedence) }
H03H 7/1783	{ Combined LC in series path }
H03H 7/1791	{ Combined LC in shunt or branch path }
H03H 7/18	.	Networks for phase shifting

- H03H 7/185 .. { comprising distributed impedance elements together with lumped impedance elements }
- H03H 7/19 .. Two-port phase shifters providing a predetermined phase shift, e.g. "all-pass" filters
- H03H 7/20 .. Two-port phase shifters providing an adjustable phase shift
- H03H 7/21 .. providing two or more phase shifted output signals, e.g. n-phase output

- H03H 7/24 . Frequency- independent attenuators
- H03H 7/25 .. comprising an element controlled by an electric or magnetic variable ([H03H 7/27](#) takes precedence)
- H03H 7/251 ... { the element being a thermistor }
- H03H 7/253 ... { the element being a diode }
- H03H 7/255 { the element being a PIN diode }
- H03H 7/256 { the element being a VARACTOR diode }
- H03H 7/258 ... { using a galvano-magnetic device }
- H03H 7/27 .. comprising a photo-electric element

- H03H 7/30 . Time-delay networks {([analogue shift registers G11C 27/04](#))}
- H03H 7/32 .. with lumped inductance and capacitance
- H03H 7/325 ... { Adjustable networks }
- H03H 7/34 .. with lumped and distributed reactance
- H03H 7/345 ... { Adjustable networks }

- H03H 7/38 . Impedance-matching networks
- H03H 7/383 .. { comprising distributed impedance elements together with lumped impedance elements }
- H03H 7/40 .. Automatic matching of load impedance to source impedance

- H03H 7/42 . Balance/unbalance networks
- H03H 7/422 .. { comprising distributed impedance elements together with lumped impedance elements }
- H03H 7/425 .. { Balance-balance networks }

WARNING

not complete, pending reorganisation, see provisionally also [H03H 1/00](#) to [H03H 1/00 A](#), [H03H 7/01 A](#), [H03H 7/0123](#) to [H03H 7/07](#) , [H03H 7/09](#) to [H03H 7/13](#) , [H03H 7/42](#) and [H03H 7/42 B](#)

- H03H 7/427 ... { Common-mode filters ([H02J 3/01](#) and [H02M 1/126](#) takes precedence)}

WARNING

not complete, pending reorganisation, see provisionally also [H03H 1/00](#) to [H03H 1/00 A](#), [H03H 7/01 A](#), [H03H 7/0123](#) to [H03H 7/07](#) , [H03H 7/09](#) to [H03H 7/13](#) and [H03H 7/42](#)

- H03H 7/46 . Networks for connecting several sources or loads, working on different frequencies or frequency bands, to a common load or source ([for use in multiplex transmission systems H04J 1/00](#))

- H03H 7/461 .. { particularly adapted for use in common antenna systems }
- H03H 7/463 .. { Duplexers }
- H03H 7/465 ... { having variable circuit topology, e.g. including switches }
- H03H 7/466 .. { particularly adapted as input circuit for receivers }
- H03H 7/468 .. { particularly adapted as coupling circuit between transmitters and antennas }

- H03H 7/48 . Networks for connecting several sources or loads, working on the same frequency or frequency band, to a common load or source ([phase shifters providing two or more output signals H03H 7/21](#))
- H03H 7/482 .. { particularly adapted for use in common antenna systems }
- H03H 7/485 .. { particularly adapted as input circuit for receivers }
- H03H 7/487 .. { particularly adapted as coupling circuit between transmitters and antennas }

- H03H 7/52 . One-way transmission networks, i.e. unilines
- H03H 7/54 . Modifications of networks to reduce influence of variations of temperature

- H03H 9/00** **Networks comprising electromechanical or electro-acoustic devices;**
Electromechanical resonators ([making single crystals C30B](#); selection of materials thereof [H01L](#); piezo-electric, electrostrictive or magnetostrictive devices per se [H01L 41/00](#) ; electromechanical transducers [H04R](#))

- H03H 9/0004 . { Impedance-matching networks ([H03H 9/145](#) takes precedence) }
- H03H 9/0009 .. { using surface acoustic wave devices }
- H03H 9/0014 .. { using bulk acoustic wave devices }

- H03H 9/0023 . { Balance-unbalance or balance-balance networks }
- H03H 9/0028 .. { using surface acoustic wave devices }
- H03H 9/0033 ... { having one acoustic track only }
- H03H 9/0038 { the balanced terminals being on the same side of the track }
- H03H 9/0042 { the balanced terminals being on opposite sides of the track }
- H03H 9/0047 ... { having two acoustic tracks ([H03H 9/008](#) , [H03H 9/0085](#) take precedence) }
- H03H 9/0052 { being electrically cascaded }
- H03H 9/0057 { the balanced terminals being on the same side of the tracks }
- H03H 9/0061 { the balanced terminals being on opposite sides of the tracks }
- H03H 9/0066 { being electrically parallel }
- H03H 9/0071 { the balanced terminals being on the same side of the tracks }
- H03H 9/0076 { the balanced terminals being on opposite sides of the tracks }
- H03H 9/008 ... { having three acoustic tracks ([H03H 9/0085](#) takes precedence) }
- H03H 9/0085 ... { having four acoustic tracks }
- H03H 9/009 { Lattice filters }
- H03H 9/0095 .. { using bulk acoustic wave devices }

- H03H 9/02 . Details
- H03H 9/02007 .. { of bulk acoustic wave devices }
- H03H 9/02015 ... { Characteristics of piezoelectric layers, e.g. cutting angles }

H03H 9/02023	{ consisting of quartz }
H03H 9/02031	{ consisting of ceramic }
H03H 9/02039	{ consisting of a material from the crystal group 32, e.g. langasite, langatate, langanite }
H03H 9/02047	...	{ Treatment of substrates }
H03H 9/02055	{ of the surface including the back surface }
H03H 9/02062	...	{ Details relating to the vibration mode }
H03H 9/0207	{ the vibration mode being harmonic }
H03H 9/02078	{ the vibration mode being overmoded }
H03H 9/02086	...	{ Means for compensation or elimination of undesirable effects }
H03H 9/02094	{ of adherence }
H03H 9/02102	{ of temperature influence (cutting angles H03H 9/02015) }
H03H 9/0211	{ of reflections }
H03H 9/02118	{ of lateral leakage between adjacent resonators }
H03H 9/02125	{ of parasitic elements }
H03H 9/02133	{ of stress }
H03H 9/02141	{ of electric discharge due to pyroelectricity }
H03H 9/02149	{ of ageing changes of characteristics, e.g. electro-acousto-migration }
H03H 9/02157	...	{ Dimensional parameters, e.g. ratio between two dimension parameters, length, width or thickness }
H03H 9/0222	..	{ of interface-acoustic, boundary, pseudo-acoustic or Stonely wave devices }
H03H 9/02228	..	{ Guided bulk acoustic wave devices or Lamb wave devices having interdigital transducers situated in parallel planes on either side of a piezoelectric layer }
H03H 9/02236	..	{ of surface skimming bulk wave devices }
H03H 9/02244	..	{ of micro-electro-mechanical resonators }
H03H 9/02259	...	{ Driving or detection means }
H03H 9/02275	{ Comb electrodes }
H03H 9/02338	...	{ Suspension means }
H03H 9/02362	{ Folded-flexure }
H03H 9/02377	{ Symmetric folded-flexure }
H03H 9/02393	...	{ Post-fabrication trimming of parameters, e.g. resonance frequency, Q factor }
H03H 9/02401	{ by annealing }
H03H 9/02409	{ by application of a DC-bias voltage (H03H 9/02417 takes precedence) }
H03H 9/02417	{ involving adjustment of the transducing gap }
H03H 9/02425	{ by electrostatically pulling the beam }
H03H 9/02433	...	{ Means for compensation or elimination of undesired effects }
H03H 9/02448	{ of temperature influence }
H03H 9/02535	..	{ of surface acoustic wave devices }
H03H 9/02543	...	{ Characteristics of substrate, e.g. cutting angles }
H03H 9/02551	{ of quartz substrates }
H03H 9/02559	{ of lithium niobate or lithium-tantalate substrates }
H03H 9/02566	{ of semiconductor substrates }
H03H 9/02574	{ of combined substrates, multilayered substrates, piezo-electrical layers on

		not-piezo- electrical substrate }
H03H 9/02582	{ of diamond substrates }
H03H 9/0259	{ of langasite substrates }
H03H 9/02598	{ of langatate substrates }
H03H 9/02606	{ of langanite substrates }
H03H 9/02614	...	{ Treatment of substrates, e.g. curved, spherical, cylindrical substrates ensuring closed round-about circuits for the acoustical waves }
H03H 9/02622	{ of the surface, including back surface }
H03H 9/02629	{ of the edges }
H03H 9/02637	...	{ Details concerning reflective or coupling arrays }
H03H 9/02645	{ Waffle-iron or dot arrays }
H03H 9/02653	{ Grooves or arrays buried in the substrate }
H03H 9/02661	{ being located inside the interdigital transducers }
H03H 9/02669	{ Edge reflection structures, i.e. resonating structures without metallic reflectors, e.g. Bleustein-Gulyaev-Shimizu (BGS), shear horizontal (SH), shear transverse (ST), Love waves devices }
H03H 9/02677	{ having specially shaped edges, e.g. stepped, U-shaped edges }
H03H 9/02685	{ Grating lines having particular arrangements }
H03H 9/02692	{ Arched grating lines }
H03H 9/027	{ U-shaped grating lines }
H03H 9/02708	{ Shifted grating lines }
H03H 9/02716	{ Tilted, fan shaped or slanted grating lines }
H03H 9/02724	{ Comb like grating lines }
H03H 9/02732	{ Bilateral comb like grating lines }
H03H 9/0274	{ Intra-transducers grating lines }
H03H 9/02748	{ Dog-legged reflectors }
H03H 9/02755	{ Meandering floating or grounded grating lines }
H03H 9/02763	{ Left and right side electrically coupled reflectors }
H03H 9/02771	{ Reflector banks }
H03H 9/02779	{ Continuous surface reflective arrays }
H03H 9/02787	{ having wave guide like arrangements }
H03H 9/02795	{ Multi-strip couplers as track changers }
H03H 9/02803	{ Weighted reflective structures }
H03H 9/02811	{ Chirped reflective or coupling arrays }
H03H 9/02818	...	{ Means for compensation or elimination of undesirable effects }
H03H 9/02826	{ of adherence }
H03H 9/02834	{ of temperature influence (cut angles H03H 9/02543)}
H03H 9/02842	{ of reflections (H03H 9/6406 takes precedence)}
H03H 9/0285	{ of triple transit echo }
H03H 9/02858	{ of wave front distortion }
H03H 9/02866	{ of bulk wave excitation and reflections }
H03H 9/02874	{ of direct coupling between input and output transducers }
H03H 9/02881	{ of diffraction of wave beam }

H03H 9/02889	{ of influence of mass loading }
H03H 9/02897	{ of strain or mechanical damage, e.g. strain due to bending influence }
H03H 9/02905	{ Measures for separating propagation paths on substrate }
H03H 9/02913	{ Measures for shielding against electromagnetic fields (shielding of electrical components in general H05K 9/00) }
H03H 9/02921	{ Measures for preventing electric discharge due to pyroelectricity }
H03H 9/02929	{ of ageing changes of characteristics, e.g. electro-acousto-migration }
H03H 9/02937	{ of chemical damage, e.g. corrosion }
H03H 9/02944	{ of ohmic loss }
H03H 9/02952	{ of parasitic capacitance }
H03H 9/0296	...	{ Surface acoustic wave [SAW] devices having both acoustic and non-acoustic properties }
H03H 9/02968	{ with optical devices (mounting in enclosures H03H 9/12) }
H03H 9/02976	{ with semiconductor devices }
H03H 9/02984	...	{ Protection measures against damaging }
H03H 9/02992	...	{ Details of bus bars, contact pads or other electrical connections for finger electrodes }
H03H 9/05	..	Holders; Supports
H03H 9/0504	...	{ for bulk acoustic wave devices }
H03H 9/0509	{ consisting of adhesive elements }
H03H 9/0514	{ consisting of mounting pads or bumps }
H03H 9/0519	{ for cantilever (H03H 9/1021 takes precedence) }
H03H 9/0523	{ for flip-chip mounting }
H03H 9/0528	{ consisting of clips }
H03H 9/0533	{ consisting of wire }
H03H 9/0538	...	{ Constructional combinations of supports or holders with electromechanical or other electronic elements }
H03H 9/0542	{ consisting of a lateral arrangement (H03H 9/0566 takes precedence) }
H03H 9/0547	{ consisting of a vertical arrangement (H03H 9/0566 takes precedence) }
H03H 9/0552	{ the device and the other elements being mounted on opposite sides of a common substrate }
H03H 9/0557	{ the other elements being buried in the substrate }
H03H 9/0561	{ consisting of a multilayered structure }
H03H 9/0566	{ for duplexers }
H03H 9/0571	{ including bulk acoustic wave [BAW] devices }
H03H 9/0576	{ including surface acoustic wave [SAW] devices }
H03H 9/058	...	{ for surface acoustic wave devices }
H03H 9/0585	{ consisting of an adhesive layer }
H03H 9/059	{ consisting of mounting pads or bumps }
H03H 9/0595	...	{ the holder support and resonator being formed in one body }
H03H 9/08	...	Holders with means for regulating temperature
H03H 9/09	...	Elastic or damping supports
H03H 9/10	...	Mounting in enclosures { (constructional combinations of enclosure with electromechanical and other electronic elements H03H 9/0538) }

H03H 9/1007	{ for bulk acoustic wave [BAW]devices}
H03H 9/1014	{ the enclosure being defined by a frame built on a substrate and a cap, the frame having no mechanical contact with the BAW device }
H03H 9/1021	{ the BAW device being of the cantilever type }
H03H 9/1028	{ the BAW device being held between spring terminals }
H03H 9/1035	{ the enclosure being defined by two sealing substrates sandwiching the piezoelectric layer of the BAW device }
H03H 9/1042	{ the enclosure being defined by a housing formed by a cavity in a resin }
H03H 9/105	{ the enclosure being defined by a cover cap mounted on an element forming part of the BAW device }
H03H 9/1057	{ for micro-electro-mechanical devices }
H03H 9/1064	{ for surface acoustic wave [SAW]devices}
H03H 9/1071	{ the enclosure being defined by a frame built on a substrate and a cap, the frame having no mechanical contact with the SAW device }
H03H 9/1078	{ the enclosure being defined by a foil covering the non-active sides of the SAW device }
H03H 9/1085	{ the enclosure being defined by a non-uniform sealing mass covering the non-active sides of the BAW device }
H03H 9/1092	{ the enclosure being defined by a cover cap mounted on an element forming part of the surface acoustic wave [SAW]device on the side of the IDT's}
H03H 9/12	for networks with interaction of optical and acoustic waves
H03H 9/125	..	Driving means, e.g. electrodes, coils
H03H 9/13	...	for networks consisting of piezo-electric or electrostrictive materials (H03H 9/145 takes precedence)
H03H 9/131	{ consisting of a multilayered structure }
H03H 9/132	{ characterized by a particular shape }
H03H 9/133	{ for electromechanical delay lines or filters }
H03H 9/135	...	for networks consisting of magnetostrictive materials (H03H 9/145 takes precedence)
H03H 9/145	...	for networks using surface acoustic waves
H03H 9/14502	{ Surface acoustic wave [SAW]transducers for a particular purpose}
H03H 9/14505	{ Unidirectional SAW transducers }
H03H 9/14508	{ Polyphase SAW }transducers}
H03H 9/14511	{ SAW transducers for non-piezoelectric substrates }
H03H 9/14514	{ Broad band transducers }
H03H 9/14517	{ Means for weighting }
H03H 9/1452	{ by finger overlap length, apodisation }
H03H 9/14523	{ Capacitive tap weighted transducers }
H03H 9/14526	{ Finger withdrawal }
H03H 9/14529	{ Distributed tap }
H03H 9/14532	{ Series weighting; Transverse weighting }
H03H 9/14535	{ Position weighting }
H03H 9/14538	{ Formation }
H03H 9/14541	{ Multilayer finger or busbar electrode }

H03H 9/14544	{ Transducers of particular shape or position (weighting H03H 9/14517) }
H03H 9/14547	{ Fan shaped; Tilted; Shifted; Slanted; Tapered; Arched; Stepped finger transducers }
H03H 9/1455	{ constituted of N parallel or series transducers }
H03H 9/14552	{ comprising split fingers }
H03H 9/14555	{ Chirped transducers (H03H 9/6406 takes precedence) }
H03H 9/14558	{ Slanted, tapered or fan shaped transducers (H03H 9/14561 , H03H 9/14564 take precedence) }
H03H 9/14561	{ Arched, curved or ring shaped transducers }
H03H 9/14564	{ Shifted fingers transducers }
H03H 9/14567	{ Stepped-fan shaped transducers }
H03H 9/1457	{ Transducers having different finger widths }
H03H 9/14573	{ Arrow type transducers }
H03H 9/14576	{ Transducers whereby only the last fingers have different characteristics with respect to the other fingers, e.g. different shape, thickness or material, split finger }
H03H 9/14579	{ the last fingers having a different shape }
H03H 9/14582	{ the last fingers having a different pitch }
H03H 9/14585	{ the last fingers being split }
H03H 9/14588	{ Horizontally-split transducers }
H03H 9/14591	{ Vertically-split transducers }
H03H 9/14594	{ Plan-rotated or plan-tilted transducers }
H03H 9/14597	{ Matching SAW transducers to external electrical circuits }
H03H 9/15	.	Constructional features of resonators consisting of piezo-electric or electrostrictive material (H03H 9/25 takes precedence)
H03H 9/17	..	having a single resonator (crystal tuning forks H03H 9/21)
H03H 9/171	...	{ implemented with thin-film techniques, i.e. of the film bulk acoustic resonator (FBAR) type }
H03H 9/172	{ Means for mounting on a substrate, i.e. means constituting the material interface confining the waves to a volume }
H03H 9/173	{ Air-gaps }
H03H 9/174	{ Membranes }
H03H 9/175	{ Acoustic mirrors }
H03H 9/176	...	{ consisting of ceramic material (H03H 9/177 , H03H 9/178 take precedence) }
H03H 9/177	...	{ of the energy-trap type }
H03H 9/178	...	{ of a laminated structure of multiple piezoelectric layers with inner electrodes }
H03H 9/19	...	consisting of quartz
H03H 9/205	..	having multiple resonators (crystal tuning forks H03H 9/21)
H03H 9/21	..	Crystal tuning forks
H03H 9/215	...	consisting of quartz
H03H 9/22	.	Constructional features of resonators consisting of magnetostrictive material
H03H 9/24	.	Constructional features of resonators of material which is not piezo-electric, electrostrictive, or magnetostrictive

- H03H 9/2405 .. { of micro-electro-mechanical resonators }
- H03H 9/2426 ... { in combination with other electronic elements }
- H03H 9/2431 ... { Ring resonators }
- H03H 9/2436 ... { Disk resonators }
- H03H 9/2447 ... { Beam resonators ([H03H 9/2468](#) takes precedence) }
- H03H 9/2452 { Free-free beam resonators }
- H03H 9/2457 { Clamped-free beam resonators }
- H03H 9/2463 { Clamped-clamped beam resonators }
- H03H 9/2468 ... { Tuning fork resonators }
- H03H 9/2473 { Double-Ended Tuning Fork (DETF) resonators }
- H03H 9/2478 { Single-Ended Tuning Fork resonators }
- H03H 9/2484 { with two fork tines, e.g. Y-beam cantilever }
- H03H 9/2489 { with more than two fork tines }
- H03H 9/2494 { H-shaped, i.e. two tuning forks with common base }

- H03H 9/25 . Constructional features of resonators using surface acoustic waves {([devices for manipulating acoustic surface waves in general G10K 11/36](#)) }

- H03H 9/30 . Time-delay networks
- H03H 9/36 .. with non-adjustable delay time ([H03H 9/40](#) , [H03H 9/42](#) take precedence)
- H03H 9/38 .. with adjustable delay time ([H03H 9/40](#) , [H03H 9/42](#) take precedence)
- H03H 9/40 .. Frequency dependent delay lines, e.g. dispersive delay lines ([H03H 9/42](#) takes precedence)
- H03H 9/42 .. using surface acoustic waves {([devices for manipulating acoustic surface waves in general G10K 11/36](#)) }
- H03H 9/423 ... { with adjustable delay time }
- H03H 9/426 ... { Magneto-elastic surface waves }
- H03H 9/44 ... Frequency dependent delay lines, e.g. dispersive delay lines

- H03H 9/46 . Filters ([multiple-port electromechanical filters H03H 9/70](#))
- H03H 9/462 .. { Micro-electro-mechanical filters }
- H03H 9/465 ... { in combination with other electronic elements }
- H03H 9/467 ... { Post-fabrication trimming of parameters, e.g. center frequency }
- H03H 9/48 .. Coupling means therefor
- H03H 9/485 ... { for micro-electro-mechanical filters }
- H03H 9/50 ... Mechanical coupling means
- H03H 9/505 { for micro-electro-mechanical filters }
- H03H 9/52 ... Electric coupling means
- H03H 9/525 { for micro-electro-mechanical filters }
- H03H 9/54 .. comprising resonators of piezo-electric or electrostrictive material ([H03H 9/64](#) takes precedence)
- H03H 9/542 ... { including passive elements ([H03H 9/545](#) takes precedence) }
- H03H 9/545 ... { including active elements }
- H03H 9/547 ... { Notch filters, e.g. notch BAW or thin film resonator filters }

H03H 9/56	...	Monolithic crystal filters
H03H 9/562	{ comprising a ceramic piezoelectric layer }
H03H 9/564	{ implemented with thin-film techniques }
H03H 9/566	{ Electric coupling means therefor (H03H 9/0095 takes precedence) }
H03H 9/568	{ consisting of a ladder configuration }
H03H 9/58	...	Multiple crystal filters
H03H 9/581	{ comprising ceramic piezoelectric layers }
H03H 9/582	{ implemented with thin-film techniques }
H03H 9/583	{ comprising a plurality of piezoelectric layers acoustically coupled }
H03H 9/584	{ Coupled Resonator Filters (CFR) }
H03H 9/585	{ Stacked Crystal Filters (SCF) }
H03H 9/586	{ Means for mounting to a substrate, i.e. means constituting the material interface confining the waves to a volume }
H03H 9/587	{ Air-gaps }
H03H 9/588	{ Membranes }
H03H 9/589	{ Acoustic mirrors }
H03H 9/60	Electric coupling means therefor {(H03H 9/0095 takes precedence) }
H03H 9/605	{ consisting of a ladder configuration }
H03H 9/62	..	comprising resonators of magnetostrictive material (H03H 9/64 takes precedence)
H03H 9/64	..	using surface acoustic waves
H03H 9/6403	...	{ Programmable filters }
H03H 9/6406	...	{ Filters characterised by a particular frequency characteristic }
H03H 9/6409	{ SAW notch filters }
H03H 9/6413	{ SAW comb filters }
H03H 9/6416	{ SAW matched filters, e.g. surface acoustic wave compressors, chirped or coded surface acoustic wave filters }
H03H 9/642	{ SAW transducers details for remote interrogation systems, e.g. surface acoustic wave transducers details for ID-tags (remote interrogation systems per se G06K 7/10009 , G01S 13/74) }
H03H 9/6423	...	{ Means for obtaining a particular transfer characteristic }
H03H 9/6426	{ Combinations of the characteristics of different transducers }
H03H 9/643	{ the transfer characteristic being determined by reflective or coupling array characteristics }
H03H 9/6433	{ Coupled resonator filters }
H03H 9/6436	{ having one acoustic track only }
H03H 9/644	{ having two acoustic tracks }
H03H 9/6443	{ being acoustically coupled }
H03H 9/6446	{ by floating multistrip couplers (H03H 9/645 , H03H 9/6453 take precedence) }
H03H 9/645	{ by grating reflectors overlapping both tracks }
H03H 9/6453	{ by at least an interdigital transducer overlapping both tracks }
H03H 9/6456	{ being electrically coupled }
H03H 9/6459	{ via one connecting electrode }

H03H 9/6463	{ the tracks being electrically cascaded }
H03H 9/6466	{ each track containing more than two transducers }
H03H 9/6469	{ via two connecting electrodes }
H03H 9/6473	{ the electrodes being electrically interconnected }
H03H 9/6476	{ the tracks being electrically parallel }
H03H 9/6479	{ Capacitively coupled SAW resonator filters }
H03H 9/6483	{ Ladder SAW filters }
H03H 9/6486	{ having crossing or intersecting acoustic tracks, e.g. intersection in a perpendicular or diagonal orientation }
H03H 9/6489	...	{ Compensation of undesirable effects }
H03H 9/6493	{ Side lobe suppression }
H03H 9/6496	{ Reducing ripple in transfer characteristic }
H03H 9/66	.	Phase shifters
H03H 9/68	..	using surface acoustic waves
H03H 9/70	.	Multiple-port networks for connecting several sources or loads, working on different frequencies or frequency bands, to a common load or source
H03H 9/703	..	{ Networks using bulk acoustic wave devices }
H03H 9/706	...	{ Duplexers }
H03H 9/72	..	Networks using surface acoustic waves
H03H 9/725	...	{ Duplexers }
H03H 9/74	.	Multiple-port networks for connecting several sources or loads, working on the same frequency or frequency band, to a common load or source (networks for phase shifting H03H 9/66)
H03H 9/76	..	Networks using surface acoustic waves

H03H 11/00 Networks using active elements

WARNING

Group [H03H 11/11](#) does not correspond to former or current IPC groups.
Concordance CPC : IPC for these groups is as follows: - [H03H 11/11](#) - [H03H 11/04](#)

H03H 11/02	.	Multiple-port networks
H03H 11/025	..	{ using current conveyors }
H03H 11/04	..	Frequency selective two-port networks
H03H 11/0405	...	{ Non-linear filters }
H03H 11/0416	...	{ using positive impedance converters (H03H 11/08 takes precedence) }
H03H 11/0422	...	{ using transconductance amplifiers, e.g. gmC filters }
H03H 11/0427	{ Filters using a single transconductance amplifier; Filters derived from a single transconductor filter, e.g. by element substitution, cascading, parallel connection (H03H 11/0433 to H03H11/C10 take precedence) }
H03H 11/0433	{ Two integrator loop filters (H03H 11/0455 takes precedence) }
H03H 11/0438	{ Tow-Thomas biquad }

H03H 11/0444	{ Simulation of ladder networks }
H03H 11/045	{ Leapfrog structures }
H03H 11/0455	{ Multiple integrator loop feedback filters }
H03H 11/0461	{ Current mode filters }
H03H 11/0466	{ Filters combining transconductance amplifiers with other active elements, e.g. operational amplifiers, transistors, voltage conveyors }
H03H 11/0472	{ Current or voltage controlled filters }
H03H 11/06	...	comprising means for compensation of loss
H03H 11/08	...	using gyrators
H03H 11/10	...	using negative impedance converters (H03H 11/08 takes precedence)
H03H 11/11	...	{ using current conveyors }
H03H 11/12	...	using amplifiers with feedback ({ H03H 11/0422 } , H03H 11/08 , H03H 11/10 take precedence)
H03H 11/1204	{ Distributed RC filters }
H03H 11/1208	{ comprising an electromechanical resonator }
H03H 11/1213	{ using transistor amplifiers (H03H 11/1204 takes precedence; parallel-T filters H03H 11/1295) }
H03H 11/1217	{ using a plurality of operational amplifiers (H03H 11/1204 takes precedence; parallel-T filters H03H 11/1295) }
H03H 11/1221	{ Theory; Synthesis (H03H 11/1226 to H03H 11/1252 take precedence) }
H03H 11/1226	{ Filters using operational amplifier poles }
H03H 11/123	{ Modifications to reduce sensitivity }
H03H 11/1234	{ Modifications to reduce detrimental influences of amplifier imperfections, e.g. limited gain-bandwidth product, limited input impedance }
H03H 11/1239	{ Modifications to reduce influence of variations of temperature }
H03H 11/1243	{ Simulation of ladder networks }
H03H 11/1247	{ Leapfrog structures }

WARNING

Not complete, pending reorganisation, see provisionally also
[H03H 11/1217](#) to [H03H 11/1252](#)

H03H 11/1252	{ Two integrator-loop-filters }
H03H 11/1256	{ Tow-Thomas biquad }

WARNING

Not complete, pending reorganisation, see provisionally also
[H03H 11/1217](#) to [H03H 11/1252](#)

H03H 11/126	{ using a single operational amplifier (H03H 11/1204 takes precedence; parallel-T filters H03H 11/1295) }
H03H 11/1265	{ Synthesis (H03H 11/1269 to H03H 11/1282 take precedence) }
H03H 11/1269	{ Filters using the operational amplifier pole }
H03H 11/1273	{ Modifications to reduce sensitivity }
H03H 11/1278	{ Modifications to reduce detrimental influences of amplifier imperfections, e.g. limited gain-bandwidth product, limited input impedance }

		e.g. limited gain-bandwidth product, limited input impedance }
H03H 11/1282	{ Modifications to reduce influence of variations of temperature }
H03H 11/1286	{ Sallen-Key biquad }

WARNING

Not complete, pending reorganisation, see provisionally also
[H03H 11/126](#) to [H03H 11/1282](#)

H03H 11/1291	{ Current or voltage controlled filters }
H03H 11/1295	{ Parallel-T filters }
H03H 11/14	...	using electro-optic devices
H03H 11/16	..	Networks for phase shifting
H03H 11/18	...	Two-port phase shifters providing a predetermined phase shift, e.g. "all-pass" filters
H03H 11/20	...	Two-port phase shifters providing an adjustable phase shift
H03H 11/22	...	providing two or more phase shifted output signals, e.g. n-phase output
H03H 11/24	..	Frequency-independent attenuators
H03H 11/245	...	{ using field-effect transistor }
H03H 11/26	..	Time-delay networks (analogue shift registers G11C 27/04)
H03H 11/265	...	{ with adjustable delay }
H03H 11/28	..	Impedance matching networks
H03H 11/30	...	Automatic matching of source impedance to load impedance
H03H 11/32	..	Balance-unbalance networks
H03H 11/34	..	Networks for connecting several sources or loads working on different frequencies or frequency bands, to a common load or source (for use in multiplex transmission systems H04J 1/00)
H03H 11/342	...	{ particularly adapted for use in common antenna systems }
H03H 11/344	...	{ Duplexers }
H03H 11/346	...	{ particularly adapted as input circuit for receivers }
H03H 11/348	...	{ particularly adapted as coupling circuit between transmitters and antenna }
H03H 11/36	..	Networks for connecting several sources or loads, working on the same frequency band, to a common load or source (phase shifters providing two or more output signals H03H 11/22)
H03H 11/362	...	{ particularly adapted for use in common antenna systems }
H03H 11/365	...	{ particularly adapted as input circuit for receivers }
H03H 11/367	...	{ particularly adapted as coupling circuit between transmitters and antenna }
H03H 11/38	..	One-way transmission networks, i.e. unilines
H03H 11/40	..	Impedance converters
H03H 11/405	...	{ Positive impedance converters (H03H 11/42 takes precedence; used in frequency selective networks H03H 11/0416) }
H03H 11/42	...	Gyrators (used in frequency selective networks H03H 11/08)
H03H 11/44	...	Negative impedance converters (H03H 11/42 takes precedence; used in frequency selective networks H03H 11/10)
H03H 11/46	.	One-port networks

- H03H 11/48 . . . simulating reactances
H03H 11/481 . . . { Simulating capacitances }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/48](#) to [H03H 11/52](#)
- H03H 11/483 . . . { Simulating capacitance multipliers }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/48](#) to [H03H 11/52](#)
- H03H 11/485 . . . { Simulating inductances using operational amplifiers }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/48](#) to [H03H 11/52](#)
- H03H 11/486 . . . { Simulating inductances using transconductance amplifiers }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/48](#) to [H03H 11/52](#)
- H03H 11/488 . . . { Simulating inductances using current conveyors }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/48](#) to [H03H 11/52](#)
- H03H 11/50 . . . using gyrators
H03H 11/52 . . . simulating negative resistances
H03H 11/525 . . . { Simulating frequency dependent negative resistance [FDNR] }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/52](#)
- H03H 11/53 . . { simulating resistances; simulating resistance multipliers }
- WARNING**
- Not complete, pending reorganisation, see provisionally also [H03H 11/48](#) to [H03H 11/52](#)
- H03H 11/54 . Modifications of networks to reduce influence of variations of temperature
- H03H 15/00** Transversal filters ([electromechanical filters H03H 9/46](#) , [H03H 9/70](#))

- H03H 15/02 . using analogue shift registers
- H03H 15/023 .. { with parallel-input configuration }

H03H 17/00 Networks using digital techniques

- H03H 17/0009 . { Time-delay networks }
- H03H 17/0018 .. { Realizing a fractional delay }
- H03H 17/0027 ... { by means of a non-recursive filter }
- H03H 17/0036 ... { by means of a recursive filter }
- H03H 17/0045 . { Impedance matching networks }
- H03H 17/0054 . { Attenuators }
- H03H 17/0063 . { R, L, C, simulating networks }
- H03H 17/02 . Frequency selective networks {(digital computers for complex mathematical operations [G06F 17/10](#))}
- H03H 17/0201 .. { Wave digital filters }
- H03H 17/0202 .. { Two or more dimensional filters; Filters for complex signals (multidimensional convolutions [G06F 17/153](#))}
- H03H 17/0211 .. { using specific transformation algorithms, e.g. WALSH functions, Fermat transforms, Mersenne transforms, polynomial transforms, Hilbert transforms (correlation computation [G06F 17/156](#))}
- H03H 17/0213 ... { Frequency domain filters using Fourier transforms }
- H03H 17/0216 ... { Quefrequency domain filters }
- H03H 17/0217 ... { Number theoretic transforms }
- H03H 17/0219 .. { Compensation of undesirable effects, e.g. quantisation noise, overflow (stability problems [H03H 17/0461](#))}
- H03H 17/0223 .. { Computation saving measures; Accelerating measures (computations per se [G06F](#))}
- H03H 17/0225 ... { Measures concerning the multipliers }
- H03H 17/0226 { comprising look-up tables }
- H03H 17/0227 ... { Measures concerning the coefficients }
- H03H 17/0229 { reducing the number of taps }
- H03H 17/023 { reducing the wordlength, the possible values of coefficients }
- H03H 17/0233 ... { Measures concerning the signal representation }
- H03H 17/0235 { reducing the wordlength of signals }
- H03H 17/0236 { using codes }
- H03H 17/0238 ... { Measures concerning the arithmetic used (performing computations [G06F 7/60](#))}
- H03H 17/0239 { Signed digit arithmetic }
- H03H 17/0241 { Distributed arithmetic }
- H03H 17/0242 { Residue number arithmetic }
- H03H 17/0248 .. { Filters characterised by a particular frequency response or filtering method }

H03H 17/025	...	{ Notch filters }
H03H 17/0251	...	{ Comb filters }
H03H 17/0252	...	{ Elliptic filters }
H03H 17/0254	...	{ Matched filters }
H03H 17/0255	...	{ Filters based on statistics (adaptive filters H03H 21/0029) }
H03H 17/0257	{ KALMAN filters }
H03H 17/0258	{ ARMA filters }
H03H 17/026	...	{ Averaging filters }
H03H 17/0261	...	{ Non linear filters }
H03H 17/0263	{ Rank order filters }
H03H 17/0264	...	{ Filter sets with mutual related characteristics }
H03H 17/0266	{ Filter banks }
H03H 17/0267	{ comprising non-recursive filters }
H03H 17/0269	{ comprising recursive filters }
H03H 17/027	{ Complementary filters; Phase complementary filters }
H03H 17/0272	{ Quadrature mirror filters }
H03H 17/0273	{ Polyphase filters }
H03H 17/0275	{ comprising non-recursive filters }
H03H 17/0276	{ having two phases }
H03H 17/0277	{ comprising recursive filters }
H03H 17/0279	{ having two phases }
H03H 17/028	...	{ Polynomial filters }
H03H 17/0282	...	{ Sinc or gaussian filters (H03H 17/0671 takes precedence) }
H03H 17/0283	..	{ Filters characterised by the filter structure (H03H 17/0202 , H03H 17/0219 to H03H 17/0248 take precedence) }
H03H 17/0285	...	{ Ladder or lattice filters }
H03H 17/0286	...	{ Combinations of filter structures }
H03H 17/0288	{ Recursive, non-recursive, ladder, lattice structures }
H03H 17/0289	{ Digital and active filter structures }
H03H 17/0291	{ Digital and sampled data filters }
H03H 17/0292	...	{ Time multiplexed filters; Time sharing filters }
H03H 17/0294	..	{ Variable filters; Programmable filters }
H03H 17/04	..	Recursive filters
H03H 17/0405	...	{ comprising a ROM addressed by the input and output data signals }
H03H 17/0411	...	{ using DELTA modulation }
H03H 17/0416	...	{ with input-sampling frequency and output-delivery frequency which differ, e.g. extrapolation; Anti-aliasing }
H03H 17/0422	{ the input and output signals being derived from two separate clocks, i.e. asynchronous sample rate conversion }
H03H 17/0427	{ characterized by the ratio between the input-sampling and output-delivery frequencies }
H03H 17/0433	{ the ratio being arbitrary or irrational }
H03H 17/0438	{ the ratio being integer }

H03H 17/0444	{ where the output-delivery frequency is higher than the input sampling frequency, i.e. interpolation }
H03H 17/045	{ where the output-delivery frequency is lower than the input sampling frequency, i.e. decimation }
H03H 17/0455	{ the ratio being rational }
H03H 17/0461	...	{ Quantisation; Rounding; Truncation; Overflow oscillations or limit cycles eliminating measures }
H03H 17/06	..	Non-recursive filters
H03H 17/0607	...	{ comprising a ROM addressed by the input data signals }
H03H 17/0614	...	{ using Delta-modulation }
H03H 17/0621	...	{ with input-sampling frequency and output-delivery frequency which differ, e.g. extrapolation; Anti-aliasing }
H03H 17/0628	{ the input and output signals being derived from two separate clocks, i.e. asynchronous sample rate conversion }
H03H 17/0635	{ characterized by the ratio between the input-sampling and output-delivery frequencies }
H03H 17/0642	{ the ratio being arbitrary or irrational }
H03H 17/065	{ the ratio being integer }
H03H 17/0657	{ where the output-delivery frequency is higher than the input sampling frequency, i.e. interpolation }
H03H 17/0664	{ where the output-delivery frequency is lower than the input sampling frequency, i.e. decimation }
H03H 17/0671	{ Cascaded integrator-comb [CIC]filters}
H03H 17/0685	{ the ratio being rational }
H03H 17/08	.	Networks for phase shifting
H03H 19/00		Networks using time-varying elements, e.g. N-path filters
H03H 19/002	.	{ N-path filters }
H03H 19/004	.	{ Switched capacitor networks }
H03H 19/006	..	{ simulating one-port networks }
H03H 19/008	.	{ with variable switch closing time }
H03H 21/00		Adaptive networks
H03H 21/0001	.	{ Analogue adaptive filters }
H03H 21/0003	..	{ comprising CCD devices }
H03H 21/0005	..	{ comprising SAW devices }
H03H 21/0007	..	{ comprising switched capacitor [SC]devices}
H03H 21/0012	.	{ Digital adaptive filters }
H03H 21/0014	..	{ Lattice filters }
H03H 21/0016	..	{ Non linear filters }

H03H 21/0018	.. { Matched filters }
H03H 21/002	.. { Filters with a particular frequency response (H03H 21/0014 to H03H 21/0018 take precedence) }
H03H 21/0021	... { Notch filters }
H03H 21/0023	... { Comb filters }
H03H 21/0025	.. { Particular filtering methods }
H03H 21/0027	... { filtering in the frequency domain }
H03H 21/0029	... { based on statistics }
H03H 21/003 { KALMAN filters }
H03H 21/0032 { ARMA filters }
H03H 21/0043	.. { Adaptive algorithms }
H03H 21/0067	.. { Means or methods for compensation of undesirable effects }
H03H 2001/00	Constructional details of impedance networks whose electrical mode of operation is not specified or applicable to more than one type of network (constructional details of electromechanical transducers H03H 9/00)
H03H 2001/0014	. Capacitor filters, i.e. capacitors whose parasitic inductance is of relevance to consider it as filter
H03H 2001/0021	. Constructional details
H03H 2001/0028	.. RFI filters with housing divided in two bodies
H03H 2001/0035	.. Wound magnetic core
H03H 2001/0042	.. Wound, ring or feed-through type capacitor
H03H 2001/005	.. Wound, ring or feed-through type inductor
H03H 2001/0057	.. comprising magnetic material
H03H 2001/0064	.. comprising semiconductor material
H03H 2001/0071	.. comprising zig-zag inductor
H03H 2001/0078	.. comprising spiral inductor on a substrate
H03H 2001/0085	.. Multilayer, e.g. LTCC, HTCC, green sheets (inside PCB filters H05K)
H03H 2001/0092	. Inductor filters, i.e. inductors whose parasitic capacitance is of relevance to consider it as filter
H03H 2003/00	Apparatus or processes specially adapted for the manufacture of impedance networks, resonating circuits, resonators
H03H 2003/007	. for the manufacture of electromechanical resonators or networks
H03H 2003/0071	.. of bulk acoustic wave and surface acoustic wave elements in the same process
H03H 2003/02	.. for the manufacture of piezo-electric or electrostrictive resonators or networks (H03H 3/08 takes precedence)
H03H 2003/021	... the resonators or networks being of the air-gap type
H03H 2003/022	... the resonators or networks being of the cantilever type
H03H 2003/023	... the resonators or networks being of the membrane type
H03H 2003/025	... the resonators or networks comprising an acoustic mirror

H03H 2003/026	...	the resonators or networks being of the tuning fork type
H03H 2003/027	...	the resonators or networks being of the micro-electro-mechanical [MEMS] type
H03H 2003/028	...	for obtaining desired values of other parameters
H03H 2003/04	...	for obtaining desired frequency or temperature coefficient
H03H 2003/0407	Temperature coefficient
H03H 2003/0414	Resonance frequency
H03H 2003/0421	Modification of the thickness of an element
H03H 2003/0428	of an electrode
H03H 2003/0435	of a piezoelectric layer
H03H 2003/0442	of a non-piezoelectric layer
H03H 2003/045	Modification of the area of an element
H03H 2003/0457	of an electrode
H03H 2003/0464	operating on an additional circuit element, e.g. a passive circuit element connected to the resonator
H03H 2003/0471	of a plurality of resonators at different frequencies
H03H 2003/0478	in a process for mass production
H03H 2003/0485	during the manufacture of a cantilever
H03H 2003/0492	during the manufacture of a tuning-fork

H03H 2007/00 **Multiple-port networks comprising only passive electrical elements as network components (receiver input circuits [H04B 1/18](#) ; networks simulating a length of communication cable [H04B 3/40](#))**

H03H 2007/006	.	MEMS
H03H 2007/008	..	the MEMS being trimmable
H03H 2007/01	.	Frequency selective two-port networks
H03H 2007/013	..	Notch or bandstop filters
H03H 2007/0192	..	Complex filters
H03H 2007/38	.	Impedance-matching networks
H03H 2007/386	..	Multiple band impedance matching

H03H 2009/00 **Networks comprising electromechanical or electro-acoustic devices; Electromechanical resonators (making single crystals [C30B](#); selection of materials thereof [H01L](#); piezo-electric, electrostrictive or magnetostrictive devices per se [H01L 41/00](#) ; electromechanical transducers [H04R](#))**

H03H 2009/0019	.	Surface acoustic wave multichip
H03H 2009/02	.	Details
H03H 2009/02165	..	Tuning
H03H 2009/02173	...	of film bulk acoustic resonators [FBAR]
H03H 2009/02181	by application of heat from a heat source
H03H 2009/02188	Electrically tuning

H03H 2009/02196	operating on the FBAR element, e.g. by direct application of a tuning DC voltage
H03H 2009/02204	operating on an additional circuit element, e.g. applying a tuning DC voltage to a passive circuit element connected to the resonator
H03H 2009/02212	Magnetically tuning
H03H 2009/02244	..	{ of micro-electro-mechanical resonators }
H03H 2009/02251	...	Design
H03H 2009/02259	...	{ Driving or detection means }
H03H 2009/02267	having dimensions of atomic scale, e.g. involving electron transfer across vibration gap
H03H 2009/02283	...	Vibrating means
H03H 2009/02291	Beams
H03H 2009/02299	Comb-like, i.e. the beam comprising a plurality of fingers or protrusions along its length
H03H 2009/02307	Dog-bone-like structure, i.e. the elongated part of the "bone" is doubly clamped
H03H 2009/02314	forming part of a transistor structure
H03H 2009/02322	Material
H03H 2009/0233	comprising perforations
H03H 2009/02338	...	{ Suspension means }
H03H 2009/02346	Anchors for ring resonators
H03H 2009/02354	applied along the periphery, e.g. at nodal points of the ring
H03H 2009/02362	{ Folded-flexure }
H03H 2009/0237	applied at the center
H03H 2009/02385	Anchors for square resonators, i.e. resonators comprising a square vibrating membrane
H03H 2009/02433	...	{ Means for compensation or elimination of undesired effects }
H03H 2009/0244	Anchor loss
H03H 2009/02456	Parasitic elements or effects, e.g. parasitic capacitive coupling between input and output
H03H 2009/02464	Pull-in
H03H 2009/02472	Stiction
H03H 2009/0248	Strain
H03H 2009/02488	...	Vibration modes
H03H 2009/02496	Horizontal, i.e. parallel to the substrate plane
H03H 2009/02503	Breath-like, e.g. Lamé mode, wine-glass mode
H03H 2009/02511	Vertical, i.e. perpendicular to the substrate plane
H03H 2009/02519	Torsional
H03H 2009/02527	Combined
H03H 2009/15	.	Constructional features of resonators consisting of piezo-electric or electrostrictive material (H03H 9/25 takes precedence)
H03H 2009/155	..	using MEMS techniques
H03H 2009/24	.	Constructional features of resonators of material which is not piezo-electric, electrostrictive, or magnetostrictive

- H03H 2009/2405 . . { of micro-electro-mechanical resonators }
- H03H 2009/241 . . . Bulk-mode MEMS resonators
- H03H 2009/2415 with concave shape [CBAR]
- H03H 2009/2421 with I shape [IBAR]
- H03H 2009/2442 . . . Square resonators

H03H 2011/00 Networks using active elements

WARNING

Group [H03H 11/11](#) does not correspond to former or current IPC groups.
Concordance CPC : IPC for these groups is as follows: - [H03H 11/11](#) - [H03H 11/04](#)

- H03H 2011/02 . Multiple-port networks
- H03H 2011/04 . . Frequency selective two-port networks
- H03H 2011/0405 . . . { Non-linear filters }
- H03H 2011/0411 Rank order or median filters
- H03H 2011/0477 . . . using current feedback operational amplifiers
- H03H 2011/0483 . . . using operational transresistance amplifiers [OTRA]
- H03H 2011/0488 . . . Notch or bandstop filters
- H03H 2011/0494 . . . Complex filters

H03H 2015/00 Transversal filters ([electromechanical filters H03H 9/46](#) , [H03H 9/70](#))

- H03H 2015/002 . Computation saving measures
- H03H 2015/005 . comprising capacitors implemented with MEMS technology
- H03H 2015/007 . Programmable filters
- H03H 2015/026 . Matched filters in charge domain

H03H 2017/00 Networks using digital techniques

- H03H 2017/0072 . Theoretical filter design
- H03H 2017/0081 . . of FIR filters
- H03H 2017/009 . . of IIR filters
- H03H 2017/02 . Frequency selective networks { ([digital computers for complex mathematical operations G06F 17/10](#)) }
- H03H 2017/0202 . . { [Two or more dimensional filters; Filters for complex signals \(multidimensional convolutions G06F 17/153](#)) }
- H03H 2017/0204 . . . Comb filters
- H03H 2017/0205 . . . Kalman filters
- H03H 2017/0207 . . . Median filters

H03H 2017/0208	...	using neural networks
H03H 2017/021	...	Wave digital filters
H03H 2017/0211	..	{ using specific transformation algorithms, e.g. WALSH functions, Fermat transforms, Mersenne transforms, polynomial transforms, Hilbert transforms (correlation computation G06F 17/156) }
H03H 2017/0213	...	{ Frequency domain filters using Fourier transforms }
H03H 2017/0214	with input-sampling frequency and output-delivery frequency which differ, e.g. interpolation, extrapolation; anti-aliasing
H03H 2017/0219	..	{ Compensation of undesirable effects, e.g. quantisation noise, overflow (stability problems H03H 17/0461) }
H03H 2017/022	...	Rounding error
H03H 2017/0222	...	Phase error
H03H 2017/0223	..	{ Computation saving measures; Accelerating measures (computations per se G06F) }
H03H 2017/0227	...	{ Measures concerning the coefficients }
H03H 2017/023	{ reducing the wordlength, the possible values of coefficients }
H03H 2017/0232	Canonical signed digit [CSD] or power of 2 coefficients
H03H 2017/0244	...	Measures to reduce settling time
H03H 2017/0245	...	Measures to reduce power consumption (H03H 17/0223 takes preference)
H03H 2017/0247	...	Parallel structures using a slower clock
H03H 2017/0294	..	{ Variable filters; Programmable filters }
H03H 2017/0295	...	Changing between two filter characteristics
H03H 2017/0297	...	Coefficients derived from input parameters
H03H 2017/0298	..	DSP implementation
H03H 2017/04	..	Recursive filters
H03H 2017/0461	...	{ Quantisation; Rounding; Truncation; Overflow oscillations or limit cycles eliminating measures }
H03H 2017/0466	Reduction of limit cycle oscillation
H03H 2017/0472	...	based on allpass structures
H03H 2017/0477	...	Direct form I
H03H 2017/0483	Transposed
H03H 2017/0488	...	Direct form II
H03H 2017/0494	Transposed
H03H 2017/06	..	Non-recursive filters
H03H 2017/0621	...	{ with input-sampling frequency and output-delivery frequency which differ, e.g. extrapolation; Anti-aliasing }
H03H 2017/0635	{ characterized by the ratio between the input-sampling and output-delivery frequencies }
H03H 2017/0671	{ Cascaded integrator-comb [CIC] filters }
H03H 2017/0678	with parallel structure, i.e. parallel CIC [PCIC]
H03H 2017/0692	...	Transposed
H03H 2021/00		Adaptive networks
H03H 2021/0001	.	{ Analogue adaptive filters }

H03H 2021/0009	..	Details
H03H 2021/001	...	Analog multipliers
H03H 2021/0012	.	{ Digital adaptive filters }
H03H 2021/0025	..	{ Particular filtering methods }
H03H 2021/0034	...	Blind source separation
H03H 2021/0036	of convolutive mixtures
H03H 2021/0038	of instantaneous mixtures
H03H 2021/004	using state space representation
H03H 2021/0041	...	Subband decomposition
H03H 2021/0043	..	{ Adaptive algorithms }
H03H 2021/0045	...	Equation error
H03H 2021/0047	Combined output and equation error
H03H 2021/0049	...	Recursive least squares algorithm
H03H 2021/005	with forgetting factor
H03H 2021/0052	combined with stochastic gradient algorithm
H03H 2021/0054	Affine projection
H03H 2021/0056	...	Non-recursive least squares algorithm [LMS]
H03H 2021/0058	Block LMS, i.e. in frequency domain
H03H 2021/0059	Delayed LMS
H03H 2021/0061	Normalized LMS [NLMS]
H03H 2021/0063	Proportionate NLMS
H03H 2021/0065	Sign-sign LMS
H03H 2021/0067	..	{ Means or methods for compensation of undesirable effects }
H03H 2021/0069	...	Finite wordlength
H03H 2021/007	..	Computation saving measures; Accelerating measures
H03H 2021/0072	...	Measures relating to the coefficients
H03H 2021/0074	Reduction of the update frequency
H03H 2021/0076	...	Measures relating to the convergence time (H03H 2021/0072 takes preference)
H03H 2021/0078	varying the step size
H03H 2021/0079	...	using look-up tables
H03H 2021/0081	..	Details
H03H 2021/0083	...	Shadow filter, i.e. one of two filters which are simultaneously adapted, wherein the results of adapting the shadow filter are used for adapting the other filter
H03H 2021/0085	..	Applications
H03H 2021/0087	...	Prediction
H03H 2021/0089	...	System identification, i.e. modeling
H03H 2021/009	with recursive filters
H03H 2021/0092	...	Equalization, i.e. inverse modeling
H03H 2021/0094	...	Interference Cancelling
H03H 2021/0096	..	with input-sampling frequency and output-delivery frequency which differ, e.g. extrapolation; anti-aliasing

- H03H 2021/0098 . Adaptive filters comprising analog and digital structures

H03H 2210/00 Indexing scheme relating to details of tunable filters

- H03H 2210/01 . Tuned parameter of filter characteristics
- H03H 2210/012 . . Centre frequency; Cut-off frequency
- H03H 2210/015 . . Quality factor or bandwidth
- H03H 2210/017 . . Amplitude, gain or attenuation
- H03H 2210/02 . Variable filter component
- H03H 2210/021 . . Amplifier, e.g. transconductance amplifier
- H03H 2210/023 . . . Tuning of transconductance via tail current source
- H03H 2210/025 . . Capacitor
- H03H 2210/026 . . Inductor
- H03H 2210/028 . . Resistor
- H03H 2210/03 . Type of tuning
- H03H 2210/033 . . Continuous
- H03H 2210/036 . . Stepwise
- H03H 2210/04 . Filter calibration method
- H03H 2210/043 . . by measuring time constant
- H03H 2210/046 . . Master -slave

H03H 2218/00 Indexing scheme relating to details of digital filters

- H03H 2218/02 . Coefficients
- H03H 2218/025 . . updated selectively, e.g. by, in the presence of noise, temporally cancelling the update and outputting a predetermined value
- H03H 2218/04 . In-phase and quadrature [I/Q] signals
- H03H 2218/06 . Multiple-input, multiple-output [MIMO]; Multiple-input, single-output [MISO]
- H03H 2218/08 . Resource sharing
- H03H 2218/085 . . Multipliers
- H03H 2218/10 . Multiplier and or accumulator units
- H03H 2218/12 . Signal conditioning
- H03H 2218/14 . Non-uniform sampling

H03H 2220/00 Indexing scheme relating to structures of digital filters

- H03H 2220/02 . Modular, e.g. cells connected in cascade

H03H 2220/04 . Pipelined

H03H 2220/06 . Systolic

H03H 2220/08 . Variable filter length

H03H 2222/00 Indexing scheme relating to digital filtering methods

H03H 2222/02 . using fuzzy logic

H03H 2222/04 . using neural networks

H03H 2222/06 . using wavelets

H03H 2240/00 Indexing scheme relating to filter banks

H03H 2250/00 Indexing scheme relating to dual- or multi-band filters

H03H 2260/00 Theory relating to impedance networks