

CPC**COOPERATIVE PATENT CLASSIFICATION****F16K**

VALVES; TAPS; COCKS; ACTUATING-FLOATS; DEVICES FOR VENTING OR AERATING {(devices for emptying and evacuating the excess liquid in valves or conduits [F16L 55/07](#))}

NOTE

Attention is drawn to the following places:

[A47J 27/09](#) Safety devices for pressure cookers
[A47J 31/46](#) Dispensing spouts, drain valves or like beverage-making apparatus
[A61B 5/0235](#) Valves specially adapted for measuring pressure in heart or blood vessels
[A61F 2/24](#) Heart valves
[A61M 16/20](#) Valves specially adapted for medical respiratory devices
[A61M 39/00](#) Tube connectors, tube couplings, valves or branch units specially adapted for medical use in general
[A62B 9/02](#) Valves for respiratory apparatus
[A62B 18/10](#) Valves for breathing masks or helmets
[A62C](#) Fire extinguishers
{ [B01D 35/04](#) Plug, tap, or cock filters }
[B05B](#) Nozzles, spray heads or other discharge apparatus for spraying or atomising
[B60C 29/00](#) Arrangements of tyre-inflating valves relative to tyres or wheel rims; Connection of valves to wheel rims, tyres or other inflatable elastic bodies
[B60G 17/048](#) Valves specially adapted for adjusting vehicle fluid-spring characteristics
[B60T](#) Valves specially adapted for vehicle brake control systems
[B62D 5/08](#) Vehicle power-assisted steering characterised by the type of valve used
[B63B 7/00](#) ,
[B63C 9/00](#) Arrangement of inflating valves for floatable life-saving equipment
[B65D 47/04](#) Container closures with discharging valves
[B65D 90/32](#) Safety valves for large containers
[B65D 90/54](#) Gates or closures on large containers
[B67C 3/28](#) Flow control devices for bottling liquids
[B67D](#) Dispensing, delivering or transferring liquids
{ [C21B 9/12](#) Hot-blast valves for blast furnaces }
[E02B 8/00](#) Details, e.g. valves, of barrages or weirs
[E02B 13/02](#) Closures for irrigation conduits
{ [E03C 1/04](#) Water-basin installations specially adapted for wash-basins or baths }
{ [E03C 1/05](#) Arrangements on wash-basins for the remote control of taps }
[E03D](#) Flushing valves for water-closets or urinals
{ [E03F 7/04](#) Valves for preventing return flow in sewer systems }

[E05F 3/12](#) Valve arrangements in door closers
[E21B 21/10](#) Valve arrangements in drilling-fluid circulation systems
[E21B 34/00](#) Valve arrangements for boreholes or wells
 { [E21D 15/51](#) Arrangement of relief valves in hydraulic mine props }
[F01B 25/10](#) Working-fluid valves for controlling machines or engines in general or of positive-displacement type
[F01D 17/10](#) Final actuators for controlling non-positive displacement machines or engines
[F01L](#) Cyclically operated valves for machines or engines
[F02D 9/08](#) Throttle valves for controlling combustion engines
[F02K 9/58](#) Propellant feed valves for rocket-engines
[F02M](#) Carburettors, fuel injection
[F02M 59/46](#) Valves for fuel injection pumps
[F04](#) Pumps
[F16F 9/34](#) Valves for shock absorbers
[F16L 29/00](#) ,
[F16L 37/28](#) Pipe joints or quick-acting couplings with fluid cut-off means
[F16L 55/00](#) Arrangement of valves in pipes
[F16L 55/055](#) Valves specially adapted to prevent or minimise the effect of water hammer
[F16L 55/46](#) Launching devices for pigs or moles
[F16N 23/00](#) Check valves for lubrication systems
 { [F16T](#) Draining-off liquids from steam traps }
[F17C 13/04](#) Arrangement of valves in pressure vessels
[F22B 37/44](#) Arrangement of safety valves on steam boilers
[F22D 5/34](#) Application of valves to automatic water-feed in boiler
[F23L 13/00](#) Valves for air supply control to burners
 { [F23Q 2/16](#) Valves for lighters with gaseous fuel and adjustable flame }
[F24C 3/12](#) ,
[F24C 5/16](#) Arrangement of valves on stoves or ranges
[F24F](#) Air conditioning; Ventilation
[F25B 41/04](#) Disposition of fluid circulation valves in refrigeration machines
[G05D](#) Controlling non-electric variables
[G10B 3/06](#) Valves for organs
[G10D 9/04](#) Valves for other wind-actuated musical instruments
 { [G21C 9/06](#) Safety valves structurally associated with nuclear reactors }
 { [H01M 2/12](#) Vent plugs in batteries or cells }

WARNING

The following IPC groups are not used in the CPC scheme. Subject matter covered by these groups is classified in the following CPC groups:

[F16K 31/11](#) covered by [F16K 31/06](#) , [F16K 31/08](#) , [F16K 31/10](#)
[F16K 31/64](#) " " [G05D](#)
[F16K 31/66](#) " " [F16K 31/06](#) ; [H01F](#)
[F16K 31/68](#) " " [G05D](#)
[F16K 31/70](#) " " [F16K 31/002](#)

[F16K 31/72](#) " " [F16K 31/00](#)

Guidance heading: **Constructional types** (check valves [F16K 15/00](#))

NOTE

In groups [F16K 1/00](#) to [F16K 13/00](#) , an initial seal breaking or final sealing movement which is different from the opening or closing movement of the valve is not considered in determining the movement to be classified.

- F16K 1/00** **Lift valves { or globe valves }, i.e. cut-off apparatus with closure members having at least a component of their opening and closing motion perpendicular to the closing faces ({ in combination with sliding valves [F16K 3/246](#) , [F16K 3/267](#) } ; diaphragm valves [F16K 7/00](#))**
- [F16K 1/02](#) . with screw-spindle ([F16K 1/12](#) to [F16K 1/28](#) take precedence; actuating mechanisms with screw-spindles [F16K 31/50](#))
 - [F16K 1/04](#) . . with a cut-off member rigid with the spindle, e.g. main valves
 - [F16K 1/06](#) . . Special arrangements for improving the flow, e.g. special shape of passages or casings
 - [F16K 1/08](#) . . . in which the spindle is perpendicular to the general direction of flow
 - [F16K 1/10](#) . . . in which the spindle is inclined to the general direction of flow
 - [F16K 1/12](#) . with streamlined valve member around which the fluid flows when the valve is opened
 - [F16K 1/123](#) . . { with stationary valve member and moving sleeve }
 - [F16K 1/126](#) . . { actuated by fluid }
 - [F16K 1/14](#) . with ball-shaped valve member (check valves [F16K 15/04](#))
 - [F16K 1/16](#) . with pivoted closure-members
 - [F16K 1/165](#) . . { with a plurality of closure members }
 - [F16K 1/18](#) . . with pivoted discs or flaps
 - [F16K 1/20](#) . . . with axis of rotation arranged externally of valve member

WARNING

Subgroups of [F16K 1/20](#) are not complete pending a reorganisation, see also [F16K 1/20](#)

- [F16K 1/2007](#) { specially adapted operating means therefor (operating means per se [F16K 31/00](#)) }
- [F16K 1/2014](#) { Shaping of the valve member }
- [F16K 1/2021](#) { with a plurality of valve members }
- [F16K 1/2028](#) { Details of bearings for the axis of rotation }
- [F16K 1/2035](#) { the axis of rotation having only one bearing }

F16K 1/2042	{ Special features or arrangements of the sealing }
F16K 1/205	{ the sealing being arranged on the valve member }
F16K 1/2057	{ the sealing being arranged on the valve seat }
F16K 1/2064	{ with a channel- or U-shaped seal covering a central body portion }
F16K 1/2071	{ and being forced into sealing contact with the valve member by a spring or a spring-like member }
F16K 1/2078	{ Sealing means for the axis of rotation }
F16K 1/2085	{ Movable sealing bodies }
F16K 1/2092	{ the movement being caused by the flowing medium }
F16K 1/22	...	with axis of rotation crossing the valve member, e.g. butterfly valves
F16K 1/221	{ specially adapted operating means therefor (operating means per se F16K 31/00) }
F16K 1/222	{ Shaping of the valve member }
F16K 1/223	{ with a plurality of valve members }
F16K 1/224	{ Details of bearings for the axis of rotation }
F16K 1/225	{ the axis of rotation having only one bearing }
F16K 1/226	Shaping or arrangements of the sealing
F16K 1/2261	{ the sealing being arranged on the valve member }
F16K 1/2263	{ the sealing being arranged on the valve seat }
F16K 1/2265	{ with a channel- or U-shaped seal covering a central body portion }
F16K 1/2266	{ and being forced into sealing contact with the valve member by a spring or a spring-like member }
F16K 1/2268	{ Sealing means for the axis of rotation }
F16K 1/228	Movable sealing bodies
F16K 1/2285	{ the movement being caused by the flowing medium }
F16K 1/24	.	with valve members that, on opening of the valve, are initially lifted from the seat and next are turned around an axis parallel to the seat
F16K 1/26	..	Shape or arrangement of the sealing { Not used }
F16K 1/28	...	Movable sealing bodies { Not used }
F16K 1/30	.	specially adapted for pressure containers
F16K 1/301	..	{ only shut-off valves, i.e. valves without additional means }
F16K 1/302	...	{ with valve member and actuator on the same side of the seat }
F16K 1/303	...	{ with a valve member, e.g. stem or shaft, passing through the seat }
F16K 1/304	..	{ Shut-off valves with additional means }
F16K 1/305	...	{ with valve member and actuator on the same side of the seat }
F16K 1/306	...	{ with a valve member, e.g. stem or shaft, passing through the seat }
F16K 1/307	..	{ Additional means used in combination with the main valve }
F16K 1/308	..	{ Connecting means }
F16K 1/32	.	Details (details of more general applicability F16K 25/00 to F16K 51/00)

- F16K 1/34 .. Cutting-off parts, e.g. valve members, seats ([F16K 1/06](#) , [F16K 1/12](#) , [F16K 1/14](#) , [F16K 1/26](#) take precedence)
- F16K 1/36 ... Valve members (for double-seat valves [F16K 1/44](#)) { for butterfly valves [F16K 1/222](#) , [F16K 1/223](#) }
- F16K 1/38 of conical shape
- F16K 1/385 { contacting in the closed position, over a substantial axial length, a seat surface having the same inclination }
- F16K 1/40 of helical shape
- F16K 1/42 ... Valve seats (for double-seat valves [F16K 1/44](#))

WARNING

Subgroups of [F16K 1/42](#) are not complete pending a reorganisation, see also [F16K 1/42](#)]

- F16K 1/422 { attachable by a threaded connection to the housing }
- F16K 1/425 { Attachment of the seat to the housing by plastical deformation, e.g. valve seat or housing being plastically deformed during mounting }
- F16K 1/427 { Attachment of the seat to the housing by one or more additional fixing elements }
- F16K 1/44 ... Details of seats or valve members of double-seat valves
- F16K 1/443 { the seats being in series }
- F16K 1/446 { with additional cleaning or venting means between the two seats }
- F16K 1/46 ... Attachment of sealing rings
- F16K 1/465 { to the valve seats }

WARNING

Not yet complete, see also [F16K 1/46](#)

- F16K 1/48 .. Attaching valve members to screw-spindles
- F16K 1/482 ... { with a collar on the spindle or a groove in the spindle, by which a fixing element is supported, the spindle reaching into the valve member }
- F16K 1/485 { with a groove in the spindle }
- F16K 1/487 ... { by a fixing element extending in the axial direction of the spindle, e.g. a screw }
- F16K 1/50 .. Preventing rotation of valve members
- F16K 1/52 .. Means for additional adjustment of the rate of flow
- F16K 1/523 ... { for limiting the maximum flow rate, using a stop }
- F16K 1/526 ... { for limiting the maximum flow rate, using a second valve }
- F16K 1/54 .. Arrangements for modifying the way in which the rate of flow varies during the actuation of the valve

F16K 3/00 Gate valves or sliding valves, i.e. cut-off apparatus with closing members having a sliding movement along the seat for opening and closing ([F16K 5/00](#) takes precedence; in barrages or weirs [E02B 8/04](#))

- F16K 3/02 . with flat sealing faces; Packings therefor
- F16K 3/0209 .. { the valve having a particular passage, e.g. provided with a filter, throttle or safety device }
- F16K 3/0218 .. { with only one sealing face }
- F16K 3/0227 .. { Packings }
- F16K 3/0236 ... { the packing being of a non-resilient material, e.g. ceramic, metal }
- F16K 3/0245 .. { Curtain gate valves }
- F16K 3/0254 .. { being operated by particular means }
- F16K 3/0263 .. { using particular material or covering means }
- F16K 3/0272 .. { permitting easy assembly or disassembly }
- F16K 3/0281 .. { Guillotine or blade-type valves, e.g. no passage through the valve member }
- F16K 3/029 .. { with two or more gates }
- F16K 3/03 .. with a closure member in the form of an iris-diaphragm
- F16K 3/04 .. with pivoted closure members
- F16K 3/06 ... in the form of closure plates arranged between supply and discharge passages
([F16K 3/10 takes precedence](#))
- F16K 3/08 with circular plates rotatable around their centres
- F16K 3/085 { the axis of supply passage and the axis of discharge passage being coaxial and parallel to the axis of rotation of the plates }
- F16K 3/10 ... with special arrangements for separating the sealing faces or for pressing them together
- F16K 3/12 .. with wedge-shaped arrangements of sealing faces
- F16K 3/14 ... with special arrangements for separating the sealing faces or for pressing them together
- F16K 3/16 .. with special arrangements for separating the sealing faces or for pressing them together ([F16K 3/10](#) , [F16K 3/14 take precedence](#))
- F16K 3/18 ... by movement of the closure members
- F16K 3/182 { by means of toggle links }
- F16K 3/184 { by means of cams }
- F16K 3/186 { by means of cams of wedge form }
- F16K 3/188 { by means of hydraulic forces }
- F16K 3/20 ... by movement of the seats
- F16K 3/202 { by movement of toggle links }
- F16K 3/205 { by means of cams }
- F16K 3/207 { by means of hydraulic forces }
- F16K 3/22 . with sealing faces shaped as surfaces of solids of revolution ([F16K 13/02 takes precedence](#); with resilient valve members [F16K 3/28](#))
- F16K 3/24 .. with cylindrical valve members
- F16K 3/243 ... { Packings ([F16K 3/246 takes precedence](#))}
- F16K 3/246 ... { Combination of a sliding valve and a lift valve }
- F16K 3/26 ... with fluid passages in the valve member

F16K 3/262 { with a transverse bore in the valve member }
F16K 3/265 { with a sleeve sliding in the direction of the flow line }
F16K 3/267 { Combination of a sliding valve and a lift valve (F16K 3/262 , F16K 3/265 take precedence) }
F16K 3/28	. with resilient valve members
F16K 3/30	. Details
F16K 3/312	.. Line blinds
F16K 3/314	.. Forms or construction of slides; Attachment of the slide to the spindle
F16K 3/316	.. Guiding of the slide
F16K 3/3165	... { with rollers or balls }
F16K 3/32	.. Means for additional adjustment of the rate of flow
F16K 3/34	.. Arrangements for modifying the way in which the rate of flow varies during the actuation of the valve
F16K 3/36	.. Features relating to lubrication
F16K 5/00	{ Plug valves; }Taps or cocks comprising only cut-off apparatus having at least one of the sealing faces shaped as a more or less complete surface of a solid of revolution, the opening and closing movement being predominantly rotary (taps of the lift-valve type F16K 1/00)
F16K 5/02	. with plugs having conical surfaces; Packings therefor
F16K 5/0207	.. { with special plug arrangement, e.g. special shape or built in means }
F16K 5/0214	.. { Plug channel at 90 degrees to the inlet }
F16K 5/0221	.. { Fixed plug and turning sleeve }
F16K 5/0228	.. { with a conical segment mounted around a supply pipe }
F16K 5/0235	.. { with the angle the spindle makes housing being other than 90 degrees }
F16K 5/0242	.. { Spindles and actuating means }
F16K 5/025	.. { Particular coverings or materials }
F16K 5/0257	.. { Packings }
F16K 5/0264	... { in the housing }
F16K 5/0271	... { between housing and plug }
F16K 5/0278	... { on the plug }
F16K 5/0285	... { spindle sealing }
F16K 5/0292	.. { Easy mounting or dismounting means }
F16K 5/04	. with plugs having cylindrical surfaces; Packings therefor
F16K 5/0407	.. { with particular plug arrangements, e.g. particular shape or built-in means }
F16K 5/0414	.. { Plug channel at 90 degrees to the inlet }
F16K 5/0421	.. { Fixed plug and turning sleeve }
F16K 5/0428	.. { with a cylindrical segment mounted around a supply pipe }
F16K 5/0435	.. { the angle the spindle makes with the housing being other than 90 degrees }

F16K 5/0442	.. { Spindles and actuating means }
F16K 5/045	.. { Particular coverings and materials }
F16K 5/0457	.. { Packings }
F16K 5/0464	... { in the housing }
F16K 5/0471	... { between housing and plug }
F16K 5/0478	... { on the plug }
F16K 5/0485	... { Spindle sealing }
F16K 5/0492	.. { Easy mounting or dismounting means }
F16K 5/06	. with plugs having spherical surfaces; Packings therefor
F16K 5/0605	.. { with particular plug arrangements, e.g. particular shape or built-in means }
F16K 5/061	.. { knee-joint }
F16K 5/0615	.. { the angle the spindle makes with the housing being other than 90 degrees }
F16K 5/0621	.. { with a spherical segment mounted around a supply pipe }
F16K 5/0626	.. { Easy mounting or dismounting means }
F16K 5/0631	... { between two flanges }
F16K 5/0636	... { the spherical plug being insertable from the top of the housing }
F16K 5/0642	... { the spherical plug being insertable from one and only one side of the housing }
F16K 5/0647	.. { Spindles or actuating means }
F16K 5/0652	... { for remote operation }
F16K 5/0657	.. { Particular coverings or materials }
F16K 5/0663	.. { Packings }
F16K 5/0668	... { Single packings }
F16K 5/0673	... { Composite packings }
F16K 5/0678 { in which only one of the components of the composite packing is contacting the plug }

WARNING

not yet complete, see also [F16K 5/0673](#)

F16K 5/0684	... { on the plug }
F16K 5/0689	... { between housing and plug }
F16K 5/0694	... { Spindle sealings }
F16K 5/08	. Details
F16K 5/10	.. Means for additional adjustment of the rate of flow
F16K 5/103	... { specially adapted for gas valves }
F16K 5/106 { with pilot flame }
F16K 5/12	.. Arrangements for modifying the way in which the rate of flow varies during the actuation of the valve
F16K 5/14	.. Special arrangements for separating the sealing faces or for pressing them together

F16K 5/16	...	for plugs with conical surfaces
F16K 5/161	{ with the housing or parts of the housing mechanically pressing the seal against the plug }
F16K 5/162	{ with the plugs or parts of the plugs mechanically pressing the seal against the housing }
F16K 5/163	{ adjustable in height }
F16K 5/165	{ Means pressing on the small diameter }
F16K 5/166	{ Means pressing on the large diameter }
F16K 5/167	{ Means pressing radially }
F16K 5/168	{ Sealing effected by the flowing medium }
F16K 5/18	...	for plugs with cylindrical surfaces
F16K 5/181	{ with the housing or parts of the housing mechanically pressing the seals against the plugs }
F16K 5/182	{ by means of conical surfaces }
F16K 5/184	{ with the plugs or parts of the plugs mechanically pressing the seals against the housing }
F16K 5/185	{ by means of conical surfaces }
F16K 5/187	{ with rolling action }
F16K 5/188	{ Sealing effected by the flowing medium }
F16K 5/20	...	for plugs with spherical surfaces
F16K 5/201	{ with the housing or parts of the housing mechanically pressing the seal against the plug }
F16K 5/202	{ with conical surfaces }
F16K 5/204	{ with the plugs or parts of the plugs mechanically pressing the seals against the housing }
F16K 5/205	{ Sealing effected by the flowing medium }
F16K 5/207	{ using bellows }
F16K 5/208	{ with tongue-shaped means }
F16K 5/22	..	Features relating to lubrication
F16K 5/222	...	{ for plugs with conical surfaces }
F16K 5/225	...	{ for plugs with cylindrical surfaces }
F16K 5/227	...	{ for plugs with spherical surfaces }

F16K 7/00 **Diaphragm { valves or } cut-off apparatus, e.g. with a member deformed, but not moved bodily, to close the passage (container gates or closures operating by deformation of flexible walls [B65D 90/56](#) ; means for plugging pipes or hoses [F16L 55/10](#))**
{ Pinch valves }

F16K 7/02	.	with tubular diaphragm
F16K 7/04	..	constrictable by external radial force
F16K 7/045	...	{ by electric or magnetic means }
F16K 7/06	...	by means of a screw-spindle, cam, or other mechanical means { (F16K 7/045 takes precedence) }

F16K 7/061	{ Screw clamps }
F16K 7/063	{ Lever clamps }
F16K 7/065	{ Cam clamps }
F16K 7/066	{ Wedge clamps }
F16K 7/068	{ by bending the hose }
F16K 7/07	...	by means of fluid pressure
F16K 7/075	{ a rigid body being located within the tubular diaphragm }
F16K 7/08	..	constrictable by twisting
F16K 7/10	.	with inflatable member
F16K 7/12	.	with flat, dished, or bowl-shaped diaphragm
F16K 7/123	..	{ the seat being formed on the bottom of the fluid line }
F16K 7/126	..	{ the seat being formed on a rib perpendicular to the fluid line }
F16K 7/14	..	arranged to be deformed against a flat seat
F16K 7/16	...	the diaphragm being mechanically actuated, e.g. by screw-spindle or cam
F16K 7/17	...	the diaphragm being actuated by fluid pressure
F16K 7/18	.	with diaphragm secured at one side only, e.g. to be laid on the seat by rolling action
F16K 7/20	.	with a compressible solid closure member
F16K 11/00		Multiple-way valves, e.g. mixing valves; Pipe fittings incorporating such valves
F16K 11/02	.	with all movable sealing faces moving as one unit
F16K 11/022	..	{ comprising a deformable member }
F16K 11/025	...	{ with an O-ring }
F16K 11/027	...	{ the fluid flowing through a constrictable tubular diaphragm }
F16K 11/04	..	comprising only lift valves
F16K 11/044	...	with movable valve members positioned between valve seats
F16K 11/0445	{ Bath/shower selectors }
F16K 11/048	...	with valve seats positioned between movable valve members
F16K 11/052	...	with pivoted closure members, e.g. butterfly valves
F16K 11/0525	{ the closure members being pivoted around an essentially central axis }
F16K 11/056	...	with ball-shaped valve members
F16K 11/0565	{ moving in a combined straight line and rotating movement }
F16K 11/06	..	comprising only sliding valves, { i.e. sliding closure elements }
F16K 11/065	...	with linearly sliding closure members
F16K 11/0655	{ with flat slides }
F16K 11/07	with cylindrical slides
F16K 11/0704	{ comprising locking elements }

F16K 11/0708	{ comprising means to avoid jamming of the slide or means to modify the flow }
F16K 11/0712	{ comprising particular spool-valve sealing means }
F16K 11/0716	{ with fluid passages through the valve member (F16K 11/0704 , F16K 11/0708 , F16K 11/0712 take precedence) }
F16K 11/072	...	with pivoted closure members
F16K 11/074	with flat sealing faces
F16K 11/0743	{ with both the supply and the discharge passages being on one side of the closure plates }
F16K 11/0746	{ with two or more closure plates comprising a single lever control }
F16K 11/076	with sealing faces shaped as surfaces of solids of revolution
F16K 11/078	...	with pivoted and linearly movable closure members
F16K 11/0782	{ Single-lever operated mixing valves with closure members having flat sealing faces }
F16K 11/0785	{ the movable closure member being pivotally supported at one point and being linked to the operating lever at only one other point }
F16K 11/0787	{ with both the supply and the discharge passages being on the same side of the closure members (F16K 11/0785 takes precedence) }
F16K 11/08	..	comprising only taps or cocks
F16K 11/083	...	with tapered plug
F16K 11/0833	{ having all the connecting conduits situated in a single plane perpendicular to the axis of the plug }
F16K 11/0836	{ having all the connecting conduits situated in more than one plane perpendicular to the axis of the plug }
F16K 11/085	...	with cylindrical plug
F16K 11/0853	{ having all the connecting conduits situated in a single plane perpendicular to the axis of the plug }
F16K 11/0856	{ having all the connecting conduits situated in more than one plane perpendicular to the axis of the plug }
F16K 11/087	...	with spherical plug
F16K 11/0873	{ the plug being only rotatable around one spindle }
F16K 11/0876	{ one connecting conduit having the same axis as the spindle }
F16K 11/10	.	with two or more closure members not moving as an unit
F16K 11/105	..	{ Three-way check or safety valves with two or more closure members }
F16K 11/12	..	with one plug turning in another
F16K 11/14	..	operated by one actuating member, e.g. a handle (with one plug turning in another F16K 11/12)
F16K 11/16	...	which only slides, or only turns, or only swings in one plane
F16K 11/161	{ only slides }
F16K 11/163	{ only turns }
F16K 11/165	{ with the rotating spindles parallel to the closure members }
F16K 11/166	{ with the rotating spindles at right angles to the closure members }

- F16K 11/168 { only swings }
- F16K 11/18 . . . with separate operating movements for separate closure members
- F16K 11/185 { with swinging shafts }
- F16K 11/20 . . operated by separate actuating members (with one plug turning in another [F16K 11/12](#))
- F16K 11/202 . . . { with concentric handles }
- F16K 11/205 . . . { with two handles at right angles to each other }
- F16K 11/207 . . . { with two handles or actuating mechanisms at opposite sides of the housing }
- F16K 11/22 . . . with an actuating member for each valve, e.g. interconnected to form multiple-way valves
- F16K 11/24 . . . with an electromagnetically-operated valve, e.g. for washing machines

F16K 13/00 **Other constructional types of cut-off apparatus** (means for plugging pipes or hoses [F16L 55/10](#)); **Arrangements for cutting-off**

- F16K 13/02 . with both sealing faces shaped as small segments of a cylinder and the moving member pivotally mounted
- F16K 13/04 . with a breakable closure member
- F16K 13/06 . . constructed to be ruptured by an explosion
- F16K 13/08 . Arrangements for cutting-off { not used }
- F16K 13/10 . . by means of liquid or granular medium

Guidance heading: Functional types

NOTE

Attention is drawn to Note (2) following the title of subclass [G05D](#) and also the subdivisions of that subclass, according to which pressure regulators and flow regulators, e.g. flow regulating valves with pressure compensator, even with the whole regulating system contained in a valve, operating with or without auxiliary power, are covered by groups [G05D 16/00](#) or [G05D 7/00](#) , respectively. However, details of the valve parts, per se, are classified in the appropriate groups of this subclass.

F16K 15/00 **Check valves** (valves specially adapted for inflatable balls [A63B 41/00](#))

- F16K 15/02 . with guided rigid valve members
- F16K 15/021 . . { the valve member being a movable body around which the medium flows when the valve is open ([F16K 15/025](#) to [F16K 15/12](#) take precedence)}

WARNING

not yet complete

- F16K 15/023 ... { the valve member consisting only of a predominantly disc-shaped flat element }
- WARNING**
- not yet complete
- F16K 15/025 .. { the valve being loaded by a helicoidal spring ([F16K 15/03](#) to [F16K 15/12](#) take precedence) }
- F16K 15/026 ... { the valve member being a movable body around which the medium flows when the valve is open }
- F16K 15/028 { the valve member consisting only of a predominantly disc-shaped flat element }
- F16K 15/03 .. with a hinged closure member
- F16K 15/031 ... { the hinge being flexible ([F16K 15/035](#) takes precedence) }
- F16K 15/033 ... { spring-loaded ([F16K 15/035](#) takes precedence) }
- F16K 15/035 ... { with a plurality of valve members }
- F16K 15/036 { Dual valve members with hinges crossing the flow line substantially diametrical }
- F16K 15/038 { having a common hinge }
- F16K 15/04 .. shaped as balls
- F16K 15/042 ... { with a plurality of balls }
- F16K 15/044 ... { spring-loaded ([F16K 15/042](#) takes precedence) }
- F16K 15/046 { by a spring other than a helicoidal spring }
- F16K 15/048 ... { Ball features }
- WARNING**
- not yet complete, see also [F16K 15/04](#)
- F16K 15/06 .. with guided stems
- F16K 15/063 ... { the valve being loaded by a helicoidal spring }
- WARNING**
- not yet complete, see also [F16K 15/06](#)
- F16K 15/066 { with a plurality of valve members }
- F16K 15/08 .. shaped as rings
- F16K 15/10 ... integral with, or rigidly fixed to, a common valve plate
- F16K 15/12 ... Springs for ring valves
- F16K 15/14 . with flexible valve members
- F16K 15/141 .. { the closure elements not being fixed to the valve body }
- F16K 15/142 ... { the closure elements being shaped as solids of revolution, e.g. toroidal or cylindrical rings }
- F16K 15/144 .. { the closure elements being fixed along all or a part of their periphery }

- F16K 15/145 . . . { the closure elements being shaped as a solids of revolution, e.g. cylindrical or conical }
- F16K 15/147 . . . { the closure elements having specially formed slits or being of an elongated easily collapsible form }
- F16K 15/148 . . { the closure elements being fixed in their centre }
- F16K 15/16 . . with tongue-shaped laminae
- F16K 15/18 . with actuating mechanism; Combined check valves and actuated valves
- F16K 15/181 . . { for check valves with a hinged closure member ([F16K 15/188](#) takes precedence)}
- F16K 15/183 . . { for ball check valves ([F16K 15/186](#) , [F16K 15/188](#) take precedence)}
- F16K 15/185 . . { for check valves with flexible valve members ([F16K 15/188](#) takes precedence)}
- F16K 15/186 . . { Check valves which can be actuated by a pilot valve }
- F16K 15/188 . . { Check valves combined with valves having a rotating tap or cock }
- F16K 15/20 . specially designed for inflatable bodies, e.g. tyres ([connecting valves to inflatable bodies B60C 29/00](#))
- F16K 15/202 . . { and with flexible valve member }
- F16K 15/205 . . { and with closure plug }
- F16K 15/207 . . { and combined with other valves, e.g. safety valves }
- F16K 17/00** **Safety valves; Equalising valves, { e.g. pressure relief valves }**
- F16K 17/003 . { reacting to pressure and temperature }
- F16K 17/006 . { specially adapted for shelters }
- F16K 17/02 . opening on surplus pressure on one side; closing on insufficient pressure on one side ([check valves F16K 15/00](#))
- F16K 17/025 . . { and remaining open after return of the normal pressure }

WARNING

This group is not complete pending a reorganisation, see also [F16K 17/02](#)

- F16K 17/04 . . spring-loaded
- F16K 17/0406 . . . { in the form of balls }
- F16K 17/0413 . . . { in the form of closure plates }
- F16K 17/042 . . . { with locking or disconnecting arrangements }
- F16K 17/0426 . . . { with seat protecting means }
- F16K 17/0433 . . . { with vibration preventing means }
- F16K 17/044 . . . { with more than one spring }
- F16K 17/0446 . . . { with an obturating member having at least a component of their opening and closing motion not perpendicular to the closing faces }
- F16K 17/0453 { the member being a diaphragm }

F16K 17/046	{ the valve being of the gate valve type or the sliding valve type }
		<u>WARNING</u>
		not yet complete, see also F16K 17/0446
F16K 17/0466	...	{ with a special seating surface }
F16K 17/0473	...	{ Multiple-way safety valves }
F16K 17/048	...	{ combined with other safety valves, or with pressure control devices }
F16K 17/0486	...	{ with mechanical actuating means }
F16K 17/0493	...	{ with a spring other than a helicoidal spring }
F16K 17/06	...	with special arrangements for adjusting the opening pressure
F16K 17/065	{ with differential piston }
F16K 17/08	...	with special arrangements for providing a large discharge passage
F16K 17/082	{ with piston }
F16K 17/085	{ with diaphragm }
F16K 17/087	{ with bellows }
F16K 17/10	...	with auxiliary valve for fluid operation of the main valve
F16K 17/105	{ using choking or throttling means to control the fluid operation of the main valve }
F16K 17/12	..	weight-loaded
F16K 17/14	..	with fracturing member
F16K 17/16	...	with fracturing diaphragm; { Rupture discs }
F16K 17/1606	{ of the reverse-buckling-type (F16K 17/1633 takes precedence) }
F16K 17/1613	{ with additional cutting means }
F16K 17/162	{ of the non reverse-buckling-type (F16K 17/1633 takes precedence) }
F16K 17/1626	{ with additional cutting means }
F16K 17/1633	{ made of graphite }
F16K 17/164	..	and remaining closed after return of the normal pressure
F16K 17/168	..	combined with manually-controlled valves, e.g. a valve combined with a safety valve
F16K 17/18	.	opening on surplus pressure on either side
F16K 17/19	..	Equalising valves predominantly for tanks { when combined with safety valve by change of position F16K 17/36 }
F16K 17/192	...	with closure member in the form of a movable liquid column
F16K 17/194	...	weight-loaded
F16K 17/196	...	spring-loaded
F16K 17/20	.	Excess-flow valves (actuated in consequence of shock or similar extraneous influence F16K 17/36)
F16K 17/205	..	{ specially adapted for flexible gas lines }
F16K 17/22	..	actuated by the difference of pressure between two places in the flow line

- F16K 17/24 . . . acting directly on the cutting-off member
- F16K 17/26 operating in either direction
- F16K 17/28 operating in one direction only
- F16K 17/285 { the cutting-off member being a ball ([F16K 17/30](#) takes precedence)}
- F16K 17/30 spring-loaded
- F16K 17/32 . . . acting on a servo-mechanism or on a catch-releasing mechanism
- F16K 17/34 . . in which the flow-energy of the flowing medium actuates the closing mechanism

- F16K 17/36 . actuated in consequence of extraneous circumstances, e.g. shock, change of position
- F16K 17/363 . . { the closure members being rotatable or pivoting ([F16K 17/386](#) takes precedence)}
- F16K 17/366 . . { the closure member being a movable ball ([F16K 17/38](#) takes precedence)}

WARNING

not yet complete, see also [F16K 17/36](#)

- F16K 17/38 . . of excessive temperature
- F16K 17/383 . . . { the valve comprising fusible, softening or meltable elements, e.g. used as link, blocking element, seal, closure plug ([F16K 17/386](#) takes precedence)}
- F16K 17/386 . . . { the closure members being rotatable or pivoting }

- F16K 17/40 . with a fracturing member, e.g. fracturing diaphragm, glass, fusible joint (valves opening on surplus pressure [F16K 17/14](#))
- F16K 17/403 . . { with a fracturing valve member }
- F16K 17/406 . . { the fracturing member being a generally elongated member, e.g. rod or wire, which is directly connected to a movable valve member, the breaking or buckling of the elongated member allowing the valve member to move to a closed or open position }

- F16K 17/42 . Valves preventing penetration of air in the outlet of containers for liquids

F16K 19/00 Arrangements of valves and flow lines specially adapted for mixing fluids (multiple-way valves [F16K 11/00](#))

- F16K 19/003 . { Specially adapted for boilers }
- F16K 19/006 . { Specially adapted for faucets }

F16K 21/00 Fluid-delivery valves, { e.g. self-closing valves } (for liquid handling [B67D](#) ; for flushing devices for water-closets or the like [E03D](#))

- F16K 21/02 . providing a continuous small flow
- F16K 21/04 . Self-closing valves, i.e. closing automatically after operation { pneumatic tools [B25B 9/00](#) }

- F16K 21/06 . . in which the closing movement, either retarded or not, starts immediately after opening
- F16K 21/08 . . . with ball-shaped closing members
- F16K 21/10 . . . with hydraulic brake cylinder acting on the closure member
- F16K 21/12 . . . with hydraulically-operated opening means; with arrangements for pressure relief before opening
- F16K 21/14 . . with special means for preventing the self-closing
- F16K 21/16 . . closing after a predetermined quantity of fluid has been delivered ([F16K 21/10 takes precedence](#))
- F16K 21/165 . . . { with means sensing the weight of said fluid quantity }

WARNING

not yet complete, see also [F16K 21/16](#)

- F16K 21/18 . . closed when a rising liquid reaches a predetermined level ([float-actuated valves F16K 31/18](#))
- F16K 21/185 . . . { with electrical or magnetical means, e.g. with magnetic floats, for sensing the liquid level }

WARNING

not yet complete, see also [F16K 21/18](#)

- F16K 21/20 . . . by means making use of air-suction through an opening closed by the rising liquid

F16K 23/00 Valves for preventing drip from nozzles

F16K 24/00 **Devices, e.g. valves, for venting or aerating enclosures** ([equalising valves F16K 17/00](#) ; arrangement or mounting in pipes or pipe systems [F16L 55/07](#) ; venting or aerating as an additional function of steam traps or like apparatus [F16T](#) ; ventilation of rooms, vehicles, see the appropriate subclass, e.g. [F24F](#))

- F16K 24/02 . the enclosure being itself a valve, tap, or cock
- F16K 24/04 . for venting only ([F16K 24/02 takes precedence](#))
- F16K 24/042 . . { actuated by a float }
- F16K 24/044 . . . { the float being rigidly connected to the valve element, the assembly of float and valve element following a substantially translational movement when actuated, e.g. also for actuating a pilot valve }

WARNING

not yet complete, see also [F16K 24/042](#)

- F16K 24/046 { the assembly of float and valve element being a single spherical element }

F16K 24/048 . . . { a transmission element, e.g. arm, being interposed between the float and the valve element, the transmission element following a non-translational, e.g. pivoting or rocking, movement when actuated }

F16K 24/06 . for aerating only ([F16K 24/02](#) takes precedence)

Guidance heading: Details

NOTE

Details not provided for in the following groups are classified in the preceding groups.

F16K 25/00 **Details relating to contact between valve members and seat** (sealing constructions, see the appropriate groups according to the type of valve; movement of valve members other than for opening and closing [F16K 29/00](#))

F16K 25/005 . { Particular materials for seats or closure elements }

F16K 25/02 . Arrangements using fluid issuing from valve members or seats

F16K 25/04 . Arrangements for preventing erosion, not otherwise provided for

F16K 27/00 **Construction of housing** (methods for welding housings [B23K](#)); **Use of materials therefor**

F16K 27/003 . { Housing formed from a plurality of the same valve elements }

F16K 27/006 . { of hydrants }

F16K 27/02 . of lift valves (for reducing the flow resistance of screw-spindle lift-valves [F16K 1/06](#))

F16K 27/0209 .. { Check valves or pivoted valves }

F16K 27/0218 ... { Butterfly valves }

F16K 27/0227 ... { with the valve members swinging around an axis located at the edge of or outside the valve member }

F16K 27/0236 .. { Diaphragm cut-off apparatus }

F16K 27/0245 .. { with ball-shaped valve members }

F16K 27/0254 .. { with conical shaped valve members }

F16K 27/0263 .. { multiple way valves }

F16K 27/0272 .. { valves provided with a lining }

F16K 27/0281 .. { Housings in two parts which can be orientated in different positions }

F16K 27/029 .. { Electromagnetically actuated valves }

WARNING

This group is not complete pending a reorganisation, see also [F16K 27/02](#)

- F16K 27/04 . of sliding valves
- F16K 27/041 . . { cylindrical slide valves }
- F16K 27/042 . . . { Hydraulic fluid leak traps }
- F16K 27/044 . . { slide valves with flat obturating members }
- F16K 27/045 . . . { with pivotal obturating members }
- F16K 27/047 . . . { with wedge-shaped obturating members }
- F16K 27/048 . . { Electromagnetically actuated valves }

WARNING

This group is not complete pending a reorganisation, see also [F16K 27/04](#)

- F16K 27/06 . of taps or cocks
- F16K 27/062 . . { with conical plugs }
- F16K 27/065 . . { with cylindrical plugs }
- F16K 27/067 . . { with spherical plugs }
- F16K 27/07 . of cutting-off parts of tanks, e.g. tank-ears

WARNING

This group is not complete pending a reorganisation, see also [F16K 51/00](#)

- F16K 27/08 . Guiding yokes for spindles; Means for closing housings; Dust caps, e.g. for tyre valves
- F16K 27/10 . Welded housings
- F16K 27/102 . . { for lift-valves }
- F16K 27/105 . . { for gate valves }
- F16K 27/107 . . { for taps or cocks }
- F16K 27/12 . Covers for housings

F16K 29/00 Arrangements for movement of valve members other than for opening and closing the valve, e.g. for grinding-in, for preventing sticking

- F16K 29/02 . providing for continuous motion

F16K 31/00 { Actuating devices; } Operating means; Releasing devices {(regulating means [G05D](#))}

- F16K 31/001 . { actuated by volume variations caused by an element soluble in a fluid or swelling in contact with a fluid ([life-boats B63C 9/24](#))}

- F16K 31/002 . { actuated by temperature variation (thermo-electric [F16K 31/025](#))}
- F16K 31/003 . { operated without a stable intermediate position, e.g. with snap action ([F16K 31/56 takes precedence](#)) }
- F16K 31/004 . { actuated by piezo-electric means }
- F16K 31/005 .. { Piezo-electric benders }
- F16K 31/006 ... { having a free end }
- F16K 31/007 .. { Piezo-electric stacks }
- F16K 31/008 ... { for sliding valves }

WARNING

This group is not complete pending a reorganisation, see also [F16K 31/007](#)

- F16K 31/02 . electric {([F16K 31/004 takes precedence](#))}; magnetic
- F16K 31/025 .. { actuated by thermo-electric means }
- F16K 31/04 .. using a motor
- F16K 31/041 ... { for rotating valves ([F16K 31/055 takes precedence](#)) }

WARNING

Subgroups [F16K 31/042](#) to [F16K 31/045](#) are not complete pending a reorganisation, see also **[F16K 31/04B](#)**

- F16K 31/042 { with electric means, e.g. for controlling the motor or a clutch between the valve and the motor }
- F16K 31/043 { characterised by mechanical means between the motor and the valve, e.g. lost motion means reducing backlash, clutches, brakes or return means }
- F16K 31/045 { with torque limiters }
- F16K 31/046 ... { with electric means, e.g. electric switches, to control the motor or to control a clutch between the valve and the motor ([F16K 31/041 takes precedence](#)) }
- F16K 31/047 ... { characterised by mechanical means between the motor and the valve, e.g. lost motion means reducing backlash, clutches, brakes or return means ([F16K 31/043 takes precedence](#)) }
- F16K 31/048 { with torque limiters ([F16K 31/041 takes precedence](#)) }
- F16K 31/05 ... specially adapted for operating hand-operated valves or for combined motor and hand operation
- F16K 31/055 { for rotating valves }
- F16K 31/06 .. using a magnet { e.g. diaphragm valves, cutting off by means of a liquid }
- F16K 31/0603 ... { Multiple-way valves }
- F16K 31/0606 { fluid passing through the solenoid coil }
- F16K 31/061 { Sliding valves }
- F16K 31/0613 { with cylindrical slides }

F16K 31/0617	{ with flat slides }
F16K 31/062	{ the valve element being at least partially ball-shaped }
F16K 31/0624	{ Lift valves }
F16K 31/0627	{ with movable valve member positioned between seats }
F16K 31/0631	{ with ball shaped valve members }
F16K 31/0634	{ with fixed seats positioned between movable valve members }
F16K 31/0637	{ with ball shaped valve members }
F16K 31/0641	{ the valve member being a diaphragm }
F16K 31/0644	...	{ One-way valve }
F16K 31/0648	{ the armature and the valve member forming one element (F16K 31/0651 takes precedence)}
F16K 31/0651	{ the fluid passing through the solenoid coil }
F16K 31/0655	{ Lift valves }
F16K 31/0658	{ Armature and valve member being one single element }
F16K 31/0662	{ with a ball-shaped valve member }
F16K 31/0665	{ with valve member being at least partially ball-shaped (F16K 31/0662 takes precedence)}
F16K 31/0668	{ Sliding valves }
F16K 31/0672	{ the valve member being a diaphragm }
F16K 31/0675	...	{ Electromagnet aspects, e.g. electric supply therefor }
F16K 31/0679	{ with more than one energising coil }
F16K 31/0682	...	{ with an articulated or pivot armature }
F16K 31/0686	...	{ Braking, pressure equilibration, shock absorbing }
F16K 31/0689	{ Braking of the valve element }
F16K 31/0693	{ Pressure equilibration of the armature }
F16K 31/0696	{ Shock absorbing, e.g. using a dash-pot }
F16K 31/08	...	using a permanent magnet
F16K 31/082	{ using a electromagnet and a permanent magnet }
F16K 31/084	{ the magnet being used only as a holding element to maintain the valve in a specific position, e.g. check valves (F16K 31/082 , F16K 31/086 take precedence)}
F16K 31/086	{ the magnet being movable and actuating a second magnet connected to the closing element }
F16K 31/088	{ the movement of the first magnet being a rotating or pivoting movement }
F16K 31/10	...	with additional mechanism between armature and closure member
F16K 31/105	{ for rotating valves }
F16K 31/12	.	actuated by fluid ({ fluid-actuated lift valves F16K 1/126 } ; fluid-actuated check valves F16K 15/00 ; fluid-actuated safety valves F16K 17/00)
F16K 31/122	..	{ the fluid acting on a piston (F16K 31/143 , F16K 31/163 , F16K 31/363 , F16K 31/383 take precedence)}
F16K 31/1221	...	{ one side of the piston being spring-loaded }

F16K 31/1223	...	{ one side of the piston being acted upon by the circulating fluid }
F16K 31/1225	...	{ with a plurality of pistons }
F16K 31/1226	...	{ the fluid circulating through the piston }
F16K 31/1228	...	{ with a stationary piston }
F16K 31/124	...	servo actuated
F16K 31/1245	{ with more than one valve }
F16K 31/126	..	{ the fluid acting on a diaphragm, bellows, or the like (F16K 31/145 , F16K 31/165 , F16K 31/365 , F16K 31/385 take precedence)}
F16K 31/1262	...	{ one side of the diaphragm being spring loaded }
F16K 31/1264	{ with means to allow the side on which the springs are positioned to be altered }
F16K 31/1266	...	{ one side of the diaphragm being acted upon by the circulating fluid }
F16K 31/1268	...	{ with a plurality of the diaphragms }
F16K 31/128	...	servo actuated
F16K 31/14	..	for mounting on, or in combination with, hand-actuated valves
F16K 31/143	...	the fluid acting on a piston
F16K 31/145	...	the fluid acting on a diaphragm
F16K 31/16	..	with a mechanism, other than pulling-or pushing-rod, between fluid motor and closure member (with float F16K 31/18)
F16K 31/163	...	the fluid acting on a piston
F16K 31/1635	{ for rotating valves }
F16K 31/165	...	the fluid acting on a diaphragm
F16K 31/1655	{ for rotating valves }
F16K 31/18	..	actuated by a float (floats F16K 33/00 ; float-actuated valves in steam-traps F16T 1/20 , in boilers F22D 5/08)
F16K 31/20	...	actuating a lift valve
F16K 31/22	with the float rigidly connected to the valve
F16K 31/24	with a transmission with parts linked together from a single float to a single valve
F16K 31/26	with the valve guided for rectilinear movement and the float attached to a pivoted arm
F16K 31/265	{ with a second lever or toggle between the pivoted arm and the valve }
F16K 31/28	with two ore more floats actuating one valve
F16K 31/30	...	actuating a gate valve or sliding valve
F16K 31/32	...	actuating a tap or cock
F16K 31/34	...	acting on pilot valve controlling the cut-off apparatus
F16K 31/36	..	in which fluid from the circuit is constantly supplied to the fluid motor
F16K 31/363	...	the fluid acting on a piston (F16K 31/38 takes precedence)
F16K 31/365	...	the fluid acting on a diaphragm

F16K 31/38	...	in which the fluid works directly on both sides of the fluid motor, one side being connected by means of a restricted passage and the motor being actuated by operating a discharge from that side (F16K 31/40 takes precedence)
F16K 31/383	the fluid acting on a piston
F16K 31/3835	{ the discharge being effected through the piston and being blockable by a mechanically-actuated member making contact with the piston }
F16K 31/385	the fluid acting on a diaphragm
F16K 31/3855	{ the discharge being effected through the diaphragm and being blockable by a mechanically-actuated member making contact with the diaphragm }
F16K 31/40	...	with electrically-actuated member in the discharge of the motor
F16K 31/402	{ acting on a diaphragm }
F16K 31/404	{ the discharge being effected through the diaphragm and being blockable by an electrically-actuated member making contact with the diaphragm }
F16K 31/406	{ acting on a piston }
F16K 31/408	{ the discharge being effected through the piston and being blockable by an electrically-actuated member making contact with the piston }
F16K 31/42	..	by means of electrically-actuated members in the supply or discharge conduits of the fluid motor (F16K 31/40 takes precedence)
F16K 31/423	...	{ the actuated members consisting of multiple way valves }
F16K 31/426	{ the actuated valves being cylindrical sliding valves }
F16K 31/44	.	Mechanical actuating means
F16K 31/445	..	{ with exterior sleeve }
F16K 31/46	..	for remote operation
F16K 31/465	...	{ by flexible transmission means, e.g. cable, chain, bowden wire }

WARNING

not complete, see also [F16K 31/46](#)

F16K 31/48	..	actuated by mechanical timing-device, e.g. with dash-pot (self-closing valves F16K 21/16)
F16K 31/485	...	{ and specially adapted for gas valves }
F16K 31/50	..	with screw-spindle { or internally threaded actuating means }
F16K 31/502	...	{ actuating pivotable valve members }
F16K 31/504	...	{ the actuating means being rotatable, rising, and having internal threads which co-operate with threads on the outside of the valve body }
F16K 31/506	...	{ with plural sets of thread, e.g. with different pitch }

WARNING

not yet complete, see also [F16K 31/50](#)

F16K 31/508 ... { the actuating element being rotatable, non-rising, and driving a non-rotatable axially-sliding element }

WARNING

not yet complete, see also [F16K 31/50](#)

F16K 31/52 .. with crank, eccentric, or cam

F16K 31/521 ... { comprising a pivoted disc or flap }

F16K 31/522 ... { comprising a tap or cock }

F16K 31/523 ... { comprising a sliding valve }

F16K 31/524 ... with a cam

F16K 31/52408 { comprising a lift valve }

F16K 31/52416 { comprising a multiple-way lift valve }

F16K 31/52425 { with a ball-shaped valve member }

F16K 31/52433 { with a streamlined or helically shaped valve member, e.g. for reducing flow losses or guiding the fluid flow }

F16K 31/52441 { with a pivoted disc or flap }

F16K 31/5245 { with a valve member of conical shape }

F16K 31/52458 { comprising a tap or cock }

F16K 31/52466 { comprising a multiple-way tap or cock }

F16K 31/52475 { comprising a sliding valve }

F16K 31/52483 { comprising a multiple-way sliding valve }

F16K 31/52491 { comprising a diaphragm cut-off apparatus }

F16K 31/528 ... with pin and slot

F16K 31/5282 { comprising a pivoted disc or flap }

F16K 31/5284 { comprising a tap or cock }

F16K 31/5286 { comprising a sliding valve }

F16K 31/5288 { comprising a diaphragm cut-off apparatus }

F16K 31/53 .. with toothed gearing

F16K 31/535 ... { for rotating valves ([F16K 31/54](#) takes precedence)}

F16K 31/54 ... with pinion and rack

F16K 31/56 .. without stable intermediate position, e.g. with snap action

F16K 31/563 ... { for rotating or pivoting valves }

F16K 31/566 ... { using a bistable spring device arranged symmetrically around the actuating stem }

F16K 31/58 .. comprising a movable discharge-nozzle

F16K 31/60 .. Handles { form, features or function of taps or faucet handles for domestic plumbing installations [E03C 1/04](#) }

F16K 31/602 ... { Pivoting levers, e.g. single-sided ([F16K 31/605](#) takes precedence)}

F16K 31/605 ... { for single handle mixing valves }

F16K 31/607 . . . { characterised by particular material, by special measures to obtain aesthetical effects, or by auxiliary functions, e.g. storage }

WARNING

not complete, see also [F16K 31/60](#)

F16K 31/62 . . Pedals or like operating members, e.g. actuated by knee or hip

F16K 33/00 **Floats for actuation of valves or other apparatus** {(float actuated valves [F16K 31/18](#))}

F16K 35/00 **Means to prevent accidental or unauthorised actuation**

F16K 35/02 . to be locked or disconnected by means of a pushing or pulling action

F16K 35/022 . . { the locking mechanism being actuated by a separate actuating element }

F16K 35/025 . . . { said actuating element being operated manually (e.g. a push-button located in the valve actuator)}

F16K 35/027 . . { the locking mechanism being actuated by pushing or pulling the valve actuator, the valve actuator being rotated subsequently to bring the valve closure element in the desired position }

F16K 35/04 . Yieldingly resisting the actuation

F16K 35/06 . using a removable actuating or locking member, e.g. a key ([F16K 35/10](#) , [F16K 35/12](#) take precedence)

F16K 35/08 . requiring setting according to a code, e.g. permutation locks

F16K 35/10 . with locking caps or locking bars

F16K 35/12 . with sealing wire

F16K 35/14 . interlocking two or more valves

F16K 35/16 . with locking member actuated by magnet

F16K 37/00 **Special means in or on valves or other cut-off apparatus for indicating or recording operation thereof, or for enabling an alarm to be given**

F16K 37/0008 . { Mechanical means ([F16K 37/0075](#) takes precedence)}

F16K 37/0016 . . { having a graduated scale }

F16K 37/0025 . { Electrical or magnetic means ([F16K 37/0075](#) takes precedence)}

F16K 37/0033 . . { using a permanent magnet, e.g. in combination with a reed relays }

F16K 37/0041 . . { for measuring valve parameters ([F16K 37/0033](#) takes precedence)}

F16K 37/005 . . { for measuring fluid parameters ([F16K 37/0033](#) takes precedence)}

- F16K 37/0058 . [Optical means, e.g. light transmission, observation ports ([F16K 37/0075 takes precedence](#))]
- F16K 37/0066 . { Hydraulic or pneumatic means ([F16K 37/0075 takes precedence](#))}
- F16K 37/0075 . { For recording or indicating the functioning of a valve in combination with test equipment }
- F16K 37/0083 .. { by measuring valve parameters }
- F16K 37/0091 .. { by measuring fluid parameters }

F16K 39/00**Devices for relieving the pressure on the sealing faces**

- F16K 39/02 . for lift valves
- F16K 39/022 .. { using balancing surfaces }
- F16K 39/024 .. { using an auxiliary valve on the main valve }
- F16K 39/026 .. { using an external auxiliary valve }
- F16K 39/028 .. { with pivoted closure members, e.g. butterfly valves }
- F16K 39/04 . for sliding valves
- F16K 39/045 .. { of rotating or pivoting type }

WARNING

Not yet complete, see [F16K 39/04](#)]

- F16K 39/06 . for taps or cocks

F16K 41/00**Spindle sealings**

- F16K 41/003 . { by fluid }
- F16K 41/006 . { by establishing an under-pressure }
- F16K 41/02 . with stuffing-box; { Sealing rings }
- F16K 41/023 .. { for spindles which only rotate, i.e. non-rising spindles ([F16K 41/043](#) , [F16K 41/063](#) and [F16K 41/083](#) take precedence)}
- F16K 41/026 ... { for rotating valves }
- F16K 41/04 . with at least one ring of rubber or like material between spindle and housing
- F16K 41/043 ... { for spindles which only rotate, i.e. non-rising spindles }
- F16K 41/046 { for rotating valves }
- F16K 41/06 . with at least one ring attached to both spindle and housing
- F16K 41/063 ... { for spindles which only rotate, i.e. non-rising spindles }

WARNING

Not yet complete, see also [F16K 41/06](#)]

F16K 41/066 { for rotating valves }

WARNING

Not yet complete, see also [F16K 41/06](#)]

F16K 41/08 . . with at least one ring provided with axially-protruding peripheral closing-lip

F16K 41/083 . . . { for spindles which only rotate, i.e. non-rising spindles }

WARNING

Not yet complete, see also [F16K 41/08](#)]

F16K 41/086 { for rotating valves }

WARNING

Not yet complete, see also [F16K 41/08](#)]

F16K 41/10 . with diaphragm, e.g. shaped as bellows or tube

F16K 41/103 . . { the diaphragm and the closure member being integrated in one member }

F16K 41/106 . . { for use with rotating spindles or valves ([F16K 41/125](#) takes precedence) }

F16K 41/12 . with approximately flat diaphragm

F16K 41/125 . . . { the part of the spindle traversing the diaphragm being rotatable or pivotable }

F16K 41/14 . with conical flange on the spindle which co-operates with a conical surface in the housing

F16K 41/16 . with a flange on the spindle which rests on a sealing ring

F16K 41/18 . . sealing only when the closure member is in the opened position

F16K 43/00 **Auxiliary closure means in valves, which in case of repair, e.g. rewashering, of the valve, can take over the function of the normal closure means; Devices for temporary replacement of parts of valves for the same purpose**

F16K 43/001 . { an auxiliary valve being actuated independently of the main valve }

F16K 43/003 . . { the auxiliary valve being a rotary valve }

F16K 43/005 . { an auxiliary valve closing automatically when the main valve is being disassembled }

F16K 43/006 . . { the auxiliary valve being held open by the main valve }

F16K 43/008 . { the main valve having a back-seat position, e.g. to service the spindle sealing }

F16K 47/00 **Means in valves for absorbing fluid energy { e.g. cushioning of opening or closure movement, eliminating of vibrations of the valve member } (for pipes [F16L 55/00](#))**

- F16K 47/02 . for preventing water-hammer or noise { e.g. for sanitary applications, toilet flush reservoirs ([F16K 47/04](#) and [F16K 47/08](#) take precedence)}
- F16K 47/023 .. { for preventing water-hammer, e.g. damping of the valve movement }
- F16K 47/026 .. { preventing noise in a single handle mixing valve }
- F16K 47/04 . for decreasing pressure { or noise level }, the throttle being incorporated in the closure member
- F16K 47/045 .. { and the closure member being rotatable }
- F16K 47/06 .. with a throttle in the form of a helical channel
- F16K 47/08 . for decreasing pressure { or noise level } and having a throttling member separate from the closure member, { e.g. screens, slots, labyrinths }
- F16K 47/10 .. in which the medium in one direction must flow through the throttling channel, and in the other direction may flow through a much wider channel parallel to the throttling channel
- F16K 47/12 .. the throttling channel being of helical form
- F16K 47/14 .. the throttling member being a perforated membrane
- F16K 47/16 .. the throttling member being a cone
- F16K 49/00 Means in or on valves for heating or cooling (for pipes [F16L 53/00](#) ; thermal insulation in connection with pipes or pipe systems [F16L 59/16](#))**
- F16K 49/002 . { Electric heating means }
- F16K 49/005 . { Circulation means for a separate heat transfer fluid }
- F16K 49/007 .. { located within the obturating element }
- F16K 51/00 Other details not peculiar to particular types of valves or cut-off apparatus**
- F16K 51/02 . specially adapted for high-vacuum installations
- F16K 99/00 Subject matter not provided for in other groups of this subclass**
- F16K 99/0001 . { Micro-valves (micro-devices [B81B 1/00](#) ; manufacture or treatment of devices or systems in or on a substrate [B81C 1/00](#) ; micro-fluidic structures [B01L 3/5027](#) ; micro-pumps [F04B 19/006](#))}
- F16K 99/0003 .. { Constructional types of microvalves; Details of the cutting-off member }
- F16K 99/0005 ... { Lift valves }
- F16K 99/0007 { of cantilever type }
- F16K 99/0009 { the valve element held by multiple arms }
- F16K 99/0011 ... { Gate valves or sliding valves }
- F16K 99/0013 ... { Rotary valves }
- F16K 99/0015 ... { Diaphragm or membrane valves }

F16K 99/0017	...	{ Capillary or surface tension valves, e.g. using electro-wetting or electro-capillarity effects }
F16K 99/0019	...	{ Valves using a micro-droplet or micro-bubble as the valve member }
F16K 99/0021	...	{ No-moving-parts valves }
F16K 99/0023	...	{ with ball-shaped valve members }
F16K 99/0025	...	{ Valves using microporous membranes }
F16K 99/0026	...	{ Valves using channel deformation }
F16K 99/0028	...	{ Valves having multiple inlets or outlets }
F16K 99/003	...	{ Valves for single use only }
F16K 99/0032	...	{ using phase transition or influencing viscosity }
F16K 99/0034	..	{ Operating means specially adapted for microvalves }
F16K 99/0036	...	{ operated by temperature variations }
F16K 99/0038	{ using shape memory alloys }
F16K 99/004	{ using radiation }
F16K 99/0042	...	{ Electric operating means therefor }
F16K 99/0044	{ using thermo-electric means }
F16K 99/0046	{ using magnets }
F16K 99/0048	{ using piezoelectric means }
F16K 99/0049	{ using an electroactive polymer (EAP) }
F16K 99/0051	{ using electrostatic means }
F16K 99/0053	{ using magnetostrictive means }
F16K 99/0055	...	{ actuated by fluids }
F16K 99/0057	{ the fluid being the circulating fluid itself, e.g. check valves }
F16K 99/0059	{ actuated by a pilot fluid }
F16K 99/0061	{ actuated by an expanding gas or liquid volume }
F16K 99/0063	...	{ using centrifugal forces }
F16K 99/0065	...	{ using chemical activation }
F16K 99/0067	{ actuated by a pyrotechnical charge }
F16K 2099/0069	..	{ Bistable microvalves }
F16K 2099/0071	..	{ with latching means }
F16K 2099/0073	.	{ Fabrication methods specifically adapted for microvalves }
F16K 2099/0074	..	{ using photolithography, e.g. etching }
F16K 2099/0076	..	{ using electrical discharge machining (EDM), milling or drilling }
F16K 2099/0078	..	{ using moulding or stamping }
F16K 2099/008	..	{ Multi-layer fabrications }
F16K 2099/0082	.	{ Microvalves adapted for a particular use }
F16K 2099/0084	..	{ Chemistry or biology, e.g. "lab-on-a-chip" technology }
F16K 2099/0086	..	{ Medical applications }
F16K 2099/0088	...	{ Implanted devices }

F16K 2099/009	..	{ Fluid power devices }
F16K 2099/0092	..	{ Inkjet printers }
F16K 2099/0094	..	{ Micro-pumps }
F16K 2099/0096	..	{ Fuel injection devices }
F16K 2099/0098	..	{ Refrigeration circuits, e.g. for cooling integrated circuits }