

CPC**COOPERATIVE PATENT CLASSIFICATION****B61F**

RAIL VEHICLE SUSPENSIONS, e.g. UNDERFRAMES, BOGIES, ARRANGEMENTS OF WHEEL AXLES; RAIL VEHICLES FOR USE ON TRACKS OF DIFFERENT WIDTH; PREVENTING DERAILING; WHEEL GUARDS; OBSTRUCTION REMOVERS, OR THE LIKE (for vehicles in general [B60](#); axles, wheels [B60B](#); tyres [B60C](#))

B61F 1/00

Underframes (making railway vehicle underframes by forging or pressing [B21K 7/12](#))

B61F 1/02

- . with a single central sill

B61F 1/04

- . of triangulated type

B61F 1/06

- . specially adapted for locomotives or motor-driven railcars

B61F 1/08

- . Details

B61F 1/10

- .. End constructions

B61F 1/12

- .. Cross bearers

B61F 1/14

- .. Attaching or supporting vehicle body-structure

B61F 3/00

Types of bogies ([B61F 5/00](#) takes precedence)

B61F 3/02

- . with more than one axle

B61F 3/04

- .. with driven axles or wheels

B61F 3/06

- ... with three or more axles

B61F 3/08

- .. without driven axles or wheels

B61F 3/10

- ... with three or more axles

B61F 3/12

- . specially modified for carrying adjacent vehicle bodies of articulated trains

B61F 3/125

- .. {with more than one axle or wheel set}

B61F 3/14

- . specially modified for reducing air resistance

B61F 3/16

- . with a separate axle for each wheel

B61F 5/00

Constructional details of bogies; Connections between bogies and vehicle underframes; Arrangements or devices for adjusting or allowing self-adjustment of wheel axles or bogies when rounding curves

B61F 5/02

- . Arrangements permitting limited transverse relative movements between vehicle underframe or bolster and bogie; Connections between underframes and bogies

B61F 5/04

- .. Bolster supports or mountings ([side bearings B61F 5/14](#))

B61F 5/06

- ... incorporating metal springs

B61F 5/08

- ... incorporating rubber springs

B61F 5/10

- ... incorporating fluid springs

B61F 5/12

- ... incorporating dampers

B61F 5/122

- {with friction surfaces}

B61F 5/125

- {with rubber elements ([B61F 5/08](#) takes precedence)}

B61F 5/127

- {with fluid as a damping medium}

B61F 5/14

- .. Side bearings

B61F 5/142	...	{made of rubber elements, graphite or the like}
B61F 5/144	...	{comprising fluid damping devices (B61F 5/146 takes precedence)}
B61F 5/146	...	{of the oil bath type; Lubrication devices for side bearings}
B61F 5/148	...	{between bolsterless bogies and underframes (B61F 5/142 - B61F 5/146 take precedence)}
B61F 5/16	..	Centre bearings or other swivel connections between underframes and bolsters or bogies
B61F 5/18	...	King-bolts
B61F 5/20	...	with springs allowing transverse movements
B61F 5/22	..	Guiding of the vehicle underframes with respect to the bogies
B61F 5/24	...	Means for damping or minimising the canting, skewing, pitching, or plunging movements of the underframes
B61F 5/245	{by active damping, i.e. with means to vary the damping characteristics in accordance with track or vehicle induced reactions, especially in high speed mode}
B61F 5/26	.	Mounting or securing axle-boxes in vehicle or bogie underframes
B61F 5/28	..	Axle-boxes integral with, or directly secured to, vehicle or bogie underframes
B61F 5/30	..	Axle-boxes mounted for movement under spring control in vehicle or bogie underframes (B61F 5/36 takes precedence over B61F 5/305 - B61F 5/34)
B61F 5/301	...	{incorporating metal springs}
B61F 5/302	{Leaf springs}
B61F 5/304	{Torsion-bar springs}
B61F 5/305	...	{incorporating rubber springs}
B61F 5/307	...	{incorporating fluid springs}
B61F 5/308	...	{incorporating damping devices}
B61F 5/32	...	Guides, e.g. plates, for axle-boxes
B61F 5/325	{The guiding device including swinging arms or the like to ensure the parallelism of the axles}
B61F 5/34	Wedge mechanisms for adjusting clearance between underframes and axles
B61F 5/36	...	Arrangements for equalising or adjusting the load on wheels or springs, e.g. yokes
B61F 5/38	.	Arrangements or devices for adjusting or allowing self- adjustment of wheel axles or bogies when rounding curves, e.g. sliding axles, swinging axles
B61F 5/383	..	{Adjustment controlled by non-mechanical devices, e.g. scanning trackside elements}
B61F 5/386	..	{fluid actuated}
B61F 5/40	..	Bogies with side frames mounted for longitudinal relative movements
B61F 5/42	..	Adjustment controlled by buffer or coupling gear
B61F 5/44	..	Adjustment controlled by movements of vehicle body
B61F 5/46	..	Adjustment controlled by a sliding axle under the same vehicle underframe
B61F 5/48	..	Trailing or leading bogies for locomotives or motor- driven railcars (B61F 5/40 takes precedence)
B61F 5/50	.	Other details

B61F 5/52	.. Bogie frames
B61F 5/523	... {comprising parts made from fibre-reinforced matrix material}
B61F 5/526	... {comprising noise reducing devices}
B61F 7/00	Rail vehicles equipped for use on tracks of different width
B61F 9/00	Rail vehicles characterised by means for preventing derailing, e.g. by use of guide wheels
B61F 9/005	. {by use of non-mechanical means, e.g. acoustic or electromagnetic devices}
B61F 11/00	Rail vehicles characterised by rail-engaging elements other than wheels, e.g. balls
B61F 13/00	Rail vehicles characterised by wheel arrangements, not otherwise provided for
B61F 15/00	Axle-boxes (mounting or securing axle-boxes B61F 5/26 ; lubrication B61F 17/00 ; bearings in general F16C)
B61F 15/02	. with journal bearings
B61F 15/04	.. for locomotives
B61F 15/06	.. for cars
B61F 15/08	.. the axle being slidable or tiltable in the bearings
B61F 15/10	... and having springs opposing such movements
B61F 15/12	. with roller, needle, or ball bearings
B61F 15/14	.. constructed for taking-up axial pressure
B61F 15/16	.. the axle being slidable or tiltable in the bearings
B61F 15/18	... and having springs opposing such movements
B61F 15/20	. Details
B61F 15/22	.. Sealing means preventing entrance of dust or leakage of oil
B61F 15/24	... preventing oil leakage when vehicle is tilted or inverted
B61F 15/26	.. Covers; Sealing thereof
B61F 15/28	.. Axle-boxes modified to ensure electrical conductivity
B61F 17/00	Lubrication specially adapted for axle-boxes of rail vehicles (lubrication in general F16N)
B61F 17/02	. with oil
B61F 17/04	.. Lubrication by stationary devices
B61F 17/06	... by means of a wick or the like
B61F 17/08 Devices for pressing the wick or the like against the rotating axle
B61F 17/10	... by means of an oil bath
B61F 17/12	... by gravity
B61F 17/14	.. Rotating lubricating devices
B61F 17/16	... with rings
B61F 17/18	... with chains
B61F 17/20	... with scoops or the like attached to, or coupled with, the axle

B61F 17/22	...	with discs, rollers, or belts engaging the axle
B61F 17/24	..	by built-in lubricating pumps
B61F 17/26	..	by external feeding means, e.g. pneumatic devices
B61F 17/28	..	Applications of oil cleaners not otherwise provided for
B61F 17/30	.	with grease
B61F 17/32	..	by manually-operated lubricators, e.g. screw cups
B61F 17/34	..	by automatic means, e.g. with spring action
B61F 17/36	.	with other, e.g. mixed, lubricating agents
B61F 19/00	Wheel guards; Bumpers; Obstruction removers or the like (for vehicles in general B60R 19/00)	
B61F 19/02	.	Wheel guards
B61F 19/04	.	Bumpers or like collision guards
B61F 19/06	.	Nets, catchers, or the like for catching obstacles or removing them from the track (mailbag catchers B61K 1/02)
B61F 19/08	..	of the drop-down type
B61F 19/10	...	automatically operated by engagement with obstacle
B61F 99/00	Subject matter not provided for in other groups of this subclass	