

CPC**COOPERATIVE PATENT CLASSIFICATION****H01P****WAVEGUIDES; RESONATORS, LINES, OR OTHER DEVICES OF THE WAVEGUIDE TYPE** (operating at optical frequencies [G02B](#); aerials

[H01Q](#); {modulating electromagnetic waves in transmission line, waveguide, cavity resonator or radiation field of aerial [H03C 7/02](#)}; networks comprising lumped impedance elements [H03H](#))

NOTE

In this subclass, the following expression is used with the meaning indicated :

- "waveguide type" as applied to transmission lines includes only high-frequency coaxial cables or Lecher lines, and as applied to resonators, delay lines, or other devices includes all devices having distributed inductance and capacitance.

H01P 1/00

Auxiliary devices (coupling devices of the waveguide type [H01P 5/00](#))

H01P 1/005

. {Diode mounting means}

H01P 1/02

. Bends; Corners; Twists

H01P 1/022

.. {in waveguides of polygonal cross-section ([H01P 1/065](#) takes precedence)}

H01P 1/025

... {in the E-plane}

H01P 1/027

... {in the H-plane}

H01P 1/04

. Fixed joints ({pipe joints [F16L](#)}; line connectors [H01R](#); cable fittings [H02G 15/00](#))

H01P 1/042

.. {Hollow waveguide joints}

H01P 1/045

.. {Coaxial joints}

H01P 1/047

.. {Strip line joints}

H01P 1/06

. Movable joints, e.g. rotating joints

H01P 1/061

.. {the relative movement being a translation along an axis common to at least two rectilinear parts, e.g. expansion joints}

H01P 1/062

.. {the relative movement being a rotation}

H01P 1/063

... {with a limited angle of rotation}

H01P 1/064

.... {the axis of rotation being perpendicular to the transmission path, e.g. hinge joint}

H01P 1/065

.... {the axis of rotation being parallel to the transmission path, e.g. stepped twist}

H01P 1/066

... {with an unlimited angle of rotation}

H01P 1/067

.... {the energy being transmitted in only one line located on the axis of rotation}

H01P 1/068

.... {the energy being transmitted in at least one ring-shaped transmission line located around the axis of rotation, e.g. "around the mast" rotary joint ([H01P 1/069](#) takes precedence; coaxial line with solid inner conductor [H01P 1/067](#))}

H01P 1/069

.... {the energy being transmitted in at least one ring-shaped transmission line located around an axial transmission line; Concentric coaxial systems}

H01P 1/08

. Dielectric windows (coupling devices for transit time tubes [H01J 23/36](#))

- H01P 1/10 . for switching or interrupting {(in systems using reflection or reradiation of radio, acoustic or other waves [G01S 7/034](#))}
- H01P 1/11 . . by ferromagnetic devices
- H01P 1/12 . . by mechanical chopper
- H01P 1/122 . . . {Waveguide switches}
- H01P 1/125 . . . {Coaxial switches}
- H01P 1/127 . . . {Strip line switches}
- H01P 1/14 . . by electric discharge devices (discharge devices [H01J 17/64](#))
- H01P 1/15 . . by semiconductor devices
- H01P 1/16 . for mode selection, e.g. mode suppression or mode promotion; for mode conversion (linking dissimilar lines or devices [H01P 5/08](#))
- H01P 1/161 . . sustaining two independent orthogonal modes, e.g. orthomode transducer {(combining or separating polarisations and frequencies [H01P 1/2131](#))}
- H01P 1/162 . . absorbing spurious or unwanted modes of propagation
- H01P 1/163 . . specifically adapted for selection or promotion of the TE 01 circular-electric mode
- H01P 1/165 . for rotating the plane of polarisation
- H01P 1/17 . . for producing a continuously rotating polarisation, e.g. circular polarisation
- H01P 1/171 . . . {using a corrugated or ridged waveguide section}
- H01P 1/172 . . . {using a dielectric element}
- H01P 1/173 . . . {using a conductive element}
- H01P 1/174 . . . {using a magnetic element ([H01P 1/175](#) takes precedence)}
- H01P 1/175 . . using Faraday rotators
- H01P 1/18 . Phase-shifters ([H01P 1/165](#) takes precedence; coupling devices with variable coupling factor [H01P 5/04](#))
- H01P 1/181 . . {using ferroelectric devices}
- H01P 1/182 . . {Waveguide phase-shifters ([H01P 1/181](#), [H01P 1/185](#), [H01P 1/19](#) take precedence)}
- H01P 1/183 . . {Coaxial phase-shifters ([H01P 1/181](#), [H01P 1/185](#), [H01P 1/19](#) take precedence)}
- H01P 1/184 . . {Strip line phase-shifters ([H01P 1/181](#), [H01P 1/185](#), [H01P 1/19](#) take precedence)}
- H01P 1/185 . . using a diode or a gas filled discharge tube
- H01P 1/19 . . using a ferromagnetic device
- H01P 1/195 . . . having a toroidal shape
- H01P 1/20 . Frequency-selective devices, e.g. filters {(variable impedance transformers, e.g. slug tuners or stub tuners [H01P 5/04](#)); resonators [H01P 7/00](#)}
- H01P 1/2002 . . {Dielectric waveguide filters ([H01P 1/212](#), [H01P 1/213](#), [H01P 1/215](#), [H01P 1/219](#) take precedence)}
- H01P 1/2005 . . {Electromagnetic photonic bandgaps [EPB], or photonic bandgaps [PBG]}
- H01P 1/2007 . . {Filtering devices for biasing networks or DC returns}
- H01P 1/201 . . Filters for transverse electromagnetic waves ([H01P 1/212](#), [H01P 1/213](#), [H01P 1/215](#), [H01P 1/219](#) take precedence)
- H01P 1/2013 . . . {Coplanar line filters}
- H01P 1/2016 . . . {Slot line filters; Fin line filters}

H01P 1/202	...	Coaxial filters (cascaded coaxial cavities H01P 1/205)
H01P 1/203	...	Strip line filters
H01P 1/20309	{with dielectric resonator}
H01P 1/20318	{with dielectric resonators as non-metallised opposite openings in the metallised surfaces of a substrate}
H01P 1/20327	{Electromagnetic interstage coupling}
H01P 1/20336	{Comb or interdigital filters}
H01P 1/20345	{Multilayer filters}
H01P 1/20354	{Non-comb or non-interdigital filters}
H01P 1/20363	{Linear resonators}
H01P 1/20372	{Hairpin resonators}
H01P 1/20381	{Special shape resonators}
H01P 1/2039	{Galvanic coupling between Input/Output}
H01P 1/205	...	Comb or interdigital filters; Cascaded coaxial cavities (H01P 1/203 takes precedence)
H01P 1/2053	{the coaxial cavity resonators being disposed parall to each other}
H01P 1/2056	{Comb filters or interdigital filters with metallised resonator holes in a dielectric block}
H01P 1/207	..	Hollow waveguide filters (H01P 1/212 , H01P 1/213 , H01P 1/215 , H01P 1/219 take precedence)
H01P 1/208	...	Cascaded cavities; Cascaded resonators inside a hollow waveguide structure (H01P 1/205 takes precedence)
H01P 1/2082	{with multimode resonators (H01P 1/2086 takes precedence)}
H01P 1/2084	{with dielectric resonators}
H01P 1/2086	{multimode}
H01P 1/2088	{Integrated in a substrate}
H01P 1/209	...	comprising one or more branching arms or cavities wholly outside the main waveguide
H01P 1/211	...	Waffle-iron filters; Corrugated structures
H01P 1/212	..	suppressing or attenuating harmonic frequencies (H01P 1/215 takes precedence)
H01P 1/213	..	combining or separating two or more different frequencies (H01P 1/215 takes precedence)
H01P 1/2131	...	{with combining or separating polarisations}
H01P 1/2133	...	{using coaxial filters (H01P 1/2131 , H01P 1/2136 take precedence)}
H01P 1/2135	...	{using strip line filters (H01P 1/2131 takes precedence)}
H01P 1/2136	...	{using comb or interdigital filters; using cascaded coaxial cavities (H01P 1/2131 , H01P 1/2135 take precedence)}
H01P 1/2138	...	{using hollow waveguide filters (H01P 1/2131 takes precedence)}
H01P 1/215	..	using ferromagnetic material
H01P 1/217	...	the ferromagnetic material acting as a tuning element in resonators
H01P 1/218	...	the ferromagnetic material acting as a frequency selective coupling element, e.g. YIG-filters

- H01P 1/219 .. Evanescent mode filters
- H01P 1/22 . Attenuating devices ([dissipative terminating devices H01P 1/26](#))
- H01P 1/222 .. {[Waveguide attenuators \(H01P 1/23 takes precedence\)](#)}
- H01P 1/225 .. {[Coaxial attenuators \(H01P 1/23 takes precedence\)](#)}
- H01P 1/227 .. {[Strip line attenuators \(H01P 1/23 takes precedence\)](#)}
- H01P 1/23 .. using ferromagnetic material
- H01P 1/24 . Terminating devices
- H01P 1/26 .. Dissipative terminations
 - ... {the [dissipative medium being a liquid or being cooled by a liquid](#)}
 - ... {[Waveguide terminations \(H01P 1/262 takes precedence\)](#)}
 - ... {[Coaxial terminations \(H01P 1/262 takes precedence\)](#)}
 - ... {[Strip line terminations \(H01P 1/262 takes precedence\)](#)}
- H01P 1/28 .. Short-circuiting plungers ([coupling devices with variable coupling factor H01P 5/04](#))
- H01P 1/30 . for compensation of, or protection against, temperature or moisture effects; {[for improving power handling capability \(H01P 1/04, H01P 1/08 take precedence\)](#)}
- H01P 1/32 . Non-reciprocal transmission devices ([H01P 1/02 to H01P 1/30 take precedence](#))
- H01P 1/36 .. Isolators
 - ... {[Edge-guided mode devices](#)}
 - ... Resonance absorption isolators
 - ... Field displacement isolators
 - ... using Faraday rotators
- H01P 1/38 .. Circulators
 - ... Junction circulators, e.g. Y-circulators
 - Strip line circulators
 - Hollow waveguide circulators
 - ... using Faraday rotators
 - ... using non- reciprocal phase shifters ([H01P 1/393 takes precedence](#))

H01P 3/00**Waveguides; Transmission lines of the waveguide type**

- H01P 3/003 . {[Coplanar lines](#)}
- H01P 3/006 .. {[Conductor backed coplanar waveguides](#)}
- H01P 3/02 . with two longitudinal conductors
- H01P 3/023 .. {[Fin lines; Slot lines](#)}
- H01P 3/026 .. {[Coplanar striplines \[CPS\]](#)}
- H01P 3/04 .. Lines formed as Lecher wire pairs
- H01P 3/06 .. Coaxial lines ([not suitable for handling frequencies considerably beyond the audio range, {coaxial cables in general} H01B 11/18](#))

NOTE

H01P 3/06
(continued)

This subgroup is only used for documents disclosing typical HF-features of coaxial cables, e.g. propagation of non-TEM-modes, multimoding, oversized coaxial cables, particular cross-section adapted for HF-propagation

- H01P 3/08 .. Microstrips; Strip lines
- H01P 3/081 ... {Micro-striplines}
- H01P 3/082 {Multilayer dielectric}
- H01P 3/084 {Suspended micro-striplines}
- H01P 3/085 ... {Triplate lines}
- H01P 3/087 {Suspended triplate lines}
- H01P 3/088 ... {Stacked transmission lines}
- H01P 3/10 . Wire waveguides, i.e. with a single solid longitudinal conductor
- H01P 3/12 . Hollow waveguides ([H01P 3/20 takes precedence](#))
- H01P 3/121 .. {integrated in a substrate}
- H01P 3/122 .. {Dielectric loaded (not air)}
- H01P 3/123 .. with a complex or stepped cross-section, e.g. ridged or grooved waveguides ([H01P 3/14 takes precedence](#))
- H01P 3/127 .. with a circular, elliptic, or parabolic cross-section
- H01P 3/13 .. specially adapted for transmission of the TE₀₁ circular-electric mode {(selection, promotion [H01P 1/163](#))}
- H01P 3/14 .. flexible
- H01P 3/16 . Dielectric waveguides, i.e. without a longitudinal conductor
- H01P 3/165 .. {Non-radiating dielectric waveguides}
- H01P 3/18 . built-up from several layers to increase operating surface, i.e. alternately conductive and dielectric layers
- H01P 3/20 . Quasi-optical arrangements for guiding a wave, e.g. focusing by dielectric lenses ([quasi-optical devices in general H01Q 15/00](#))
- H01P 5/00** **Coupling devices of the waveguide type** (non-reciprocal devices [H01P 1/32](#); for introducing or removing wave energy to or from the discharge in transit-time tubes [H01J 23/36](#))
- H01P 5/02 . with invariable factor of coupling ([H01P 5/12 takes precedence](#) {choke joints [H01P 1/04](#), [H01P 1/06](#)})
- H01P 5/022 .. {Transitions between lines of the same kind and shape, but with different dimensions}
- H01P 5/024 ... {between hollow waveguides}
- H01P 5/026 ... {between coaxial lines}
- H01P 5/028 ... {between strip lines}
- H01P 5/04 . with variable factor of coupling
- H01P 5/08 . for linking dissimilar lines or devices ([H01P 1/16](#), [H01P 5/04 take precedence](#); linking lines of the same kind but with different dimensions [H01P 5/02](#))
- H01P 5/082 .. {Transitions between hollow waveguides of different shape, e.g. between a rectangular and a circular waveguide}
- H01P 5/085 .. {Coaxial-line/strip-line transitions}

H01P 5/087	.. {Transitions to a dielectric waveguide}
H01P 5/10	.. for coupling balanced with unbalanced lines or devices
H01P 5/1007	... {Microstrip transitions to Slotline or finline}
H01P 5/1015	... {Coplanar line transitions to Slotline or finline}
H01P 5/1022	... {Transitions to dielectric waveguide}
H01P 5/103	... Hollow-waveguide/coaxial-line transitions
H01P 5/107	... Hollow-waveguide/strip-line transitions
H01P 5/12	. Coupling devices having more than two ports (H01P 5/04 takes precedence)
H01P 5/16	.. Conjugate devices, i.e. devices having at least one port decoupled from one other port
H01P 5/18	... consisting of two coupled guides, e.g. directional couplers
H01P 5/181 {the guides being hollow waveguides}
H01P 5/182 {the waveguides being arranged in parallel}
H01P 5/183 {at least one of the guides being a coaxial line}
H01P 5/184 {the guides being strip lines or microstrips}
H01P 5/185 {Edge coupled lines}
H01P 5/186 {Lange couplers}
H01P 5/187 {Broadside coupled lines}
H01P 5/188 {the guides being dielectric waveguides}
H01P 5/19	.. of the junction type
H01P 5/20 Magic-T junctions
H01P 5/22 Hybrid ring junctions
H01P 5/222 {180° rat race hybrid rings}
H01P 5/225 {180° reversed phase hybrid rings}
H01P 5/227 {90° branch line couplers}
H01P 7/00	Resonators of the waveguide type ({variable impedance transformers H01P 5/04 }; structurally associated with transit-time tubes and interacting with the discharge therein H01J 23/18 ; {generators of electronic oscillations using resonators of this type H03B 5/18 , H03B 7/14 , H03B 9/14 ; electronic amplifiers using resonators of this type H03F 3/54 }; microwave heating devices H05B 6/64)
H01P 7/005	. {Helical resonators; Spiral resonators}
H01P 7/02	. Lecher resonators
H01P 7/04	. Coaxial resonators
H01P 7/06	. Cavity resonators
H01P 7/065	.. {integrated in a substrate}
H01P 7/08	. Strip line resonators
H01P 7/082	.. {Microstripline resonators (H01P 7/088 takes precedence)}
H01P 7/084	.. {Triplate line resonators (H01P 7/088 takes precedence)}
H01P 7/086	.. {Coplanar waveguide resonators (H01P 7/088 takes precedence)}
H01P 7/088	.. {Tunable resonators}
H01P 7/10	. Dielectric resonators

H01P 7/105 . . {Multimode resonators}

H01P 9/00 **Delay lines of the waveguide type** (structurally associated with transit-time tubes and interacting with the discharge therein [H01J 23/24](#))

H01P 9/003 . {Delay equalizers}

H01P 9/006 . {Meander lines}

H01P 9/02 . Helical lines

H01P 9/04 . Interdigital lines

H01P 11/00 **Apparatus or processes specially adapted for manufacturing waveguides or resonators, lines, or other devices of the waveguide type** (manufacture of coaxial cables [H01B 13/00](#))

H01P 11/001 . {Manufacturing waveguides or transmission lines of the waveguide type}

H01P 11/002 . . {Manufacturing hollow waveguides}

H01P 11/003 . . {Manufacturing lines with conductors on a substrate, e.g. strip lines, slot lines}

H01P 11/005 . . {Manufacturing coaxial lines}

H01P 11/006 . . {Manufacturing dielectric waveguides}

H01P 11/007 . {Manufacturing frequency-selective devices (resonators [H01P 11/008](#))}

H01P 11/008 . {Manufacturing resonators}