

CPC**COOPERATIVE PATENT CLASSIFICATION****B60Q**

VEHICLE LIGHTING OR SIGNALLING (arrangement of signalling or lighting devices, the mounting or supporting thereof for rail vehicles [B61D](#), for cycles [B62J](#), for ships [B63B](#), for aircrafts [B64D](#); lighting in general, lighting devices per se [F21](#), [H05B](#); signalling in general [G08](#); electric switches per se [H01H](#))

NOTES

1. This subclass covers also:
 - electric signalling of lighting circuits so far as specially arranged in vehicles;
 - arrangements or adaptations of lighting switches or signal-initiating means
2. Attention is drawn to the Note following the title of class [B60](#)
3. Attention is drawn to the following places :

| | |
|------------------------------|------------------------------------------------------------|
| B60K 28/00 | Safety devices, e.g. sleeping driver |
| B60R 25/00 | Anti theft |
| B62D | Driving assistance |
| B62D 15/02 | Steering aids |
| B60K 31/0008 | Cruise control |
| F21S 48/00 | Lighting devices or systems specially adapted for vehicles |
| G01S | Infra red night vision |
| G01S 13/931 | Anti Collision |
| G05D 1/00 | Automatic pilot |
| G06K 9/00 | Pattern recognition |
| G06T 3/00 | Image transformation |
| G06T 5/00 | Image enhancement |
| G06T 7/00 | Image analysis |
| G08B 21/00 | Alarms in general |
| G08G | Traffic control |
| G08G 1/16 | Anti-collision systems |
| H04N | Television systems |

WARNING

The following IPC groups are not used in the CPC scheme. Subject matter covered by these groups is classified in the following CPC groups:

| | | |
|----------------------------|------------|----------------------------|
| B60Q 1/128 | covered by | B60Q 1/124 |
| B60Q 1/132 | covered by | B60Q 1/124 |
| B60Q 1/136 | covered by | B60Q 1/124 |

B60Q 1/00

Arrangements or adaptations of optical signalling or lighting devices (for lighting vehicle interior [B60Q 3/00](#); {circuit arrangements for electric light sources in general [H05B 37/00](#)})

- B60Q 1/0005
 - {Devices preventing the lights from becoming dirty or damaged (protecting lighting devices from damage in general [F21V 15/00](#)), e.g. protection grids (fastening of grids or protective cages in general [F21V 17/00](#)), cleaning by air flow (windshield wipers for cleaning optical devices of vehicles [B60S 1/04](#))}
- B60Q 1/0011
 - {with light guides for distributing the light between several lighting or signalling devices (using light guides inside a single device [F21S 8/00](#), light guides per se [G02B 6/0001](#))}
- B60Q 1/0017
 - {Devices integrating an element dedicated to another function}
- B60Q 1/0023
 - . {the element being a sensor, e.g. distance sensor, camera}
- B60Q 1/0029
 - {Spatial arrangement}
- B60Q 1/0035
 - . {relative to the vehicle}
- B60Q 1/0041
 - . {of several lamps in relation to each other}
- B60Q 1/0047
 - . . {Signalling unit mounted on a headlamp unit}
- B60Q 1/0052
 - . . {concentric}
- B60Q 1/0058
 - . . {Stacked, i.e. one lamp located behind the other in the optical axis direction}
- B60Q 1/0064
 - {with provision for maintenance, e.g. changing the light bulb (swivel arrangements [B60Q 1/0425](#); fastening of covers [F21S 48/15](#); changing light sources in general [F21V 19/04](#); fastening of light sources or lamp holders [F21S 48/1104](#), [F21S 48/211](#))}
- B60Q 1/007
 - . {via a removable cap (fastening of the light source by a cap holding the light source [F21S 48/1104](#), [F21S 48/211](#))}
- B60Q 1/0076
 - {Switches therefor ([B60Q 1/1446](#), [B60Q 1/343](#), [B60Q 1/40](#) take precedence, arrangements or fitting of control knobs on dashboard [B60K 37/06](#))}
- B60Q 1/0082
 - . {mounted on the steering wheel}
- B60Q 1/0088
 - {Details of electrical connections ([B60Q 1/305](#) takes precedence; electrical connectors in general [H01R](#); electrical connection of the light source itself [F21S 48/1109](#), [F21S 48/212](#))}
- B60Q 1/0094
 - . {Arrangement of electronic circuits separated from the light source (e.g. mounting of housings for starter circuits for discharge lamps, circuits per se [H05B](#), arrangements being part of the light source holder [F21V 17/06](#), [F21S 48/1109](#), [F21S 48/212](#))}
- B60Q 1/02
 - the devices being primarily intended to illuminate the way ahead or to illuminate other areas of way or environments
- B60Q 1/04
 - . the devices being headlights
- B60Q 1/0408
 - . . {built into the vehicle body, e.g. details concerning the mounting of the headlamps on the vehicle body ([B60Q 1/0491](#), [B60Q 1/05](#) take precedence, integrated front ends [B62D 25/00](#))}
- B60Q 1/0416
 - . . . {the housing being mounted on the vehicle body using rails}
- B60Q 1/0425
 - . . . {the housing being swivel mounted on the vehicle body}
- B60Q 1/0433
 - . . . {the housing being fastened onto the vehicle body using screws (adjustable headlamp by rotation of a screw [B60Q 1/0683](#))}
- B60Q 1/0441
 - . . . {the housing being fastened onto the vehicle body using means other than screws}
- B60Q 1/045
 - . . . {with provision for adjusting the alignment of the headlamp housing with respect to the vehicle body (adjusting the light beam [B60Q 1/06](#))}

| | | |
|-------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B60Q 1/0458 | | {the front cover being directly mounted onto the vehicle body (mounting the cover on the housing F21S 48/15)} |
| B60Q 1/0466 | | {with arrangement for sealing the headlamp with respect to the vehicle body, or for concealing gaps between the headlamp and the vehicle body} |
| B60Q 1/0475 | | {with provisions for pre-mounting, for temporary holding the headlamp before or during final mounting} |
| B60Q 1/0483 | | {mounted on a bracket, e.g. details concerning the mounting of the lamps on the vehicle body} |
| B60Q 1/0491 | | {Shock absorbing devices therefor (resilient mounting of lighting devices in general F21V 15/04 ; shock absorbing devices in general F16F 15/04)} |
| B60Q 1/05 | | Retractable |
| B60Q 1/06 | | adjustable, e.g. remotely controlled from inside vehicle (B60Q 1/05 takes precedence; {changing the characteristics or distribution of the light by adjustment of parts, e.g. reflectors, light sources, lenses, screens F21V 14/00 }) |
| B60Q 1/064 | | by fluid means |
| B60Q 1/068 | | by mechanical means |
| B60Q 1/0683 | | {Adjustable by rotation of a screw} |
| B60Q 1/0686 | | {using a position indicator mounted on the headlight and permanently attached thereto} |
| B60Q 1/072 | | comprising a flexible element, e.g. chain |
| B60Q 1/076 | | by electrical means {including means to transmit the movements, e.g. shafts or joints} |
| B60Q 1/08 | | automatically |
| B60Q 1/085 | | {due to special conditions, e.g. adverse weather, type of road, badly illuminated road signs or potential dangers (B60Q 1/10 , B60Q 1/12 , B60Q 1/1423 take precedence)} |
| B60Q 1/10 | | due to vehicle inclination, e.g. due to load distribution |
| B60Q 1/105 | | by fluid means |
| B60Q 1/11 | | by mechanical means |
| B60Q 1/115 | | by electric means {(details of the electric drive components, e.g. motors, shafts, ball joints B60Q 1/076)} |
| B60Q 1/12 | | due to steering position |
| B60Q 1/121 | | {with fluid actuating means} |
| B60Q 1/122 | | {with electrical actuating means (details of the electric drive components, e.g. motors, shafts, ball joints B60Q 1/076)} |
| B60Q 1/124 | | by mechanical means |
| B60Q 1/14 | | having dimming means {(lighting power supply circuits in general H05B)} |
| B60Q 1/1407 | | {General lighting circuits comprising dimming circuits (dimming circuits per se B60Q 1/1415)} |
| B60Q 1/1415 | | {Dimming circuits} |
| B60Q 1/1423 | | {Automatic dimming circuits, i.e. switching between high beam and low beam due to change of ambient light or light level in road traffic} |

| | |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B60Q 1/143 | {combined with another condition, e.g. using vehicle recognition from camera images or activation of wipers} |
| B60Q 1/1438 | {Actuating means for dimming masks or screens (adjustable screens per se F21V 11/04)} |
| B60Q 1/1446 | {controlled by mechanically actuated switches} |
| B60Q 1/1453 | {Hand actuated switches} |
| B60Q 1/1461 | {Multifunction switches for dimming headlights and controlling additional devices, e.g. for controlling direction indicating lights} |
| B60Q 1/1469 | {controlled by or attached to a single lever, e.g. steering column stalk switches} |
| B60Q 1/1476 | {comprising switch controlling means located near the free end of the lever, e.g. press buttons, rotatable rings} |
| B60Q 1/1484 | {mounted on the steering wheel} |
| B60Q 1/1492 | {Foot actuated switches} |
| B60Q 1/16 | . . . illuminating the way asymmetrically |
| B60Q 1/18 | . . . being additional front lights {(bracket mounted headlights B60Q 1/0483)} |
| B60Q 1/20 | Fog lights {(single shaped beam lighting devices specially adapted for vehicles for penetrating fog or preventing glare F21S 8/12)} |
| B60Q 1/22 | . . for reverse drive |
| B60Q 1/24 | . . for lighting other areas than only the way ahead |
| B60Q 1/245 | . . . {using spotlights adjustable from within the vehicle (adjustable headlights B60Q 1/06)} |
| B60Q 1/26 | . the devices being primarily intended to indicate the vehicle, or parts thereof, or to give signals, to other traffic {(such devices mounted on the vehicle rear part F21S 48/20 ; means for the lighting or illuminating of aerials, e.g. for purpose of warning H01Q 1/06)} |
| B60Q 1/2603 | . . {Attenuation of the light according to ambient luminosity, e.g. for braking or direction indicating lamps} |
| B60Q 1/2607 | . . {comprising at least two indicating lamps} |
| B60Q 1/2611 | . . {Indicating devices mounted on the roof of the vehicle (flashing light sources in general F21S 10/06)} |
| B60Q 1/2615 | . . {mounted on the vehicle body, e.g. with magnets} |
| B60Q 1/2619 | . . {built in the vehicle body} |
| B60Q 1/2623 | . . . {Details of the fastening means} |
| B60Q 1/2626 | {Screw-nut fasteners} |
| B60Q 1/263 | {Snap-in fasteners} |
| B60Q 1/2634 | {Fastening by rotating the device housing about its longitudinal axis, e.g. bayonet fasteners} |
| B60Q 1/2638 | . . . {Positioning the device housing by indexing means separate from the fastening means, e.g. pins, rails} |
| B60Q 1/2642 | . . . {with provision for adjusting the alignment of the device housing with respect to the vehicle body} |
| B60Q 1/2646 | {using dowels or expansible elements} |
| B60Q 1/2649 | . . . {with provision for pre-mounting or temporary holding the device before or during final mounting} |

- B60Q 1/2653 . . . {with arrangement for sealing the device with respect to the vehicle body, or for concealing gaps between the device and the vehicle body}
- B60Q 1/2657 . . {mounted on a shaft, e.g. telescopic (lamps on antennas or powerlines [F21S 8/085](#))}
- B60Q 1/2661 . . {mounted on parts having other functions (on wheels [B60Q 1/323](#))}
- B60Q 1/2665 . . . {on rear-view mirrors (lighting devices for vehicle interior on or for rear-view mirrors [B60Q 3/023](#); adaptations or arrangements of mirrors for use on cycles [B62J 29/00](#); rear-view mirror arrangements [B60R 1/02](#); mirror assemblies combined with lamps [B60R 1/1207](#))}
- B60Q 1/2669 . . . {on door or boot handles (lighting devices for vehicle interior on door handles [B60Q 3/0233](#); vehicle doors [B60J 5/00](#) illuminating devices on or for locks or keys [E05B 17/10](#); Keyhole finders [E05B 15/08](#))}
- B60Q 1/2673 . . . {on parts worn by the driver, e.g. clothes (professional or sporting clothes with reflecting or luminous means [A41D 13/01](#)), gloves (protective gloves with reflecting or luminous means [A41D 19/0157](#)), or bags, specially adapted to provide auxiliary vehicle signalling}
- B60Q 1/2676 {Helmets (helmets in general [A42B 3/00](#); helmets with signalling or lighting devices [A42B 3/0433](#))}
- B60Q 1/268 . . . {on windscreens or windows ([B60Q 1/302](#) takes precedence; windows or windscreens in general [B60J 1/00](#); lighting devices for vehicle interior on or for windows [B60Q 3/0213](#))}
- B60Q 1/2684 . . . {on wipers or windscreen washers (vehicle wipers [B60S 1/04](#); windscreen washers [B60S 1/46](#))}
- B60Q 1/2688 . . . {on exhaust pipes (exhaust or silencing apparatuses in general [F01N](#))}
- B60Q 1/2692 . . {retractable lights (retractable headlights [B60Q 1/05](#))}
- B60Q 1/2696 . . {Mounting of devices using LEDs (fastening of LEDs on printed circuits [F21V 19/001](#))}
- B60Q 1/28 . . for indicating front of vehicle
- B60Q 1/30 . . for indicating rear of vehicle, e.g. by means of reflecting surfaces
- B60Q 1/302 . . . {mounted in the vicinity, e.g. in the middle, of a rear window}
- B60Q 1/305 . . . {Indicating devices for towed vehicles}
- B60Q 1/307 . . . {mounted on loading platforms (warning signals on loading platforms [B60P 1/4464](#))}
- B60Q 1/32 . . for indicating vehicle sides, {e.g. clearance lights}
- B60Q 1/323 . . . {on or for doors or running boards, e.g. to facilitate acces to the vehicle (illumination of door locks [E05B 17/10](#))}
- B60Q 1/326 . . . {on or for wheels}
- B60Q 1/34 . . for indicating change of drive direction ([B60Q 1/22](#) takes precedence)
- B60Q 1/343 . . . {Manually actuated switching arrangements therefor (Hand actuated multifunction switches [B60Q 1/1461](#); [B60Q 1/40](#) takes precedence)}
- B60Q 1/346 . . . {with automatic actuation}
- B60Q 1/36 . . . using movable members, e.g. arms with built-in flashing lamps
- B60Q 1/38 . . . using immovably-mounted light sources, e.g. fixed flashing lamps
- B60Q 1/382 {Electronic temporisation with semiconductor amplification}
- B60Q 1/385 {Electronic temporisation with relay amplification}

- B60Q 1/387 {Mechanical temporisation}
- B60Q 1/40 . . . having {mechanical, electric or electronic} automatic return to inoperative position
- B60Q 1/42 {having mechanical automatic return to inoperative position} due to steering-wheel position, {e.g. with roller wheel control}
- B60Q 1/425 {using a latching element for resetting a switching element (Hand actuated multifunction switches [B60Q 1/1461](#))}
- B60Q 1/44 . . for indicating braking action or preparation for braking, {e.g. by detection of the foot approaching the brake pedal}
- B60Q 1/441 . . . {Electric switches operable by the driver's pedals (electric switches in general [H01H](#))}
- B60Q 1/442 . . . {visible on the front side of the vehicle, e.g. for pedestrians}
- B60Q 1/444 . . . {with indication of the braking strength or speed changes, e.g. by changing shape or intensity of the indication ([B60Q 1/1407](#), [B60Q 1/442](#), [B60Q 1/447](#) take precedence)}
- B60Q 1/445 . . . {controlled by inertial devices}
- B60Q 1/447 {with indication of the braking strength or speed changes, e.g. by changing the shape or intensity of the indication}
- B60Q 1/448 . . . {specially adapted for vehicles with ABS}
- B60Q 1/46 . . for giving flashing caution signals during drive, other than signalling change of direction, e.g. flashing the headlights, {hazard lights (flashing lights in general [F21S 10/06](#))}
- B60Q 1/48 . . for parking purposes {(warning arrangements in garages [E04H 6/42](#))}
- B60Q 1/482 . . . {for locating vehicle in parking lot}
- B60Q 1/484 . . . {for showing outline of vehicle}
- B60Q 1/486 . . . {for indicating that vehicle is in a parked state}
- B60Q 1/488 . . . {for indicating intention to park}
- B60Q 1/50 . . for indicating other intentions or conditions, e.g. request for waiting or overtaking
- B60Q 1/503 . . . {using luminous text displays}
- B60Q 1/506 . . . {for signaling silent vehicles, e.g. for warning that a hybrid or electric vehicle is approaching}
- B60Q 1/52 . . . for indicating emergencies {(braking indicating devices [B60Q 1/44](#), portable emergency signal devices [B60Q 7/00](#))}
- B60Q 1/525 {indicating risk of collision between vehicles or with pedestrians (using video cameras [B62D 1/00](#); Radars designed for anti-collision purposes between land vehicles or between land vehicle and fixed obstacles [G01S 13/931](#); Control of position or course in two dimensions for land vehicles [G05D 1/021](#); Anti-collision systems for road vehicles [G08G 1/16](#))}
- B60Q 1/54 . . . for indicating speed {outside of the vehicle (automatic vehicle speed controlling fittings including unintended speed signalling devices to the vehicle driver [B60K 31/18](#))}
- B60Q 1/56 . . for illuminating registrations or the like, {e.g. for licence plates (license plates [B60R 13/10](#))}

B60Q 3/00**Arrangements or adaptations of lighting devices for vehicle interior**

- B60Q 3/001 . {manually adjustable, e.g. colours, orientation, intensity (automatically adjusted [B60Q 3/0293](#))}
- B60Q 3/002 . {using light guides}
- B60Q 3/004 . . {inside a single lighting device}
- B60Q 3/005 . . {to distribute light between several lighting devices}
- B60Q 3/007 . {with means for electrical plugging into vehicle, e.g. in cigarette lighter, in special plug (arrangement of electrically heated lighters [B60N 3/14](#))}
- B60Q 3/008 . {using UV light}
- B60Q 3/02 . for lighting passenger or driving compartment
- B60Q 3/0203 . . {Details of mounting onto vehicle interior, e.g. onto ceiling, floor (mounting of lighting devices [F21V 21/04](#), vehicle liners [B60R 13/02](#), connectors [H01R 33/00](#))}
- B60Q 3/0206 . . . {Modular mounting systems, e.g. using tracks, rails, multiple plugs (for lighting devices in general [F21V 21/005](#))}
- B60Q 3/0209 . . {mounted onto or for lighting specific vehicle fittings}
- B60Q 3/0213 . . . {on or for sun roofs, or windows (windows per se [B60J 1/00](#), sun roofs per se [B60J 7/00](#))}
- B60Q 3/0216 . . . {on or for doors or steps (vehicle doors [B60J 5/00](#))}
- B60Q 3/022 . . . {on or for small compartments, e.g. glove compartment (stowing small appliances in vehicles [B60R 7/00](#))}
- B60Q 3/0223 . . . {on or for seats, arm rests or head rests (vehicle seats per se [B60N 2/00](#))}
- B60Q 3/0226 . . . {on or for sun visors (sun visors per se [B60J 3/0204](#))}
- B60Q 3/023 . . . {on or for rear view mirrors (rear view mirror per se [B60R 1/00](#))}
- B60Q 3/0233 . . . {on or for door handles or hand grabs (door handles per se [B60N 3/02](#))}
- B60Q 3/0236 . . . {on or for smoking related tools, e.g. cigarette lighters, ashtrays (cigarette lighters [B60N 3/14](#), ashtrays [B60N 3/083](#))}
- B60Q 3/024 . . . {on or for steering wheel or gear shift (steering wheels [B62D 1/04](#), gear shifts [B60K 20/00](#))}
- B60Q 3/0243 . . . {others, e.g. cup holders, ignition locks (lighting for door locks [E05B 15/08](#), [E05B 17/10](#))}
- B60Q 3/0246 . . {for mass transit vehicles ([B60Q 3/0209](#), [B60Q 3/04](#) take precedence, illumination of sides, boards or panels in general [G09F 13/00](#))}
- B60Q 3/025 . . . {Overall lighting}
- B60Q 3/0253 . . . {Specific lighting, e.g. reading lamps}
- B60Q 3/0256 . . . {Emergency lighting, e.g. escape routes (illumination of emergency signs [G09F 13/00](#))}
- B60Q 3/0259 . . . {Circuits or control therefore}
- B60Q 3/0263 . . {Mounted on a shaft (for lighting devices in general [F21V 21/26](#) and [F21V 21/32](#))}
- B60Q 3/0266 . . {Retractable, concealable lamps}
- B60Q 3/0269 . . {with provision for being portable (portable lighting devices in general [F21L](#))}

- B60Q 3/0273 . . {Specifically arranged for convertibles}
- B60Q 3/0276 . . {additional interior lighting specifically arranged to prevent conductor dazzling, e.g. by constricting the conductor's pupil}
- B60Q 3/0279 . . {overall lighting alone or in combination with specific lighting, e.g. arrangement of room lamps, combination of room lamps with reading lamps (fastening of components within lighting devices [F21V 17/00](#), [F21V 19/00](#) and [F21V 23/00](#))}
- B60Q 3/0283 . . . {using lighting panels or mats, e.g. electro-luminescent panels, LED mats (electroluminescent light sources [H05B 33/00](#))}
- B60Q 3/0286 . . {Specific lighting, e.g. reading lamps, directional or focussed lighting towards small surfaces, e.g. using blends (fastening of components within lighting devices [F21V 17/00](#), [F21V 19/00](#) and [F21V 23/00](#))}
- B60Q 3/0289 . . {Strip lighting, edge marking, e.g. using elongated light sources along or around parts to be illuminated}
- B60Q 3/0293 . . {circuits or control for interior lights (circuits for light sources in general [H05B 37/00](#) and [H05B 39/00](#), for electric vehicles [B60L 1/14](#), electronic switching [H03K 17/00](#), remote control [H04Q 9/00](#))}
- B60Q 3/0296 . . {Switches specifically designed for interior lights, e.g. switching by tilting the lens (mechanical switches in general [H01H](#), electronic switches in general [H03K 17/00](#), arrangement of instruments in vehicles in general [B60K 35/00](#) and [B60K 37/00](#))}
- B60Q 3/04 . . for dashboard {(lighting of individual instruments [G01D](#), association of lighting devices with LCDs [G02F 1/1335](#))}
- B60Q 3/042 . . . {lighting onto the surface to be illuminated}
- B60Q 3/044 . . . {lighting through the surface to be illuminated}
- B60Q 3/046 . . . {Circuits or control therefore (for electric vehicles [B60L 1/14](#); electronic switching [H03K 17/00](#); remote control [H04Q 9/00](#); circuits for light sources in general [H05B 37/00](#), [H05B 39/00](#))}
- B60Q 3/048 {for varying the light intensity (controlling the light intensity of displays [G09G](#); circuits for controlling the light intensity emitted by particular light sources [H05B](#))}
- B60Q 3/06 . for lighting compartments other than passenger or driving space, e.g. luggage or engine compartment
- B60Q 3/065 . . {with provision for being portable (portable lighting devices in general [F21L](#))}
- B60Q 5/00** **Arrangements or adaptations of acoustic signal devices {(sound producing devices in general [G10K](#))}**
- B60Q 5/001 . {Switches therefor}
- B60Q 5/003 . . {mounted on the steering wheel}
- B60Q 5/005 . {automatically actuated}
- B60Q 5/006 . . {indicating risk of collision between vehicles or with pedestrians (using video cameras [B62D 1/00](#); Radars designed for anti-collision purposes between land vehicles or between land vehicle and fixed obstacles [G01S 13/931](#); Control of position or course in two dimensions for land vehicles [G05D 1/021](#); Anti-collision systems for road vehicles [G08G 1/16](#))}
- B60Q 5/008 . . {for signaling silent vehicles, e.g. for warning that a hybrid or electric vehicle is approaching}

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B60Q 7/00 | Arrangement or adaptation of portable emergency signal devices on {board} vehicles {to be placed on roadways or vehicles, e.g. warning triangles}, (arrangements for enforcing caution on roads, e.g. marker posts, E01F 9/00 ; signs G09F , e.g. reflecting warning triangles G09F 13/16) |
| B60Q 7/005 | <ul style="list-style-type: none"> • {Devices without lamps} |
| B60Q 7/02 | <ul style="list-style-type: none"> • to be attached to overhanging loads or extending parts of vehicle |
| B60Q 9/00 | Arrangements or adaptations of signal devices not provided for in one of the preceding main groups, {e.g. haptic signalling} |
| B60Q 9/001 | <ul style="list-style-type: none"> • {Alarm devices when the motor is stopped and the lights are on} |
| B60Q 9/002 | <ul style="list-style-type: none"> • {for parking purposes, e.g. for warning the driver that his vehicle has contacted or is about to contact an obstacle (warning arrangements in garages E04H 6/42)} |
| B60Q 9/003 | <ul style="list-style-type: none"> • • {using physical contactors, e.g. arms that trigger alarm upon contact with obstacle} |
| B60Q 9/004 | <ul style="list-style-type: none"> • • {using wave sensors (radar designed for anti-collision purposes between land vehicles or between land vehicles and fixed obstacles G01S 13/931)} |
| B60Q 9/005 | <ul style="list-style-type: none"> • • • {using a video camera} |
| B60Q 9/006 | <ul style="list-style-type: none"> • • • {using a distance sensor} |
| B60Q 9/007 | <ul style="list-style-type: none"> • • {providing information about the distance to an obstacle, e.g. varying sound} |
| B60Q 9/008 | <ul style="list-style-type: none"> • {for anti-collision purposes} |
| B60Q 11/00 | Arrangements of monitoring devices for devices provided for in groups B60Q 1/00 to B60Q 9/00 {(testing of electric installations on road vehicle G01R 31/00)} |
| B60Q 11/002 | <ul style="list-style-type: none"> • {Emergency driving lights in the event of failure of the principal lighting circuit} |
| B60Q 11/005 | <ul style="list-style-type: none"> • {for lighting devices, e.g. indicating if lamps are burning or not} |
| B60Q 11/007 | <ul style="list-style-type: none"> • • {the lighting devices indicating change of drive direction (change of drive direction indicators B60Q 1/34)} |
| B60Q 2200/00 | Special features or arrangements of vehicle headlamps |
| B60Q 2200/30 | <ul style="list-style-type: none"> • Special arrangements for adjusting headlamps, e.g. means for transmitting the movements for adjusting the lamps |
| B60Q 2200/32 | <ul style="list-style-type: none"> • • Ball-joints |
| B60Q 2200/34 | <ul style="list-style-type: none"> • • Deformable parts, i.e. the adjustment is performed by bending or stretching a part |
| B60Q 2200/36 | <ul style="list-style-type: none"> • • Conjoint adjustments, i.e. a mechanical link allows conjoint adjustment of several units |
| B60Q 2200/38 | <ul style="list-style-type: none"> • • Automatic calibration of motor-driven means for adjusting headlamps, i.e. when switching on the headlamps, not during mounting at factories |
| B60Q 2300/00 | Indexing codes for automatically adjustable headlamps or automatically dimmable headlamps |
| B60Q 2300/05 | <ul style="list-style-type: none"> • Special features for controlling or switching of the light beam |
| B60Q 2300/052 | <ul style="list-style-type: none"> • • Switching delay, i.e. the beam is not switched or changed instantaneously upon occurrence of a condition change |

- B60Q 2300/054 . . Variable non-standard intensity, i.e. emission of various beam intensities different from standard intensities, e.g. continuous or stepped transitions of intensity
- B60Q 2300/056 . . Special anti-blinding beams, e.g. a standard beam is chopped or moved in order not to blind
- B60Q 2300/10 . Indexing codes relating to particular vehicle conditions
- B60Q 2300/11 . . Linear movements of the vehicle
- B60Q 2300/112 . . . Vehicle speed
- B60Q 2300/114 . . . Vehicle acceleration or deceleration
- B60Q 2300/116 . . . Vehicle at a stop
- B60Q 2300/12 . . Steering parameters
- B60Q 2300/122 . . . Steering angle
- B60Q 2300/124 . . . Steering speed
- B60Q 2300/126 . . . Hysteresis behavior based on steering
- B60Q 2300/128 . . . Steering dead zone
- B60Q 2300/13 . . Attitude of the vehicle body
- B60Q 2300/132 . . . Pitch
- B60Q 2300/134 . . . Yaw
- B60Q 2300/136 . . . Roll
- B60Q 2300/14 . . Other vehicle conditions
- B60Q 2300/142 . . . Turn signal actuation
- B60Q 2300/144 . . . Rearward ratio actuation
- B60Q 2300/146 . . . Abnormalities, e.g. fail-safe
- B60Q 2300/20 . Indexing codes relating to the driver or the passengers
- B60Q 2300/21 . . Manual control
- B60Q 2300/22 . . Seat occupation
- B60Q 2300/23 . . Driver's line of sight
- B60Q 2300/30 . Indexing codes relating to the vehicle environment
- B60Q 2300/305 . . Calendar date or clock time
- B60Q 2300/31 . . Atmospheric conditions
- B60Q 2300/312 . . . Adverse weather
- B60Q 2300/314 . . . Ambient light
- B60Q 2300/32 . . Road surface or travel path
- B60Q 2300/322 . . . Road curvature
- B60Q 2300/324 . . . Road inclination, e.g. uphill or downhill
- B60Q 2300/33 . . Driving situation
- B60Q 2300/331 . . . characterised by the driving side, e.g. on the left or right hand side
- B60Q 2300/332 . . . on city roads
- B60Q 2300/3321 Detection of streetlights
- B60Q 2300/333 . . . on suburban or country roads
- B60Q 2300/334 . . . on motorways

| | |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| B60Q 2300/335 | . . . Number or size of road lanes |
| B60Q 2300/336 | . . . Crossings |
| B60Q 2300/337 | . . . Tunnels or bridges |
| B60Q 2300/338 | . . . Overtaking |
| B60Q 2300/40 | . Indexing codes relating to other road users or special conditions |
| B60Q 2300/41 | . . preceding vehicle |
| B60Q 2300/42 | . . oncoming vehicle |
| B60Q 2300/43 | . . following vehicle |
| B60Q 2300/45 | . . Special conditions, e.g. pedestrians, road signs or potential dangers |
| B60Q 2300/47 | . . Direct command from other road users, i.e. the command for switching or changing the beam is sent by other vehicles or road devices |
| B60Q 2400/00 | Special features or arrangements of exterior signal lamps for vehicles |
| B60Q 2400/10 | . Electroluminescent surfaces, i.e. signalling by way of electroluminescent strips or panels |
| B60Q 2400/20 | . Multi-color single source or LED matrix, e.g. yellow blinker and red brake lamp generated by single lamp |
| B60Q 2400/30 | . Daytime running lights [DRL], e.g. circuits or arrangements therefor |
| B60Q 2400/40 | . Welcome lights, i.e. specific or existing exterior lamps to assist leaving or approaching the vehicle |
| B60Q 2400/50 | . Projected signs, i.e. symbol or information is projected onto the road |
| B60Q 2500/00 | Special features or arrangements of vehicle interior lamps |
| B60Q 2500/10 | . embedded in interior trim, e.g. integrated in headliner layers |
| B60Q 2500/20 | . associated with air conditioning arrangements |
| B60Q 2900/00 | Features of lamps not covered by other groups in B60Q |
| B60Q 2900/10 | . Retrofit arrangements |
| B60Q 2900/20 | . Arrangements for easy recycling, e.g. for easy dismantling or use of special materials |
| B60Q 2900/30 | . Lamps commanded by wireless transmissions |