

**CPC****COOPERATIVE PATENT CLASSIFICATION****H02P****CONTROL OR REGULATION OF ELECTRIC MOTORS, ELECTRIC GENERATORS OR DYNAMO-ELECTRIC CONVERTERS; CONTROLLING TRANSFORMERS, REACTORS OR CHOKE COILS****NOTES**

1. This subclass covers arrangements for starting, regulating, electronically commutating, braking, or otherwise controlling motors, generators, dynamo-electric converters, clutches, brakes, gears, transformers, reactors or choke coils, of the types classified in the relevant subclasses, e.g. [H01F](#), [H02K](#).
2. This subclass does not cover similar arrangements for the apparatus of the types classified in subclass [H02N](#), which arrangements are covered by that subclass.
3. In this subclass, the following terms or expressions are used with the meanings indicated:
  - “control” means influencing a variable in any way, e.g. changing its direction or its value (including changing it to or from zero), maintaining it constant or limiting its range of variation;
  - “regulation” means maintaining a variable at a desired value, or within a desired range of values, by comparison of the actual value with the desired value.
4. In this subclass, it is desirable to add the indexing codes of groups [H02P 2101/00](#) and [H02P 2103/00](#)

**H02P 1/00**

**Arrangements for starting electric motors or dynamo-electric converters**  
 (starting of synchronous motors with electronic commutators except reluctance motors, [H02P 6/20](#), [H02P 6/22](#); starting dynamo-electric motors rotating step by step [H02P 8/04](#); vector control [H02P 21/00](#))

- [H02P 1/02](#) . Details
- [H02P 1/021](#) . . {Protection against "no voltage condition"}
- [H02P 1/022](#) . . {Security devices, e.g. correct phase sequencing}
- [H02P 1/023](#) . . . {Protection against sparking of contacts or sticking together}
- [H02P 1/024](#) . . . {Protection against simultaneous starting by two starting devices}
- [H02P 1/025](#) . . . {Protection against starting if starting resistor is not at zero position}
- [H02P 1/026](#) . . . {Means for delayed starting}
- [H02P 1/027](#) . . {Special design of starting resistor}
- [H02P 1/028](#) . . {wherein the motor voltage is increased at low speed, to start or restart high inertia loads}
- [H02P 1/029](#) . . {Restarting, e.g. after power failure}
- [H02P 1/04](#) . . Means for controlling progress of starting sequence in dependence upon time or upon current, speed, or other motor parameter
- [H02P 1/06](#) . . . Manually-operated multi-position starters
- [H02P 1/08](#) . . . Manually-operated on/off switch controlling power-operated multi-position switch or impedances for starting a motor

- H02P 1/10 . . . Manually-operated on/off switch controlling relays or contactors operating sequentially for starting a motor ([sequence determined by power-operated multi-position switch H02P 1/08](#))
- H02P 1/12 . . . Switching devices centrifugally operated by the motor
- H02P 1/14 . . . Pressure-sensitive resistors centrifugally operated by the motor
- H02P 1/16 . for starting dynamo-electric motors or dynamo-electric converters
- H02P 1/163 . . {for starting an individual reluctance motor}
- H02P 1/166 . . {Driving load with high inertia}
- H02P 1/18 . . for starting an individual dc motor
- H02P 1/20 . . . by progressive reduction of resistance in series with armature winding
- H02P 1/22 . . . in either direction of rotation
- H02P 1/24 . . for starting an individual ac commutator motor ([starting of ac/dc commutator motors H02P 1/18](#))

**NOTE**

Group [H02P 1/029](#) takes precedence over groups [H02P 1/26](#) to [H02P 1/54](#)

- H02P 1/26 . . for starting an individual polyphase induction motor
- H02P 1/265 . . . {Means for starting or running a triphase motor on a single phase supply}
- H02P 1/28 . . . by progressive increase of voltage applied to primary circuit of motor
- H02P 1/30 . . . by progressive increase of frequency of supply to primary circuit of motor
- H02P 1/32 . . . by star-delta switching
- H02P 1/34 . . . by progressive reduction of impedance in secondary circuit
- H02P 1/36 . . . . the impedance being a liquid resistance
- H02P 1/38 . . . by pole-changing
- H02P 1/40 . . . in either direction of rotation
- H02P 1/42 . . for starting an individual single-phase induction motor {(H02P 27/04 takes precedence)}
- H02P 1/423 . . . {by using means to limit the current in the main winding}
- H02P 1/426 . . . {by using a specially adapted frequency converter}
- H02P 1/44 . . . by phase-splitting with a capacitor
- H02P 1/445 . . . . {by using additional capacitors switched at start up}
- H02P 1/46 . . for starting an individual synchronous motor {(H02P 27/04 takes precedence)}
- H02P 1/465 . . . {for starting an individual single-phase synchronous motor}
- H02P 1/48 . . . by pole-changing
- H02P 1/50 . . . by changing over from asynchronous to synchronous operation ([H02P 1/48 takes precedence](#))
- H02P 1/52 . . . by progressive increase of frequency of supply to motor
- H02P 1/54 . . for starting two or more dynamo-electric motors
- H02P 1/56 . . . simultaneously
- H02P 1/58 . . . sequentially

**H02P 3/00**

**Arrangements for stopping or slowing electric motors, generators, or dynamo-electric converters** (stopping of synchronous motors with electronic commutators except reluctance motors, [H02P 6/24](#); stopping dynamo-electric motors rotating step by step [H02P 8/24](#); vector control [H02P 21/00](#))

**H02P 3/02**

- Details

**H02P 3/025**

- • {holding the rotor in a fixed position after deceleration}

**H02P 3/04**

- • Means for stopping or slowing by a separate brake, e.g. friction brake, eddy-current brake ([brakes F16D](#), [H02K 49/00](#))

**H02P 3/06**

- for stopping or slowing an individual dynamo-electric motor or dynamo-electric converter

**H02P 3/065**

- • {for stopping or slowing a reluctance motor}

**H02P 3/08**

- • for stopping or slowing a dc motor

**H02P 3/10**

- • • by reversal of supply connections

**H02P 3/12**

- • • by short-circuit or resistive braking

**H02P 3/14**

- • • by regenerative braking

**H02P 3/16**

- • • by combined electrical and mechanical braking

**H02P 3/18**

- • for stopping or slowing an ac motor

**H02P 3/20**

- • • by reversal of phase sequence of connections to the motor

**H02P 3/22**

- • • by short-circuit or resistive braking

**H02P 3/24**

- • • by applying dc to the motor

**H02P 3/26**

- • • by combined electrical and mechanical braking

**H02P 4/00**

**Arrangements specially adapted for regulating or controlling the speed or torque of electric motors that can be connected to two or more different electric power supplies** (vector control [H02P 21/00](#))

**H02P 5/00**

**Arrangements specially adapted for regulating or controlling the speed or torque of two or more electric motors** ([H02P 6/04](#), [H02P 8/40](#) take precedence)

**WARNING**

Group [H02P 5/00](#) is impacted by reclassification into groups [H02P 6/04](#), [H02P 8/40](#), [H02P 8/40](#).

All groups listed in this Warning should be considered in order to perform a complete search.

**H02P 5/46**

- for speed regulation of two or more dynamo-electric motors in relation to one another

**H02P 5/48**

- • by comparing mechanical values representing the speeds

**H02P 5/485**

- • • using differential movement of the two motors, e.g. using differential gearboxes

**H02P 5/49**

- • • by intermittently closing or opening electrical contacts

**H02P 5/50**

- • by comparing electrical values representing the speeds

**H02P 5/505**

- • • using equalising lines, e.g. rotor and stator lines of first and second motors

**H02P 5/51**

- • • Direct ratio control

- H02P 5/52 . . additionally providing control of relative angular displacement
- H02P 5/54 . . . Speed and position comparison between the motors by mechanical means
- H02P 5/56 . . . Speed and position comparison between the motors by electrical means
- H02P 5/60 . controlling combinations of dc and ac dynamo-electric motors ([H02P 5/46](#) takes precedence)
- H02P 5/68 . controlling two or more dc dynamo-electric motors ([H02P 5/46](#), [H02P 5/60](#) take precedence)
- H02P 5/685 . . electrically connected in series, i.e. carrying the same current
- H02P 5/69 . . mechanically coupled by gearing
- H02P 5/695 . . . Differential gearing
- H02P 5/74 . controlling two or more ac dynamo-electric motors ([H02P 5/46](#), [H02P 5/60](#) take precedence)
- H02P 5/747 . . mechanically coupled by gearing
- H02P 5/753 . . . Differential gearing

**H02P 6/00** **Arrangements for controlling synchronous motors or other dynamo-electric motors using electronic commutation dependent on the rotor position; Electronic commutators therefor** ([vector control H02P 21/00](#))

**NOTE**

Group [H02P 6/26](#) takes precedence over groups [H02P 6/04](#)–[H02P 6/24](#) and [H02P 6/28](#) – [H02P 6/34](#)

**WARNING**

Group [H02P 6/00](#) is impacted by reclassification into group [H02P 6/32](#).

Groups [H02P 6/00](#) and [H02P 6/32](#) should be considered in order to perform a complete search.

- H02P 6/005 . {Arrangements for controlling doubly fed motors}
- H02P 6/006 . {Controlling linear motors}
- H02P 6/007 . {wherein the position is detected using the ripple of the current caused by the commutation}
- H02P 6/04 . Arrangements for controlling or regulating the speed or torque of more than one motor ([H02P 6/10](#) takes precedence)

**WARNING**

Group [H02P 6/04](#) is impacted by reclassification into group [H02P 6/10](#).

Groups [H02P 6/04](#) and [H02P 6/10](#) should be considered in order to perform a complete search.

- H02P 2006/045 . . {Control of current}
- H02P 6/06 . Arrangements for speed regulation of a single motor wherein the motor speed is measured and compared with a given physical value so as to adjust the motor speed

- H02P 6/08
  - Arrangements for controlling the speed or torque of a single motor ([H02P 6/10](#), [H02P 6/28](#) take precedence)
  - WARNING**
  - Group [H02P 6/08](#) is impacted by reclassification into group [H02P 6/10](#).
  - Groups [H02P 6/08](#) and [H02P 6/10](#) should be considered in order to perform a complete search.
- H02P 6/085
  - • {in a bridge configuration}
- H02P 6/10
  - Arrangements for controlling torque ripple, e.g. providing reduced torque ripple
  - WARNING**
  - Group [H02P 6/10](#) is incomplete pending reclassification of documents from group [H02P 6/04](#) and group [H02P 6/08](#).
  - Groups [H02P 6/04](#), [H02P 6/08](#) and [H02P 6/10](#) should be considered in order to perform a complete search.
- H02P 6/12
  - Monitoring commutation; Providing indication of commutation failure
- H02P 6/14
  - Electronic commutators
- H02P 6/15
  - • Controlling commutation time
- H02P 6/153
  - • • {wherein the commutation is advanced from position signals phase in function of the speed}
- H02P 6/157
  - • • {wherein the commutation is function of electro-magnetic force [EMF]}
- H02P 6/16
  - • Circuit arrangements for detecting position
- H02P 6/17
  - • • and for generating speed information
- H02P 6/18
  - • • without separate position detecting elements
- H02P 6/181
  - • • • {using different methods depending on the speed}
- H02P 6/182
  - • • • using back-emf in windings
- H02P 6/183
  - • • • {using an injected high frequency signal}
- H02P 6/185
  - • • • using inductance sensing, e.g. pulse excitation
- H02P 6/186
  - • • • {using difference of inductance or reluctance between the phases}
- H02P 6/187
  - • • • {using the star point voltage}
- H02P 6/188
  - • • • {using the voltage difference between the windings ([H02P 6/182](#) takes precedence)}
- H02P 6/20
  - Arrangements for starting ([H02P 6/08](#) takes precedence)
- H02P 6/21
  - • Open loop start
- H02P 6/22
  - • in a selected direction of rotation
- H02P 6/24
  - Arrangements for stopping
- H02P 6/26
  - Arrangements for controlling single phase motors
- H02P 6/28
  - Arrangements for controlling current ([H02P 6/10](#) takes precedence)
- H02P 6/30
  - Arrangements for controlling the direction of rotation ([H02P 6/22](#) takes precedence)

- H02P 6/32
- Arrangements for controlling wound field motors, e.g. motors with exciter coils

**WARNING**

Group [H02P 6/32](#) is incomplete pending reclassification of documents from group [H02P 6/00](#).

Groups [H02P 6/00](#) and [H02P 6/32](#) should be considered in order to perform a complete search.

- H02P 6/34
- Modelling or simulation for control purposes

**H02P 7/00**

**Arrangements for regulating or controlling the speed or torque of electric DC motors**

**WARNING**

Group [H02P 7/00](#) is impacted by reclassification into groups [H02P 7/02](#), [H02P 7/025](#).

Groups [H02P 7/00](#), [H02P 7/02](#), and [H02P 7/025](#) should be considered in order to perform a complete search.

- H02P 7/0094
- {wherein the position is detected using the ripple of the current caused by the commutator}

- H02P 7/02
- the DC motors being of the linear type

**WARNING**

Group [H02P 7/02](#) is incomplete pending reclassification of documents from group [H02P 7/00](#).

Groups [H02P 7/00](#) and [H02P 7/02](#) should be considered in order to perform a complete search.

- H02P 7/025
- the DC motors being of the moving coil type, e.g. voice coil motors

**WARNING**

Group [H02P 7/025](#) is incomplete pending reclassification of documents from group [H02P 7/00](#).

Groups [H02P 7/00](#) and [H02P 7/025](#) should be considered in order to perform a complete search.

- H02P 7/03
- for controlling the direction of rotation of DC motors

- H02P 7/04
- {by means of a H-bridge circuit}

- H02P 7/05
- {by means of electronic switching}

- H02P 7/06
- for regulating or controlling an individual dc dynamo-electric motor by varying field or armature current

- H02P 7/063
- {using centrifugal devices, e.g. switch, resistor}

- H02P 7/066
- {using a periodic interrupter, e.g. Tirrill regulator}

- H02P 7/08
- by manual control without auxiliary power

- H02P 7/10
- of motor field only

- H02P 7/12
- Switching field from series to shunt excitation or vice versa

- H02P 7/14
- of voltage applied to the armature with or without control of field {Ward-Leonard}

- H02P 7/18
- by master control with auxiliary power

- H02P 7/20 . . . using multi-position switch, e.g. drum, controlling motor circuit by means of relays ([H02P 7/24](#), [H02P 7/30](#) take precedence)
  - H02P 7/22 . . . using multi-position switch, e.g. drum, controlling motor circuit by means of pilot-motor-operated multi-position switch or pilot-motor-operated variable resistance ([H02P 7/24](#), [H02P 7/30](#) take precedence)
  - H02P 7/24 . . . using discharge tubes or semiconductor devices
  - H02P 7/245 . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/26 . . . . using discharge tubes
  - H02P 7/265 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/28 . . . . using semiconductor devices
  - H02P 7/2805 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/281 . . . . . the DC motor being operated in four quadrants
- NOTE**
- Group [H02P 7/281](#) takes precedence over groups [H02P 7/282](#) – [H02P 7/298](#).
- H02P 7/2815 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/282 . . . . . controlling field supply only
  - H02P 7/2825 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/285 . . . . . controlling armature supply only
  - H02P 7/2855 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/288 . . . . . using variable impedance
  - H02P 7/2885 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/29 . . . . . using pulse modulation
  - H02P 7/291 . . . . . with on-off control between two set points, e.g. controlling by hysteresis
  - H02P 7/2913 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/292 . . . . . using static converters, e.g. AC to DC
  - H02P 7/293 . . . . . using phase control ([H02P 7/295](#) takes precedence)
  - H02P 7/295 . . . . . of the kind having a thyristor or the like in series with the power supply and the motor
  - H02P 7/298 . . . . . controlling armature and field supply
  - H02P 7/2985 . . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
  - H02P 7/30 . . . using magnetic devices with controllable degree of saturation, i.e. transducers

- H02P 7/305 . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
- H02P 7/32 . . . using armature-reaction-excited machines, e.g. metadyne, amplidyne, rototrol
- H02P 7/325 . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
- H02P 7/34 . . . using Ward-Leonard arrangements
- H02P 7/343 . . . . in which both generator and motor fields are controlled

**WARNING**

Group [H02P 7/343](#) is impacted by reclassification into group [H02P 7/347](#).

Groups [H02P 7/343](#) and [H02P 7/347](#) should be considered in order to perform a complete search.

- H02P 7/347 . . . . in which only the generator field is controlled

**WARNING**

Group [H02P 7/347](#) is incomplete pending reclassification of documents from group [H02P 7/343](#).

Groups [H02P 7/343](#) and [H02P 7/347](#) should be considered in order to perform a complete search.

- H02P 7/348 . . . {for changing between series and parallel connections of motors}

## **H02P 8/00 Arrangements for controlling dynamo-electric motors of the kind having motors rotating step by step (vector control [H02P 21/00](#))**

- H02P 8/005 . {of linear motors}
- H02P 8/02 . specially adapted for single-phase or bi-pole stepper motors, e.g. watch-motors, clock-motors

**NOTE**

Groups [H02P 8/005](#) and [H02P 8/02](#) take precedence over groups [H02P 8/04](#) to [H02P 8/42](#)

- H02P 8/04 . Arrangements for starting
- H02P 8/06 . . in selected direction of rotation
- H02P 8/08 . . Determining position before starting
- H02P 8/10 . . Shaping pulses for starting; Boosting current during starting
- H02P 8/12 . Control or stabilisation of current
- H02P 8/14 . Arrangements for controlling speed or speed and torque ([H02P 8/12](#), [H02P 8/22](#) take precedence)
- H02P 8/16 . . Reducing energy dissipated or supplied
- H02P 8/165 . . . {using two level supply voltage}
- H02P 8/18 . . Shaping of pulses, e.g. to reduce torque ripple
- H02P 8/20 . . characterised by bidirectional operation
- H02P 8/22 . Control of step size; Intermediate stepping, e.g. micro-stepping
- H02P 8/24 . Arrangements for stopping ([H02P 8/32](#) takes precedence)



- H02P 8/26 . . Memorising final pulse when stopping
- H02P 8/28 . . Disconnecting power source when stopping
- H02P 8/30 . . Holding position when stopped
- H02P 8/32 . Reducing overshoot or oscillation, e.g. damping
- H02P 8/34 . Monitoring operation ([H02P 8/36 takes precedence](#))
- H02P 8/36 . Protection against faults, e.g. against overheating, step-out; Indicating faults ([emergency protective arrangements with automatic interruption of supply H02H 7/08](#))
- H02P 8/38 . . the fault being step-out
- H02P 8/40 . Special adaptations for controlling two or more stepping motors

### **WARNING**

Group [H02P 8/40](#) is incomplete pending reclassification of documents from group [H02P 5/00](#).

Groups [H02P 5/00](#) and [H02P 8/40](#) should be considered in order to perform a complete search.

- H02P 8/42 . characterised by non-stepper motors being operated step by step

### **H02P 9/00 Arrangements for controlling electric generators for the purpose of obtaining a desired output** ([Ward-Leonard arrangements H02P 7/34](#); [vector control H02P 21/00](#); [feeding a network by two or more generators H02J](#); [for charging batteries H02J 7/14](#))

- H02P 9/006 . {[Means for protecting the generator by using control \(H02H 7/06 takes precedence; control effected upon generator excitation circuit to reduce harmful effects of overloads or transients H02P 9/10\)](#)}
- H02P 9/007 . {[Control circuits for doubly fed generators](#)}
- H02P 9/008 . {[wherein the generator is controlled by the requirements of the prime mover](#)}
- H02P 9/009 . {[Circuit arrangements for detecting rotor position](#)}
- H02P 9/02 . Details
- H02P 9/04 . Control effected upon non-electric prime mover and dependent upon electric output value of the generator ([effecting control of the prime mover in general, see the relevant class for such prime mover](#))
- H02P 9/06 . Control effected upon clutch or other mechanical power transmission means and dependent upon electric output value of the generator ([effecting control of the power transmission means, see the relevant class for such means](#))
- H02P 9/08 . Control of generator circuit during starting or stopping of driving means, e.g. for initiating excitation
- H02P 9/10 . Control effected upon generator excitation circuit to reduce harmful effects of overloads or transients, e.g. sudden application of load, sudden removal of load, sudden change of load
- H02P 9/102 . . {[for limiting effects of transients](#)}
- H02P 9/105 . . {[for increasing the stability](#)}
- H02P 9/107 . . {[for limiting effects of overloads](#)}
- H02P 9/12 . . for demagnetising; for reducing effects of remanence; for preventing pole reversal
- H02P 9/123 . . . {[for demagnetising; for reducing effects of remanence](#)}

- H02P 9/126 . . . {for preventing pole reversal}
- H02P 9/14 . by variation of field ([H02P 9/08](#), [H02P 9/10](#) take precedence)
- H02P 9/16 . . due to variation of ohmic resistance in field circuit, using resistances switched in or out of circuit step by step
- H02P 9/18 . . . the switching being caused by a servomotor, measuring instrument, or relay
- H02P 9/20 . . due to variation of continuously-variable ohmic resistance
- H02P 9/22 . . . comprising carbon pile resistance
- H02P 9/24 . . due to variation of make-to-break ratio of intermittently-operating contacts, e.g. using Tirrill regulator
- H02P 9/26 . . using discharge tubes or semiconductor devices ([H02P 9/34](#) takes precedence)
- H02P 9/28 . . . using discharge tubes
- H02P 9/30 . . . using semiconductor devices
- H02P 9/302 . . . . {Brushless excitation}
- H02P 9/305 . . . . {controlling voltage ([H02P 9/302](#) takes precedence)}
- H02P 9/307 . . . . . {more than one voltage output}
- H02P 9/32 . . using magnetic devices with controllable degree of saturation ([H02P 9/34](#) takes precedence)
- H02P 9/34 . . using magnetic devices with controllable degree of saturation in combination with controlled discharge tube or controlled semiconductor device
- H02P 9/36 . . using armature-reaction-excited machines
- H02P 9/38 . . Self-excitation by current derived from rectification of both output voltage and output current of generator
- H02P 9/40 . by variation of reluctance of magnetic circuit of generator
- H02P 9/42 . to obtain desired frequency without varying speed of the generator
- H02P 9/44 . Control of frequency and voltage in predetermined relation, e.g. constant ratio
- H02P 9/46 . Control of asynchronous generator by variation of capacitor
- H02P 9/48 . Arrangements for obtaining a constant output value at varying speed of the generator, e.g. on vehicle ([H02P 9/04](#) to [H02P 9/46](#) take precedence)
  
- H02P 11/00** **Arrangements for controlling dynamo-electric converters** (starting [H02P 1/00](#); stopping or slowing [H02P 3/00](#); vector control [H02P 21/00](#); feeding a network in conjunction with a generator or another converter [H02J](#))
- H02P 11/04 . for controlling dynamo-electric converters having a dc output
- H02P 11/06 . for controlling dynamo-electric converters having an ac output
  
- H02P 13/00** **Arrangements for controlling transformers, reactors or choke coils, for the purpose of obtaining a desired output** (regulation systems using transformers, reactors or choke coils [G05F](#); transformers [H01F](#); feeding a network in conjunction with a generator or a converter [H02J](#); control or regulation of converters [H02M](#))
- H02P 13/06 . by tap-changing; by rearranging interconnections of windings
- H02P 13/08 . by sliding current collector along winding
- H02P 13/10 . by moving core, coil winding, or shield, e.g. by induction regulator

- H02P 13/12 . by varying magnetic bias
- H02P 15/00** **Arrangements for controlling dynamo-electric brakes or clutches** (controlling speed of dynamo-electric motors by means of a separate brake [H02P 29/04](#), vector control [H02P 21/00](#) {see provisionally also [H02K 49/00](#) and [H02P 29/0022](#)})
- WARNING**
- Not complete, see also [H02K 49/00](#) and [H02P 29/0022](#)
- H02P 15/02 . Conjoint control of brakes and clutches
- H02P 17/00** **Arrangements for controlling dynamo-electric gears** (vector control [H02P 21/00](#))
- H02P 21/00** **Arrangements or methods for the control of electric machines by vector control, e.g. by control of field orientation**
- NOTES**
1. When classifying in this group, classification should also be made in group [H02P 25/00](#) when the method of control is characterised by the kind of motor being controlled.
  2. When classifying in this group, classification should also be made in group [H02P 27/00](#) when the method of control is characterised by the kind of supply voltage of the motor being controlled.
- H02P 21/0003 . {Control strategies in general, e.g. linear type e.g. P, PI, PID, using robust control}
- H02P 21/0007 . . {using sliding mode control}
- H02P 21/001 . . {using fuzzy control}
- H02P 21/0014 . . {using neural networks}
- H02P 21/0017 . . {Model reference adaptation, e.g. MRAS or MRAC, useful for control or parameter estimation}
- H02P 21/0021 . . {using different modes of control depending on a parameter, e.g. the speed}
- H02P 21/0025 . . {implementing a off line learning phase to determine and store useful data for on-line control}
- H02P 21/0085 . {specially adapted for high speeds, e.g. above nominal speed}
- H02P 21/0089 . . {using field weakening}
- H02P 21/02 . specially adapted for optimising the efficiency at low load
- H02P 21/04 . specially adapted for very low speeds
- H02P 21/05 . specially adapted for damping motor oscillations, e.g. for reducing hunting
- H02P 21/06 . Rotor flux based control involving the use of rotor position or rotor speed sensors
- H02P 21/08 . . Indirect field-oriented control; Rotor flux feed-forward control
- H02P 21/09 . . . Field phase angle calculation based on rotor voltage equation by adding slip frequency and speed proportional frequency
- H02P 21/10 . . Direct field-oriented control; Rotor flux feed-back control
- H02P 21/12 . Stator flux based control involving the use of rotor position or rotor speed sensors

- H02P 21/13 . Observer control, e.g. using Luenberger observers or Kalman filters
- H02P 21/14 . Estimation or adaptation of machine parameters, e.g. flux, current or voltage
- H02P 21/141 . . {Flux estimation}
- H02P 21/143 . . {Inertia or moment of inertia estimation}
- H02P 21/16 . . Estimation of constants, e.g. the rotor time constant
- H02P 21/18 . . Estimation of position or speed
- H02P 21/20 . . Estimation of torque
- H02P 21/22 . Current control, e.g. using a current control loop
- H02P 21/24 . Vector control not involving the use of rotor position or rotor speed sensors
- H02P 21/26 . . Rotor flux based control
- H02P 21/28 . . Stator flux based control
- H02P 21/30 . . . Direct torque control [DTC] or field acceleration method [FAM]
- H02P 21/32 . . Determining the initial rotor position ([H02P 21/34](#) takes precedence)
- H02P 21/34 . Arrangements for starting
- H02P 21/36 . Arrangements for braking or slowing; Four quadrant control
- H02P 21/50 . {Vector control arrangements or methods not otherwise provided for in [H02P 21/00](#)- [H02P 21/36](#)}

**H02P 23/00**

**Arrangements or methods for the control of AC motors characterised by a control method other than vector control**

**NOTE**

When classifying in this group, subject matter also relating to groups [H02P 21/00](#), [H02P 25/00](#) or [H02P 27/00](#) is further classified in those groups whenever appropriate.

- H02P 23/0004 . {Control strategies in general, e.g. linear type e.g. P, PI, PID, using robust control}
- H02P 23/0009 . . {using sliding mode control}
- H02P 23/0013 . . {using fuzzy control}
- H02P 23/0018 . . {using neural networks}
- H02P 23/0022 . . {Model reference adaptation, e.g. MRAS or MRAC, useful for control or parameter estimation}
- H02P 23/0027 . . {using different modes of control depending on a parameter, e.g. the speed}
- H02P 23/0031 . . {implementing a off line learning phase to determine and store useful data for on-line control}
- H02P 23/0077 . {Characterised by the use of a particular software algorithm}
- H02P 23/0086 . {specially adapted for high speeds, e.g. above nominal speed}
- H02P 23/009 . . {using field weakening}
- H02P 23/02 . specially adapted for optimising the efficiency at low load
- H02P 23/03 . specially adapted for very low speeds
- H02P 23/04 . specially adapted for damping motor oscillations, e.g. for reducing hunting
- H02P 23/06 . Controlling the motor in four quadrants
- H02P 23/07 . . Polyphase or monophas asynchronous induction motors

- H02P 23/08 . Controlling based on slip frequency, e.g. adding slip frequency and speed proportional frequency
- H02P 23/10 . Controlling by adding a dc current ([dc current braking H02P 3/24](#))
- H02P 23/12 . Observer control, e.g. using Luenberger observers or Kalman filters
- H02P 23/14 . Estimation or adaptation of motor parameters, e.g. rotor time constant, flux, speed, current or voltage
- H02P 23/16 . Controlling the angular speed of one shaft ([H02P 23/18 takes precedence](#))
- H02P 23/18 . Controlling the angular speed together with angular position or phase
- H02P 23/183 . . {of one shaft without controlling the prime mover}
- H02P 23/186 . . {of one shaft by controlling the prime mover}
- H02P 23/20 . Controlling the acceleration or deceleration
- H02P 23/22 . Controlling the speed digitally using a reference oscillator, a speed proportional pulse rate feedback and a digital comparator
- H02P 23/24 . Controlling the direction, e.g. clockwise or counterclockwise
- H02P 23/26 . Power factor control [PFC]
- H02P 23/28 . Controlling the motor by varying the switching frequency of switches connected to a DC supply and the motor phases
- H02P 23/30 . Direct torque control [DTC] or field acceleration method [FAM]

**H02P 25/00 Arrangements or methods for the control of AC motors characterised by the kind of AC motor or by structural details**

**NOTE**

When classifying in this group, subject matter also relating to groups [H02P 21/00](#), [H02P 23/00](#) or [H02P 27/00](#) is further classified in those groups whenever appropriate.

- H02P 25/02 . characterised by the kind of motor
- H02P 25/022 . . Synchronous motors ([H02P 25/064 takes precedence](#))

**WARNING**

Group [H02P 25/022](#) is impacted by reclassification into group [H02P 25/024](#).

Groups [H02P 25/022](#) and [H02P 25/024](#) should be considered in order to perform a complete search.

- H02P 25/024 . . . controlled by supply frequency

**WARNING**

Group [H02P 25/024](#) is incomplete pending reclassification of documents from group [H02P 25/022](#) .

Groups [H02P 25/022](#) and [H02P 25/024](#) should be considered in order to perform a complete search.

- H02P 25/026 . . . . thereby detecting the rotor position

**WARNING**

Group [H02P 25/026](#) is impacted by reclassification into group [H02P 25/03](#).

Groups [H02P 25/026](#) and [H02P 25/03](#) should be considered in order to perform a complete search.

- H02P 25/028 . . . with four quadrant control

**WARNING**

Group [H02P 25/028](#) is impacted by reclassification into group [H02P 25/034](#).

Groups [H02P 25/028](#) and [H02P 25/034](#) should be considered in order to perform a complete search.

- H02P 25/03 . . . with brushless excitation

**WARNING**

Group [H02P 25/03](#) is incomplete pending reclassification of documents from group [H02P 25/026](#).

Groups [H02P 25/026](#) and [H02P 25/03](#) should be considered in order to perform a complete search.

- H02P 25/032 . . Reciprocating, oscillating or vibrating motors

- H02P 25/034 . . . Voice coil motors (voice coil motors driven by DC power [H02P 7/025](#))

**WARNING**

Group [H02P 25/034](#) is incomplete pending reclassification of documents from group [H02P 25/028](#).

Groups [H02P 25/028](#) and [H02P 25/034](#) should be considered in order to perform a complete search.

- H02P 25/04 . . Single phase motors, e.g. capacitor motors

- H02P 25/06 . . Linear motors

**WARNING**

Group [H02P 25/06](#) is impacted by reclassification into group [H02P 25/062](#), [H02P 25/064](#) and [H02P 25/066](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- H02P 25/062 . . . of the induction type

**WARNING**

Group [H02P 25/062](#) is incomplete pending reclassification of documents from group [H02P 25/06](#).

Groups [H02P 25/06](#) and [H02P 25/062](#) should be considered in order to perform a complete search.

H02P 25/064 . . . of the synchronous type

**WARNING**

Group [H02P 25/064](#) is incomplete pending reclassification of documents from group [H02P 25/06](#).

Groups [H02P 25/06](#) and [H02P 25/064](#) should be considered in order to perform a complete search.

H02P 25/066 . . . . of the stepping type

**WARNING**

Group [H02P 25/066](#) is incomplete pending reclassification of documents from group [H02P 25/06](#).

Groups [H02P 25/06](#) and [H02P 25/066](#) should be considered in order to perform a complete search.

H02P 25/08 . . Reluctance motors

H02P 25/0805 . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}

H02P 25/083 . . . Arrangements for increasing the switching speed from one coil to the next one

**WARNING**

Group [H02P 25/083](#) is impacted by reclassification into group [H02P 25/089](#).

Groups [H02P 25/083](#) and [H02P 25/089](#) should be considered in order to perform a complete search.

H02P 25/086 . . . Commutation

**WARNING**

Group [H02P 25/086](#) is impacted by reclassification into group [H02P 25/0925](#).

Groups [H02P 25/086](#) and [H02P 25/0925](#) should be considered in order to perform a complete search.

H02P 25/089 . . . . Sensorless control (direct torque control [H02P 23/30](#))

**WARNING**

Group [H02P 25/089](#) is incomplete pending reclassification of documents from group [H02P 25/083](#).

Groups [H02P 25/083](#) and [H02P 25/089](#) should be considered in order to perform a complete search.

H02P 25/092 . . . Converters specially adapted for controlling reluctance motors

H02P 25/0925 . . . . {wherein the converter comprises only one switch per phase}

**WARNING**

Group [H02P 25/0925](#) is incomplete pending reclassification of documents from group [H02P 25/086](#).

Groups [H02P 25/086](#) and [H02P 25/0925](#) should be considered in order to perform a complete search.

- H02P 25/098 . . . Arrangements for reducing torque ripple
- H02P 25/10 . . Commutator motors, e.g. repulsion motors
- H02P 25/102 . . . {Repulsion motors}
- H02P 25/105 . . . {Four quadrant control}
- H02P 25/107 . . . {Polyphase or monophaser commutator motors}
- H02P 25/12 . . . with shiftable brushes
- H02P 25/14 . . . Universal motors ([H02P 25/12](#) takes precedence)
- H02P 25/145 . . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value, speed feedback}
- H02P 25/16 . characterised by the circuit arrangement or by the kind of wiring
- H02P 25/18 . . with arrangements for switching the windings, e.g. with mechanical switches or relays
- H02P 25/182 . . . {whereby the speed is regulated by using centrifugal devices, e.g. switch, resistor}
- H02P 25/184 . . . {wherein the motor speed is changed by switching from a delta to a star, e.g. wye, connection of its windings, or vice versa.}
- H02P 25/186 . . . {whereby the speed is regulated by using a periodic interrupter ([H02P 25/30](#) takes precedence)}
- H02P 25/188 . . . {wherein the motor windings are switched from series to parallel or vice-versa to control speed or torque}
- H02P 25/20 . . . for pole-changing
- H02P 25/22 . . Multiple windings; Windings for more than three phases
- H02P 25/24 . . Variable impedance in stator or rotor circuit
- H02P 25/26 . . . with arrangements for controlling secondary impedance
- H02P 25/28 . . using magnetic devices with controllable degree of saturation, e.g. transducers
- H02P 25/30 . . the motor being controlled by a control effected upon an ac generator supplying it
- H02P 25/32 . . using discharge tubes
- H02P 25/325 . . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}

**H02P 27/00** **Arrangements or methods for the control of AC motors characterised by the kind of supply voltage** (of two or more motors [H02P 5/00](#); of synchronous motors with electronic commutators [H02P 6/00](#); of DC motors [H02P 7/00](#); of stepping motors [H02P 8/00](#))

**NOTE**

When classifying in this group, subject matter also relating to groups [H02P 21/00](#), [H02P 23/00](#) or [H02P 25/00](#) is further classified in those groups whenever appropriate

- H02P 27/02 . using supply voltage with constant frequency and variable amplitude
- H02P 27/024 . . using AC supply for only the rotor circuit or only the stator circuit
- H02P 27/026 . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}



- H02P 27/04 . using variable-frequency supply voltage, e.g. inverter or converter supply voltage
- H02P 27/045 . . {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}
- H02P 27/047 . . {V/F converter, wherein the voltage is controlled proportionally with the frequency}
- H02P 27/048 . . using AC supply for only the rotor circuit or only the stator circuit
- H02P 27/05 . . using AC supply for both the rotor and the stator circuits, the frequency of supply to at least one circuit being variable
- H02P 27/06 . . using dc to ac converters or inverters ([H02P 27/05 takes precedence](#))
- H02P 27/08 . . . with pulse width modulation
- H02P 27/085 . . . . {wherein the PWM mode is adapted on the running conditions of the motor, e.g. the switching frequency}
- H02P 27/10 . . . . using bang-bang controllers
- H02P 27/12 . . . . pulsing by guiding the flux vector, current vector or voltage vector on a circle or a closed curve, e.g. for direct torque control
- H02P 27/14 . . . . with three or more levels of voltage
- H02P 27/16 . . using ac to ac converters without intermediate conversion to dc ([H02P 27/05 takes precedence](#))
- H02P 27/18 . . . varying the frequency by omitting half waves

**H02P 29/00**

**Arrangements for regulating or controlling electric motors, appropriate for both AC and DC motors** ([arrangements for starting electric motors H02P 1/00](#); [arrangements for stopping or slowing electric motors H02P 3/00](#); [control of motors that can be connected to two or more different electric power supplies H02P 4/00](#); [regulating or controlling the speed or torque of two or more electric motors H02P 5/00](#); [vector control H02P 21/00](#))

**WARNING**

Group [H02P 29/00](#) is impacted by reclassification into groups [H02P 29/10](#), [H02P 29/20](#), [H02P 29/40](#), [H02P 29/50](#), [H02P 29/60](#), [H02P 29/62](#), [H02P 29/64](#), [H02P 29/66](#) and [H02P 29/68](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- H02P 29/0005 . {for preventing over- or under speed}
- H02P 29/0011 . {for controlling one motor used for different sequential operations}
- H02P 29/0016 . {Control of angular speed of one shaft without controlling the prime mover}
- H02P 29/0022 . . {Controlling a brake between the prime mover and the load}
- H02P 29/0027 . . {Controlling a clutch between the prime mover and the load}
- H02P 29/0033 . {Controlling the mechanical load according to the amount of current drawn or delivered by the motor}
- H02P 29/0038 . {Reduction of harmonics}
- H02P 29/0044 . {Controlling or determining the motor or drive temperature (AC motor parameter estimation [H02P 23/14](#); motor parameter estimation for vector control [H02P 21/14](#); protection against overload [H02P 29/02](#); protection against faults of stepper motors [H02P 8/36](#))}

- H02P 29/005 . . {for raising the temperature of the motor}
- H02P 29/0055 . . {controlling or determining the winding temperature ([H02P 29/0072](#) takes precedence)}
- H02P 29/0061 . . {controlling or determining the rotor temperature}
- H02P 29/0066 . . . {the rotor having permanent magnets ([H02P 29/0083](#) takes precedence)}
- H02P 29/0072 . . . {the rotor having windings}
- H02P 29/0077 . . . . {by rotor current detection}
- H02P 29/0083 . . {by back-emf evaluation to obtain the motor temperature (back-emf based rotor position determination [H02P 6/182](#))}
- H02P 29/0088 . . {based on the temperature of a drive component or a semiconductor component}
- H02P 29/0094 . . . {compensating for Hall sensor temperature non-linearity}
- H02P 29/02 . . Providing protection against overload without automatic interruption of supply (protection against faults of stepper motors [H02P 8/36](#))

**NOTE**

## Informative note

References listed below indicate places which could also be of interest when carrying out a search in respect of the subject matter covered by the preceding group:

Emergency protective circuit arrangements with automatic interruption if supply, in general [H02H 7/08](#);

Emergency protective circuit arrangements for limiting excess current or voltage without disconnection in general [H02H 7/08](#)

- H02P 29/024 . . Detecting a fault condition, e.g. short circuit, locked rotor, open circuit or loss of load

**WARNING**

Group [H02P 29/024](#) is impacted by reclassification into group [H02P 29/0241](#).

Groups [H02P 29/024](#) and [H02P 29/0241](#) should be considered in order to perform a complete search.

- H02P 29/0241 . . . {the fault being an overvoltage}

**WARNING**

Group [H02P 29/0241](#) is incomplete pending reclassification of documents from group [H02P 29/024](#).

Groups [H02P 29/024](#) and [H02P 29/0241](#) should be considered in order to perform a complete search.

- H02P 29/0243 . . . {the fault being a broken phase}
- H02P 29/025 . . . {the fault being a power interruption}
- H02P 29/026 . . . {the fault being a power fluctuation}
- H02P 29/027 . . . {the fault being an over-current}

H02P 29/028

- the motor continuing operation despite the fault condition, e.g. eliminating, compensating for or remedying the fault

**WARNING**

Group [H02P 29/028](#) is impacted by reclassification into group [H02P 29/032](#).

Groups [H02P 29/028](#) and [H02P 29/032](#) should be considered in order to perform a complete search.

H02P 29/032

- Preventing damage to the motor, e.g. setting individual current limits for different drive conditions

**WARNING**

Group [H02P 29/032](#) is incomplete pending reclassification of documents from group [H02P 29/028](#).

Groups [H02P 29/028](#) and [H02P 29/032](#) should be considered in order to perform a complete search.

H02P 29/04

- by means of a separate brake

H02P 29/045

- {whereby the speed is regulated by measuring the motor speed and comparing it with a given physical value}

H02P 29/10

- for preventing overspeed or under speed

**WARNING**

Group [H02P 29/10](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/10](#) should be considered in order to perform a complete search.

H02P 29/20

- for controlling one motor used for different sequential operations

**WARNING**

Group [H02P 29/20](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/20](#) should be considered in order to perform a complete search.

H02P 29/40

- Regulating or controlling the amount of current drawn or delivered by the motor for controlling the mechanical load

**WARNING**

Group [H02P 29/40](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/40](#) should be considered in order to perform a complete search.

H02P 29/50

- Reduction of harmonics

**WARNING**

Group [H02P 29/50](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/50](#) should be considered in order to perform a complete search.

H02P 29/60

- Controlling or determining the temperature of the motor or of the drive  
(H02P 29/02 takes precedence)

**WARNING**

Group [H02P 29/60](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/60](#) should be considered in order to perform a complete search.

H02P 29/62

- for raising the temperature of the motor

**WARNING**

Group [H02P 29/62](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/62](#) should be considered in order to perform a complete search.

H02P 29/64

- Controlling or determining the temperature of the winding

**WARNING**

Group [H02P 29/64](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/64](#) should be considered in order to perform a complete search.

H02P 29/66

- Controlling or determining the temperature of the rotor

**WARNING**

Group [H02P 29/66](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/66](#) should be considered in order to perform a complete search.

H02P 29/68

- based on the temperature of a drive component or a semiconductor component

**WARNING**

Group [H02P 29/68](#) is incomplete pending reclassification of documents from group [H02P 29/00](#).

Groups [H02P 29/00](#) and [H02P 29/68](#) should be considered in order to perform a complete search.

H02P 31/00

Arrangements for regulating or controlling electric motors not provided for in groups [H02P 1/00](#) to [H02P 5/00](#), [H02P 7/00](#) or [H02P 21/00](#) to [H02P 29/00](#)

### **Indexing scheme associated with groups relating to the arrangements for controlling electric generators**

H02P 2101/00

**Special adaptation of control arrangements for generators**

H02P 2101/10

- for water-driven turbines

H02P 2101/15

- for wind-driven turbines

- H02P 2101/20 . for steam-driven turbines
- H02P 2101/25 . for combustion engines
- H02P 2101/30 . for aircraft
- H02P 2101/35 . for ships
- H02P 2101/40 . for railway vehicles
- H02P 2101/45 . for motor vehicles, e.g. car alternators

#### **H02P 2103/00 Controlling arrangements characterised by the type of generator**

- H02P 2103/10 . of the asynchronous type
- H02P 2103/20 . of the synchronous type

#### **H02P 2201/00 Indexing scheme relating to controlling arrangements characterised by the converter used**

- H02P 2201/01 . AC-AC converter stage controlled to provide a defined AC voltage
- H02P 2201/03 . AC-DC converter stage controlled to provide a defined DC link voltage ([general aspects of plural converters in cascade H02M](#))
- H02P 2201/05 . Capacitive half bridge, i.e. resonant inverter having two capacitors and two switches
- H02P 2201/07 . DC-DC step-up or step-down converter inserted between the power supply and the inverter supplying the motor, e.g. to control voltage source fluctuations, to vary the motor speed ([general aspects of plural converters in cascade H02M](#))
- H02P 2201/09 . Boost converter, i.e. DC-DC step up converter increasing the voltage between the supply and the inverter driving the motor ([general aspects of plural converters in cascade H02M](#))
- H02P 2201/11 . Buck converter, i.e. DC-DC step down converter decreasing the voltage between the supply and the inverter driving the motor ([general aspects of plural converters in cascade H02M](#))
- H02P 2201/13 . DC-link of current link type, e.g. typically for thyristor bridges, having an inductor in series with rectifier
- H02P 2201/15 . Power factor Correction [PFC] circuit generating the DC link voltage for motor driving inverter ([motor power factor control H02P 23/26](#))

#### **H02P 2203/00 Indexing scheme relating to controlling arrangements characterised by the means for detecting the position of the rotor**

- H02P 2203/01 . Motor rotor position determination based on the detected or calculated phase inductance, e.g. for a Switched Reluctance Motor
- H02P 2203/03 . Determination of the rotor position, e.g. initial rotor position, during standstill or low speed operation
- H02P 2203/05 . Determination of the rotor position by using two different methods and/or motor models
- H02P 2203/07 . Motor variable determination based on the ON-resistance of a power switch, i.e. the voltage across the switch is measured during the ON state of the switch and used to determine the current in the motor and to calculate the speed
- H02P 2203/09 . Motor speed determination based on the current and/or voltage without using a tachogenerator or a physical encoder

- H02P 2203/11
  - Determination or estimation of the rotor position or other motor parameters based on the analysis of high frequency signals ([position detection of motors with electronic commutators in dependence of the position H02P 6/185](#))
- H02P 2205/00**      **Indexing scheme relating to controlling arrangements characterised by the control loops**
  - H02P 2205/01
    - Current loop, i.e. comparison of the motor current with a current reference
  - H02P 2205/03
    - Power loop, i.e. comparison of the motor power with a power reference
  - H02P 2205/05
    - Torque loop, i.e. comparison of the motor torque with a torque reference
  - H02P 2205/07
    - Speed loop, i.e. comparison of the motor speed with a speed reference
- H02P 2207/00**      **Indexing scheme relating to controlling arrangements characterised by the type of motor**
  - H02P 2207/01
    - Asynchronous machines
  - H02P 2207/03
    - Double rotor motors or generators, i.e. electromagnetic transmissions having double rotor with motor and generator functions, e.g. for electrical variable transmission
  - H02P 2207/05
    - Synchronous machines, e.g. with permanent magnets or DC excitation
  - H02P 2207/055
    - . Surface mounted magnet motors
  - H02P 2207/07
    - Doubly fed machines receiving two supplies both on the stator only wherein the power supply is fed to different sets of stator windings or to rotor and stator windings
  - H02P 2207/073
    - . wherein only one converter is used, the other windings being supplied without converter e.g. doubly-fed induction machines
  - H02P 2207/076
    - . wherein both supplies are made via converters: especially doubly-fed induction machines; e.g. for starting
- H02P 2209/00**      **Indexing scheme relating to controlling arrangements characterised by the waveform of the supplied voltage or current**
  - H02P 2209/01
    - Motors with neutral point connected to the power supply
  - H02P 2209/03
    - Motors with neutral point disassociated, i.e. the windings ends are not connected directly to a common point
  - H02P 2209/05
    - Polyphase motors supplied from a single-phase power supply or a DC power supply
  - H02P 2209/07
    - Trapezoidal waveform
  - H02P 2209/09
    - PWM with fixed limited number of pulses per period
  - H02P 2209/095
    - . One pulse per half period
  - H02P 2209/11
    - Sinusoidal waveform
  - H02P 2209/13
    - Different type of waveforms depending on the mode of operation