

CPC COOPERATIVE PATENT CLASSIFICATION

G11C **STATIC STORES** (information storage based on relative movement between record carrier and transducer [G11B](#); semiconductor devices for storage [H01L](#), e.g. [H01L 27/108](#) - [H01L 27/115](#); pulse technique in general [H03K](#), e.g. electronic switches [H03K 17/00](#); {using a static store as a picture recording medium [H04N 5/907](#)})

NOTES

1. This subclass covers devices or arrangements for storage of digital or analogue information in which no relative movement takes place between an information storage element and a transducer; which incorporate a selecting-device for writing-in or reading-out the information into or from the store
2. This subclass does not cover elements not adapted for storage and not provided with such means as referred to in Note (3) below, which elements are classified in the appropriate subclass, e.g. of [H01](#), [H03K](#).
3. In this subclass, the following terms are used with the meaning indicated:
 - "storage element" is an element which can hold at least one item of information and is provided with means for writing-in or reading-out this information;
 - "memory" is a device, including storage elements, which can hold information to be extracted when desired.

WARNING

The following IPC groups are not used in the CPC scheme. Subject matter covered by these groups is classified in the following CPC groups:

G11C 8/02	covered by	G11C 8/00 , H03K 17/00
G11C 11/4193	covered by	G11C 11/00
G11C 11/4195	covered by	G11C 11/00
G11C 11/4197	covered by	G11C 11/00

5/00	Details of stores covered by G11C 11/00	5/141	. . {Battery and back-up supplies (back-up supplies per se H02J 9/061)}
5/005	. {Circuit means for protection against loss of information of semiconductor storage devices (manufacturing semi-conductor by using bombardement with radiation H01L 21/26 ; error detection, monitoring G06F 11/00)}	5/142	. . {Contactless power supplies, e.g. RF, induction, IR (in general H02J 5/00)}
5/02	. Disposition of storage elements, e.g. in the form of a matrix array	5/143	. . {Detection of memory cassette insertion/removal; Continuity checks of supply and ground lines (in general G01R 31/02); Detection of supply variations/interruptions/levels (G11C 5/148 takes precedence); Switching between alternative supplies (back-up supplies per se H02J 9/061), (G11C 5/141 takes precedence)}
5/025	. . {Geometric lay-out considerations of storage- and peripheral-blocks in a semiconductor storage device (geometrical lay-out of the components in integrated circuits, H01L 27/0207)}	5/144	. . . {Detection of predetermined disconnection or reduction of power supply, e.g. power down or power standby}
5/04	. . Supports for storage elements, Supports for storage elements, {e.g. memory modules }; Mounting or fixing of storage elements on such supports	5/145	. . {Applications of charge pumps (charge pumps per se H02M 3/07); Boosted voltage circuits (for logic circuits or inverting circuits H03K 19/00); Clamp circuits therefor (G11C 5/141 takes precedence)}
5/05	. . . Supporting of cores in matrix	5/146	. . . {Substrate bias generators (G11C 5/141 takes precedence ; in general G05F 3/205)}
5/06	. Arrangements for interconnecting storage elements electrically, e.g. by wiring	5/147	. . {Voltage reference generators, voltage and current regulators (in general G05F 3/24); Internally lowered supply level (in general G05F 1/462); Compensation for voltage drops (G11C 5/141 takes precedence)}
5/063	. . {Voltage and signal distribution in integrated semi-conductor memory access lines, e.g. word-line, bit-line, cross-over resistance, propagation delay}	5/148	. . {Details of power up or power down circuits, standby circuits or recovery circuits}
5/066	. . {Means for reducing external access-lines for a semiconductor memory clip, e.g. by multiplexing at least address and data signals}		
5/08	. . for interconnecting magnetic elements, e.g. toroidal cores		
5/10	. . for interconnecting capacitors		
5/12	. Apparatus or processes for interconnecting storage elements, e.g. for threading magnetic cores	7/00	Arrangements for writing information into, or reading information out from, a digital store (G11C 5/00 takes precedence ; auxiliary circuits for stores using semiconductor devices G11C 11/4063 , G11C 11/413)
5/14	. Power supply arrangements (in general G05F , H02J , H02M), {e.g. Power down/chip (de)selection, layout of wiring/power grids, multiple supply levels}	7/005	. {with combined beam-and individual cell access}

- 7/02 . . . with means for avoiding parasitic signals
- 7/04 . . . with means for avoiding disturbances due to temperature effects
- 7/06 . . . Sense amplifiers; Associated circuits, {e.g. timing or triggering circuits} ([amplifiers per se H03F, H03K](#))
- 7/062 . . . {Differential amplifiers of non-latching type, e.g. comparators, long-tailed pairs}
- 7/065 . . . {Differential amplifiers of latching type}
- 7/067 . . . {Single-ended amplifiers}
- 7/08 . . . Control thereof
- 7/10 . . . Input/output (I/O) data interface arrangements, e.g. I/O data control circuits, I/O data buffers ([level conversion circuits in general H03K 19/0175](#))
- 7/1003 . . . {Interface circuits for daisy chain or ring bus memory arrangements}
- 7/1006 . . . {Data managing, e.g. manipulating data before writing or reading out, data bus switches or control circuits therefor}
- 7/1009 . . . {Data masking during input/output}
- 7/1012 . . . {Data reordering during input/output, e.g. crossbars, layers of multiplexers, shifting or rotating}
- 7/1015 . . . {Read-write modes for single port memories, i.e. having either a random port or a serial port}
- 7/1018 . . . {Serial bit line access mode, e.g. using bit line address shift registers, bit line address counters, bit line burst counters}
- 7/1021 {Page serial bit line access mode, i.e. using an enabled row address stroke pulse with its associated word line address and a sequence of enabled column address stroke pulses each with its associated bit line address}
- 7/1024 {Extended data output [EDO] mode, i.e. keeping output buffer enabled during an extended period of time}
- 7/1027 {Static column decode serial bit line access mode, i.e. using an enabled row address stroke pulse with its associated word line address and a sequence of enabled bit line addresses}
- 7/103 . . . {using serially addressed read-write data registers ([G11C 7/1036 takes precedence](#))}
- 7/1033 {using data registers of which only one stage is addressed for sequentially outputting data from a predetermined number of stages, e.g. nibble read-write mode}
- 7/1036 . . . {using data shift registers}
- 7/1039 . . . {using pipelining techniques, i.e. using latches between functional memory parts, e.g. row/column decoders, I/O buffers, sense amplifiers}
- 7/1042 . . . {using interleaving techniques, i.e. read-write of one part of the memory while preparing another part}
- 7/1045 . . . {Read-write mode select circuits}
- 7/1048 . . . {Data bus control circuits, e.g. precharging, presetting, equalising}
- 7/1051 . . . {Data output circuits, e.g. read-out amplifiers, data output buffers, data output registers, data output level conversion circuits}
- 7/1054 . . . {Optical output buffers}
- 7/1057 . . . {Data output buffers, e.g. comprising level conversion circuits, circuits for adapting load}
- 7/106 . . . {Data output latches}
- 7/1063 . . . {Control signal output circuits, e.g. status or busy flags, feedback command signals}
- 7/1066 . . . {Output synchronization}
- 7/1069 . . . {I/O lines read out arrangements ([global or local sense amplifiers for bit lines G11C 7/06](#))}
- 7/1072 . . . {for memories with random access ports synchronised on clock signal pulse trains, e.g. synchronous memories, self timed memories}
- 7/1075 . . . {for multiport memories each having random access ports and serial ports, e.g. video RAM}
- 7/1078 . . . {Data input circuits, e.g. write amplifiers, data input buffers, data input registers, data input level conversion circuits}
- 7/1081 . . . {Optical input buffers}
- 7/1084 . . . {Data input buffers, e.g. comprising level conversion circuits, circuits for adapting load}
- 7/1087 . . . {Data input latches}
- 7/109 . . . {Control signal input circuits}
- 7/1093 . . . {Input synchronization}
- 7/1096 . . . {Write circuits, e.g. I/O line write drivers}
- 7/12 . . . Bit line control circuits, e.g. drivers, boosters, pull-up circuits, pull-down circuits, precharging circuits, equalising circuits, for bit lines
- 7/14 . . . Dummy cell management; Sense reference voltage generators
- 7/16 . . . Storage of analogue signals in digital stores using an arrangement comprising analogue/digital (A/D) converters, digital memories and digital/analogue (D/A) converters
- 7/18 . . . Bit line organisation; Bit line lay-out
- 7/20 . . . Memory initialisation circuits, e.g. when powering up or down, memory clear, latent image memory
- 7/22 . . . Read-write (R-W) timing or clocking circuits; Read-write (R-W) control signal generators or management
- 7/222 . . . {Clock generating, synchronizing or distributing circuits within memory device}
- 7/225 . . . {Clock input buffers}
- 7/227 . . . {Timing of memory operations based on dummy memory elements or replica circuits}
- 7/24 . . . Memory cell safety or protection circuits, e.g. arrangements for preventing inadvertent reading or writing; Status cells; Test cells
- 8/00** . . . **Arrangements for selecting an address in a digital store (for stores using transistors [G11C 11/407](#), [G11C 11/413](#); {switching or gating circuits for general use [H03K 17/00](#)})**
- 8/005 . . . {with travelling wave access}
- 8/04 . . . using a sequential addressing device, e.g. shift register, counter {([FIFO G06F 5/06](#); [LIFO G06F 7/78](#); [multidimensional memory addressing G06F 12/0207](#))}
- 8/06 . . . Address interface arrangements, e.g. address buffers ([level conversion circuits in general H03K 19/0175](#))
- 8/08 . . . Word line control circuits, e.g. drivers, boosters, pull-up circuits, pull-down circuits, precharging circuits, for word lines
- 8/10 . . . Decoders
- 8/12 . . . Group selection circuits, e.g. for memory block selections, chip selection, array selection
- 8/14 . . . Word line organisation; Word line lay-out

- 8/16 . Multiple access memory array, e.g. addressing one storage element via at least independent addressing line groups {[multiport memories in general G11C 7/1075](#)}
- 8/18 . Address timing or clocking circuits; Address control signal generation or management, e.g. for row address strobe [RAS] or column address strobe [CAS] signals
- 8/20 . Address safety or protection circuits, i.e. arrangements for preventing unauthorised or accidental access
- 11/00 Digital stores characterised by the use of particular electric or magnetic storage elements; Storage elements therefor**
([G11C 14/00 - G11C 21/00 take precedence](#))
- 11/005 . {[comprising combined but independently operative RAM-ROM, RAM-PROM, RAM-EPROM cells](#)}
- NOTE**
- Group [G11C 11/56](#) takes precedence over groups [G11C 11/02 - G11C 11/54](#)
- 11/02 . using magnetic elements {[\(using multibit magnetic storage elements G11C 11/5607; counters with magnetic elements H03K 23/76; pulse generators, static switches, logic circuits with such elements H03K 3/45, H03K 17/80, H03K 19/16; measurement of magnetic variables G01R 33/00\)](#)}
- 11/04 . . using rod-type storage elements {[\(contains no documents; see G11C 11/06085, G11C 11/14, G11C 11/155\)](#)}
- 11/06 . . using single-aperture storage elements, e.g. ring core; using multi-aperture plates in which each individual aperture forms a storage element
- 11/06007 . . . {[using a single aperture or single magnetic closed circuit](#)}
- NOTE**
- Provisionally contains the following details; control write -, read -, address circuitry (pulse generators in general [H03K 5/00, H03K 17/00](#)); arrangements for temperature compensation; checking of the correct functioning and repair arrangements (checking methods in general [G06F 11/00, G06F 11/28](#); testing magnetic elements [per se G01R 33/00](#)); magnetic properties, choice of materials or the like (materials [per se H01F 1/00](#))
- 11/06014 {[using one such element pro bit](#)}
- 11/06021 {[with destructive read-out](#)}
- 11/06028 {[Matrixes](#)}
- 11/06035 {["bit"-organised, e.g. 2 1/2D, 3D or a similar organisation, i.e. bit core selection for writing or reading, by at least two coincident partial currents](#)}
- 11/06042 {["word"-organised, e.g. 2D organisation or linear selection, i.e. full current selection through all the bit-cores of a word during reading](#)}
- 11/0605 {[with non-destructive read-out](#)}
- 11/06057 {[Matrixes](#)}
- 11/06064 {["bit"-organised \(2 1/2D, 3D or similar organisation\)](#)}
- 11/06071 {["word"-organised \(2D organisation or linear selection\)](#)}
- 11/06078 {[using two or more such elements pro bit](#)}
- 11/06085 . . . {[Multi-aperture structures or multi-magnetic closed circuits, each aperture storing a "bit", realised by rods, plates, grids, waffle-irons, \(i.e. grooved plates\) or similar devices](#)}
- 11/06092 . . . {[Multi-aperture structures or multi-magnetic closed circuits using two or more apertures per bit](#)}
- 11/061 . . . using element with single aperture or magnetic loop for storage, one element per bit, and for destructive read-out {[\(contains no documents, see G11C 11/06007, G11C 11/06014, G11C 11/06021, G11C 11/06028\)](#)}
- 11/063 bit organised, such as 2 1/2D, 3D organisation, i.e. for selection of an element by means of at least two coincident parital currents both for reading and for writing {[\(contains no documents; see G11C 11/06035\)](#)}
- 11/065 word organised, such as 2D organisation, or linear selection, i.e. for selection of all the elements of a word by means of a single full current for reading {[\(contains no documents; see G11C 11/06042\)](#)}
- 11/067 . . . using elements with single aperture or magnetic loop for storage, one element per bit, and for non-destructive read-out {[\(contains no documents, see G11C 11/0605 - G11C 11/06071\)](#)}
- 11/08 . . using multi-aperture storage elements, e.g. using transfluxors; using plates incorporating several individual multi-aperture storage elements ([G11C 11/10 takes precedence; using multi-aperture plates in which each individual aperture forms a storage element G11C 11/06](#))
- 11/10 . . using multi-axial storage elements
- 11/12 . . using tensors; using twistors, i.e. elements in which one axis of magnetisation is twisted
- 11/14 . . using thin-film elements
- 11/15 . . . using multiple magnetic layers ([G11C 11/155 takes precedence](#))
- 11/155 . . . with cylindrical configuration
- 11/16 . . using elements in which the storage effect is based on magnetic spin effect {[\(sensors using magnetoresistive multilayer structures G01R 33/093; thin layer magnetic read heads for magnetic discs G11B 5/31; non-reciprocal magnetic elements in waveguides H01P; composition of ferromagnetic material H01F 1/00; gyrators H03H 7/002\)](#)}
- 11/161 . . . {[details concerning the memory cell structure, e.g. the layers of the ferromagnetic memory cell](#)}
- 11/165 . . . {[Auxiliary circuits](#)}
- 11/1653 {[Address circuits or decoders](#)}
- 11/1655 {[Bit-line or column circuits](#)}
- 11/1657 {[Word-line or row circuits](#)}
- 11/1659 {[Cell access](#)}
- 11/1673 {[Reading or sensing circuits or methods](#)}
- 11/1675 {[Writing or programming circuits or methods](#)}
- 11/1677 {[Verifying circuits or methods](#)}
- 11/1693 {[Timing circuits or methods](#)}

- 11/1695 {Protection circuits or methods}
 - 11/1697 {Power supply circuits}
 - 11/18 using Hall-effect devices
 - 11/19 using non-linear reactive devices in resonant circuits
{(contains no documents, see [G11C 11/20](#))}
 - 11/20 using parametrons, {i.e. ferroresonant triggers;
with overcritical feedback magnetic amplifiers
or similar (pulse generators using parametrons
and ferroresonant devices [H03K 19/162](#),
[H03K 19/164](#); counters using such elements
[H03K 23/001](#))}
 - 11/21 using electric elements
 - 11/22 using ferroelectric elements {(using multibit
ferroelectric storage elements [G11C 11/5657](#);
pulse generators using ferroelectric elements
[H03K 3/45](#); counters using such elements
[H03K 23/76](#))}
 - 11/221 {using ferroelectric capacitors}
 - 11/223 {using MOS with ferroelectric gate insulating
film}
 - 11/225 {Auxiliary circuits}
 - 11/2253 {Address circuits or decoders}
 - 11/2255 {Bit-line or column circuits}
 - 11/2257 {Word-line or row circuits}
 - 11/2259 {Cell access}
 - 11/2273 {Reading or sensing circuits or methods}
 - 11/2275 {Writing or programming circuits or
methods}
 - 11/2277 {Verifying circuits or methods}
 - 11/2293 {Timing circuits or methods}
 - 11/2295 {Protection circuits or methods}
 - 11/2297 {Power supply circuits}
 - 11/23 using electrostatic storage on a common layer,
e.g. Forrester-Haef tubes, {William tubes}
([G11C 11/22](#) takes precedence; {construction of
Williams tubes [H01J 31/00](#)})
 - 11/24 using capacitors ([G11C 11/22](#) takes precedence;
using a combination of semiconductor devices
and capacitors [G11C 11/34](#), e.g. [G11C 11/40](#))
 - 11/26 using discharge tubes {(counters using such
elements [H03K 25/00](#))}
 - 11/265 {counting tubes, e.g. decatrons, trochotrons
(counters using such elements [H03K 29/00](#))}
 - 11/28 using gas-filled tubes {(counting tubes
[G11C 11/265](#); pulse generators, electronic
switches, logic circuits using such elements
[H03K 3/37](#), [H03K 17/52](#), [H03K 19/04](#))}
 - 11/30 using vacuum tubes {(counting tubes
[G11C 11/265](#); pulse generators, electronic
switches, logic circuits using such elements
[H03K 3/37](#), [H03K 17/52](#), [H03K 19/04](#))}
 - 11/34 using semiconductor devices {(processes or
apparatus for the manufacture or treatment of
semiconductor or solid state devices [H01L 21/00](#);
integrated circuit devices [H01L 27/00](#); generating
electric pulses, e.g. bistable devices using
semiconductor devices [H03K 3/00](#))}
 - 11/35 with charge storage in a depletion layer, e.g.
charged coupled devices {(in shift registers
[G11C 19/282](#))}
 - 11/36 using diodes, e.g. as threshold elements,
{i.e. diodes assuming a stable ON-stage
when driven above their threshold (S- or N-
characteristic)}
 - 11/38 using tunnel diodes
 - 11/39 using thyristors {or the avalanche or negative
resistance type, e.g. PNP, SCR, SCS, UJT}
 - 11/40 using transistors
 - 11/401 forming cells needing refreshing or charge
regeneration, {i.e. dynamic cells}
 - 11/402 with charge regeneration individual to
each memory cell, i.e. internal refresh
 - 11/4023 {using field effect transistors}
 - 11/4026 {using bipolar transistors}
 - 11/403 with charge regeneration common to a
multiplicity of memory cells, i.e. external
refresh
 - 11/404 with one charge-transfer gate, e.g. MOS
transistor, per cell
 - 11/4045 {using a plurality of serially
connected access transistors, each
having a storage capacitor}
- WARNING**
Not complete, see also
[G11C 11/404](#)
- 11/405 with three charge-transfer gates, e.g.
MOS transistors, per cell
 - 11/406 Management or control of the refreshing
or charge-regeneration cycles
 - 11/40603 {Arbitration, priority and concurrent
access to memory cells for read/write or
refresh operations}
 - 11/40607 {Refresh operations in memory devices
with an internal cache or data buffer}
 - 11/40611 {External triggering or timing of
internal or partially internal refresh
operations, e.g. auto-refresh or CAS-
before-RAS triggered refresh}
 - 11/40615 {Internal triggering or timing of refresh,
e.g. hidden refresh, self refresh, pseudo-
SRAMs}
 - 11/40618 {Refresh operations over multiple banks
or interleaving}
 - 11/40622 {Partial refresh of memory arrays}
 - 11/40626 {Temperature related aspects of refresh
operations}
 - 11/4063 Auxiliary circuits, e.g. for addressing,
decoding, driving, writing, sensing or
timing
 - 11/4067 for memory cells of the bipolar type
 - 11/407 for memory cells of the field-effect type
 - 11/4072 Circuits or initialisation, powering
up or down, clearing memory or
presetting
 - 11/4074 Power supply or voltage generation
circuits, e.g. bias voltage generators,
substrate voltage generators, back-up
power, power control circuits
 - 11/4076 Timing circuits ([for regeneration
management \[G11C 11/406\]\(#\)](#))
 - 11/4078 Safety or protection circuits, e.g.
for preventing inadvertent or
unauthorised reading or writing;
Status cells; Test cells ([protection of
memory contents during checking or
testing \[G11C 29/52\]\(#\)](#))
 - 11/408 Address circuits

11/4082	{Address Buffers; level conversion circuits}	11/48	. using displaceable coupling elements, e.g. ferromagnetic cores, to produce change between different states of mutual or self-inductance {(contains no documents; see G11C 17/00 and subgroups)}
11/4085	{Word line control circuits, e.g. word line drivers, - boosters, - pull-up, - pull-down, - precharge}	11/50	. using actuation of electric contacts to store the information (mechanical stores G11C 23/00 ; switches providing a selected number of consecutive operations of the contacts by a single manual actuation of the operating part H01H 41/00)
11/4087	{Address decoders, e.g. bit - or word line decoders; Multiple line decoders}	11/52	. . using electromagnetic relays
11/409	Read-write (R-W) circuits	11/54	. using elements simulating biological cells, e.g. neuron
11/4091	Sense or sense/refresh amplifiers, or associated sense circuitry, e.g. for coupled bit-line precharging, equalising or isolating	11/56	. using storage elements with more than two stable states represented by steps, e.g. of voltage, current, phase, frequency (counting arrangements comprising multi-stable elements of this type H03K 25/00 , H03K 29/00)
11/4093	Input/output (I/O) data interface arrangements, e.g. data buffers (level conversion circuits in general H03K 19/0175)	11/5607	. . {using magnetic storage elements}
11/4094	Bit-line management or control circuits	11/5614	. . {using conductive bridging RAM [CBRAM] or programming metallization cells [PMC]}
11/4096	Input/output (I/O) data management or control circuits, e.g. reading or writing circuits, I/O drivers, bit-line switches	11/5621	. . {using charge storage in a floating gate}
11/4097	Bit-line organisation, e.g. bit-line layout, folded bit lines	11/5628	. . . {Programming or writing circuits; Data input circuits}
11/4099	Dummy cell treatment; Reference voltage generators	11/5635 {Erasing circuits}
11/41	forming {static} cells with positive feedback, i.e. cells not needing refreshing or charge regeneration, e.g. bistable multivibrator or Schmitt trigger	11/5642	. . . {Sensing or reading circuits; Data output circuits}
11/411	using bipolar transistors only	11/565	. . {using capacitive charge storage elements}
11/4113	{with at least one cell access to base or collector of at least one of said transistors, e.g. via access diodes, access transistors}	11/5657	. . {using ferroelectric storage elements}
11/4116	{with at least one cell access via separately connected emitters of said transistors or via multiple emitters, e.g. T2L, ECL}	11/5664	. . {using organic memory material storage elements}
11/412	using field-effect transistors only {(latent image memory G11C 7/20 ; multi-port cells G11C 8/16)}	11/5671	. . {using charge trapping in an insulator}
11/4125	{Cells incorporating circuit means for protection against loss of information (in general G11C 5/005)}	11/5678	. . {using amorphous/crystalline phase transition storage elements}
11/413	Auxiliary circuits, e.g. for addressing, decoding, driving, writing, sensing, timing, power reduction (in general G11C 5/00 - G11C 8/00)	11/5685	. . {using storage elements comprising metal oxide memory material, e.g. perovskites}
11/414	for memory cells of the bipolar type	11/5692	. . {read-only digital stores using storage elements with more than two stable states}
11/415	Address circuits	13/00	Digital stores characterised by the use of storage elements not covered by groups G11C 11/00, G11C 23/00 - G11C 25/00
11/416	Read-write circuits	13/0002	. {using resistance random access memory [RRAM] elements}
11/417	for memory cells of the field-effect type	13/0004	. . {comprising amorphous/crystalline phase transition cells}
11/418	Address circuits	13/0007	. . {comprising metal oxide memory material, e.g. perovskites}
11/419	Read-write circuits	13/0009	. . {RRAM elements whose operation depends upon chemical change}
11/42	. .	using opto-electronic devices, i.e. light-emitting and photoelectric devices electrically - or optically - {feedback -} coupled	13/0011	. . . {comprising conductive bridging RAM [CBRAM] or programming metallization cells [PMCs]}
11/44	. .	using super-conductive elements, e.g. cryotron {(pulse generators using such elements H03K 3/38 ; counters H03K 23/001)}	13/0014	. . . {comprising cells based on organic memory material}
11/46	. .	using thermoplastic elements	13/0016 {comprising polymers}
			13/0019 {comprising bio-molecules}
			13/0021	. . {Auxiliary circuits}
			13/0023	. . . {Address circuits or decoders}
			13/0026 {Bit-line or column circuits}
			13/0028 {Word-line or row circuits}
			13/003	. . . {Cell access}
			13/0033	. . . {Disturbance prevention or evaluation; Refreshing of disturbed memory data}

13/0035	. . . {Evaluating degradation, retention or wearout, e.g. by counting writing cycles}	13/042	. . {using information stored in the form of an interference pattern (hologram , lippman ; holography G03H , G02B 5/32)}
13/0038	. . . {Power supply circuits}	13/043	. . . {using magnetic-optical storage elements}
13/004	. . . {Reading or sensing circuits or methods}	13/044	. . . {using electro-optical elements}
2013/0042 {Read using differential sensing, e.g. bit line [BL] and bit line bar [BLB]}	13/045	. . . {using photochromic storage elements}
2013/0045 {Read using current through the cell}	13/046	. . . {using other storage elements storing information in the form of an interference pattern}
2013/0047 {Read destroying or disturbing the data}	13/047	. . {using electro-optical elements (G11C 13/042 takes precedence)}
2013/005 {Read using potential difference applied between cell electrodes}	13/048	. . {using other optical storage elements}
2013/0052 {Read process characterized by the shape, e.g. form, length, amplitude of the read pulse}	13/06	. . using magneto-optical elements (G11C 13/042 takes precedence) magneto-optics in general (G02F)
2013/0054 {Read is performed on a reference element, e.g. cell, and the reference sensed value is used to compare the sensed value of the selected cell}	14/00	Digital stores characterised by arrangements of cells having volatile and non-volatile storage properties for back-up when the power is down (bistable elements storing the actual state when the supply voltage fails H03K 3/02335 , H03K 3/0375 , H03K 3/2865 , H03K 3/356008)
2013/0057 {Read done in two steps, e.g. wherein the cell is read twice and one of the two read values serving as a reference value}	14/0009	. {in which the volatile element is a DRAM cell}
13/0059	. . . {Security or protection circuits or methods}	14/0018	. . {and the nonvolatile element is an EEPROM element, e.g. a floating gate or MNOS transistor}
13/0061	. . . {Timing circuits or methods}	14/0027	. . {and the nonvolatile element is a ferroelectric element}
13/0064	. . . {Verifying circuits or methods}	14/0036	. . {and the nonvolatile element is a magnetic RAM [MRAM] element or ferromagnetic cell}
2013/0066 {Verify correct writing whilst writing is in progress, e.g. by detecting onset or cessation of current flow in cell and using the detector output to terminate writing}	14/0045	. . {and the nonvolatile element is a resistive RAM element, i.e. programmable resistors, e.g. formed of phase change or chalcogenide material}
13/0069	. . . {Writing or programming circuits or methods}	14/0054	. {in which the volatile element is a SRAM cell}
2013/0071 {Write using write potential applied to access device gate}	14/0063	. . {and the nonvolatile element is an EEPROM element, e.g. a floating gate or MNOS transistor}
2013/0073 {Write using bi-directional cell biasing}	14/0072	. . {and the nonvolatile element is a ferroelectric element}
2013/0076 {Write operation performed depending on read result}	14/0081	. . {and the nonvolatile element is a magnetic RAM [MRAM] element or ferromagnetic cell}
2013/0078 {Write using current through the cell}	14/009	. . {and the nonvolatile element is a resistive RAM element, i.e. programmable resistors, e.g. formed of phase change or chalcogenide material}
2013/008 {Write by generating heat in the surroundings of the memory material, e.g. thermowrite}	15/00	Digital stores in which information comprising one or more characteristic parts is written into the store and in which information is read-out by searching for one or more of these characteristic parts, i.e. associative or content-addressed stores (in which information is addressed to a specific location G11C 11/00 ; selection information using addressing means, e.g. hashing, tree addressing, chaining G06F 11/22 ; information retrieval systems using a computer G06F 17/30)
2013/0083 {Write to perform initialising, forming process, electro forming or conditioning}	15/02	. using magnetic elements
2013/0085 {Write a page or sector of information simultaneously, e.g. a complete row or word line}	15/04	. using semiconductor elements
2013/0088 {Write with the simultaneous writing of a plurality of cells}	15/043	. . {using capacitive charge storage elements}
2013/009 {Write using potential difference applied between cell electrodes}	15/046	. . {using non-volatile storage elements}
2013/0092 {Write characterized by the shape, e.g. form, length, amplitude of the write pulse}	15/06	. using cryogenic elements
2013/0095 {Write using strain induced by, e.g. piezoelectric, thermal effects}	16/00	Erasable programmable read-only memories (G11C 14/00 takes precedence)
13/0097	. . . {Erasing, e.g. resetting, circuits or methods}	16/02	. electrically programmable (programmable multibit digital storage elements G11C 11/5621)
13/02	. using elements whose operation depends upon chemical change (G11C 13/0009 takes precedence); using electrochemical charge G11C 11/00)	16/04	. . using variable threshold transistors, e.g. FAMOS
13/025	. . {using fullerenes, e.g. C60, or nanotubes, e.g. carbon or silicon nanotubes}		
13/04	. using optical elements {using other beam accessed elements, e.g. electron, ion beam (using electrostatic memory tubes G11C 11/23 ; recording of television signals H04N 5/76)}		
13/041	. . {using photochromic storage elements (G11C 13/042 takes precedence)}		

16/0408	. . . {comprising cells containing floating gate transistors (G11C 16/0483 , G11C 16/0491 take precedence)}	16/28 using differential sensing or reference cells, e.g. dummy cells
16/0416 {comprising cells containing a single floating gate transistor and no select transistor, e.g. UV EPROM}	16/30	. . . Power supply circuits
16/0425 {comprising cells containing a merged floating gate and select transistor}	16/32	. . . Timing circuits
16/0433 {comprising cells containing a single floating gate transistor and one or more separate select transistors}	16/34	. . . Determination of programming status, e.g. threshold voltage, overprogramming or underprogramming, retention
16/0441 {comprising cells containing multiple floating gate devices, e.g. separate read-and-write FAMOS transistors with connected floating gates}	16/3404 {Convergence or correction of memory cell threshold voltages; Repair or recovery of overerased or overprogrammed cells}
16/045 {Floating gate memory cells with both P and N channel memory transistors, usually sharing a common floating gate}	16/3409 {Circuits or methods to recover overerased nonvolatile memory cells detected during erase verification, usually by means of a "soft" programming step}
16/0458 {comprising plural independent floating gates which store independent data (for storage of more than two stable states at a single floating gate G11C 11/5621)}	16/3413 {Circuits or methods to recover overprogrammed nonvolatile memory cells detected during program verification, usually by means of a "soft" erasing step}
16/0466	. . . {comprising cells with charge storage in an insulating layer, e.g. MNOS, SNOS (G11C 16/0483 , G11C 16/0491 take precedence)}	16/3418 {Disturbance prevention or evaluation; Refreshing of disturbed memory data}
16/0475 {comprising plural independent storage sites which store independent data (for storage of more than two stable states at a single storage site G11C 11/5621)}	16/3422 {Circuits or methods to evaluate read or write disturbance in nonvolatile memory, without steps to mitigate the problem}
16/0483	. . . {comprising cells having several storage transistors connected in series}	16/3427 {Circuits or methods to prevent or reduce disturbance of the state of a memory cell when neighbouring cells are read or written}
16/0491	. . . {Virtual ground arrays}	16/3431 {Circuits or methods to detect disturbed nonvolatile memory cells, e.g. which still read as programmed but with threshold less than the program verify threshold or read as erased but with threshold greater than the erase verify threshold, and to reverse the disturbance via a refreshing programming or erasing step}
16/06	. . Auxiliary circuits, e.g. for writing into memory (in general G11C 7/00)	16/3436 {Arrangements for verifying correct programming or erasure}
16/08	. . . Address circuits; Decoders; Word-line control circuits	16/344 {Arrangements for verifying correct erasure or for detecting overerased cells}
16/10	. . . Programming or data input circuits	16/3445 {Circuits or methods to verify correct erasure of nonvolatile memory cells}
16/102 {External programming circuits, e.g. EPROM programmers; In-circuit programming or reprogramming; EPROM emulators}	16/345 {Circuits or methods to detect overerased nonvolatile memory cells, usually during erasure verification}
16/105 {Circuits or methods for updating contents of nonvolatile memory, especially with 'security' features to ensure reliable replacement, i.e. preventing that old data is lost before new data is reliably written}	16/3454 {Arrangements for verifying correct programming or for detecting overprogrammed cells}
16/107 {Programming all cells in an array, sector or block to the same state prior to flash erasing}	16/3459 {Circuits or methods to verify correct programming of nonvolatile memory cells}
16/12 Programming voltage switching circuits	16/3463 {Circuits or methods to detect overprogrammed nonvolatile memory cells, usually during program verification}
16/14 Circuits for erasing electrically, e.g. erase voltage switching circuits	16/3468 {Prevention of overerasure or overprogramming, e.g. by verifying whilst erasing or writing}
16/16 for erasing blocks, e.g. arrays, words, groups	16/3472 {Circuits or methods to verify correct erasure of nonvolatile memory cells whilst erasing is in progress, e.g. by detecting onset or cessation of current flow in cells and using the detector output to terminate erasure}
16/18 Circuits for erasing optically		
16/20 Initialising; Data preset; Chip identification		
16/22	. . . Safety or protection circuits preventing unauthorised or accidental access to memory cells		
16/225 {Preventing erasure, programming or reading when power supply voltages are outside the required ranges}		
16/24	. . . Bit-line control circuits		
16/26	. . . Sensing or reading circuits; Data output circuits		

- 16/3477 {Circuits or methods to prevent overerasing of nonvolatile memory cells, e.g. by detecting onset or cessation of current flow in cells and using the detector output to terminate erasing}
- 16/3481 {Circuits or methods to verify correct programming of nonvolatile memory cells whilst programming is in progress, e.g. by detecting onset or cessation of current flow in cells and using the detector output to terminate programming}
- 16/3486 {Circuits or methods to prevent overprogramming of nonvolatile memory cells, e.g. by detecting onset or cessation of current flow in cells and using the detector output to terminate programming}
- 16/349 {Arrangements for evaluating degradation, retention or wearout, e.g. by counting erase cycles}
- 16/3495 {Circuits or methods to detect or delay wearout of nonvolatile EPROM or EEPROM memory devices, e.g. by counting numbers of erase or reprogram cycles, by using multiple memory areas serially or cyclically}
- 17/00 Read-only memories programmable only once; Semi-permanent stores, e.g. manually-replaceable information cards ({multibit read-only memories [G11C 11/5692](#); } erasable programmable read-only memories [G11C 16/00](#); coding, decoding or code conversion, in general [H03M](#); {combination of ROM and RAM [G11C 11/005](#), [G11C 14/00](#); for electrical control of combustion engines [F02D 41/2406](#)})**
- 17/005 . . . {with a storage element common to a large number of data, e.g. perforated card ([G11C 17/02](#), [G11C 17/04](#) take precedence)}
- 17/02 . . . using magnetic or induction elements ([G11C 17/14](#) takes precedence)
- 17/04 . . . using capacitive elements ([G11C 17/06](#), [G11C 17/14](#) take precedence)
- 17/06 . . . using diode elements ([G11C 17/14](#) takes precedence)
- 17/08 . . . using semiconductor devices, e.g. bipolar elements ([G11C 17/06](#), [G11C 17/14](#) take precedence)
- 17/10 . . . in which contents are determined during manufacturing by a predetermined arrangement of coupling elements, e.g. mask-programmable ROM
- 17/12 . . . using field-effect devices
- 17/123 {comprising cells having several storage transistors connected in series}
- 17/126 {Virtual ground arrays}
- 17/14 . . . in which contents are determined by selectively establishing, breaking or modifying connecting links by permanently altering the state of coupling elements, e.g. PROM
- 17/143 . . . {using laser-fusible links}
- 17/146 . . . {Write once memory, i.e. allowing changing of memory content by writing additional bits}
- 17/16 . . . using electrically-fusible links
- 17/165 . . . {Memory cells which are electrically programmed to cause a change in resistance, e.g. to permit multiple resistance steps to be programmed rather than conduct to or from non-conduct change of fuses and antifuses (digital stores using resistance random access memory elements [G11C 13/0002](#))}
- 17/18 . . . Auxiliary circuits, e.g. for writing into memory (in general [G11C 7/00](#))
- 19/00 Digital stores in which the information is moved stepwise, e.g. shift register (counting chains [H03K 23/00](#)) {stack stores, push-down stores (linear pulse counters [H03K 23/54](#), pulse distributors [H03K 5/15](#), methods and arrangements for shifting data [G06F 5/01](#))}**
- 19/005 . . . {with ferro-electric elements (condensers)}
- 19/02 . . . using magnetic elements ([G11C 19/14](#) takes precedence)
- 19/04 . . . using cores with one aperture or magnetic loop
- 19/06 . . . using structures with a number of apertures or magnetic loops, e.g. transfluxors {laddic}
- 19/08 . . . using thin films in plane structure ({thin magnetic films and apparatus or processes specially adapted for manufacturing or assembling the same [H01F 10/00](#), [H01F 41/14](#))}
- 19/0808 {using magnetic domain propagation}
- 19/0816 {using a rotating or alternating coplanar magnetic field}
- 19/0825 {using a variable perpendicular magnetic field}
- 19/0833 {using magnetic domain interaction}
- 19/0841 {using electric current}
- 19/085 {Generating magnetic fields therefor, e.g. uniform magnetic field for magnetic domain stabilisation (coil construction [H01F 5/00](#); electromagnets [H01F 7/06](#))}
- 19/0858 {Generating, replicating or annihilating magnetic domains (also comprising different types of magnetic domains, e.g. "Hard Bubbles") ([G11C 19/0866](#) takes precedence)}
- 19/0866 {Detecting magnetic domains (measuring or detecting magnetic fields in general [G01R 33/02](#))}
- 19/0875 {Organisation of a plurality of magnetic shift registers ([FIFO \[G06F 5/06\]\(#\)](#); [LIFO \[G06F 7/78\]\(#\)](#))}
- 19/0883 {Means for switching magnetic domains from one path into another path, i.e. transfer switches, swap gates, decoders (logic circuits using magnetic domains [H03K 19/168](#))}
- 19/0891 {using hybrid structure, e.g. ion doped layers}
- 19/10 . . . using thin films on rods; with twistors
- 19/12 . . . using non-linear reactive devices in resonant circuits, {e.g. parametrons; magnetic amplifiers with overcritical feedback}
- 19/14 . . . using magnetic elements in combination with active elements, e.g. discharge tubes, semiconductor elements ({contains no documents, see provisionally [G11C 19/02](#) - [G11C 19/10](#))}
- 19/18 . . . using capacitors as main elements of the stages {(if capacitors are used as auxiliary stage in between main stages with other elements, the latter take precedence; [G11C 19/005](#) takes precedence)}

- 19/182 . . {in combination with semiconductor elements, e.g. bipolar transistors, diodes}
- 19/184 . . . {with field-effect transistors, e.g. MOS-FET}
- 19/186 {using only one transistor per capacitor, e.g. bucket brigade shift register}
- 19/188 . . . {Organisation of a multiplicity of shift registers, e.g. regeneration, timing, input-output circuits ([FIFO G06F 5/06](#); [LIFO G06F 7/78](#))}
- 19/20 . using discharge tubes ([G11C 19/14](#) takes precedence)
- 19/202 . . {with vacuum tubes ([G11C 19/207](#) takes precedence)}
- 19/205 . . {with gas-filled tubes ([G11C 19/207](#) takes precedence)}
- 19/207 . . {with counting tubes}
- 19/28 . using semiconductor elements ([G11C 19/14](#) takes precedence)
- 19/282 . . {with charge storage in a depletion layer, i.e. charge coupled devices (C.C.D.)}
- 19/285 . . . {Peripheral circuits, e.g. for writing into the first stage; for reading-out of the last stage}
- 19/287 . . {Organisation of a multiplicity of shift registers ([FIFO G06F 5/06](#); [LIFO G06F 7/78](#))}
- 19/30 . using opto-electronic devices, i.e. light emitting and photoelectric devices electrically or optically coupled
- 19/32 . using super-conductive elements
- 19/34 . using storage elements with more than two stable states represented by steps, e.g. of voltage, current, phase, frequency {(in RAM multistable cells [G11C 11/56](#); in capacitive analog stores [G11C 27/04](#))}
- 19/36 . . using {multistable} semiconductor elements
- 19/38 . two-dimensional, e.g. horizontal and vertical shift registers
- 21/00 Digital stores in which the information circulates {continuously} (stepwise [G11C 19/00](#))**
- 21/005 . {using electrical delay line (construction of such lines [H03H 7/30](#), [H03H 11/26](#))}
- 21/02 . using electromechanical delay lines, e.g. using a mercury tank {(construction of such lines [H03H 9/00](#))}
- 21/023 . . {using piezo-electric transducers, e.g. mercury tank}
- 21/026 . . {using magnetostriction transducers, e.g. nickel delay line}
- 23/00 Digital stores characterised by movement of mechanical parts to effect storage, e.g. using balls; Storage elements therefor (storing by actuating contacts [G11C 11/50](#))**
- 25/00 Digital stores characterised by the use of flowing media; Storage elements therefor {(multiple fluid-circuit element arrangements for performing digital operations [F15C 1/12](#))}**
- 27/00 Electric analogue stores, e.g. for storing instantaneous values {(integrating circuits acting as stores [G06G 7/18](#); pulse counters with step by step integration and static storage [H03K 25/00](#))}**
- 27/005 . {with non-volatile charge storage, e.g. on floating gate or MNOS}
- 27/02 . Sample-and-hold arrangements ([G11C 27/04](#) takes precedence; sampling electrical signals, in general [H03K](#))
- 27/022 . . {using a magnetic memory element}
- 27/024 . . {using a capacitive memory element ([G11C 27/04](#) takes precedence)}
- 27/026 . . . {associated with an amplifier ([G11C 27/028](#) takes precedence)}
- 27/028 . . . {Current mode circuits, e.g. switched current memories}
- 27/04 . Shift registers (charge coupled devices [per se](#) [H01L 29/76](#))
- 29/00 Checking stores for correct operation; {Subsequent repair}; Testing stores during standby or offline operation {(testing of electronic circuits in general [G01R 31/28](#); error detection or error correction in computer memories during normal operation [G06F 11/1008](#), [G06F 11/1666](#); testing of computers during standby [G06F 11/22](#))}**
- 29/003 . {in serial memories}
- 29/006 . {at wafer scale level, i.e. WSI (for test and configuration during manufacture [H01L 22/00](#))}
- 29/02 . Detection or location of defective auxiliary circuits, e.g. defective refresh counters
- 29/021 . . {in voltage or current generators}
- 29/022 . . {in I/O circuitry}
- 29/023 . . {in clock generator or timing circuitry}
- 29/024 . . {in decoders}
- 29/025 . . {in signal lines}
- 29/026 . . {in sense amplifiers}
- 29/027 . . {in fuses}
- 29/028 . . {with adaption or trimming of parameters}
- 29/04 . Detection or location of defective memory elements, {e.g. cell construction details, timing of test signals}
- 2029/0401 . . {in embedded memories}
- 2029/0403 . . {during or with feedback to manufacture}
- 2029/0405 . . {comprising complete test loop}
- 2029/0407 . . {on power on}
- 2029/0409 . . {Online test}
- 2029/0411 . . {Online error correction}
- 29/06 . Acceleration testing
- 29/08 . Functional testing, e.g. testing during refresh, power-on self testing [POST] or distributed testing
- 29/10 . . . Test algorithms, e.g. memory scan (MScan) algorithms; Test patterns, e.g. checkerboard patterns
- 29/12 . . . Built-in arrangements for testing, e.g. built-in self testing [BIST] {or interconnection details}
- 29/12005 {comprising voltage or current generators}
- 29/1201 {comprising I/O circuitry}
- 29/12015 {comprising clock generation or timing circuitry}
- 2029/1202 {Word line control}
- 2029/1204 {Bit line control}
- 2029/1206 {Location of test circuitry on chip or wafer}
- 2029/1208 {Error catch memory}
- 29/14 Implementation of control logic, e.g. test mode decoders
- 29/16 using microprogrammed units, e.g. state machines

29/18 Address generation devices; Devices for accessing memories, e.g. details of addressing circuits	29/70	. {Masking faults in memories by using spares or by reconfiguring}
2029/1802 {Address decoder}	29/702	. . {by replacing auxiliary circuits, e.g. spare voltage generators, decoders or sense amplifiers, to be used instead of defective ones}
2029/1804 {Manipulation of word size}	29/72	. . {with optimized replacement algorithms}
2029/1806 {Address conversion or mapping, i.e. logical to physical address}	29/74	. . {using duplex memories, i.e. using dual copies}
29/20 using counters or linear-feedback shift registers [LFSR]	29/76	. . {using address translation or modifications}
29/22 Accessing serial memories	29/765	. . . {in solid state disks}
29/24 Accessing extra cells, e.g. dummy cells or redundant cells	29/78	. . {using programmable devices}
29/26 Accessing multiple arrays (G11C 29/24 takes precedence)	29/781	. . . {combined in a redundant decoder}
2029/2602 {Concurrent test}	29/783	. . . {with refresh of replacement cells, e.g. in DRAMs}
29/28 Dependent multiple arrays, e.g. multi-bit arrays	29/785	. . . {with redundancy programming schemes}
29/30 Accessing single arrays	29/787 {using a fuse hierarchy (for memories using fuses in general G11C 17/16)}
29/32 Serial access; Scan testing	29/789 {using non-volatile cells or latches (erasable programmable memory cells in general G11C 16/00)}
2029/3202 {Scan chain}	29/80	. . . {with improved layout}
29/34 Accessing multiple bits simultaneously	29/802 {by encoding redundancy signals}
29/36 Data generation devices, e.g. data inverters	29/804 {to prevent clustered faults}
2029/3602 {Pattern generator}	29/806 {by reducing size of decoders}
29/38 Response verification devices	29/808 {using a flexible replacement scheme}
29/40 using compression techniques	29/81 {using a hierarchical redundancy scheme}
2029/4002 {Comparison of products, i.e. test results of chips or with golden chip}	29/812 {using a reduced amount of fuses}
29/42 using error correcting codes [ECC] or parity check	29/814 {for optimized yield}
29/44 Indication or identification of errors, e.g. for repair	29/816 {for an application-specific layout}
29/4401 {for self repair}	29/818 {for dual-port memories}
2029/4402 {Internal storage of test result, quality data, chip identification, repair information}	29/82 {for EEPROMs}
29/46 Test trigger logic	29/822 {for read only memories}
29/48	. . . Arrangements in static stores specially adapted for testing by means external to the store, e.g. using direct memory access [DMA] or using auxiliary access paths (external testing equipment G11C 29/56)	29/824 {for synchronous memories}
29/50	. . Marginal testing, e.g. race, voltage or current testing	29/83	. . . {with reduced power consumption}
29/50004	. . . {of threshold voltage}	29/832 {with disconnection of faulty elements}
29/50008	. . . {of impedance}	29/835	. . . {with roll call arrangements for redundant substitutions}
29/50012	. . . {of timing}	29/838	. . . {with substitution of defective spares}
29/50016	. . . {of retention}	29/84	. . . {with improved access time or stability}
2029/5002	. . . {Characteristic}	29/842 {by introducing a delay in a signal path}
2029/5004	. . . {Voltage}	29/844 {by splitting the decoders in stages}
2029/5006	. . . {Current}	29/846 {by choosing redundant lines at an output stage}
29/52	. Protection of memory contents; Detection of errors in memory contents	29/848 {by adjacent switching}
29/54	. Arrangements for designing test circuits, e.g. design for test [DFT] tools	29/86	. . {in serial access memories, e.g. shift registers, CCDs, bubble memories}
29/56	. External testing equipment for static stores, e.g. automatic test equipment [ATE]; Interfaces therefor	29/88	. . {with partially good memories}
29/56004	. . {Pattern generation}	29/883	. . . {using a single defective memory device with reduced capacity, e.g. half capacity}
29/56008	. . {Error analysis, representation of errors}	29/886	. . . {combining plural defective memory devices to provide a contiguous address range, e.g. one device supplies working blocks to replace defective blocks in another device}
29/56012	. . {Timing aspects, clock generation, synchronisation}	99/00	Subject matter not provided for in other groups of this subclass
29/56016	. . {Apparatus features}	2207/00	Indexing scheme relating to arrangements for writing information into, or reading information out from, a digital store
2029/5602	. . {Interface to device under test}	2207/002	. Isolation gates, i.e. gates coupling bit lines to the sense amplifier
2029/5604	. . {Display of error information}	2207/005	. Transfer gates, i.e. gates coupling the sense amplifier output to data lines, I/O lines or global bit lines
2029/5606	. . {Error catch memory}		

- 2207/007 . . Register arrays
- 2207/06 . . Sense amplifier related aspects
- 2207/061 . . . Sense amplifier enabled by a address transition detection related control signal
- 2207/063 . . . Current sense amplifiers
- 2207/065 . . . Sense amplifier drivers
- 2207/066 . . . Frequency reading type sense amplifier
- 2207/068 . . . Integrator type sense amplifier
- 2207/10 . . Aspects relating to interfaces of memory device to external buses
- 2207/101 . . . Analog or multilevel bus
- 2207/102 . . . Compression or decompression of data before storage
- 2207/104 . . . Embedded memory devices, e.g. memories with a processing device on the same die or ASIC memory designs
- 2207/105 . . . Aspects related to pads, pins or terminals
- 2207/107 . . . Serial-parallel conversion of data or prefetch
- 2207/108 . . . Wide data ports
- 2207/12 . . Equalization of bit lines
- 2207/16 . . Solid state audio ([deprecated, only for historical reasons, G06F 3/16, G11B](#))
- 2207/22 . . Control and timing of internal memory operations
- 2207/2209 . . . Concurrent read and write ([for multi-port memory G11C 7/1075](#))
- 2207/2218 . . . Late write
- 2207/2227 . . . Standby or low power modes
- 2207/2236 . . . Copy
- 2207/2245 . . . Memory devices with an internal cache buffer
- 2207/2254 . . . Calibration
- 2207/2263 . . . Write conditionally, e.g. only if new data and old data differ
- 2207/2272 . . . Latency related aspects
- 2207/2281 . . . Timing of a read operation ([sense amplifier timing G11C 7/06, G11C 7/08](#))
- 2207/229 . . . Timing of a write operation ([sense amplifier timing G11C 7/06, G11C 7/08](#))
- 2211/00 Indexing scheme relating to digital stores characterized by the use of particular electric or magnetic storage elements; Storage elements therefor**
- 2211/401 . . Indexing scheme relating to cells needing refreshing or charge regeneration, i.e. dynamic cells
- 2211/4013 . . . Memory devices with multiple cells per bit, e.g. twin-cells
- 2211/4016 . . . Memory devices with silicon-on-insulator cells
- 2211/406 . . . Refreshing of dynamic cells
- 2211/4061 Calibration or ate or cycle tuning
- 2211/4062 Parity or ECC in refresh operations
- 2211/4063 Interleaved refresh operations
- 2211/4065 Low level details of refresh operations
- 2211/4066 Pseudo-SRAMs
- 2211/4067 Refresh in standby or low power modes
- 2211/4068 Voltage or leakage in refresh operations
- 2211/56 . . Indexing scheme relating to [G11C 11/56](#) and sub-groups for features not covered by these groups
- 2211/561 . . . Multilevel memory cell aspects
- 2211/5611 Multilevel memory cell with more than one control gate
- 2211/5612 Multilevel memory cell with more than one floating gate
- 2211/5613 Multilevel memory cell with additional gates, not being floating or control gates
- 2211/5614 Multilevel memory cell comprising negative resistance, quantum tunneling or resonance tunneling elements
- 2211/5615 Multilevel magnetic memory cell using non-magnetic non-conducting interlayer, e.g. MTJ
- 2211/5616 Multilevel magnetic memory cell using non-magnetic conducting interlayer, e.g. GMR, SV, PSV
- 2211/5617 Multilevel ROM cell programmed by source, drain or gate contacting
- 2211/562 . . . Multilevel memory programming aspects
- 2211/5621 Multilevel programming verification
- 2211/5622 Concurrent multilevel programming of more than one cell
- 2211/5623 Concurrent multilevel programming and reading
- 2211/5624 Concurrent multilevel programming and programming verification
- 2211/5625 Self-converging multilevel programming
- 2211/563 . . . Multilevel memory reading aspects
- 2211/5631 Concurrent multilevel reading of more than one cell
- 2211/5632 Multilevel reading using successive approximation
- 2211/5633 Mixed concurrent serial multilevel reading
- 2211/5634 Reference cells
- 2211/564 . . . Miscellaneous aspects
- 2211/5641 Multilevel memory having cells with different number of storage levels
- 2211/5642 Multilevel memory with buffers, latches, registers at input or output
- 2211/5643 Multilevel memory comprising cache storage devices
- 2211/5644 Multilevel memory comprising counting devices
- 2211/5645 Multilevel memory with current-mirror arrangements
- 2211/5646 Multilevel memory with flag bits, e.g. for showing that a "first page" of a word line is programmed but not a "second page"
- 2211/5647 Multilevel memory with bit inversion arrangement
- 2211/5648 Multilevel memory programming, reading or erasing operations wherein the order or sequence of the operations is relevant
- 2211/5649 Multilevel memory with plate line or layer, e.g. in order to lower programming voltages
- 2211/565 Multilevel memory comprising elements in triple well structure
- 2213/00 Indexing scheme relating to [G11C 13/00](#) for features not covered by this group**
- 2213/10 . . . Resistive cells; Technology aspects
- 2213/11 . . . Metal ion trapping, i.e. using memory material including cavities, pores or spaces in form of tunnels or channels wherein metal ions can be trapped but do not react and form an electro-deposit creating filaments or dendrites
- 2213/12 . . . Non-metal ion trapping, i.e. using memory material trapping non-metal ions given by the electrode or another layer during a write operation, e.g. trapping, doping

- 2213/13 . . Dissociation, i.e. using memory material including molecules which, during a write operation, are dissociated in ions which migrate further in the memory material
- 2213/14 . . Use of different molecule structures as storage states, e.g. part of molecule being rotated
- 2213/15 . . Current-voltage curve
- 2213/16 . . Memory cell being a nanotube, e.g. suspended nanotube
- 2213/17 . . Memory cell being a nanowire transistor
- 2213/18 . . Memory cell being a nanowire having RADIAL composition
- 2213/19 . . Memory cell comprising at least a nanowire and only two terminals
- 2213/30 . Resistive cell, memory material aspects
- 2213/31 . . Material having complex metal oxide, e.g. perovskite structure
- 2213/32 . . Material having simple binary metal oxide structure
- 2213/33 . . Material including silicon
- 2213/34 . . Material includes an oxide or a nitride
- 2213/35 . . Material including carbon, e.g. graphite, grapheme
- 2213/50 . Resistive cell structure aspects
- 2213/51 . . Structure including a barrier layer preventing or limiting migration, diffusion of ions or charges or formation of electrolytes near an electrode
- 2213/52 . . Structure characterized by the electrode material, shape, etc.
- 2213/53 . . Structure wherein the resistive material being in a transistor, e.g. gate
- 2213/54 . . Structure including a tunneling barrier layer, the memory effect implying the modification of tunnel barrier conductivity
- 2213/55 . . Structure including two electrodes, a memory active layer and at least two other layers which can be a passive or source or reservoir layer or a less doped memory active layer
- 2213/56 . . Structure including two electrodes, a memory active layer and a so called passive or source or reservoir layer which is NOT an electrode, wherein the passive or source or reservoir layer is a source of ions which migrate afterwards in the memory active layer to be only trapped there, to form conductive filaments there or to react with the material of the memory active layer in redox way
- 2213/70 . Resistive array aspects
- 2213/71 . . Three dimensional array
- 2213/72 . . Array wherein the access device being a diode
- 2213/73 . . Array where access device function, e.g. diode function, being merged with memorizing function of memory element
- 2213/74 . . Array wherein each memory cell has more than one access device
- 2213/75 . . Array having a NAND structure comprising, for example, memory cells in series or memory elements in series, a memory element being a memory cell in parallel with an access transistor
- 2213/76 . . Array using an access device for each cell which being not a transistor and not a diode
- 2213/77 . . Array wherein the memory element being directly connected to the bit lines and word lines without any access device being used
- 2213/78 . . Array wherein the memory cells of a group share an access device, all the memory cells of the group having a common electrode and the access device being not part of a word line or a bit line driver
- 2213/79 . . Array wherein the access device being a transistor
- 2213/80 . . Array wherein the substrate, the cell, the conductors and the access device are all made up of organic materials
- 2213/81 . . Array wherein the array conductors, e.g. word lines, bit lines, are made of nanowires
- 2213/82 . . Array having, for accessing a cell, a word line, a bit line and a plate or source line receiving different potentials
- 2216/00 Indexing scheme relating to [G11C 16/00](#) and subgroups, for features not directly covered by these groups**
- 2216/02 . Structural aspects of erasable programmable read-only memories
- 2216/04 . . Nonvolatile memory cell provided with a separate control gate for erasing the cells, i.e. erase gate, independent of the normal read control gate
- 2216/06 . . Floating gate cells in which the floating gate consists of multiple isolated silicon islands, e.g. nanocrystals
- 2216/08 . . Nonvolatile memory wherein data storage is accomplished by storing relatively few electrons in the storage layer, i.e. single electron memory
- 2216/10 . . Floating gate memory cells with a single polysilicon layer
- 2216/12 . Reading and writing aspects of erasable programmable read-only memories
- 2216/14 . . Circuits or methods to write a page or sector of information simultaneously into a nonvolatile memory, typically a complete row or word line in flash memory
- 2216/16 . . Flash programming of all the cells in an array, sector or block simultaneously
- 2216/18 . . Flash erasure of all the cells in an array, sector or block simultaneously
- 2216/20 . . Suspension of programming or erasing cells in an array in order to read other cells in it
- 2216/22 . . Nonvolatile memory in which reading can be carried out from one memory bank or array whilst a word or sector in another bank or array is being erased or programmed simultaneously
- 2216/24 . . Nonvolatile memory in which programming can be carried out in one memory bank or array whilst a word or sector in another bank or array is being erased simultaneously
- 2216/26 . . Floating gate memory which is adapted to be one-time programmable [OTP], e.g. containing multiple OTP blocks permitting limited update ability
- 2216/28 . . Floating gate memory programmed by reverse programming, e.g. programmed with negative gate voltage and erased with positive gate voltage or programmed with high source or drain voltage and erased with high gate voltage
- 2216/30 . . Reduction of number of input/output pins by using a serial interface to transmit or receive addresses or data, i.e. serial access memory

2229/00 Indexing scheme relating to checking stores for correct operation, subsequent repair or testing stores during standby or offline operation

- 2229/70 . Indexing scheme relating to [G11C 29/70](#), for implementation aspects of redundancy repair
- 2229/72 . . Location of redundancy information
- 2229/723 . . . Redundancy information stored in a part of the memory core to be repaired
- 2229/726 . . . Redundancy information loaded from the outside into the memory
- 2229/74 . . Time at which the repair is done
- 2229/743 . . . After packaging
- 2229/746 . . . Before packaging
- 2229/76 . . Storage technology used for the repair
- 2229/763 . . . E-fuses, e.g. electric fuses or antifuses, floating gate transistors
- 2229/766 . . . Laser fuses