

CPC COOPERATIVE PATENT CLASSIFICATION

F16C SHAFTS; FLEXIBLE SHAFTS; ELEMENTS OR CRANKSHAFT MECHANISMS; ROTARY BODIES OTHER THAN GEARING ELEMENTS; BEARINGS

NOTES

1. In this subclass the following expression is used with the meaning indicated:
 - "rotary bodies other than gearing elements" covers any element which rotates so far as its features are affected only by the fact that it rotates.
2. Attention is drawn to the following places:
 - [A01B 71/04](#) Bearings for agricultural machines
 - [B21B 31/07](#) Adaptation of roll bearings for metal-rolling mills
 - [B61C 17/10](#) Connecting-rods, bearings for driving wheels of railway locomotives
 - [B61F 15/00](#) Axle-boxes for railway vehicles
 - [B62K 21/06](#) Bearings for steering heads
 - [E06B 9/174](#), [E06B 9/50](#) Bearings specially adapted for roller shutters or for roller blinds
 - [E21B 10/22](#) Bearings for drill bits
 - [F01C 21/02](#) Arrangement of bearings in rotary-piston machines or engines
 - [F01D 25/16](#) Arrangement of bearings in non-positive displacement machines or engines
 - [F02C 7/06](#) Arrangement of bearings in gas-turbine plants
 - [G01C 19/16](#) Bearings for gyroscopes
 - [G01D 11/02](#) Bearings or suspensions for moving parts of measuring instruments
 - [G01G 21/02](#) Arrangements of bearings in weighing apparatus
 - [G01R 1/10](#) Arrangements of bearings in instruments for measuring electric variables
 - [G01R 11/12](#) Arrangements of bearings for apparatus for measuring time integral of electric power or current
 - [G02C 5/22](#) Hinges for spectacles
 - [G04B 31/00](#) Bearings for clockwork
 - [H02N 15/00](#) Magnetic levitation devices.

- | | |
|---|---|
| <p>1/00 Flexible shafts (flexible shafts in dental machines for boring or cutting A61C 1/18); Mechanical means for transmitting movement in a flexible sheathing</p> <p>1/02 . for conveying rotary movements</p> <p>1/04 . . Articulated shafts</p> <p>1/06 . . with guiding sheathing, tube or box (F16C 1/04 takes precedence; guiding sheathings F16C 1/26)</p> <p>1/08 . . End connections</p> <p>1/10 . Means for transmitting linear movement in a flexible sheathing, e.g. "Bowden-mechanisms" (guiding-sheathings F16C 1/26)</p> <p>1/101 . . {Intermediate connectors for joining portions of split flexible shafts and/or sheathings}</p> <p>1/102 . . {Arrangements to mount end fittings of the sheathings to support walls or brackets}</p> <p>1/103 . . . {to a hole in the wall or bracket}</p> <p>1/105 . . . {to a slot in the bracket}</p> <p>1/106 . . {Plurality of transmitting means, e.g. two or more parallel "Bowden cables"}</p> <p>1/107 . . {Sealing details}</p> <p>1/108 . . {Reducing or controlling of vibrations, e.g. by resilient damping of noise}</p> <p>1/12 . . Arrangements for transmitting movement to or from the flexible member</p> <p>1/14 . . . Construction of the end-piece of the flexible member; Attachment thereof to the flexible member</p> <p>1/145 {Attachment of the end-piece to the flexible member}</p> <p>1/16 . . . in which the end-piece is guided rectilinearly</p> | <p>1/18 . . . in which the end portion of the flexible member is laid along a curved surface of a pivoted member</p> <p>1/20 . . Construction of flexible members moved to and fro in the sheathing</p> <p>1/205 . . . {Details of the outer surface of the flexible member, e.g. coatings}</p> <p>1/22 . . Adjusting; Compensating length</p> <p>1/223 . . . {by adjusting the effective length of the flexible member}</p> <p>1/226 . . . {by adjusting the effective length of the sheathing}</p> <p>1/24 . Lubrication; Lubricating equipment</p> <p>1/26 . Construction of guiding-sheathings or guiding-tubes</p> <p>1/262 . . {End fittings; Attachment thereof to the sheathing or tube}</p> <p>1/265 . . . {with a swivel tube connected to the end-fitting of a sheathing, e.g. with a spherical joint}</p> <p>1/267 . . {Details of the inner surface of the sheathing or tube, e.g. coatings}</p> <p>1/28 . . with built in bearings {, e.g. sheathing with rolling elements between the sheathing and the core element}</p> <p>3/00 Shafts (flexible shafts F16C 1/00; marine propeller shafts, paddle wheel shafts B63H 23/34); Axles; Cranks; eccentrics</p> <p>3/02 . Shafts; Axles</p> <p>3/023 . . {made of several parts, e.g. by welding}</p> <p>3/026 . . {Shafts made of fibre reinforced resin}</p> <p>3/03 . . telescopic (axially displaceable couplings F16D 3/06)</p> <p>3/035 . . . with built-in bearings</p> |
|---|---|

- 3/04 . Crankshafts, eccentric-shafts; Cranks, eccentrics
- 3/06 . . Crankshafts
- 3/08 . . . made in one piece (features relating to lubrication [F16C 3/14](#), to cooling [F16C 3/16](#))
- 3/10 . . . assembled of several parts, e.g. by welding {by crimping}
- 3/12 releasably connected
- 3/14 . . . Features relating to lubrication
- 3/16 . . . Features relating to cooling
- 3/18 . . Eccentric-shafts
- 3/20 . . Shape of crankshafts or eccentric-shafts having regard to balancing
- 3/22 . . Cranks; Eccentrics (constructional features of crank-pins [F16C 11/02](#))
- 3/24 . . . with return cranks, i.e. a second crank carried by the crank-pin
- 3/26 . . . Elastic crank-webs; Resiliently-mounted crank-pins
- 3/28 . . . Adjustable cranks or eccentrics
- 3/30 . . . with arrangements for overcoming dead-centres
- 5/00 Crossheads; Constructions of connecting-rod heads or piston-rod connections rigid with crossheads (piston-rods, i.e. rods rigidly connected to the piston, [F16J 7/00](#))**
- 7/00 Connecting-rods or like links pivoted at both ends (coupling-rods for locomotive driving-wheels [B61C 17/10](#)); Construction of connecting-rod heads (heads rigid with crossheads [F16C 5/00](#))**
- 7/02 . Constructions of connecting-rods with constant length
- 7/023 . . {for piston engines, pumps or the like}
- 7/026 . . {made of fibre reinforced resin}
- 7/04 . with elastic intermediate part of fluid cushion
- 7/06 . Adjustable connecting-rods
- 7/08 . made from sheet metal
- 9/00 Bearings for crankshafts or connecting-rods; Attachment of connecting-rods (lubrication of connecting-rods in connection with crankshafts [F16C 3/14](#); connections to crossheads [F16C 5/00](#); to pistons [F16J 1/14](#))**
- 9/02 . Crankshaft bearings
- 9/03 . . Arrangements for adjusting play
- 9/04 . Connecting-rod bearings; Attachments thereof
- 9/045 . . {the bearing cap of the connecting rod being split by fracturing}
- 9/06 . . Arrangements for adjusting play in bearings, operating either automatically or not
- 11/00 Pivots; Pivotal connections (arrangements of steering linkage connections [B62D 7/16](#))**
- 11/02 . Trunnions; Crank-pins (fastening crank-pins to webs, crank-pins integral with cranks [F16C 3/06](#), [F16C 3/22](#))
- 11/04 . Pivotal connections (hinges for doors, windows or wings [E05D](#))
- 11/045 . . {with at least a pair of arms pivoting relatively to at least one other arm, all arms being mounted on one pin (crank-pins [F16C 11/02](#))}
- 11/06 . . Ball-joints; Other joints having more than one degree of angular freedom, i.e. universal joints (universal joints in which flexibility is produced by means of pivots or sliding or rolling connecting parts [F16D 3/16](#))
- 11/0604 . . . {Construction of the male part}
- 11/0609 {made from two or more parts}
- 11/0614 . . . {the female part of the joint being open on two sides}
- 11/0619 . . . {the female part comprising a blind socket receiving the male part}
- 11/0623 {Construction or details of the socket member}
- 11/0628 {with linings}
- 11/0633 {the linings being made of plastics}
- 11/0638 {characterised by geometrical details}
- 11/0642 {Special features of the plug or cover on the blind end of the socket}
- 11/0647 {Special features relating to adjustment for wear or play; Wear indicators}
- 11/0652 {combined with a damper other than elastic linings}
- 11/0657 {the socket member being mainly made of plastics}
- 11/0661 . . . {the two co-operative parts each having both convex and concave interfaces}
- 11/0666 . . . {Sealing means between the socket and the inner member shaft}
- 11/0671 {allowing operative relative movement of joint parts due to flexing of the sealing means}
- 11/0676 {allowing operational relative movement of joint parts due to sliding between parts of the sealing means}
- 11/068 . . . {Special features relating to lubrication}
- 11/0685 . . . {Manufacture of ball-joints and parts thereof, e.g. assembly of ball-joints}
- 11/069 {with at least one separate part to retain the ball member in the socket; Quick-release systems}
- 11/0695 . . . {Mounting of ball-joints, e.g. fixing them to a connecting rod}
- 11/08 . . . with resilient bearings
- 11/083 {by means of parts of rubber or like materials}
- 11/086 {with an elastomeric member in the blind end of a socket}
- 11/10 . . Arrangements for locking
- 11/103 . . . {frictionally clamped}
- 11/106 {for ball joints}
- 11/12 . . incorporating flexible connections, e.g. leaf springs
- 13/00 Rolls, drums, discs, or the like (guide rollers in feeding webs [B65H 27/00](#); calender rolls, bearings therefor [D21G 1/02](#); rotary drums or rollers for heat-exchange or heat-transfer apparatus [F28F 5/02](#); special adaptations, see the relevant classes); Bearings or mountings therefor**
- 13/003 . {Bowed or curved rolls (rollers with a bowed axis as tentering devices for tensioning, smoothing or guiding webs [B65H 23/0258](#))}
- 13/006 . {Guiding rollers, wheels or the like, formed by or on the outer element of a single bearing or bearing unit, e.g. two adjacent bearings, whose ratio of length to diameter is generally less than one}
- 13/02 . Bearings
- 13/022 . . {supporting a hollow roll mantle rotating with respect to a yoke or axle}

- 13/024 . . . {adjustable for positioning, e.g. radial movable bearings for controlling the deflection along the length of the roll mantle}
- 13/026 {by fluid pressure}
- 13/028 {with a plurality of supports along the length of the roll mantle, e.g. hydraulic jacks}
- 13/04 . . Bearings with only partial enclosure of the member to be borne; Bearings with local support at two or more points
- 13/06 . . self-adjusting
- 15/00 Construction of rotary bodies to resist centrifugal force (flywheels, correction weights [F16F 15/30](#), [F16F 15/32](#))**

Bearings for rotary parts ([F16C 9/00](#), [F16C 13/02](#) take precedence; allowing for linear movement also [F16C 31/00](#))

- 17/00 Sliding-contact bearings for exclusively rotary movement** ([F16C 32/06](#) takes precedence; adjustable bearings [F16C 23/00](#), [F16C 25/00](#))
- 17/02 . for radial load only
- 17/022 . . {with a pair of essentially semicircular bearing sleeves}
- 17/024 . . {with flexible leaves to create hydrodynamic wedge, e.g. radial foil bearings}
- 17/026 . . {with helical grooves in the bearing surface to generate hydrodynamic pressure, e.g. heringbone grooves}
- 17/028 . . {with fixed wedges to generate hydrodynamic pressure, e.g. multi-lobe bearings}
- 17/03 . . with tiltably-supported segments, e.g. Michell bearings {hydrostatic bearings with tiltably supported bearing pads [F16C 32/0666](#); made from a plurality of rods [F16C 33/26](#); with flexible leaves [F16C 17/024](#); hydrodynamic bearings with chambers [F16C 33/1075](#)}
- 17/035 . . . {the segments being integrally formed with, or rigidly fixed to, a support-element}
- 17/04 . for axial load only
- 17/042 . . {with flexible leaves to create hydrodynamic wedge, e.g. axial foil bearings}
- 17/045 . . {with grooves in the bearing surface to generate hydrodynamic pressure, e.g. spiral groove thrust bearings}
- 17/047 . . {with fixed wedges to generate hydrodynamic pressure}
- 17/06 . . with tiltably-supported segments, e.g. Michell bearings {(with flexible leaves [F16C 17/042](#); hydrostatic [F16C 32/0666](#))}
- 17/065 . . . {the segments being integrally formed with, or rigidly fixed to, a support-element}
- 17/08 . . for supporting the end face of a shaft or other member, e.g. footstep bearings
- 17/10 . for both radial and axial load
- 17/102 . . {with grooves in the bearing surface to generate hydrodynamic pressure}
- 17/105 . . . {with at least one bearing surface providing angular contact, e.g. conical or spherical bearing surfaces}
- 17/107 . . . {with at least one surface for radial load and at least one surface for axial load}
- 17/12 . characterised by features not related to the direction of the load

- 17/14 . . specially adapted for operating in water
- 17/18 . . with floating brasses or brushing, rotatable at a reduced speed {([F16C 17/03](#), [F16C 17/06](#) take precedence)}
- 17/20 . . with emergency supports or bearings
- 17/22 . . with arrangements compensating for thermal expansion
- 17/24 . . with devices affected by abnormal or undesired positions, e.g. for preventing overheating, for safety
- 17/243 . . . {related to temperature and heat, e.g. for preventing overheating}
- 17/246 . . . {related to wear, e.g. sensors for measuring wear}
- 17/26 . Systems consisting of a plurality of sliding-contact bearings

19/00 Bearings with rolling contact, for exclusively rotary movement (adjustable bearings [F16C 23/00](#), [F16C 25/00](#); {electrically insulating bearings [H02K 5/173](#)})

- 19/02 . with bearing balls essentially of the same size in one or more circular rows
- 19/04 . . for radial load mainly
- 19/06 . . . with a single row or balls
- 19/08 . . . with two or more rows of balls
- 19/10 . . for axial load mainly
- 19/12 . . . for supporting the end face of a shaft or other member, e.g. footstep bearings
- 19/14 . . for both radial and axial load
- 19/16 . . . with a single row of balls
- 19/163 {with angular contact}
- 19/166 {Four-point-contact ball bearings}
- 19/18 . . . with two or more rows of balls
- 19/181 {with angular contact}
- 19/182 {in tandem arrangement}
- 19/183 {with two rows at opposite angles}
- 19/184 {in O-arrangement}
- 19/185 {with two raceways provided integrally on a part other than a race ring, e.g. a shaft or housing}
- 19/186 {with three raceways provided integrally on parts other than race rings, e.g. third generation hubs}
- 19/187 {with all four raceways integrated on parts other than race rings, e.g. fourth generation hubs}
- 19/188 {with at least one row for radial load in combination with at least one row for axial load}
- 19/20 . . with loose spacing bodies, e.g. balls, between the bearing balls
- 19/22 . with bearing rollers essentially of the same size in one or more circular rows, e.g. needle bearings
- 19/225 . . {Details of the ribs supporting the end of the rollers}
- 19/24 . . for radial load mainly
- 19/26 . . . with a single row of rollers
- 19/28 . . . with two or more rows of rollers
- 19/30 . . for axial load mainly
- 19/305 . . . {consisting of rollers held in a cage}
- 19/32 . . . for supporting the end face of a shaft or other member, e.g. footstep bearings
- 19/34 . . for both radial and axial load

- 19/36 . . . with a single row of rollers
- 19/361 {with cylindrical rollers}
- 19/362 {the rollers being crossed within the single row}
- 19/364 {with tapered rollers, i.e. rollers having essentially the shape of a truncated cone}
- 19/38 . . . with two or more rows of rollers
- 19/381 {with at least one row for radial load in combination with at least one row for axial load}
- 19/383 {with tapered rollers, i.e. rollers having essentially the shape of a truncated cone}
- 19/385 {with two rows, i.e. double-row tapered roller bearings}
- 19/386 {in O-arrangement}
- 19/388 {with four rows, i.e. four row tapered roller bearings}
- 19/40 . . with loose spacing bodies between the rollers
- 19/44 . . Needle bearings
- 19/46 . . . with one row or needles
- 19/463 {consisting of needle rollers held in a cage, i.e. subunit without race rings}
- 19/466 {comprising needle rollers and an outer ring, i.e. subunit without inner ring}
- 19/48 . . . with two or more rows of needles
- 19/49 . Bearings with both balls and rollers
- 19/492 . . {with two or more rows with angular contact}
- 19/495 . . . {with two rows}
- 19/497 {in O-arrangement}
- 19/50 . Other types of ball or roller bearings
- 19/502 . . {with rolling elements in rows not forming a full circle}
- 19/505 . . {with the diameter of the rolling elements of one row differing from the diameter of those of another row}
- 19/507 . . {with rolling elements journaled in one of the moving parts, e.g. stationary rollers to support a rotating part}
- 19/52 . with devices affected by abnormal or undesired conditions
- 19/522 . . {related to load on the bearing, e.g. bearings with load sensors or means to protect the bearing against overload}
- 19/525 . . {related to temperature and heat, e.g. insulation}
- 19/527 . . {related to vibration and noise}
- 19/54 . Systems consisting of a plurality of bearings with rolling friction ([spindle bearings F16C 35/08](#))
- 19/541 . . {Systems consisting of juxtaposed rolling bearings including at least one angular contact bearing}
- 19/542 . . . {with two rolling bearings with angular contact}
- 19/543 {in O-arrangement}
- 19/545 . . {Systems comprising at least one rolling bearing for radial load in combination with at least one rolling bearing for axial load}
- 19/546 . . {Systems with spaced apart rolling bearings including at least one angular contact bearing}
- 19/547 . . . {with two angular contact rolling bearings}
- 19/548 {in O-arrangement}
- 19/55 . . with intermediate floating {or independently-driven} rings rotating at reduced speed {or with other differential ball or roller bearings}
- 19/56 . . in which the rolling bodies of one bearing differ in diameter from those of another
- 21/00** **Combinations of sliding-contact bearings with ball or roller bearings, for exclusively rotary movement** ([F16C 17/24](#), [F16C 19/52](#) take precedence)
- 21/005 . {the external zone of a bearing with rolling members, e.g. needles, being cup-shaped, with or without a separate thrust-bearing disc or ring, e.g. for universal joints ([seals F16C 33/72](#), [F16D 3/38](#))}
- 23/00** **Bearings for exclusively rotary movement adjustable for aligning or positioning** ([F16C 27/00](#) takes precedence; {hydrostatic bearings [F16C 32/067](#)})
- 23/02 . Sliding-contact bearings
- 23/04 . . self-adjusting
- 23/041 . . . {with edge relief}
- 23/043 . . . {with spherical surfaces, e.g. spherical plain bearings}
- 23/045 {for radial load mainly, e.g. radial spherical plain bearings}
- 23/046 {with split outer rings}
- 23/048 {for axial load mainly}
- 23/06 . Ball or roller bearings
- 23/08 . . self-adjusting
- 23/082 . . . {by means of at least one substantially spherical surface}
- 23/084 {sliding on a complementary spherical surface}
- 23/086 {forming a track for rolling elements}
- 23/088 . . . {by means of crowning}
- 23/10 . Bearings, parts of which are eccentrically adjustable with respect to each other
- 25/00** **Bearings for exclusively rotary movement adjustable for wear or play** ([F16C 27/00](#) takes precedence)
- 25/02 . Sliding-contact bearings
- 25/04 . . self-adjusting
- 25/045 . . . {with magnetic means to preload the bearing}
- 25/06 . Ball or roller bearings
- 25/08 . . self-adjusting
- 25/083 . . . {with resilient means acting axially on a race ring to preload the bearing}
- 25/086 . . . {with magnetic means to preload the bearing}
- 27/00** **Elastic or yielding bearings or bearing supports, for exclusively rotary movement (shock-damping bearings for watches or clocks [G04B 31/02](#))**
- 27/02 . Sliding-contact bearings
- 27/04 . Ball or roller bearings, e.g. with resilient rolling bodies
- 27/045 . . {with a fluid film, e.g. squeeze film damping}
- 27/06 . by means of parts of rubber or like materials ([F16C 27/08](#) takes precedence; with sliding surfaces of rubber or synthetic rubber [F16C 33/22](#))
- 27/063 . . {Sliding contact bearings}
- 27/066 . . {Ball or roller bearings}
- 27/08 . primarily for axial load, e.g. for vertically-arranged shafts

Other bearings {(for bridges [E01D 19/04](#))}**29/00 Bearings for parts moving only linearly**

([F16C 32/06](#) takes precedence; incorporated in flexible shafts [F16C 1/28](#) {parts of bearings in general and special methods for making bearings or parts thereof in general [F16C 33/00](#)})

- 29/001 . {adjustable for alignment or positioning}
- 29/002 . {Elastic or yielding linear bearings or bearing supports}
- 29/004 . {Fixing of a carriage or rail, e.g. rigid mounting to a support structure or a movable part}
- 29/005 . {Guide rails or tracks for a linear bearing, i.e. adapted for movement of a carriage or bearing body there along}
- 29/007 . {Hybrid linear bearings, i.e. including more than one bearing type, e.g. sliding contact bearings as well as rolling contact bearings}
- 29/008 . {Systems with a plurality of bearings, e.g. four carriages supporting a slide on two parallel rails}
- 29/02 . Sliding-contact bearings
- 29/025 . . {Hydrostatic or aerostatic (this type of bearing for rotary parts [F16C 32/06](#))}
- 29/04 . Ball or roller bearings
- 29/041 . . {having rollers crossed within a row}
- 29/043 . . {with two massive rectangular rails having facing grooves}
- 29/045 . . {having rolling elements journaled in one of the moving parts}
- 29/046 . . . {with balls journaled in pockets}
- 29/048 . . {with thin walled races, e.g. tracks of sheet metal}
- 29/06 . . in which the rolling bodies circulate partly without carrying load
- 29/0602 . . . {Details of the bearing body or carriage or parts thereof, e.g. methods for manufacturing or assembly}
- 29/0604 {of the load bearing section}
- 29/0607 {of parts or members for retaining the rolling elements, i.e. members to prevent the rolling elements from falling out of the bearing body or carriage}
- 29/0609 {of the ends of the bearing body or carriage where the rolling elements change direction, e.g. end caps}
- 29/0611 {of the return passages, i.e. the passages where the rolling elements do not carry load}
- 29/0614 . . . {with a shoe type bearing body, e.g. a body facing one side of the guide rail or track only}
- 29/0616 {for supporting load essentially in a single direction}
- 29/0619 {with rollers or needles}
- 29/0621 {for supporting load in essentially two directions, e.g. by multiple points of contact or two rows of rolling elements}
- 29/0623 {with balls}
- 29/0626 {with rollers}
- 29/0628 {crossed within a row}
- 29/063 . . . {with a bearing body, e.g. a carriage or part thereof, provided between the legs of a U-shaped guide rail or track}
- 29/0633 . . . {with a bearing body defining a U-shaped carriage, i.e. surrounding a guide rail or track on three sides}
- 29/0635 {whereby the return paths are provided as bores in a main body of the U-shaped carriage, e.g. the main body of the U-shaped carriage is a single part with end caps provided at each end}
- 29/0638 {with balls}
- 29/064 {with two rows of balls, one on each side of the rail}
- 29/0642 {with four rows of balls}
- 29/0645 {with load directions in O-arrangement}
- 29/0647 {with load directions in X-arrangement}
- 29/065 {with rollers}
- 29/0652 {whereby the return paths are at least partly defined by separate parts, e.g. covers attached to the legs of the main body of the U-shaped carriage}
- 29/0654 {with balls}
- 29/0657 {with two rows of balls, one on each side of the rail}
- 29/0659 {with four rows of balls}
- 29/0661 {with load directions in O-arrangement}
- 29/0664 {with load directions in X-arrangement}
- 29/0666 {with rollers}
- 29/0669 {whereby the main body of the U-shaped carriage is an assembly of at least three major parts, e.g. an assembly of a top plate with two separate legs attached thereto in the form of bearing shoes ([bearing shoes per se \[F16C 29/0614\]\(#\)](#))}
- 29/0671 {with balls}
- 29/0673 {with rollers}
- 29/0676 . . . {with a bearing body or carriage almost fully embracing the guide rail or track, e.g. a circular sleeve with a longitudinal slot for the support posts of the rail}
- 29/0678 . . . {with a bearing body, i.e. the body carrying the circulating rolling elements, provided in the interior of a sleeve-like guide member defining the opposing raceways, e.g. in a telescopic shaft ([telescopic shafts with built-in bearings \[F16C 3/035\]\(#\); yielding coupling allowing axial displacement by rolling elements \[F16D 3/065\]\(#\)](#))}
- 29/068 . . . {with the bearing body fully encircling the guide rail or track}
- 29/0683 {the bearing body encircles a rail or rod of circular cross-section, i.e. the linear bearing is not suited to transmit torque}
- 29/0685 {with balls}
- 29/0688 {whereby a sleeve surrounds the circulating balls and thicker part of the sleeve form the load bearing tracks}
- 29/069 {whereby discrete load bearing elements, e.g. discrete load bearing plates or discrete rods, are provided in a retainer and form the load bearing tracks}

- 29/0692 {the bearing body encircles a guide rail or track of non-circular cross-section, e.g. with grooves or protrusions, i.e. the linear bearing is suited to transmit torque ([telescopic shafts with built-in bearings F16C 3/035](#); yielding coupling allowing axial displacement by rolling elements [F16D 3/065](#))}
- 29/0695 {with balls}
- 29/0697 {with polygonal guide rail or track}
- 29/08 . . Arrangements for covering or protecting the ways {(protective coverings for parts of machine tools [B23Q 11/08](#))}
- 29/082 . . {fixed to the way}
- 29/084 . . {fixed to the carriage or bearing body movable along the guide rail or track}
- 29/086 . . . {Seals being essentially U-shaped, e.g. for a U-shaped carriage}
- 29/088 . . . {Seals extending in the longitudinal direction of the carriage or bearing body}
- 29/10 . Arrangements for locking the bearings
- 29/12 . Arrangements for adjusting play
- 29/123 . . {using elastic means}
- 29/126 . . {using tapered surfaces or wedges}
- 31/00 Bearings for parts which both rotate and move linearly**
- 31/02 . Sliding-contact bearings
- 31/04 . Ball or roller bearings
- 31/06 . . in which the rolling bodies circulate partly without carrying load
- 32/00 Bearings not otherwise provided for**
- 32/02 . Knife-edge bearings
- 32/04 . using magnetic or electric supporting means
- 32/0402 . . {combined with other supporting means, e.g. hybrid bearings with both magnetic and fluid supporting means}
- 32/0404 . . {Electrostatic bearings}
- 32/0406 . . {Magnetic bearings}
- 32/0408 . . . {Passive magnetic bearings}
- 32/041 {with permanent magnets on one part attracting the other part}
- 32/0412 {for radial load mainly}
- 32/0414 {with facing axial projections}
- 32/0417 {for axial load mainly}
- 32/0419 {with facing radial projections}
- 32/0421 {for both radial and axial load}
- 32/0423 {with permanent magnets on both parts repelling each other}
- 32/0425 {for radial load mainly}
- 32/0427 {for axial load mainly}
- 32/0429 {for both radial and axial load, e.g. conical magnets}
- 32/0431 {with bearings for axial load combined with bearings for radial load}
- 32/0434 {for parts moving linearly}
- 32/0436 {with a conductor on one part movable with respect to a magnetic field, e.g. a body of copper on one part and a permanent magnet on the other part}
- 32/0438 {with a superconducting body, e.g. a body made of high temperature superconducting material such as YBaCuO}
- 32/044 . . . {Active magnetic bearings}
- 32/0442 {with devices affected by abnormal, undesired or non-standard conditions such as shock-load, power outage, start-up or touchdown}
- 32/0444 {Details of devices to control the actuation of the electromagnets}
- 32/0446 {Determination of the actual position of the moving member, e.g. details of sensors}
- 32/0448 {by using the electromagnet itself as sensor, e.g. sensorless magnetic bearings}
- 32/0451 {Details of controllers, i.e. the units determining the power to be supplied, e.g. comparing elements, feedback arrangements with P.I.D. control}
- 32/0453 {for controlling two axes, i.e. combined control of x-axis and y-axis}
- 32/0455 {including digital signal processing [DSP] and analog/digital conversion [A/D, D/A]}
- 32/0457 {Details of the power supply to the electromagnets}
- 32/0459 {Details of the magnetic circuit}
- 32/0461 {of stationary parts of the magnetic circuit}
- 32/0463 {with electromagnetic bias, e.g. by extra bias windings}
- 32/0465 {with permanent magnets provided in the magnetic circuit of the electromagnets}
- 32/0468 {of moving parts of the magnetic circuit, e.g. of the rotor}
- 32/047 {Details of housings; Mounting of active magnetic bearings}
- 32/0472 {for linear movement}
- 32/0474 {for rotary movement}
- 32/0476 {with active support of one degree of freedom, e.g. axial magnetic bearings}
- 32/0478 {with permanent magnets to support radial load}
- 32/048 {with active support of two degrees of freedom, e.g. radial magnetic bearings}
- 32/0482 {with three electromagnets to control the two degrees of freedom}
- 32/0485 {with active support of three degrees of freedom}
- 32/0487 {with active support of four degrees of freedom}
- 32/0489 {with active support of five degrees of freedom, e.g. two radial magnetic bearings combined with an axial bearing}
- 32/0491 {with electromagnets acting in axial and radial direction, e.g. with conical magnets}
- 32/0493 {integrated in an electrodynamic machine, e.g. self-bearing motor}
- 32/0495 {generating torque and axial force}
- 32/0497 {generating torque and radial force}
- 32/06 . . with moving member supported by a fluid cushion formed, at least to a large extent, otherwise than by movement of the shaft, e.g. hydrostatic air-cushion bearings
- 32/0603 . . {supported by a gas cushion, e.g. an air cushion}

32/0607	. . . {the gas being retained in a gap, e.g. squeeze film bearings}	33/1035 {by a magnetic field acting on a magnetic liquid}
32/0611 {by means of vibrations}	33/104 {in a porous body, e.g. oil impregnated sintered sleeve}
32/0614	. . . {the gas being supplied under pressure, e.g. aerostatic bearings}	33/1045 {Details of supply of the liquid to the bearing}
32/0618 {via porous material}	33/105 {Conditioning, e.g. metering, cooling, filtering}
32/0622 {via nozzles, restrictors}	33/1055 {from radial inside, e.g. via a passage through the shaft and/or inner sleeve}
32/0625 {via supply slits}	33/106 {Details of distribution or circulation inside the bearings, e.g. details of the bearing surfaces to affect flow or pressure of the liquid}
32/0629	. . {supported by a liquid cushion, e.g. oil cushion}	33/1065 {Grooves on a bearing surface for distributing or collecting the liquid}
32/0633	. . . {the liquid being retained in a gap}	33/107 {Grooves for generating pressure}
32/0637 {by a magnetic field, e.g. ferrofluid bearings}	33/1075 {Wedges, e.g. ramps or lobes, for generating pressure}
32/064	. . . {the liquid being supplied under pressure}	33/108 {with a plurality of elements forming the bearing surfaces, e.g. bearing pads}
32/0644 {Details of devices to control the supply of liquids to the bearings}	33/1085 {Channels or passages to recirculate the liquid in the bearing}
32/0648 {by sensors or pressure-responsive control devices in or near the bearings}	33/109 {Lubricant compositions or properties, e.g. viscosity}
32/0651 {Details of the bearing area <u>per se</u> }	33/1095 {with solids as lubricant, e.g. dry coatings, powder}
32/0655 {of supply openings}	33/12 Structural composition; Use of special materials or surface treatments, e.g. for rust-proofing
32/0659 {of pockets or grooves}	33/121 {Use of special materials}
32/0662	. . {Details of hydrostatic bearings independent of fluid supply or direction of load}	33/122 {Multilayer structures of sleeves, washers or liners}
32/0666	. . . {of bearing pads}	33/124 {Details of overlays}
32/067	. . . {of bearings adjustable for aligning, positioning, wear or play}	33/125 {Details of bearing layers, i.e. the lining}
32/0674 {by means of pre-load on the fluid bearings}	33/127 {Details of intermediate layers, e.g. nickel dams}
32/0677	. . . {of elastic or yielding bearings or bearing supports}	33/128 {Porous bearings, e.g. bushes of sintered alloy}
32/0681	. . {Construction or mounting aspects of hydrostatic bearings, for exclusively rotary movement, related to the direction of load}	33/14 Special methods of manufacture; Running-in
32/0685	. . . {for radial load only}	33/145 {of sintered porous bearings}
32/0688 {with floating bearing elements}	33/16 Sliding surface consisting mainly of graphite
32/0692	. . . {for axial load only}	33/18 Sliding surface consisting mainly of wood or fibrous material
32/0696	. . . {for both radial and axial load}	33/20 Sliding surface consisting mainly of plastics (F16C 33/22 - F16C 33/28 take precedence)

Details or accessories of bearings

33/00	Parts of bearings; Special methods for making bearings or parts thereof (metal-working or like operations, see the relevant classes)	33/201 {Composition of the plastic}
33/02	. Parts of sliding-contact bearings	33/203 {Multilayer structures, e.g. sleeves comprising a plastic lining}
33/04	. . Brasses; Bushes; linings	33/205 {with two layers}
33/043	. . . {Sliding surface consisting mainly of ceramics, cermets or hard carbon, e.g. diamond like carbon [DLC]}	33/206 {with three layers}
33/046	. . . {divided or split, e.g. half-bearings or rolled sleeves}	33/208 {Methods of manufacture, e.g. shaping, applying coatings}
33/06	. . . Sliding surface mainly made of metal (F16C 33/24 - F16C 33/28 take precedence; {casting metal bearing surfaces B22D 15/02 , B22D 19/08 })	33/22 Sliding surface consisting mainly of rubber or synthetic rubber (F16C 33/24 - F16C 33/28 take precedence)
33/08 Attachment of brasses, bushes or linings to the bearing housing	33/24 with different areas of the sliding surface consisting of different materials
33/10 Construction relative to lubrication {(lubrication in general F16N)}	33/26 made from wire coils; made from a number of discs, rings, rods, or other members
33/1005 {with gas, e.g. air, as lubricant}	33/28 with embedded reinforcements shaped as frames or meshed materials
33/101 {Details of the bearing surface, e.g. means to generate pressure such as lobes or wedges}		
33/1015 {Pressure generating grooves}		
33/102 {with grease as lubricant}		
33/1025 {with liquid, e.g. oil, as lubricant}		
33/103 {retained in or near the bearing}		

33/30	. Parts of ball or roller bearings	33/418 {Details of individual pockets, e.g. shape or ball retaining means}
33/303	. . {of hybrid bearings, e.g. rolling bearings with steel races and ceramic rolling elements}	33/42	. . . made from wire or sheet metal strips (F16C 33/40 , F16C 33/41 take precedence)
33/306	. . {Means to synchronise movements}	33/422 {made from sheet metal}
33/32	. . Balls	33/425 {from a single part, e.g. ribbon cages with one corrugated annular part}
33/34	. . Rollers; Needles	33/427 {from two parts, e.g. ribbon cages with two corrugated annular parts}
33/36	. . . with bearing-surfaces other than cylindrical, e.g. tapered; with grooves in the bearing surfaces	33/44	. . . Selection of substances (F16C 33/40 , F16C 33/41 take precedence)
33/363 {with grooves in the bearing-surfaces}	33/445 {Coatings}
33/366 {Tapered rollers, i.e. rollers generally shaped as truncated cones}	33/46	. . Cages for rollers or needles
33/37	. . Loose spacing bodies	33/4605	. . . {Details of interaction of cage and race, e.g. retention or centring}
33/3706	. . . {with concave surfaces conforming to the shape of the rolling elements, e.g. the spacing bodies are in sliding contact with the rolling elements}	33/4611	. . . {with hybrid structure, i.e. with parts made of distinct materials}
33/3713	. . . {with other rolling elements serving as spacing bodies, e.g. the spacing bodies are in rolling contact with the load carrying rolling elements}	33/4617	. . . {Massive or moulded cages having cage pockets surrounding the rollers, e.g. machined window cages}
33/372	. . . rigid	33/4623 {formed as one-piece cages, i.e. monoblock cages}
33/374	. . . resilient	33/4629 {made from metal, e.g. cast or machined window cages}
33/38	. . Ball cages	33/4635 {made from plastic, e.g. injection moulded window cages}
33/3806	. . . {Details of interaction of cage and race, e.g. retention, centring}	33/4641 {comprising two annular parts joined together}
33/3812	. . . {formed of interconnected segments, e.g. chains}	33/4647 {made from metal, e.g. two cast parts joined by rivets}
33/3818	. . . {formed of unconnected segments}	33/4652 {made from plastic, e.g. two injection moulded parts joined by a snap fit}
33/3825	. . . {formed as a flexible belt, e.g. spacers connected by a thin film}	33/4658 {comprising three annular parts, i.e. three piece roller cages}
33/3831	. . . {with hybrid structure, i.e. with parts made of distinct materials}	33/4664 {with more than three parts, e.g. two end rings connected by individual stays}
33/3837	. . . {Massive or moulded cages having cage pockets surrounding the balls, e.g. machined window cages}	33/467	. . . {Details of individual pockets, e.g. shape or roller retaining means}
33/3843 {formed as one-piece cages, i.e. monoblock cages}	33/4676 {of the stays separating adjacent cage pockets, e.g. guide means for the bearing-surface of the rollers}
33/385 {made from metal, e.g. cast or machined window cages}	33/4682 {of the end walls, e.g. interaction with the end faces of the rollers}
33/3856 {made from plastic, e.g. injection moulded window cages}	33/4688	. . . {with rolling elements with smaller diameter than the load carrying rollers, e.g. cages with counter-rotating spacers}
33/3862 {comprising two annular parts joined together}	33/4694	. . . {Single-split roller or needle cages}
33/3868 {made from metal, e.g. two cast parts joined by rivets}	33/48	. . . for multiple rows of rollers or needles
33/3875 {made from plastic, e.g. two injection moulded parts joined by a snap fit}	33/485 {with two or more juxtaposed cages joined together or interacting with each other}
33/3881 {with more than three parts, e.g. two end rings connected by individual stays}	33/49	. . . comb-shaped
33/3887	. . . {Details of individual pockets, e.g. shape or ball retaining means}	33/491 {applied as pairs for retaining both ends of the rollers or needles}
33/3893	. . . {with rolling elements with smaller diameter than the load carrying balls, e.g. cages with counter-rotating spacers}	33/492 {joined by rods}
33/40	. . . for multiple rows of balls	33/494 {Massive or moulded comb cages}
33/405 {with two or more juxtaposed cages joined together or interacting with each other}	33/495 {formed as one piece cages, i.e. monoblock comb cages}
33/41	. . . comb-shaped	33/497 {made from metal, e.g. cast or machined comb cages}
33/412 {Massive or moulded comb cages, e.g. snap ball cages}	33/498 {made from plastic, e.g. injection moulded comb cages}
33/414 {formed as one-piece cages, i.e. monoblock comb cages}	33/50	. . . formed of interconnected members, e.g. chains
33/416 {made from plastic, e.g. injection moulded comb cages}	33/502 {formed of arcuate segments retaining one or more rollers or needles}

33/504 {with two segments, e.g. two semicircular cage parts}	33/6625 {Controlling or conditioning the grease supply}
33/506 {formed as a flexible belt}	33/6629 {Details of distribution or circulation inside the bearing, e.g. grooves on the cage or passages in the rolling elements}
33/508 {formed of links having an H-shape, i.e. links with a single stay placed between two rollers and with two end portions extending along the end faces of the two rollers}	33/6633 {Grease properties or compositions, e.g. rheological properties}
33/51 formed of unconnected members	33/6637 {with liquid lubricant}
33/513 {formed of arcuate segments for carrying one or more rollers}	33/664 {Retaining the liquid in or near the bearing}
33/516 {with two segments, e.g. double-split cages with two semicircular parts}	33/6644 {by a magnetic field acting on a magnetic liquid}
33/52 with no part entering between, or touching, the bearing surfaces of the rollers (F16C 33/50 takes precedence)	33/6648 {in a porous or resinous body, e.g. a cage impregnated with the liquid}
33/523 {with pins extending into holes or bores on the axis of the rollers}	33/6651 {in recesses or cavities provided in retainers, races or rolling elements}
33/526 {extending through the rollers and joining two lateral cage parts}	33/6655 {in a reservoir in the sealing means}
33/54 made from wire, strips, or sheet metal (F16C 33/48 , F16C 33/49 take precedence)	33/6659 {Details of supply of the liquid to the bearing, e.g. passages or nozzles}
33/541 {Details of individual pockets, e.g. shape or roller retaining means}	33/6662 {the liquid being carried by air or other gases, e.g. mist lubrication}
33/542 {made from sheet metal}	33/6666 {from an oil bath in the bearing housing, e.g. by an oil ring or centrifugal disc}
33/543 {from a single part}	33/667 {related to conditioning, e.g. cooling, filtering}
33/545 {rolled from a band}	33/6674 {related to the amount supplied, e.g. gaps to restrict flow of the liquid}
33/546 {with a M- or W-shaped cross section}	33/6677 {from radial inside, e.g. via a passage through the shaft and/or inner ring}
33/547 {from two parts, e.g. two discs or rings joined together}	33/6681 {Details of distribution or circulation inside the bearing, e.g. grooves on the cage or passages in the rolling elements}
33/548 {with more than three parts, e.g. two end rings connected by a plurality of stays or pins}	33/6685 {Details of collecting or draining, e.g. returning the liquid to a sump}
33/56 Selection of substances (F16C 33/48 , F16C 33/49 take precedence)	33/6688 {Lubricant compositions or properties, e.g. viscosity}
33/565 {Coatings}	33/6692 {Liquids other than oil, e.g. water, refrigerants, liquid metal}
33/58 Raceways; Race rings	33/6696 {with solids as lubricant, e.g. dry coatings, powder}
33/581 {integral with other parts, e.g. with housings or machine elements such as shafts or gear wheels}	33/72 Sealings
33/583 {Details of specific parts of races}	33/723 {Shaft end sealing means, e.g. cup-shaped caps or covers}
33/585 {of raceways, e.g. ribs to guide the rollers}	33/726 {with means to vent the interior of the bearing}
33/586 {outside the space between the races, e.g. end faces or bore of inner ring}	33/74 of sliding-contact bearings
33/588 {Races of sheet metal}	33/741 {by means of a fluid}
33/60 divided {or split, e.g. comprising two juxtaposed rings}	33/743 {retained in the sealing gap}
33/605 {with a separate retaining member, e.g. flange, shoulder, guide ring, secured to a race ring, adjacent to the race surface, so as to abut the end of the rolling elements, e.g. rollers, or the cage}	33/745 {by capillary action}
33/61 formed by wires	33/746 {by a magnetic field}
33/62 Selection of substances	33/748 {flowing to or from the sealing gap, e.g. vacuum seals with differential exhaust}
33/64 Special methods of manufacture	33/76 of ball or roller bearings
33/66 Special parts or details in view of lubrication	33/761 {specifically for bearings with purely axial load}
33/6603 {with grease as lubricant}	33/762 {by means of a fluid}
33/6607 {Retaining the grease in or near the bearing}	33/763 {retained in the sealing gap}
33/6611 {in a porous or resinous body, e.g. a cage impregnated with the grease}	33/765 {by a magnetic field}
33/6614 {in recesses or cavities provided in retainers, races or rolling elements}	33/766 {by pumping action}
33/6618 {in a reservoir in the sealing means}	33/767 {integral with the race}
33/6622 {Details of supply and/or removal of the grease, e.g. purging grease}	33/768 {between relatively stationary parts, i.e. static seals}
		33/78 with a diaphragm, disc, or ring, with or without resilient members (F16C 33/761 takes precedence)

33/7803 {suited for particular types of rolling bearings}	35/047	. . . {with a base plate substantially parallel to the axis of rotation, e.g. horizontally mounted pillow blocks}
33/7806 {for spherical roller bearings}	35/06	. . Mounting {or dismounting} of ball or roller bearings; Fixing them onto shaft or in housing
33/7809 {for needle roller bearings}	35/061	. . . {mounting a plurality of bearings side by side}
33/7813 {for tapered roller bearings}	35/062	. . . {Dismounting of ball or roller bearings}
33/7816 {Details of the sealing or parts thereof, e.g. geometry, material}	35/063	. . . Fixing them on the shaft (with interposition of an element F16C 35/07)
33/782 {of the sealing region}	35/0635 {the bore of the inner ring being of special non-cylindrical shape which co-operates with a complementary shape on the shaft, e.g. teeth, polygonal sections}
33/7823 {of sealing lips}	35/067	. . . Fixing them in a housing (with interposition of an element F16C 35/07)
33/7826 {of the opposing surface cooperating with the seal, e.g. a shoulder surface of a bearing ring}	35/07	. . . Fixing them on the shaft or housing with interposition of an element
33/783 {of the mounting region}	35/073 between shaft and inner race ring
33/7833 {Special methods of manufacture}	35/077 between housing and outer race ring
33/7836 {floating with respect to both races}	35/078	. . . using pressure fluid as mounting aid
33/784 {mounted to a groove in the inner surface of the outer race and extending toward the inner race}	35/08	. for spindles
33/7843 {with a single annular sealing disc}	35/10	. . with sliding-contact bearings
33/7846 {with a gap between the annular disc and the inner race}	35/12	. . with ball or roller bearings {(adjustable bearings F16C 23/00, F16C 25/00; elastic bearings F16C 27/00)}
33/785 {Bearing shields made of sheet metal}	37/00	Cooling of bearings
33/7853 {with one or more sealing lips to contact the inner race}	37/002	. {of fluid bearings}
33/7856 {with a single sealing lip}	37/005	. {of magnetic bearings}
33/7859 {with a further sealing element}	37/007	. {of rolling bearings}
33/7863 {mounted to the inner race, e.g. a flinger to use centrifugal effect}	39/00	Relieving load on bearings
33/7866 {with sealing lips}	39/02	. using mechanical means
33/7869 {mounted with a cylindrical portion to the inner surface of the outer race and having a radial portion extending inward}	39/04	. using hydraulic or pneumatic means
33/7873 {with a single sealing ring of generally L-shaped cross-section}	39/06	. using magnetic means
33/7876 {with sealing lips}	39/063	. . {Permanent magnets}
33/7879 {with a further sealing ring}	39/066	. . . {with opposing permanent magnets repelling each other}
33/7883 {mounted to the inner race and of generally L-shape, the two sealing rings defining a sealing with box-shaped cross-section}	41/00	Other accessories, {e.g. devices integrated in the bearing not relating to the bearing function as such}
33/7886 {mounted outside the gap between the inner and outer races, e.g. sealing rings mounted to an end face or outer surface of a race}	41/001	. {Integrated brakes or clutches for stopping or coupling the relatively movable parts}
33/7889 {mounted to an inner race and extending toward the outer race}	41/002	. {Conductive elements, e.g. to prevent static electricity}
33/7893 {mounted to a cage or integral therewith}	41/004	. {Electro-dynamic machines, e.g. motors, generators, actuators}
33/7896 {with two or more discrete sealings arranged in series}	41/005	. {Fluid passages not relating to lubrication or cooling}
33/80	. . . Labyrinth sealings {(F16C 33/761 takes precedence)}	41/007	. {Encoders, e.g. parts with a plurality of alternating magnetic poles}
33/805 {in addition to other sealings, e.g. dirt guards to protect sealings with sealing lips}	41/008	. {Identification means, e.g. markings, RFID-tags; Data transfer means}
33/82	. . . Arrangements for electrostatic or magnetic action against dust or other particles	41/02	. Arrangements for equalizing the load on a plurality of bearings or their elements
35/00	Rigid support of bearing units; Housings, e.g. caps, covers (F16C 23/00 takes precedence)	41/04	. Preventing damage to bearing during storage or transport thereof or when otherwise out of use
35/02	. in the case of sliding-contact bearings	41/045	. . {Devices for provisionally retaining needles or rollers in a bearing race before mounting of the bearing on a shaft}
35/04	. in the case of ball or roller bearings	43/00	Assembling bearings
35/042	. . {Housings for rolling element bearings for rotary movement}	43/02	. Assembling sliding-contact bearings
35/045	. . . {with a radial flange to mount the housing}	43/04	. Assembling rolling-contact bearings

- 43/045 . . {Mounting or replacing seals}
- 43/06 . . Placing rolling bodies in cages or bearings
- 43/065 . . . {in cages}
- 43/08 . . . by deforming the cages or the races
- 43/083 {by plastic deformation of the cage}
- 43/086 {by plastic deformation of the race}

2202/00 Solid materials defined by their properties

- 2202/02 . Mechanical properties
- 2202/04 . . Hardness
- 2202/06 . . Strength or rigidity
- 2202/08 . . Resilience, elasticity, super-elasticity
- 2202/10 . . Porosity
- 2202/20 . Thermal properties
- 2202/22 . . Coefficient of expansion
- 2202/24 . . Insulating
- 2202/28 . . Shape memory material
- 2202/30 . Electric properties; Magnetic properties
- 2202/32 . . Conductivity
- 2202/34 . . . Super-conductivity
- 2202/36 . . Piezo-electric
- 2202/40 . . Magnetic (magnetic material in general [H01F 1/00](#))
- 2202/42 . . . soft-magnetic, ferromagnetic
- 2202/44 . . . hard-magnetic, permanent magnetic, e.g. samarium-cobalt
- 2202/50 . Lubricating properties
- 2202/52 . . Graphite
- 2202/54 . . Molybdenum disulfide
- 2202/60 . Oil repelling
- 2202/64 . Water absorbing
- 2202/66 . Water repelling
- 2202/70 . Anti-bacterial, anti-microbial
- 2204/00 **Metallic materials; Alloys (alloys in general [C22C](#); [F16C 2206/00](#) takes precedence)**
- 2204/02 . Noble metals
- 2204/04 . . based on silver
- 2204/10 . Alloys based on copper
- 2204/12 . . with tin as the next major constituent
- 2204/14 . . with zinc as the next major constituent
- 2204/16 . . with lead as the next major constituent
- 2204/18 . . with bismuth as the next major constituent
- 2204/20 . Alloys based on aluminium
- 2204/22 . . with tin as the next major constituent
- 2204/24 . . with lead as the next major constituent
- 2204/26 . Alloys based on magnesium
- 2204/30 . Alloys based on one of tin, lead, antimony, bismuth, indium, e.g. materials for providing sliding surfaces
- 2204/32 . . Alloys based on lead
- 2204/34 . . Alloys based on tin
- 2204/36 . . Alloys based on bismuth
- 2204/40 . Alloys based on refractory metals
- 2204/42 . . Alloys based on titanium
- 2204/44 . . Alloys based on chromium
- 2204/46 . . Alloys based on molybdenum
- 2204/50 . Alloys based on zinc
- 2204/52 . Alloys based on nickel, e.g. Inconel
- 2204/60 . Ferrous alloys, e.g. steel alloys
- 2204/62 . . Low carbon steel, i.e. carbon content below 0.4 wt%

- 2204/64 . . Medium carbon steel, i.e. carbon content from 0.4 to 0.8 wt%
- 2204/66 . . High carbon steel, i.e. carbon content above 0.8 wt%, e.g. through-hardenable steel
- 2204/70 . . with chromium as the next major constituent
- 2204/72 . . . with nickel as further constituent, e.g. stainless steel
- 2204/74 . . with manganese as the next major constituent
- 2204/80 . Amorphous alloys

2206/00 Materials with ceramics, cermets, hard carbon or similar non-metallic hard materials as main constituents

- 2206/02 . Carbon based material
- 2206/04 . . Diamond like carbon [DLC]
- 2206/06 . . Composite carbon material, e.g. carbon fibre reinforced carbon (C/C)
- 2206/40 . Ceramics, e.g. carbides, nitrides, oxides, borides of a metal
- 2206/42 . . based on ceramic oxides
- 2206/44 . . . based on aluminium oxide (Al₂O₃)
- 2206/48 . . . based on zirconia (ZrO₂)
- 2206/56 . . based on ceramic carbides, e.g. silicon carbide (SiC)
- 2206/58 . . based on ceramic nitrides
- 2206/60 . . . Silicon nitride (Si₃N₄)
- 2206/80 . Cermets, i.e. composites of ceramics and metal ([in general \[C22C 29/00\]\(#\)](#))
- 2206/82 . . based on tungsten carbide [WC]

2208/00 Plastics; Synthetic resins, e.g. rubbers

- 2208/02 . comprising fillers, fibres
- 2208/04 . . Glass fibres
- 2208/10 . Elastomers; Rubbers
- 2208/12 . . Polyurethan [PU]
- 2208/14 . . Silicone rubber
- 2208/20 . Thermoplastic resins
- 2208/22 . . comprising two or more thermoplastics
- 2208/30 . . Fluoropolymers ([F16C 2208/58 takes precedence](#))
- 2208/32 . . . Polytetrafluorethylene [PTFE] ([F16C 2208/58 takes precedence](#))
- 2208/34 . . . Polyvinylidene fluoride [PVDF] ([F16C 2208/58 takes precedence](#))
- 2208/36 . . Polyarylene ether ketones [PAEK], e.g. PEK, PEEK ([F16C 2208/58 takes precedence](#))
- 2208/40 . . Imides, e.g. polyimide [PI], polyetherimide [PEI] ([F16C 2208/58 takes precedence](#))
- 2208/42 . . . Polyamideimide [PAI] ([F16C 2208/58 takes precedence](#))
- 2208/44 . . . Polybenzimidazole [PBI] ([F16C 2208/58 takes precedence](#))
- 2208/48 . . Liquid crystal polymers [LCP] ([F16C 2208/58 takes precedence](#))
- 2208/52 . . Polyphenylene sulphide [PPS] ([F16C 2208/58 takes precedence](#))
- 2208/54 . . Polysulphones, e.g. polysulphone [PSU], polyethersulphone [PES], polyethersulphone-block copolymer [PPSU] ([F16C 2208/58 takes precedence](#))
- 2208/58 . . Several materials as provided for in [F16C 2208/30](#) - [F16C 2208/54](#) mentioned as option
- 2208/60 . . Polyamides [PA]
- 2208/62 . . . high performance polyamides, e.g. PA12, PA46

2208/66	. . Acetals, e.g. polyoxymethylene [POM]	2223/12	. . with carburizing
2208/70	. . Polyesters, e.g. polyethylene-terephthlate [PET], polybutylene-terephthlate [PBT]	2223/14	. . with nitriding
2208/72	. . Acrylics, e.g. polymethylmethacrylate [PMMA]	2223/16	. . with carbo-nitriding
2208/76	. . Polyolefins, e.g. polypropylene [PP]	2223/18	. . with induction hardening
2208/78	. . . Polyethylene [PE], e.g. ultra-high molecular weight polyethylene [UHMWPE]	2223/30	. Coating surfaces (in general B05C , C23C)
2208/80	. Thermosetting resins	2223/32	. . by attaching pre-existing layers, e.g. resin sheets or foils by adhesion to a substrate; Laminating (in general B32B)
2208/82	. . Composites, i.e. fibre reinforced thermosetting resins	2223/40	. . by dipping in molten material (in general C23C 2/00)
2208/86	. . Epoxy resins	2223/42	. . by spraying the coating material, e.g. plasma spraying (in general C23C 4/00)
2208/90	. . Phenolic resin	2223/44	. . by casting molten material on the substrate (in general C23C 6/00)
2210/00	Fluids	2223/46	. . by welding, e.g. by using a laser to build a layer (in general B23K 9/04)
2210/02	. defined by their properties	2223/60	. . by vapour deposition, e.g. PVD, CVD (in general C23C 14/00)
2210/04	. . by viscosity	2223/70	. . by electroplating or electrolytic coating, e.g. anodising, galvanising (in general C25D)
2210/06	. . magnetic fluids	2223/80	. . by powder coating (in general B22F 7/00)
2210/08	. molten metals	2226/00	Joining parts; Fastening; Assembling or mounting parts (fasteners, securing, joints in general F16B)
2210/10	. water based	2226/10	. Force connections, e.g. clamping (shrinkage connections, force fits, friction grips in general F16B 4/00 , for rigidly connecting coaxial parts F16D 1/00)
2212/00	Natural materials, i.e. based on animal or plant products such as leather, wood or cotton or extracted therefrom, e.g. lignin	2226/12	. . by press-fit, e.g. plug-in
2212/04	. Wood	2226/14	. . by shrink fit, i.e. heating and shrinking part to allow assembly (for metal parts in general B23P 11/02)
2212/08	. Woven, unwoven fabrics, e.g. felt	2226/16	. . by wedge action, e.g. by tapered or conical parts
2220/00	Shaping	2226/18	. . by magnets, i.e. magnetic attraction to hold parts together
2220/02	. by casting (in general B22D ; for plastics B29C 39/00)	2226/30	. Material joints (in general B23K)
2220/04	. . by injection-moulding (of plastics in general B29C 45/00)	2226/32	. . by soldering
2220/06	. . in-situ casting or moulding	2226/34	. . . by brazing
2220/08	. . by compression-moulding	2226/36	. . by welding
2220/20	. by sintering pulverised material, e.g. powder metallurgy (in general B22F)	2226/38	. . . with ultrasonic welding
2220/24	. by built-up welding (in general B23K 9/04)	2226/40	. . with adhesive
2220/28	. by winding impregnated fibres (in general B29C 70/00)	2226/50	. Positive connections
2220/40	. by deformation without removing material	2226/52	. . with plastic deformation, e.g. caulking or staking
2220/42	. . by working of thin walled material such as sheet or tube (in general B21D)	2226/54	. . . with rivets (in general F16B 19/00)
2220/44	. . by rolling (in general B21H)	2226/60	. . with threaded parts, e.g. bolt and nut connections (in general F16B 23/00 - F16B 43/00)
2220/46	. . by forging (in general B21J)	2226/62	. . with pins, bolts or dowels
2220/48	. . by extrusion, e.g. of metallic profiles (in general B21C 23/00)	2226/70	. . with complementary interlocking parts
2220/60	. by removing material, e.g. machining	2226/72	. . . with bayonet joints, i.e. parts are rotated to create positive interlock
2220/62	. . by turning, boring, drilling (in general B23B)	2226/74	. . . with snap-fit, e.g. by clips
2220/66	. . by milling (in general B23C)	2226/76	. . . with tongue and groove or key and slot
2220/68	. . by electrical discharge or electrochemical machining (in general B23H)	2226/78 of jigsaw-puzzle type
2220/70	. . by grinding (in general B24B)	2226/80	. . with splines, serrations or similar profiles to prevent movement between joined parts
2220/80	. by separating parts, e.g. by severing, cracking	2229/00	Setting preload
2220/82	. . by cutting (in general B26D)	2231/00	Running-in; Initial operation
2220/84	. . by perforating; by punching; by stamping-out (in general B26F)	2233/00	Monitoring condition, e.g. temperature, load, vibration
2223/00	Surface treatments; Hardening; Coating	2235/00	Cleaning
2223/02	. Mechanical treatment, e.g. finishing		
2223/04	. . by sizing, by shaping to final size by small plastic deformation, e.g. by calibrating or coining (in general B23P 9/00)		
2223/06	. . polishing (in general B24B 29/00 , B24B 31/00)		
2223/08	. . shot-peening, blasting (in general B24C)		
2223/10	. Hardening, e.g. carburizing, carbo-nitriding (in general C21D , C23C 8/00)		

2237/00	Repair or replacement	
2240/00	Specified values or numerical ranges of parameters; Relations between them (properties of materials F16C 2202/00)	
2240/02	• Flow, e.g. volume flow or mass flow	
2240/06	• Temperature	
2240/08	• Time	
2240/12	• Force, load, stress, pressure	
2240/14	• • Preload	
2240/18	• • Stress	
2240/22	• • Fluid pressure	
2240/26	• Speed, e.g. rotational speed	
2240/30	• Angles, e.g. inclinations	
2240/34	• • Contact angles	
2240/40	• Linear dimensions, e.g. length, radius, thickness, gap	
2240/42	• • Groove sizes	
2240/44	• • Hole or pocket sizes	
2240/46	• • Gap sizes or clearances	
2240/48	• • Particle sizes	
2240/50	• • Crowning, e.g. crowning height or crowning radius	
2240/54	• • Surface roughness	
2240/56	• • Tolerances; Accuracy of linear dimensions	
2240/60	• • Thickness, e.g. thickness of coatings	
2240/64	• • • in the nano-meter range	
2240/70	• • Diameters; Radii	
2240/76	• • • Osculation, i.e. relation between radii of balls and raceway groove	
2240/80	• • • Pitch circle diameters [PCD]	
2240/82	• • • • Degree of filling, i.e. sum of diameters of rolling elements in relation to PCD	
2240/84	• • • • with full complement of balls or rollers, i.e. sum of clearances less than diameter of one rolling element	
2240/90	• Surface areas	
2240/94	• Volume	
2300/00	Application independent of particular apparatuses	
2300/02	• General use or purpose, i.e. no use, purpose, special adaptation or modification indicated or a wide variety of uses mentioned	
2300/10	• related to size	
2300/12	• • Small applications, e.g. miniature bearings	
2300/14	• • Large applications, e.g. bearings having an inner diameter exceeding 500 mm	
2300/20	• related to type of movement	
2300/22	• • High-speed rotation	
2300/28	• • Reciprocating movement	
2300/30	• related to direction with respect to gravity	
2300/32	• • Horizontal, e.g. bearings for supporting a horizontal shaft	
2300/34	• • Vertical, e.g. bearings for supporting a vertical shaft	
2300/40	• related to environment, i.e. operating conditions	
2300/42	• • corrosive, i.e. with aggressive media or harsh conditions	
2300/52	• • low temperature, e.g. cryogenic temperature	
2300/54	• • high-temperature	
2300/62	• • low pressure, e.g. elements operating under vacuum conditions	
2300/64	• • high pressure, e.g. elements exposed to high pressure gases or fluids	
2310/00	Agricultural machines (in general A01)	
2314/00	Personal or domestic articles, e.g. household appliances such as washing machines, dryers (in general A41 - A47)	
2314/70	• Furniture	
2314/72	• • Drawers	
2314/73	• • Chairs	
2316/00	Apparatus in health or amusement (in general A61 - A63)	
2316/10	• in medical appliances, e.g. in diagnosis, dentistry, instruments, prostheses, medical imaging appliances	
2316/13	• • Dental machines	
2316/18	• • Pumps for pumping blood	
2316/30	• Articles for sports, games and amusement, e.g. roller skates, toys	
2320/00	Apparatus used in separating or mixing (in general B01 - B09)	
2320/16	• Mixing apparatus	
2320/23	• Milling apparatus (in general B02C)	
2320/42	• Centrifuges (in general B04B)	
2322/00	Apparatus used in shaping articles (in general B21 - B32)	
2322/12	• Rolling apparatus, e.g. rolling stands, rolls	
2322/14	• Stamping, deep-drawing or punching, e.g. die sets	
2322/34	• Sawing machines (in general B23D)	
2322/39	• General build up of machine tools, e.g. spindles, slides, actuators (in general B23Q)	
2322/50	• Hand tools, workshop equipment or manipulators (in general B25)	
2322/59	• • Manipulators, e.g. robot arms (in general B25J)	
2324/00	Apparatus used in printing (in general B41 - B44)	
2324/16	• Printing machines (in general B41F)	
2326/00	Articles relating to transporting (in general B60 - B68)	
2326/01	• Parts of vehicles in general (engines F16C 2360/00)	
2326/02	• • Wheel hubs or castors (in general B60B)	
2326/05	• • Vehicle suspensions, e.g. bearings, pivots or connecting rods used therein (in general B60G)	
2326/06	• • Drive shafts (in general B60K)	
2326/08	• • Vehicle seats, e.g. in linear movable seats (in general B60N)	
2326/09	• • Windscreen wipers, e.g. pivots therefore (in general B60S)	
2326/10	• Railway vehicles (in general B61)	
2326/20	• Land vehicles (in general B62)	
2326/24	• • Steering systems, e.g. steering rods or columns (in general B62D)	
2326/26	• • Bicycle steering or suspension (in general B62K)	
2326/28	• • Bicycle propulsion, e.g. crankshaft and its support (in general B62M)	
2326/30	• Ships, e.g. propelling shafts and bearings therefor (in general B63H)	
2326/43	• Aeroplanes; Helicopters (in general B64C)	
2326/47	• Cosmonautic vehicles, i.e. bearings adapted for use in outer-space (in general B64G)	
2326/58	• Conveyor systems, e.g. rollers or bearings therefor (in general B65G)	

2340/00	Apparatus for treating textiles (in general D01 - D07)	2380/27	. . Motor coupled with a gear, e.g. worm gears
2340/18	. Apparatus for spinning or twisting (in general D01H)	2380/28	. . Motor, generator coupled with a flywheel
2340/24	. Godet rolls (in general D02)		
2350/00	Machines or articles related to building (in general E01 - E06)		
2350/26	. Excavators (in general E02F)		
2350/52	. Locks, e.g. cables to actuate door locks (in general E05B)		
2350/54	. Hinges, e.g. sliding bearings for hinges (in general E05D)		
2352/00	Apparatus for drilling (in general E21)		
2360/00	Engines or pumps (in general F01 - F04)		
2360/18	. Camshafts (in general F01L)		
2360/22	. Internal combustion engines (in general F02B)		
2360/23	. Gas turbine engines (in general F02C)		
2360/24	. . Turbochargers (in general F02C 6/12)		
2360/31	. Wind motors (in general F03D)		
2360/42	. Pumps with cylinders or pistons (in general F04B)		
2360/43	. Screw compressors (in general F04C)		
2360/44	. Centrifugal pumps (in general F04D)		
2360/45	. . Turbo-molecular pumps (in general F04D 19/04)		
2360/46	. Fans, e.g. ventilators		
2361/00	Apparatus or articles in engineering in general (F15 - F17)		
2361/31	. Axle		
2361/41	. Couplings (in general F16D 3/00)		
2361/43	. Clutches, e.g. disengaging bearing (in general F16D 11/00 - F16D 47/00)		
2361/45	. Brakes (in general B60T , F16D 49/00 - F16D 65/00)		
2361/53	. Spring-damper, e.g. gas springs (in general F16F 9/00)		
2361/55	. Flywheel systems (in general F16F 15/00)		
2361/61	. Toothed gear systems, e.g. support of pinion shafts (in general F16H 57/02)		
2361/63	. Gears with belts and pulleys		
2361/65	. Gear shifting, change speed gear, gear box		
2361/71	. Chains (in general F16G)		
2361/91	. Valves		
2362/00	Apparatus for lighting or heating (in general F21 - F28)		
2362/40	. Ovens or other heatings (in general F24)		
2362/52	. Compressors of refrigerators, e.g. air-conditioners (in general F25)		
2370/00	Apparatus relating to physics, e.g. instruments (in general G01 - G12)		
2370/12	. Hard disk drives or the like		
2370/20	. Optical, e.g. movable lenses or mirrors; Spectacles (in general G02)		
2370/22	. . Polygon mirror		
2370/38	. Electrographic apparatus (in general G03G)		
2380/00	Electrical apparatus (in general H01 - H05)		
2380/16	. X-ray tubes (in general H01J 35/00)		
2380/18	. Handling tools for semiconductor devices		
2380/26	. Dynamo-electric machines or combinations therewith, e.g. electro-motors and generators (in general H02K)		