

# CPC COOPERATIVE PATENT CLASSIFICATION

**F25B REFRIGERATION MACHINES, PLANTS OR SYSTEMS; COMBINED HEATING AND REFRIGERATION SYSTEMS; HEAT-PUMP SYSTEMS** ({evaporation or evaporation apparatus for physical or chemical purposes, e.g. evaporation of liquids for gas phase reactions [B01B 1/005](#)}; heat-transfer, heat-exchange or heat-storage materials, e.g. refrigerants, or materials for the production of heat or cold by chemical reactions other than by combustion [C09K 5/00](#); pumps, compressors [F04](#); use of heat-pumps for domestic- or space-heating or for domestic hot-water supply [F24D](#); air-conditioning, air-humidification [F24F](#); fluid heaters using heat pumps [F24H](#))

## NOTES

1. Attention is drawn to Note (2) following the title of subclass [F24F](#).
2. When classifying heat pump circuits or systems, groups [F25B 1/00](#) - [F25B 25/00](#) and [F25B 29/00](#) take precedence over group [F25B 30/00](#).

### Compression machines, plant, or systems

- 1/00 Compression machines, plant, or systems with non-reversible cycle** ([F25B 3/00](#), [F25B 5/00](#), [F25B 6/00](#), [F25B 7/00](#), [F25B 9/00](#) take precedence)
- 1/005
  - {of the single unit type ([F25B 1/10](#) takes precedence)}
- 1/02
  - with compressor of reciprocating-piston type ({[F25B 1/005](#), } [F25B 1/10](#) take precedence)
- 1/04
  - with compressor of rotary type ({[F25B 1/005](#), } [F25B 1/10](#) take precedence)
- 1/047
  - . of screw type
- 1/053
  - . of turbine type
- 1/06
  - with compressor of jet type, e.g. using liquid under pressure ({[F25B 1/005](#), } [F25B 1/10](#) take precedence)
- 1/08
  - . using vapour under pressure
- 1/10
  - with multi-stage compression (with cascade operation [F25B 7/00](#))
- 3/00 Self-contained rotary compression machines, i.e. with compressor, condenser, and evaporator rotating as a single unit**
- 5/00 Compression machines, plant, or systems, with several evaporator circuits, e.g. for varying refrigerating capacity** (with cascade operation [F25B 7/00](#))
- 5/02
  - arranged in parallel
- 5/04
  - arranged in series
- 6/00 Compression machines, plant, or systems, with several condenser circuits**
- 6/02
  - arranged in parallel
- 6/04
  - arranged in series
- 7/00 Compression machines, plant, or systems, with cascade operation, i.e. with two or more circuits, the heat from the condenser of one circuit being absorbed by the evaporator of the next circuit** ([F25B 9/00](#) takes precedence)
- 9/00 Compression machines, plant, or systems, in which the refrigerant is air or other gas of low boiling point**
- 9/002
  - {characterised by the refrigerant}
- 9/004
  - . {the refrigerant being air (air conditioning [F24F](#))}

- 9/006
  - . {the refrigerant containing more than one component ([F25B 9/004](#) takes precedence; refrigerant materials *per se* [C09K 5/00](#))}
- 9/008
  - . {the refrigerant being carbon dioxide}
- 9/02
  - using Joule-Thompson effect; using vortex effect
- 9/04
  - . using vortex effect
- 9/06
  - using expanders ([F25B 9/10](#) takes precedence)
- 9/065
  - . {using pressurised gas jets}
- 9/08
  - using ejectors ([F25B 9/10](#) takes precedence)
- 9/10
  - with several cooling stages
- 9/12
  - using <sup>3</sup>He-<sup>4</sup>He dilution
- 9/14
  - characterised by the cycle used, e.g. Stirling cycle ({engine plants with Vuilleumier-type cycles [F02G 1/0445](#))}
- 9/145
  - . {pulse-tube cycle}
- 11/00 Compression machines, plant, or systems, using turbines, e.g. gas turbines**
- 11/02
  - as expanders ([F25B 9/06](#) takes precedence)
- 11/04
  - . centrifugal type
- 13/00 Compression machines, plant or systems with reversible cycle** (defrosting cycles [F25B 47/02](#))

### Sorption machines, plant, or systems

- 15/00 Sorption machines, plant, or systems, operating continuously, e.g. absorption type**
- 15/002
  - {using the endothermic solution of salt}
- 15/004
  - {of rotary type}
- 15/006
  - {with cascade operation}
- 15/008
  - {with multi-stage operation ([F25B 15/006](#) takes precedence)}
- 15/02
  - without inert gas ({[F25B 15/004](#), [F25B 15/006](#), [F25B 15/008](#)}, [F25B 15/12](#), [F25B 15/14](#), [F25B 15/16](#) take precedence)
- 15/025
  - . {Liquid transfer means}
- 15/04
  - . the refrigerant being ammonia evaporated from aqueous solution ({[F25B 15/025](#) takes precedence})
- 15/06
  - . the refrigerant being water vapour evaporated from a salt solution, e.g. lithium bromide ({[F25B 15/025](#) takes precedence})
- 15/08
  - . the refrigerant being sulfuric acid ({[F25B 15/025](#) takes precedence})

- 15/09 . . the refrigerant being hydrogen desorbed from a hydride { (F25B 15/025 takes precedence) }
- 15/10 . with inert gas { (F25B 15/004, F25B 15/006, F25B 15/008), F25B 15/12, F25B 15/14, F25B 15/16 take precedence }
- 15/12 . with resorber { (F25B 15/004, F25B 15/006, F25B 15/008), F25B 15/14 take precedence }
- 15/14 . using osmosis { (F25B 15/004, F25B 15/006, F25B 15/008 take precedence) }
- 15/16 . using desorption cycle { (F25B 15/004, F25B 15/006, F25B 15/008 take precedence) }
- 17/00 Sorption machines, plant, or systems, operating intermittently, e.g. absorption or adsorption type**
- 17/02 . the absorbent or adsorbent being a liquid, e.g. brine (F25B 17/10 takes precedence)
- 17/04 . . with two or more boilers operating alternately
- 17/06 . . with the boiler and evaporator built-up as a unit in a tiltable or revolving arrangement
- 17/08 . the absorbent or adsorbent being a solid, e.g. salt (F25B 17/12 takes precedence)
- 17/083 . . {with two or more boiler-sorbers operating alternately }
- 17/086 . . {with two or more boiler-sorber/evaporator units }
- 17/10 . using the endothermic solution of salt
- 17/12 . using desorption of hydrogen from a hydride

**Machines, plant, or systems, with a single mode of operation, not covered by groups F25B 1/00 - F25B 17/00**

- 19/00 Machines, plant, or systems, using evaporation of a refrigerant but without recovery of the vapour**
- 19/005 . {the refrigerant being a liquefied gas }
- 19/02 . using fluid jet, e.g. of steam { (F25B 19/005 takes precedence) }
- 19/04 . . using liquid jet, e.g. of water
- 21/00 Machines, plant, or systems, using electric or magnetic effects { (magnetic refrigerating material H01F 1/012 and H01F 1/017) }**
- 21/02 . using Peltier effect; using Nernst-Ettinghausen effect (thermo-electric elements H01L 35/00, H01L 37/00)
- 21/04 . . reversible
- 23/00 Machines, plant, or systems, with a single mode of operation not covered by groups F25B 1/00 - F25B 21/00, e.g. using selective radiation effect**
- 23/003 . {using selective radiation effect }
- 23/006 . {boiling cooling systems }
- 25/00 Machines, plant, or systems, using a combination of modes of operation covered by two or more of the groups F25B 1/00 - F25B 23/00 (combinations of two or more modes of operation covered by a single main group, see the relevant group)**
- 25/005 . {using primary and secondary systems }
- 25/02 . Compression-sorption machines, plants, or systems
- 27/00 Machines, plant, or systems, using particular sources of energy (F25B 30/06 takes precedence)**
- 27/002 . {using solar energy (use of solar heat not otherwise provided for F24J 2/00) }
- 27/005 . . {in compression type systems }
- 27/007 . . {in sorption type systems }

- 27/02 . using waste heat, e.g. from internal-combustion engines
- 29/00 Combined heating and refrigeration systems, e.g. operating alternately or simultaneously**
- 29/003 . {of the compression type system }
- 29/006 . {of the sorption type system }
- 30/00 Heat pumps**
- 30/02 . of the compression type
- 30/04 . of the sorption type
- 30/06 . characterised by the source of low potential heat

**Component parts or details**

- 31/00 Compressor arrangements (compressors per se F04)**
- 31/002 . {lubrication (of compressors per se F04B, of machines or engines in general F01M) }
- 31/004 . . {oil recirculating arrangements }
- 31/006 . {cooling of compressor or motor (of compressors per se F04B 39/06) }
- 31/008 . . {by injecting a liquid (for compressors in general F04B 39/062) }
- 31/02 . of motor-compressor units
- 31/023 . . {with compressor of reciprocating-piston type }
- 31/026 . . {with compressor of rotary type }
- 33/00 Boilers; Analysers; Rectifiers (boiler-absorbers F25B 35/00)**
- 35/00 Boiler-absorbers, i.e. boilers usable for absorption or adsorption**
- 35/02 . using a liquid as sorbent, e.g. brine
- 35/04 . using a solid as sorbent
- 37/00 Absorbers; Adsorbers (boiler-absorbers F25B 35/00; separating processes involving the treatment of liquids with adsorbents B01D 15/00; separation of gases or vapours by adsorption B01D 53/02; separation of gases or vapours by absorption B01D 53/14; investigating using adsorption or absorption G01N 30/00; { (absorption or adsorption in general B01J 20/00) }**
- 39/00 Evaporators; Condensers**
- 39/02 . Evaporators
- 39/022 . . {with plate-like or laminated elements }
- 39/024 . . . {with elements constructed in the shape of a hollow panel (for heat exchange in general F28F 3/12) }
- 39/026 . . {specially adapted for sorption type systems }
- 39/028 . . {having distributing means }
- 39/04 . Condensers
- 40/00 Subcoolers, desuperheaters or superheaters**
- 40/02 . Subcoolers
- 40/04 . Desuperheaters
- 40/06 . Superheaters
- 41/00 Fluid-circulation arrangements, e.g. for transferring liquid from evaporator to boiler (pumps per se, sealings therefor F04)**
- 41/003 . {fluid line arrangements }
- 41/006 . {optical fluid control arrangements }
- 41/02 . using electro-osmosis
- 41/04 . Disposition of valves (valves per se F16K)

41/043	. . {in the circuit between evaporator and compressor}	2309/021	. . with a cryosurgical probe tip having a specific construction
41/046	. . {of fluid flow reversing valves}	2309/022	. . characterised by the expansion element
41/06	. Flow restrictors, e.g. capillary tubes; Disposition thereof	2309/023	. . with two stage expansion
41/062	. . {Expansion valves (regulating valves per se G05D)}	2309/06	. Compression machines, plant or systems characterised by the refrigerant being carbon dioxide
41/065	. . . {Float control valves}	2309/061	. . with cycle highest pressure above the supercritical pressure
41/067	. . {capillary tubes}	2309/14	. Compression machines, plant or systems characterised by the cycle used
<b>43/00</b>	<b>Arrangements for separating or purifying gases or liquids (in analysers or rectifiers F25B 33/00); Arrangements for vaporising the residuum of liquid refrigerant, e.g. by heat (F25B 40/00 takes precedence)</b>	2309/1401	. . Ericsson or Ericsson cycles
43/003	. {filters (in general B01D)}	2309/1402	. . Pulse-tube cycles with acoustic driver
43/006	. {accumulators}	2309/1403	. . Pulse-tube cycles with heat input into acoustic driver
43/02	. for separating lubricants from the refrigerant	2309/1404	. . Pulse-tube cycles with loudspeaker driven acoustic driver
43/04	. for withdrawing non-condensable gases	2309/1405	. . Pulse-tube cycles with travelling waves
43/043	. . {for compression type systems}	2309/1406	. . Pulse-tube cycles with pulse tube in co-axial or concentric geometrical arrangements
43/046	. . {for sorption type systems}	2309/1407	. . Pulse-tube cycles with pulse tube having in-line geometrical arrangements
<b>45/00</b>	<b>Arrangements for charging or discharging refrigerant</b>	2309/1408	. . Pulse-tube cycles with pulse tube having U-turn or L-turn type geometrical arrangements
<b>47/00</b>	<b>Arrangements for preventing or removing deposits or corrosion, not provided for in another subclass</b>	2309/1409	. . Pulse-tube cycles with pulse tube having special type of geometrical arrangements not being a coaxial, in-line or U-turn type
47/003	. {for preventing corrosion}	2309/1411	. . Pulse-tube cycles characterised by control details, e.g. tuning, phase shifting or general control
47/006	. {for preventing frost}	2309/1412	. . Pulse-tube cycles characterised by heat exchanger details
47/02	. Defrosting cycles	2309/1413	. . Pulse-tube cycles characterised by performance, geometry or theory
47/022	. . {hot gas defrosting}	2309/1414	. . Pulse-tube cycles characterised by pulse tube details
47/025	. . . {by reversing the cycle}	2309/1415	. . Pulse-tube cycles characterised by regenerator details
47/027	. . {for defrosting sorption type systems}	2309/1416	. . Pulse-tube cycles characterised by regenerator stack details
<b>49/00</b>	<b>Arrangement or mounting of control or safety devices (testing refrigerators G01M; control in general G05)</b>	2309/1417	. . Pulse-tube cycles without any valves in gas supply and return lines
49/005	. {of safety devices (F25B 49/02 and F25B 49/04 take precedence)}	2309/1418	. . Pulse-tube cycles with valves in gas supply and return lines
49/02	. for compression type machines, plant or systems	2309/14181	. . . the valves being of the rotary type
49/022	. . {Compressor control arrangements (in general F04B)}	2309/1419	. . Pulse-tube cycles with pulse tube having a basic pulse tube refrigerator [PTR], i.e. comprising a tube with basic schematic
49/025	. . {Motor control arrangements (motors per se H02K)}	2309/1421	. . Pulse-tube cycles characterised by details not otherwise provided for
49/027	. . {Condenser control arrangements}	2309/1422	. . Pulse tubes with basic schematic including a counter flow heat exchanger instead of a regenerative heat exchanger
49/04	. for sorption type machines, plant or systems	2309/1423	. . Pulse tubes with basic schematic including an inertance tube
49/043	. . {Operating continuously}	2309/1424	. . Pulse tubes with basic schematic including an orifice and a reservoir
49/046	. . {Operating intermittently}	2309/14241	. . . Pulse tubes with basic schematic including an orifice reservoir multiple inlet pulse tube
<b>2300/00</b>	<b>Special arrangements or features for refrigeration machines, plants or systems, combined heating and refrigeration systems or heat-pump systems</b>	2309/1425	. . Pulse tubes with basic schematic including several pulse tubes
<b>2309/00</b>	<b>Gas cycle refrigeration machines</b>	2309/1426	. . Pulse tubes with basic schematic including at the pulse tube warm end a so called warm end expander
2309/001	. with a linear configuration or a linear motor	2309/1427	. . Control of a pulse tube
2309/002	. with parallel working cold producing expansion devices in one circuit		
2309/003	. characterised by construction or composition of the regenerator		
2309/004	. using a compressor of the rotary type		
2309/005	. using an expander of the rotary type		
2309/006	. using a distributing valve of the rotary type		
2309/02	. using the Joule-Thompson effect		

- 2309/1428 . . Control of a Stirling refrigeration machine
- 2313/00 Compression machines, plant, or systems with reversible cycle not otherwise provided for**
- 2313/001 . with two or more accumulators
- 2313/002 . geothermal
- 2313/003 . Indoor unit with water as a heat sink or heat source
- 2313/004 . Outdoor unit with water as a heat sink or heat source
- 2313/005 . Outdoor unit expansion valves
- 2313/006 . two pipes connecting the outdoor side to the indoor side with multiple indoor units
- 2313/007 . three pipes connecting the outdoor side to the indoor side with multiple indoor units
- 2313/008 . Refrigerant heaters
- 2313/009 . indoor unit in circulation with outdoor unit in first operation mode, indoor unit in circulation with an other heat exchanger in second operation mode or outdoor unit in circulation with an other heat exchanger in third operation mode
- 2313/021 . Indoor unit or outdoor unit with auxiliary heat exchanger not forming part of the indoor or outdoor unit
- 2313/0211 . . the auxiliary heat exchanger being only used during defrosting
- 2313/0212 . . the auxiliary heat exchanger being only used during dehumidifying
- 2313/0213 . . the auxiliary heat exchanger being only used during heating
- 2313/0214 . . the auxiliary heat exchanger being used parallel to the indoor unit during heating operation
- 2313/0215 . . the auxiliary heat exchanger being used parallel to the outdoor heat exchanger during heating operation
- 2313/023 . using multiple indoor units
- 2313/0231 . . with simultaneous cooling and heating
- 2313/0232 . . with bypasses
- 2313/02321 . . . during cooling
- 2313/02322 . . . during defrosting
- 2313/02323 . . . during heating
- 2313/0233 . . in parallel arrangements
- 2313/02331 . . . during cooling
- 2313/02332 . . . during defrosting
- 2313/02333 . . . during dehumidification
- 2313/02334 . . . during heating
- 2313/0234 . . in series arrangements
- 2313/02341 . . . during cooling
- 2313/02342 . . . during defrosting
- 2313/02343 . . . during dehumidification
- 2313/02344 . . . during heating
- 2313/025 . using multiple outdoor units
- 2313/0251 . . being defrosted alternately
- 2313/0252 . . with bypasses
- 2313/02521 . . . during cooling
- 2313/02522 . . . during defrosting
- 2313/02523 . . . during heating
- 2313/0253 . . in parallel arrangements
- 2313/02531 . . . during cooling
- 2313/02532 . . . during defrosting
- 2313/02533 . . . during heating
- 2313/0254 . . in series arrangements
- 2313/02541 . . . during cooling
- 2313/02542 . . . during defrosting
- 2313/02543 . . . during heating
- 2313/027 . characterised by the reversing means
- 2313/0271 . . the compressor allows rotation in reverse direction
- 2313/0272 . . using bridge circuits of one-way valves
- 2313/02731 . . using one three-way valve
- 2313/02732 . . using two three-way valves
- 2313/02741 . . using one four-way valve
- 2313/02742 . . using two four-way valves
- 2313/02743 . . using three four-way valves
- 2313/0276 . . using six-way valves
- 2313/0279 . . using nine-way valves
- 2313/02791 . . using shut-off valves
- 2313/02792 . . using reversing valve changing the refrigerant flow direction due to pressure differences of the refrigerant and not by external actuation
- 2313/029 . Control issues
- 2313/0291 . . related to the pressure of the indoor unit
- 2313/0292 . . related to reversing valves
- 2313/0293 . . related to the indoor fan, e.g. controlling speed
- 2313/0294 . . related to the outdoor fan, e.g. controlling speed
- 2313/031 . Sensor arrangements
- 2313/0311 . . Pressure sensors near the expansion valve
- 2313/0312 . . Pressure sensors near the indoor heat exchanger
- 2313/0313 . . Pressure sensors near the outdoor heat exchanger
- 2313/0314 . . Temperature sensors near the indoor heat exchanger
- 2313/0315 . . Temperature sensors near the outdoor heat exchanger
- 2313/0316 . . Temperature sensors near the refrigerant heater
- 2315/00 Sorption refrigeration cycles or details thereof**
- 2315/001 . Crystallization prevention
- 2315/002 . Generator absorber heat exchanger [GAX]
- 2315/003 . Hydrates for sorption cycles
- 2315/004 . Inert heat-exchangers
- 2315/005 . Regeneration
- 2315/006 . Reversible sorption cycles
- 2315/007 . Parallel systems therefor
- 2321/00 Details of machines, plants, or systems, using electric or magnetic effects**
- 2321/001 . by using electro-caloric effects
- 2321/002 . by using magneto-caloric effects
- 2321/0021 . . with a static fixed magnet
- 2321/0022 . . with a rotating or otherwise moving magnet
- 2321/0023 . . with modulation, influencing or enhancing an existing magnetic field
- 2321/003 . by using thermionic electron cooling effects
- 2321/02 . using Peltier effects; using Nernst-Ettinghausen effects
- 2321/021 . . Control thereof
- 2321/0211 . . . of fans
- 2321/0212 . . . of electric power, current or voltage
- 2321/023 . . Mounting details thereof
- 2321/025 . . Removal of heat
- 2321/0251 . . . by a gas
- 2321/0252 . . . by liquids or two-phase fluids
- 2327/00 Refrigeration system using an engine for driving a compressor**
- 2327/001 . of the internal combustion type
- 2333/00 Details of boilers; Analysers; Rectifiers**

- 2333/001 . the generator or boiler having an analyser
- 2333/002 . the generator or boiler is heated electrically
- 2333/003 . the generator or boiler is heated by combustion gas
- 2333/004 . the generator or boiler uses an inert gas as pressure equalizing medium
- 2333/005 . the generator or boiler uses electromagnetic energy in the form of microwaves for desorbing the sorbate from the sorbate/sorbent compound
- 2333/0051 . . the energy is used for heating an auxiliary medium which is used as heating source for desorbing the sorbate from the sorbate/sorbent compound
- 2333/006 . the generator or boiler having a rectifier
- 2333/007 . the generator or boiler heated by heat exchangers with steam or hot water as heating fluid or by a secondary boiling-condensing heater
- 2339/00 Details of evaporators; Details of condensers**
- 2339/02 . Details of evaporators
- 2339/021 . . Evaporators in which refrigerant is sprayed on a surface to be cooled
- 2339/022 . . Evaporators constructed from a pair of plates forming a space in which is located a refrigerant carrying coil
- 2339/023 . . Evaporators consisting of one or several sheets on one face of which is fixed a refrigerant carrying coil
- 2339/024 . . Evaporators with refrigerant in a vessel in which is situated a heat exchanger
- 2339/0241 . . . having plate-like elements
- 2339/0242 . . . having tubular elements
- 2339/04 . Details of condensers
- 2339/041 . . of evaporative condensers
- 2339/042 . . of pcm condensers
- 2339/043 . . Condensers made by assembling plate-like or laminated elements
- 2339/044 . . Condensers with an integrated receiver
- 2339/0441 . . . containing a drier or a filter
- 2339/0442 . . . characterised by the mechanical fixation of the receiver to the header
- 2339/0443 . . . the receiver being positioned horizontally
- 2339/0444 . . . where the flow of refrigerant through the condenser receiver is split into two or more flows, each flow following a different path through the condenser receiver
- 2339/0445 . . . with throttle portions
- 2339/0446 . . . characterised by the refrigerant tubes connecting the header of the condenser to the receiver; Inlet or outlet connections to receiver
- 2339/045 . . Condensers made by assembling a tube on a plate-like element or between plate-like elements
- 2339/046 . . Condensers with refrigerant heat exchange tubes positioned inside or around a vessel containing water or pcm to cool the refrigerant gas
- 2339/047 . . Water-cooled condensers
- 2341/00 Details of ejectors not being used as compression device; Details of flow restrictors or expansion valves**
- 2341/001 . Ejectors not being used as compression device
- 2341/0011 . . Ejectors with the cooled primary flow at reduced or low pressure
- 2341/0012 . . Ejectors with the cooled primary flow at high pressure
- 2341/0013 . . Ejector control arrangements
- 2341/0014 . . Ejectors with a high pressure hot primary flow from a compressor discharge
- 2341/0015 . . using two or more ejectors
- 2341/0016 . . Ejectors for creating an oil recirculation
- 2341/06 . Details of flow restrictors or expansion valves
- 2341/061 . . Bidirectional expansion restrictors
- 2341/062 . . Capillary expansion valves
- 2341/063 . . Feed forward expansion valves
- 2341/064 . . Superheater expansion valves
- 2341/065 . . Electric expansion valves
- 2341/0651 . . . actuated by electric heating means, e.g. a heated bimetallic element
- 2341/0652 . . . being opened and closed cyclically, e.g. with pulse width modulation
- 2341/0653 . . . actuated by an electric motor
- 2341/066 . . Refrigeration circuits using more than one expansion valve
- 2341/0661 . . . arranged in parallel
- 2341/0662 . . . arranged in series
- 2341/067 . . Expansion valves having a pilot valve
- 2341/0671 . . . the pilot valve is electrically actuated
- 2341/068 . . Expansion valves combined with a sensor
- 2341/0681 . . . the sensor is heated
- 2341/0682 . . . the sensor contains sorbent materials
- 2341/0683 . . . the sensor is disposed in the suction line and influenced by the temperature or the pressure of the suction gas
- 2345/00 Details for charging or discharging refrigerants; Service stations therefor**
- 2345/001 . Charging refrigerant to a cycle
- 2345/002 . Collecting refrigerant from a cycle
- 2345/003 . Control issues for charging or collecting refrigerant to or from a cycle
- 2345/004 . with several tanks to collect or charge a cycle
- 2345/005 . Service stations therefor
- 2345/0051 . . having a carrying handle
- 2345/0052 . . having wheels
- 2345/006 . characterised by charging or discharging valves
- 2345/007 . characterised by the weighing of refrigerant or oil
- 2347/00 Details for preventing or removing deposits or corrosion**
- 2347/02 . Details of defrosting cycles
- 2347/021 . . Alternate defrosting
- 2347/022 . . Cool gas defrosting
- 2347/023 . . Set point defrosting
- 2400/00 General features or devices for refrigeration machines, plants or systems, combined heating and refrigeration systems or heat-pump systems, i.e. not limited to a particular subgroup of F25B**
- 2400/01 . Heaters
- 2400/02 . Centrifugal separation of gas, liquid or oil
- 2400/03 . Suction accumulators with deflectors
- 2400/04 . Refrigeration circuit bypassing means
- 2400/0401 . . for the compressor
- 2400/0403 . . for the condenser
- 2400/0405 . . for the desuperheater
- 2400/0407 . . for the ejector
- 2400/0409 . . for the evaporator
- 2400/0411 . . for the expansion valve or capillary tube
- 2400/0413 . . for the filter or drier
- 2400/0415 . . for the receiver



2400/0417	. . for the subcooler	2500/05	. Cost reduction
2400/0419	. . for the superheater	2500/06	. Damage
2400/05	. Compression system with heat exchange between particular parts of the system	2500/07	. Exceeding a certain pressure value in a refrigeration component or cycle
2400/051	. . between the accumulator and another part of the cycle	2500/08	. Exceeding a certain temperature value in a refrigeration component or cycle
2400/052	. . between the capillary tube and another part of the refrigeration cycle	2500/09	. Improving heat transfers
2400/053	. . between the storage receiver and another part of the system	2500/11	. Reducing heat transfers
2400/054	. . between the suction tube of the compressor and another part of the cycle	2500/12	. Sound
2400/06	. Several compression cycles arranged in parallel	2500/13	. Vibrations
2400/061	. . the capacity of the first system being different from the second	2500/14	. the presence of moisture in a refrigeration component or cycle
2400/07	. Details of compressors or related parts	2500/15	. Hunting, i.e. oscillation of controlled refrigeration variables reaching undesirable values
2400/071	. . Compressor mounted in a housing in which a condenser is integrated	2500/16	. Lubrication
2400/072	. . Intercoolers therefor	2500/17	. Size reduction
2400/073	. . Linear compressors	2500/18	. Optimization, e.g. high integration of refrigeration components
2400/074	. . with multiple cylinders	2500/19	. Calculation of parameters
2400/075	. . with parallel compressors	2500/21	. Reduction of parts
2400/0751	. . . the compressors having different capacities	2500/22	. Preventing, detecting or repairing leaks of refrigeration fluids
2400/076	. . having multiple cylinders driven by a rotating swash plate	2500/221	. . Preventing leaks from developing
2400/077	. . Compressor control units, e.g. terminal boxes, mounted on the compressor casing wall containing for example starter, protection switches or connector contacts	2500/222	. . Detecting refrigerant leaks
2400/08	. Refrigeration machines, plants and systems having means for detecting the concentration of a refrigerant	2500/23	. High amount of refrigerant in the system
2400/09	. Refrigeration machines, plants and systems having means for detecting the concentration of a sorbent solution	2500/24	. Low amount of refrigerant in the system
2400/11	. Drop catchers	2500/25	. Standardisation of apparatus or parts
2400/12	. Inflammable refrigerants	2500/26	. characterised by the startup of the refrigeration cycle
2400/121	. . using R1234	2500/27	. characterised by the stop of the refrigeration cycle
2400/13	. Economisers	2500/28	. Means for preventing liquid refrigerant entering into the compressor
2400/14	. Power generation using energy from the expansion of the refrigerant	2500/29	. High ambient temperatures
2400/141	. . the extracted power is not recycled back in the refrigerant circuit	2500/31	. Low ambient temperatures
2400/15	. Micro-electro-mechanical devices	2500/32	. Weight
2400/16	. Receivers	<b>2600/00</b>	<b>Control issues</b>
2400/161	. . arranged in parallel	2600/01	. Timing
2400/162	. . characterised by the plug or stop	2600/02	. Compressor control
2400/17	. Re-condensers	2600/021	. . Inverters therefor
2400/18	. Refrigerant conversion	2600/022	. . for multi-stage operation
2400/19	. Pumping down refrigerant from one part of the cycle to another part of the cycle, e.g. when the cycle is changed from cooling to heating, or before a defrost cycle is started	2600/023	. . controlling swash plate angles
2400/21	. Modules for refrigeration systems	2600/024	. . by controlling the electric parameters, e.g. current or voltage
2400/22	. Refrigeration systems for supermarkets	2600/025	. . by controlling speed
2400/23	. Separators	2600/0251	. . . with on-off operation
2400/24	. Storage receiver heat	2600/0252	. . . with two speeds
<b>2500/00</b>	<b>Problems to be solved</b>	2600/0253	. . . with variable speed
2500/01	. Geometry problems, e.g. for reducing size	2600/026	. . by controlling unloaders
2500/02	. Increasing the heating capacity of a reversible cycle during cold outdoor conditions	2600/0261	. . . external to the compressor
2500/03	. Cavitations	2600/0262	. . . internal to the compressor
2500/04	. Clogging	2600/027	. . by controlling pressure
		2600/0271	. . . the discharge pressure
		2600/0272	. . . the suction pressure
		2600/05	. Refrigerant levels
		2600/07	. Remote controls
		2600/11	. Fan speed control
		2600/111	. . of condenser fans
		2600/112	. . of evaporator fans
		2600/13	. Pump speed control
		2600/15	. during shut down
		2600/17	. by controlling the pressure of the condenser

2600/19	. Refrigerant outlet condenser temperature	2700/2107	. . of a Peltier element
2600/21	. Refrigerant outlet evaporator temperature	2700/2108	. . of a receiver
2600/23	. Time delays	2700/2109	. . of a separator
2600/25	. Control of valves	2700/2111	. . of a heat storage receiver
2600/2501	. . Bypass valves	2700/2113	. . of a suction accumulator
2600/2503	. . Condenser exit valves	2700/2115	. . of a compressor or the drive means therefor
2600/2505	. . Fixed-differential control valves	2700/21151	. . . at the suction side of the compressor
2600/2507	. . Flow-diverting valves	2700/21152	. . . at the discharge side of the compressor
2600/2509	. . Economiser valves	2700/21153	. . . of electronic components
2600/2511	. . Evaporator distribution valves	2700/21154	. . . of an inverter
2600/2513	. . Expansion valves	2700/21155	. . . of the oil
2600/2515	. . Flow valves	2700/21156	. . . of the motor
2600/2517	. . Head-pressure valves	2700/21157	. . . . at the coil or rotor
2600/2519	. . On-off valves	2700/2116	. . of a condenser
2600/2521	. . On-off valves controlled by pulse signals	2700/21161	. . . the fluid cooled by the condenser
2600/2523	. . Receiver valves	2700/21162	. . . of the refrigerant at the inlet of the condenser
2600/2525	. . Pressure relief valves	2700/21163	. . . of the refrigerant at the outlet of the condenser
<b>2700/00</b>	<b>Sensing or detecting of parameters; Sensors therefor</b>	2700/2117	. . of an evaporator
2700/01	. Sensors determining characteristics of the burner for a generator	2700/21171	. . . of the fluid cooled by the evaporator
2700/02	. Humidity	2700/21172	. . . . at the inlet
2700/03	. Oil level	2700/21173	. . . . at the outlet
2700/04	. Refrigerant level	2700/21174	. . . of the refrigerant at the inlet of the evaporator
2700/05	. Load shedding of a compressor	2700/21175	. . . of the refrigerant at the outlet of the evaporator
2700/06	. Piston positions of a compressor		
2700/11	. Sensor to detect if defrost is necessary		
2700/111	. . using an emitter and receiver, e.g. sensing by emitting light or other radiation and receiving reflection by a sensor		
2700/13	. Mass flow of refrigerants		
2700/131	. . at the outlet of a subcooler		
2700/133	. . through the condenser		
2700/1331	. . . at the inlet		
2700/1332	. . . at the outlet		
2700/135	. . through the evaporator		
2700/1351	. . . of the cooled fluid upstream or downstream of the evaporator		
2700/1352	. . . at the inlet		
2700/1353	. . . at the outlet		
2700/15	. Power, e.g. by voltage or current		
2700/151	. . of the compressor motor		
2700/17	. Speeds		
2700/171	. . of the compressor		
2700/172	. . of the condenser fan		
2700/173	. . of the evaporator fan		
2700/19	. Pressures		
2700/191	. . near an expansion valve		
2700/193	. . of the compressor		
2700/1931	. . . Discharge pressures		
2700/1932	. . . Oil pressures		
2700/1933	. . . Suction pressures		
2700/195	. . of the condenser		
2700/197	. . of the evaporator		
2700/21	. Temperatures		
2700/2101	. . in a bypass		
2700/2102	. . at the outlet of the gas cooler		
2700/2103	. . near a heat exchanger		
2700/2104	. . of an indoor room or compartment		
2700/2105	. . Oil temperatures		
2700/2106	. . of fresh outdoor air		