

CPC COOPERATIVE PATENT CLASSIFICATION

E05D HINGES OR OTHER SUSPENSION DEVICES FOR DOORS, WINDOWS OR WINGS

({foldable tables [A47B 3/00](#); hinged panels [A47B 5/00](#); foldable chairs [A47C 4/00](#); making hinges [B21D 53/40](#), [B21K 13/02](#); making holes for taking-up fittings [B27F 5/12](#); for vehicle tailboards [B60P 1/26](#); for refuse receptacles [B65F 1/1646](#) } ; pivotal connections in general [F16C 11/00](#) { ; mounting of stove or range doors [F24C 15/023](#); for folding flat displays of portable computers [G06F 1/1616](#)})

WARNING

The following IPC groups are not used in the CPC scheme. Subject matter covered by these groups is classified in the following CPC groups:

E05D 5/16	covered by	E05D 5/14
E05D 7/081	covered by	E05D 7/08
E05D 7/083	covered by	E05D 7/082
E05D 15/04	covered by	E05D 15/02 , E05D 15/28 , E05D 15/403
E05D 15/522	covered by	E05D 15/52
E05D 15/523	covered by	E05D 15/52
E05D 15/524	covered by	E05D 15/52

1/00	Pinless hinges; Substitutes for hinges	5/00	Construction of single parts, e.g. the parts for attachment
1/02	. made of one piece	5/02	. Parts for attachment, e.g. flaps
1/04	. with guide members shaped as circular arcs	5/0207	. . {for attachment to vehicles (E05D 5/043 , E05D 5/062 take precedence)}
2001/045	. . {for telescopic hinges}	5/0215	. . {for attachment to profile members or the like}
1/06	. consisting of two easily-separable parts	5/0223	. . . {with parts, e.g. screws, extending through the profile wall or engaging profile grooves}
3/00	Hinges with pins (E05D 7/08 takes precedence)}	5/023 {with parts extending through the profile wall}
3/02	. with one pin	5/0238 {with parts engaging profile grooves}
3/022	. . {allowing an additional lateral movement, e.g. for sealing}	5/0246	. . {for attachment to glass panels}
2003/025	. . {having three knuckles}	2005/0253	. . . {the panels having conical or stepped recesses}
2003/027	. . . {the end knuckles being mutually connected}	2005/0261	. . . {connecting two or more glass panels}
3/04	. . engaging three or more parts, e.g. sleeves, movable relatively to one another for connecting two or more wings to another member	2005/0269 {the panels being coplanar}
3/06	. with two or more pins (E05D 7/08 takes precedence)	5/0276	. . {for attachment to cabinets or furniture, the hinge having two or more pins (E05D 5/046 , E05D 5/065 , E05D 7/125 take precedence)}
3/08	. . for swing-doors, i.e. openable by pushing from either side	2005/0284	. . {for embedding in concrete or masonry}
3/10	. . with non-parallel pins	2005/0292	. . {for passing through insulating layers}
3/12	. . with two parallel pins and one arm	5/04	. Flat flaps
3/122	. . . {Gear hinges}	5/043	. . . {specially adapted for vehicles}
3/125	. . . {specially adapted for vehicles}	5/046	. . . {specially adapted for cabinets or furniture}
3/127 {for vehicle doors}	5/06	. Bent flaps
3/14	. . with four parallel pins and two arms	5/062	. . . {specially adapted for vehicles}
3/142	. . . {with at least one of the hinge parts having a cup-shaped fixing part, e.g. for attachment to cabinets or furniture (E05D 11/1021 takes precedence)}	5/065	. . . {specially adapted for cabinets or furniture}
3/145	. . . {specially adapted for vehicles}	2005/067	. . . {gooseneck shaped}
3/147 {for vehicle doors}	5/08	. of cylindrical shape
3/16	. . with seven parallel pins and four arms	5/10	. Pins, sockets or sleeves; Removable pins (E05D 15/522 takes precedence)
2003/163	. . . {Horizontal pivot-axis}	2005/102	. . {Pins}
2003/166	. . . {Vertical pivot-axis}	2005/104	. . . {characterised by the materials}
3/18	. . with sliding pins or guides	2005/106	. . . {with non-cylindrical portions}
3/183	. . . {with at least one of the hinge parts having a cup-shaped fixing part, e.g. for attachment to cabinets or furniture}	2005/108	. . . {with elastically deformable parts}
3/186	. . . {Scissors hinges, with two crossing levers and five parallel pins}	5/12	. . Securing pins in sockets, movably or not
		5/121	. . . {Screw-threaded pins}
		2005/122 {externally threaded}
		2005/124 {internally threaded}
		5/125	. . . {Non-removable, snap-fitted pins (removable snap-fitted pins E05D 7/1022 , E05D 7/1055)}

- 5/127 . . . {by forcing the pin into the socket ([E05D 5/125 takes precedence](#))}
- 5/128 . . . {the pin having a recess or through-hole engaged by a securing member}
- 5/14 . . Construction of sockets or sleeves
- 2005/145 . . . {with elastically deformable parts}
- 5/16 . . . to be secured without special attachment parts on the socket or sleeve
- 7/00 Hinges or pivots of special construction (used for special suspension arrangements [E05D 15/00](#); so as to be self-closing [E05F 1/06](#), [E05F 1/12](#); with means for raising wings before being turned [E05F 7/02](#))**
 - 7/0009 . {Adjustable hinges ([E05D 7/04 takes precedence](#))}
 - 7/0018 . . {at the hinge axis}
 - 7/0027 . . . {in an axial direction}
 - 2007/0036 {with axially fixed hinge pins}
 - 7/0045 . . . {in a radial direction}
 - 7/0054 {by means of eccentric parts}
 - 2007/0063 {Eccentric hinge pins}
 - 2007/0072 {with sliding sleeves}
 - 2007/0081 {with swinging or rolling sleeves}
 - 7/009 . {Elongate hinges, e.g. piano-hinges}
 - 7/02 . for use on the right-hand as well as the left-hand side; Convertible right-hand or left-hand hinges
 - 7/04 . Hinges adjustable relative to the wing or the frame
 - 7/0407 . . {the hinges having two or more pins and being specially adapted for cabinets or furniture}
 - 7/0415 . . {with adjusting drive means}
 - 7/0423 . . . {Screw-and-nut mechanisms ([E05D 7/0407](#), [E05D 7/043 take precedence](#))}
 - 7/043 . . {by means of dowel attachments}
 - 2007/0438 . . . {with bolts fixedly mounted on the hinge part}
 - 2007/0446 . . . {with threaded bolts fixedly mounted on the hinge part}
 - 2007/0453 . . . {with threaded sleeves}
 - 2007/0461 . . {in angular arrangement to the wing or the frame}
 - 2007/0469 . . {in an axial direction}
 - 2007/0476 . . {Pocket hinges}
 - 2007/0484 . . {in a radial direction}
 - 2007/0492 . . {in three directions}
 - 7/06 . to allow tilting of the members
 - 7/08 . for use in suspensions comprising two spigots placed at opposite edges of the wing, especially at the top and the bottom, e.g. trunnions ([E05D 15/266 takes precedence](#))}
 - 7/081 . . the pivot axis of the wing being situated near one edge of the wing, especially at the top and bottom, e.g. trunnions
 - 7/082 . . the pivot axis of the wing being situated at a considerable distance from the edges of the wing, {e.g. for balanced wings}
 - 7/083 . . . with a fixed pivot axis
 - 7/084 . . . with a movable pivot axis
 - 7/085 with two or more pivot axes, e.g. used at the same time
 - 7/086 . . . Braking devices structurally combined with hinges ([braking devices for windows per se E05F 5/00](#))
 - 7/10 . to allow easy separation {or connection} of the parts at the hinge axis ({[E05D 5/12](#) and [E05D 15/50 take precedence](#) } ; substitutes for hinges [E05D 1/06](#))
 - 7/1005 . . {by axially moving free pins, balls or sockets}
 - 7/1011 . . . {biased by free springs ([E05D 7/1016 takes precedence](#))}
 - 7/1016 . . . {requiring a specific angular position}
 - 7/1022 . . . {with snap-fitted pins}
 - 2007/1027 . . . {by axially moving free pins}
 - 2007/1033 . . . {by axially moving free balls}
 - 2007/1038 . . . {by axially moving free sockets}
 - 7/1044 . . {in an axial direction ([E05D 7/1005 takes precedence](#))}
 - 7/105 . . . {requiring a specific angular position}
 - 7/1055 . . . {with snap-fitted pins}
 - 7/1061 . . {in a radial direction ([E05D 7/1005 takes precedence](#))}
 - 7/1066 . . . {requiring a specific angular position}
 - 7/1072 {the pin having a non-circular cross-section}
 - 7/1077 . . . {with snap-fitted pins}
 - 7/1083 . . {facilitating simultaneous assembly of a plurality of hinges, e.g. for mounting heavy wings}
 - 2007/1088 . . . {using hinge pins having different lengths}
 - 2007/1094 . . {Guiding devices therefor}
 - 7/12 . to allow easy detachment of the hinge from the wing or the frame ({[E05D 15/507 takes precedence](#))}
 - 7/121 . . {specially adapted for vehicles}
 - 7/123 . . {specially adapted for cabinets or furniture}
 - 7/125 . . . {the hinge having two or more pins}
 - 2007/126 . . {in an axial direction}
 - 2007/128 . . {in a radial direction}
 - 7/14 . Hinges for safes
 - 9/00 Flaps or sleeves specially designed for making from particular material, e.g. hoop-iron, sheet metal, plastics**
 - 9/005 . {from plastics ([E05D 1/02 takes precedence](#))}
 - 11/00 Additional features or accessories of hinges {(edge protecting devices [E06B 3/88](#))}**
 - 11/0009 . {Templates for marking the position of fittings on wings or frames (implements for making doors, windows or frames [E04F 21/003](#))}
 - 11/0018 . {Anti-tamper devices}
 - 11/0027 . . {arranged on or near the hinge and comprising parts interlocking as the wing closes, e.g. security studs}
 - 2011/0036 . . . {near the hinge}
 - 2011/0045 . . . {on the hinge}
 - 11/0054 . {Covers, e.g. for protection}
 - 2011/0063 . . {for screw-heads or bolt-heads}
 - 2011/0072 . . {for the gap between hinge parts}
 - 11/0081 . {for transmitting energy, e.g. electrical cable routing}
 - 2011/009 . {Impact absorbing hinges for vehicle doors}
 - 11/02 . Lubricating arrangements
 - 11/04 . relating to the use of free balls as bearing-surfaces ([E05D 7/06 takes precedence](#))
 - 2011/045 . . {located in line with the hinge axis}
 - 11/06 . Devices for limiting the opening movement of hinges
 - 11/08 . Friction devices between relatively-movable hinge parts ([E05D 7/086 takes precedence](#))
 - 11/081 . . {with both radial and axial friction, e.g. conical friction surfaces}
 - 11/082 . . {with substantially radial friction, e.g. cylindrical friction surfaces}

- 11/084 . . . {the friction depending on direction of rotation or opening angle of the hinge}
- 2011/085 . . . {the friction depending on the opening angle}
- 11/087 . . {with substantially axial friction, e.g. friction disks}
- 2011/088 . . {with automatic disengagement}
- 11/10 . . Devices for preventing movement between relatively-movable hinge parts
- 11/1007 . . {with positive locking}
- 11/1014 . . {for maintaining the hinge in only one position, e.g. closed}
- 11/1021 . . . {the hinge having two or more pins and being specially adapted for cabinets or furniture}
- 11/1028 . . {for maintaining the hinge in two or more positions, e.g. intermediate or fully open}
- 2011/1035 . . . {with circumferential and evenly distributed detents around the pivot-axis}
- 11/1042 . . . {the maintaining means being a cam and a torsion bar, e.g. motor vehicle hinge mechanisms}
- 11/105 . . . {the maintaining means acting perpendicularly to the pivot axis}
- 11/1057 {specially adapted for vehicles
([E05D 11/1064](#) takes precedence)}
- 11/1064 {with a coil spring perpendicular to the pivot axis}
- 11/1071 {specially adapted for vehicles}
- 11/1078 . . . {the maintaining means acting parallel to the pivot}
- 11/1085 {specially adapted for vehicles}
- 2011/1092 . . {the angle between the hinge parts being adjustable}
- 13/00 Accessories for sliding or lifting wings, e.g. pulleys, safety catches** ({closers or openers for horizontally sliding wings [E05F 1/02](#), [E05F 1/08](#)}; counterbalance devices {for swinging wings} [E05F 1/00](#), [E05F 3/00](#))
- 13/003 . . {Anti-dropping devices ([E05D 13/1223](#), [E05D 13/1246](#), [E05D 13/1269](#), [E05D 13/1292](#) take precedence)}
- 13/006 . . {fixed to the wing, i.e. safety catches}
- 13/04 . . {Fasteners specially adapted for holding sliding wings open (for holding wings closed [E05C](#))}
- 13/06 . . {with notches for vertically sliding wings}
- 13/08 . . {acting by friction for vertically sliding wings}
- 13/10 . . {Counterbalance devices}
- 13/12 . . {with springs}
- 13/1207 . . . {with tension springs}
- 13/1215 {specially adapted for overhead wings
([E05D 13/1223](#) takes precedence)}
- 13/1223 {Spring safety devices}
- 13/123 . . . {with compression springs}
- 13/1238 {specially adapted for overhead wings
([E05D 13/1246](#) takes precedence)}
- 13/1246 {Spring safety devices}
- 13/1253 . . . {with canted-coil torsion springs}
- 13/1261 {specially adapted for overhead wings
([E05D 13/1269](#) takes precedence)}
- 13/1269 {Spring safety devices}
- 13/1276 . . . {with coiled ribbon springs, e.g. constant force springs ([E05D 13/1253](#) takes precedence)}
- 13/1284 {specially adapted for overhead wings
([E05D 13/1292](#) takes precedence)}
- 13/1292 {Spring safety devices}
- 13/14 . . {with weights}
- 13/145 . . . {specially adapted for overhead wings}
- 15/00 Suspension arrangements for wings** (arrangements of wings not characterised by the construction of the supporting means [E06B 3/32](#))
- 15/02 . . for revolving wings
- 15/04 . . with arms fixed on the wing pivoting about an axis outside of the wing
- 15/06 . . for wings sliding horizontally more or less in their own plane
- 15/0604 . . {allowing an additional movement ([E05D 15/10](#) takes precedence; raising wings before sliding [E05D 15/565](#))}
- 15/0608 {caused by track lay-out}
- 15/0613 {with multi-directional trolleys}
- 15/0617 . . {of cantilever type}
- 15/0621 . . {Details, e.g. suspension or supporting guides
([E05D 15/0604](#), [E05D 15/08](#) - [E05D 15/14](#) take precedence)}
- 15/0626 {for wings suspended at the top}
- 15/063 {on wheels with fixed axis}
- 15/0634 {with height adjustment}
- 15/0639 {by vertical bolts}
- 15/0643 {on balls or floating rollers}
- 15/0647 {on sliding blocks}
- 15/0652 {Tracks ([E05D 15/063](#) - [E05D 15/0647](#) and [E05D 15/0656](#) take precedence)}
- 15/0656 {Bottom guides}
- 15/066 . . . {for wings supported at the bottom}
- 15/0665 {on wheels with fixed axis}
- 15/0669 {with height adjustment}
- 15/0673 {by vertical bolts}
- 15/0678 {on balls or floating rollers}
- 15/0682 {on sliding blocks}
- 15/0686 {Tracks ([E05D 15/0665](#) - [E05D 15/0682](#) and [E05D 15/0691](#) take precedence)}
- 15/0691 {Top guides}
- 2015/0695 . . . {Magnetic suspension or supporting means}
- 15/08 . . consisting of two or more independent parts movable each in its own guides
- 15/10 . . movable out of one plane into a second parallel plane
- 15/1002 . . . {specially adapted for use in railway-cars or mass transit vehicles ([E05D 15/1007](#), [E05D 15/1023](#), [E05D 15/1044](#), [E05D 15/1068](#) take precedence)}
- 15/1005 . . . {the wing being supported on arms movable in horizontal planes}
- 15/1007 {specially adapted for use in railway-cars or mass transit vehicles}
- 15/101 {specially adapted for vehicles
([E05D 15/1007](#) takes precedence)}
- 15/1013 {specially adapted for windows}
- 15/1015 {with an intermediate tilt position}
- 2015/1018 . . . {with the track rotating around its axis}
- 15/1021 . . . {involving movement in a third direction, e.g. vertically}
- 15/1023 {specially adapted for use in railway-cars or mass transit vehicles}
- 2015/1026 . . . {accessories, e.g. sliding or rolling guides, latches}
- 2015/1028 . . . {with only the wing moving transversely}

2015/1031 {the wing supported on arms extending from the carriage}	15/246 {with additional guide rail for producing an additional movement}
2015/1034 {the carriage having means for preventing rotation of the wing}	15/248 {with lever arms for producing an additional movement}
2015/1036 {the arms being movable in vertical, e.g. transverse, planes}	15/26	. for folding wings
2015/1039 {the wing sliding transversely on the carriage}	15/262	. . {folding vertically}
15/1042	. . . {with transversely moving carriage (E05D 15/1065 takes precedence)}	15/264	. . {for bi-fold wings}
15/1044 {specially adapted for use in railway-cars or mass transit vehicles}	15/266	. . . {comprising two pivots placed at opposite edges of the wing}
15/1047 {specially adapted for vehicles (E05D 15/1044 takes precedence)}	2015/268	. . {the wings being successively folded}
2015/1049 {the carriage swinging or rotating in a transverse plane}	15/28	. supported on arms movable in horizontal plane
2015/1052 {transversely over-dimensioned track sections or carriage}	15/30	. . with pivoted arms and sliding guides
2015/1055 {with slanted or curved track sections or cams}	15/32	. . with two pairs of pivoted arms
2015/1057 {the carriage swinging or rotating in those track sections}	15/34	. . . with wings opening parallel to themselves
2015/106 {transversely orientated track sections}	15/36	. moving along slide-ways so arranged that one guide-member of the wing moves in a direction substantially perpendicular to the movement of another guide member
2015/1063 {disconnecting the carriage from the track}	15/38	. . for upwardly-moving wings, e.g. up-and-over doors
15/1065	. . . {with transversely moving track}	15/40	. supported on arms movable in vertical planes
15/1068 {specially adapted for use in railway-cars or mass transit vehicles}	15/401	. . {specially adapted for overhead wings (E05D 15/403 - E05D 15/46 take precedence)}
2015/1071 {the track being directly linked to the fixed frame, e.g. slidingly}	15/403	. . {with arms fixed on the wing pivoting about an axis outside the wing}
2015/1073 {rocking transversely}	15/405	. . {with curved arms fixed on the wing, rolling on a support}
2015/1076 {swinging transversely, e.g. on arms}	15/406	. . {with pivoted arms and sliding guides (E05D 15/42 , E05D 15/44 take precedence)}
2015/1078 {swinging or rotating in a horizontal plane}	15/408	. . . {with sliding guides fixed to the wing}
15/1081 {specially adapted for vehicles (E05D 15/1068 takes precedence)}	15/42	. . with pivoted arms and horizontally-sliding guides
2015/1084 {the carriage being directly linked to the fixed frame, e.g. slidingly}	15/425	. . . {specially adapted for overhead wings}
2015/1086 {swingingly, e.g. on arms}	15/44	. . with pivoted arms and vertically-sliding guides
2015/1089 {the carriage having means for preventing rotation of the wing}	15/445	. . . {specially adapted for overhead wings}
2015/1092 {the carriage swinging or rotating in curved track sections}	15/46	. . with two pairs of pivoted arms
2015/1094 {disconnecting itself from the track}	15/463	. . . {specially adapted for overhead wings}
2015/1097 {with the carriage and track forming a telescopic element}	15/466	. . . {specially adapted for windows}
15/12	. . consisting of parts connected at their edges	15/48	. allowing alternative movements (E05D 15/0604 takes precedence) ; for vertically-sliding wings E05D 15/22)
15/14	. . with movable arms situated in the plane of the wing	2015/482	. . {for panic doors}
15/16	. for wings sliding vertically more or less in their own plane	2015/485	. . {Swinging or sliding movements}
15/165	. . {Details, e.g. sliding or rolling guides (E05D 15/18 - E05D 15/24 take precedence)}	2015/487	. . {Tilting or swinging movements}
15/18	. . consisting of two or more independent parts, movable each in its own guides	15/50	. . for opening at either of two opposite edges {(hinges or pivots of special construction to allow easy separation or connection of the parts at the hinge axis E05D 7/10 ; to allow easy detachment of the hinge from the wing or the frame E05D 7/12)}
15/20	. . movable out of one plane into a second parallel plane	15/502	. . . {by axial separation of the hinge parts at the hinge axis}
15/22	. . allowing an additional movement (E05D 15/20 takes precedence)}	15/505	. . . {by radial separation of the hinge parts at the hinge axis}
2015/225	. . . {specially adapted for overhead wings}	15/507	. . . {by detachment of the hinge from the wing or the frame}
15/24	. . consisting of parts connected at their edges	15/52	. . for opening about a vertical as well as a horizontal axis
15/242	. . . {Hinge connections between the parts}	15/5202	. . . {with non-horizontally extending checks}
15/244	. . . {Upper part guiding means}	15/5205	. . . {with horizontally-extending checks}
		15/5208	. . . {with means for transmitting movements between vertical and horizontal sliding bars, rods or cables}
		15/5211	. . . {Concealed suspension fittings}

E05D

- 15/5214 . . . {Corner supports}
- 15/5217 . . . {Tilt-lock devices}
- 15/522 . . . with disconnecting means for the appropriate pivoting parts
- 15/523 using movable rods
- 15/524 Actuating mechanisms
- 15/526 . . . Safety devices {(E05D 15/5217 takes precedence)}
- 2015/5263 {acting parallel to the plane of the wing}
- 2015/5266 {acting perpendicular to the plane of the wing}
- 15/54 . . for opening both inwards and outwards
- 15/56 . with successive different movements {(raising wings before being turned E05F 7/02)}
- 15/565 . . {for raising wings before sliding}
- 15/58 . . with both swinging and sliding movements
- 15/581 . . . {the swinging axis laying in the sliding direction (E05D 15/1015 takes precedence)}
- 15/582 . . . {with horizontal swinging axis (E05D 15/581 takes precedence)}
- 15/583 {specially adapted for overhead wings}
- 2015/585 . . . {with stationary hinge parts}
- 2015/586 . . . {with travelling hinge parts}
- 2015/587 . . . {with axially separating hinge parts}
- 2015/588 . . . {with radially separating hinge parts}
- 2700/00 Hinges or other suspension devices especially for doors or windows**
- 2700/02 . Hinges with one pivot axis and one bearing surface
- 2700/04 . Hinges with one pivot axis and more than one bearing surface
- 2700/10 . Various door and window fittings, e.g. suspension devices for double hung windows or screens
- 2700/12 . Suspension devices for doors or windows movable in a direction perpendicular to their plane or pivotable about an axis being situated at a considerable distance from the edge of the wing by means of pivot arms