

# CPC COOPERATIVE PATENT CLASSIFICATION

**G01B MEASURING LENGTH, THICKNESS OR SIMILAR LINEAR DIMENSIONS; MEASURING ANGLES; MEASURING AREAS; MEASURING IRREGULARITIES OF SURFACES OR CONTOURS** {(measuring human body, [see the relevant places](#), where such exist, e.g. [A41H 1/00](#), [A43D 1/02](#), [A61B 5/103](#); measuring appliances combined with walking-sticks [A45B 3/08](#); sorting according to dimensions [B07](#); tool-setting or drawing instruments not specially modified for measuring [B23B 49/00](#), [B23Q 15/00](#) - [B23Q 17/00](#), [B43L](#); combinations of measuring devices with writing-appliances [B43K 29/08](#); geodetical, nautical or aeronautical measuring, surveying, rangefinding [G01C](#); photogrammetry [G01C 11/00](#); measuring force or stress, in general [G01L 1/00](#); investigating or analysing particle size, investigating or analysing surface area of porous material [G01N](#); measuring position, distance or direction, in general, by reception or emission of radiowaves or other waves and based on propagation effects, e.g. Doppler effect, propagation time, direction of propagation [G01S](#); geophysical measuring [G01V](#); measuring length or roll diameter of film in cameras or projectors [G03B 1/60](#); combinations of measuring devices with means for controlling or regulating [G05](#); methods or arrangements for converting the position of a manually-operated writing or tracing member into an electrical signal [G06K 11/00](#); measuring elapsed travel of recording medium in recording and playback equipment, sensing diameter of record in autochange gramophones [G11B](#); means structurally associated with electric rotary current collectors for indicating brush wear [H01R 39/58](#); indicating consumption of electrodes in arc lamps [H05B 31/34](#))}

## NOTES

1. This subclass covers measuring of position or displacement in terms of linear or angular dimensions.
2. In this subclass, the groups are distinguished by the means of measurement which is of major importance. Thus the mere application of other means for giving a final indication does not affect the classification.
3. Attention is drawn to the Notes following the title of class [G01](#).
4. Machines operated on similar principles to the hand-held devices specified in this subclass are classified with these devices.
5. Measuring arrangements or details thereof covered by two or more of groups [G01B 3/00](#) - [G01B 17/00](#) are classified in group [G01B 21/00](#) if no single other group can be selected as being predominantly applicable.

<b>1/00</b>	<b>Measuring instruments characterised by the selection of material therefor</b>	3/1002 . . . {Tape measures without casings}
		3/1005 . . . {Braking or locking members, i.e. means for preventing rotation or the tape or for holding the tape at a certain position; Damping means, i.e. means for absorbing shock due to rewinding of the tape; Winding mechanisms, e.g. springs, electrical motors, crank-handles}
<b>3/00</b>	<b>Instruments as specified in the subgroups and characterised by the use of mechanical measuring means</b> (arrangements for measuring particular parameters <a href="#">G01B 5/00</a> ; devices of general interest specially adapted or mounted for storing and repeatedly paying-out and re-storing lengths of material <a href="#">B65H 75/34</a> )	2003/1007 . . . . {Locking members}
		2003/101 . . . . {acting on the drum}
		2003/1012 . . . . {engaging the tape in a direction parallel to the tape itself}
3/002 . {Details}		2003/1015 . . . . {engaging the tape in a direction transversal to the tape itself}
3/004 . . {Scales; Graduations}		2003/1017 . . . . {acting on the whole coil}
3/006 . . . {having both coarse and fine graduation}		2003/102 . . . . {Damping means}
3/008 . . {Arrangements for controlling the measuring force}		2003/1023 . . . . {Winding mechanisms}
3/02 . Rulers or tapes with scales or marks for direct reading		2003/1025 . . . . {Hand operated, e.g. crank-handles}
3/04 . . rigid		2003/1028 . . . . {Electrical motors}
3/06 . . . folding		2003/103 . . . . {Springs}
3/08 . . . extensible		2003/1033 . . . . {Means for activating locking, braking or releasing of the tape, e.g. buttons}
3/10 . . flexible {, e.g. tape measures}		2003/1035 . . . . {by pivotal operation}
		2003/1038 . . . . {by translatory motion operation}
		3/1041 . . . {Casings, i.e. structures to contain the tape}
		2003/1043 . . . . {internal structure and constructional details}

## NOTE

{Group [G01B 3/1002](#) takes precedence over groups [G01B 3/1005](#) - [G01B 3/1084](#)}

2003/1046	. . . . {external shape; elements for generating an offset}	3/42	. . of limit-gauge type, i.e. "go/no-go" ( <a href="#">G01B 3/40 takes precedence</a> )
2003/1048	. . . . {mounting elements integral to the casing for fixing to external structures or for holding, e.g. handles}	3/44	. . . preadjustable for wear or tolerance
2003/1051	. . . . {plurality of tapes within the same casing}	3/46	. Plug gauges for internal dimensions with engaging surfaces which are at a fixed distance, although they may be preadjustable
2003/1053	. . . . {tape exit slot, e.g. shape or exit direction}	3/48	. . for internal screw-threads
3/1056	. . . {End-hooks; Attachment of end-hooks to the tape; Distal and proximal ends of the tape}	3/50	. . of limit-gauge type, i.e. "go/no-go" ( <a href="#">G01B 3/48 takes precedence</a> )
2003/1058	. . . {Manufacturing or assembling methods}	3/52	. . . preadjustable for wear or tolerance
3/1061	. . . {Means for reading or displaying length measurement}	3/56	. Gauges for measuring angles or tapers, e.g. conical calipers
2003/1064	. . . . {Windows, e.g. lens, glass or cross-hairs}	3/563	. . {Protractors ( <a href="#">for use in geodesy G01C 1/00; protractor heads for drawing machines B43L 13/08</a> )}
2003/1066	. . . . {Index sliding on tape}	3/566	. . {Squares}
2003/1069	. . . . {Electronic or mechanical displaying means}	<b>5/00</b>	<b>Measuring arrangements characterised by the use of mechanical means (instruments of the types covered by group G01B 3/00 per se G01B 3/00)</b>
3/1071	. . . {External support or attachment means, i.e. not provided in the tape measure itself}	5/0002	. {Arrangements for supporting, fixing or guiding the measuring instrument or the object to be measured}
2003/1074	. . . . {for the casing}	5/0004	. . {Supports ( <a href="#">in general F16M; G01B 5/025 takes precedence</a> )}
2003/1076	. . . . {for the end-hook}	5/0007	. . {Surface plates}
2003/1079	. . . . {for the tape itself}	5/0009	. . {Guiding surfaces; Arrangements compensating for non-linearity there-of}
3/1082	. . . {Details of the tape <a href="#">per se</a> , e.g. scale structure, indicia on scale, particular material for the tape}	5/0011	. {Arrangements for eliminating or compensation of measuring errors due to temperature or weight}
3/1084	. . . {Particular applications of tape measures or special adaptations thereto}	5/0014	. . {due to temperature ( <a href="#">on machine tools B23Q 11/0003</a> )}
2003/1087	. . . . {for illuminating}	5/0016	. . {due to weight ( <a href="#">on machine tools B23Q 11/001</a> )}
2003/1089	. . . . {for drawing, marking, cutting}	5/0018	. {for measuring key-ways}
2003/1092	. . . . {measuring instruments cooperating with the tape measure, e.g. bubble-type level}	5/0021	. {for measuring the volumetric dimension of an object}
2003/1094	. . . . {for calculating, recording, indicating; aide memoire}	5/0023	. {Measuring of sport goods, e.g. bowling accessories, golfclubs, game balls}
2003/1097	. . . . {Tape measures with an adhesive surface}	5/0025	. {Measuring of vehicle parts ( <a href="#">G01B 5/003 takes precedence</a> )}
3/11	. Chains for measuring length	5/0028	. . {Brakes, brakeshoes, clutches}
3/12	. Measuring wheels	5/003	. {Measuring of motor parts}
3/14	. Templates for checking contours ( <a href="#">(templates for mounting doors or windows E04F 21/0007)</a> )	5/0032	. . {Valves, actuating devices for valves}
3/16	. Compasses, i.e. with a pair of pivoted arms	5/0035	. {Measuring of dimensions of trees}
3/163	. . {without measuring scale}	5/0037	. {Measuring of dimensions of welds}
3/166	. . {provided with a measuring scale}	5/004	. for measuring coordinates of points
3/18	. Micrometers	5/008	. . using coordinate measuring machines
3/20	. Slide gauges	5/012	. . . Contact-making feeler heads therefor
3/205	. . {provided with a counter for digital indication of the measured dimension}	5/016	. . . . Constructional details of contacts
3/22	. Feeler-pin gauges, e.g. dial gauges ( <a href="#">for determining profiles G01B 5/20</a> )	5/02	. for measuring length, width or thickness ( <a href="#">G01B 5/004, G01B 5/08 take precedence</a> )
3/24	. . with open yoke, i.e. calipers	5/025	. . {Measuring of circumference; Measuring length of ring-shaped articles ( <a href="#">G01B 5/0035 takes precedence</a> )}
3/26	. . Plug gauges	5/04	. . specially adapted for measuring length or width of objects while moving
3/28	. . Depth gauges	5/043	. . . {for measuring length}
3/30	. Bars, blocks, or strips in which the distance between a pair of faces is fixed, although it may be preadjustable, e.g. end measure, feeler strip	5/046	. . . {for measuring width}
3/303	. . {pre-adjustable, e.g. by means of micrometerscrew}	5/06	. . for measuring thickness
3/306	. . . {with inclined slide plane}	5/061	. . . {height gauges}
3/32	. . Holders therefor	5/063	. . . . {provided with a slide which may be moved along a vertical support by means of a micrometer screw}
3/34	. Ring or other apertured gauges, e.g. "go/no-go" gauge		
3/36	. . for external screw-threads		
3/38	. Gauges with an open yoke and opposed faces, i.e. calipers, in which the internal distance between the faces is fixed, although it may be preadjustable		
3/40	. . for external screw-threads		

- 5/065 . . . . {provided with a slide which may be fixed along its vertical support in discrete calibrated position}
- 5/066 . . . {of coating}
- 5/068 . . . {of objects while moving ([G01B 5/066](#) takes precedence)}
- 5/08 . for measuring diameters {([G01B 5/0035](#) takes precedence; measuring radius of curvature [G01B 5/213](#))}
- 5/10 . . of objects while moving
- 5/12 . . internal diameters
- 5/14 . for measuring distance or clearance between spaced objects or spaced apertures ([G01B 5/24](#) takes precedence)
- 5/143 . . {between holes on a workpiece}
- 5/146 . . {measuring play on bearings}
- 5/16 . . between a succession of regularly spaced objects or regularly spaced apertures
- 5/163 . . . {of screw-threads}
- 5/166 . . . {of gear teeth}
- 5/18 . for measuring depth
- 5/20 . for measuring contours or curvatures
- 5/201 . . {for measuring roundness}
- 5/202 . . {of gears}
- 5/204 . . {of screw-threads}
- 5/205 . . {of turbine blades or propellers}
- 5/207 . . using a plurality of fixed, simultaneously operating transducers ([G01B 5/213](#) - [G01B 5/22](#) take precedence)
- 5/213 . . for measuring radius of curvature
- 5/22 . . Spherometers
- 5/24 . for measuring angles or tapers; for testing alignment of axes
- 5/241 . . {for measuring conicity}
- 5/242 . . {Sine bars; Sine plates}
- 5/243 . . {for measuring chamfer ([see G01B 3/56](#))}
- 5/245 . . for testing perpendicularity
- 5/25 . . for testing the alignment of axes
- 5/252 . . . for measuring eccentricity, i.e. lateral shift between two parallel axes
- 5/255 . . for testing wheel alignment
- 5/26 . for measuring areas, e.g. planimeter ([integrators in general G06G](#))
- 5/28 . for measuring roughness or irregularity of surfaces
- 5/285 . . {for controlling evenness}
- 5/30 . for measuring the deformation in a solid, e.g. mechanical strain gauge
- 7/00 Measuring arrangements characterised by the use of electric or magnetic means**
- 7/001 . {Constructional details of gauge heads ([G01B 7/012](#) takes precedence)}
- 7/002 . {Constructional details of contacts for gauges actuating one or more contacts ([G01B 7/016](#) takes precedence)}
- 7/003 . {for measuring position, not involving coordinate determination ([coordinate measuring G01B 7/004](#))}
- 7/004 . for measuring coordinates of points
- 7/008 . . using coordinate measuring machines
- 7/012 . . . Contact-making feeler heads therefor
- 7/016 . . . . Constructional details of contacts
- 7/02 . for measuring length, width or thickness ([G01B 7/004](#), [G01B 7/12](#) take precedence)
- 7/023 . . {for measuring distance between sensor and object ([G01B 7/082](#) and [G01B 7/102](#) take precedence)}
- 7/026 . . {for measuring length of cable, band or the like, which has been paid out, e.g. from a reel ([measuring length of objects while moving G01B 7/04](#))}
- 7/04 . . specially adapted for measuring length or width of objects while moving
- 7/042 . . . {for measuring length}
- 7/044 . . . . {using capacitive means}
- 7/046 . . . . {using magnetic means}
- 7/048 . . . {for measuring width}
- 7/06 . . for measuring thickness {([measuring during the manufacture of coatings C23C 14/54](#))}
- 7/063 . . . {using piezo-electric resonators}
- 7/066 . . . . {for measuring thickness of coating (apparatus or processes for the manufacture of piezo-electric or electrostrictive resonators for obtaining desired frequency [H03H 3/04](#))}
- 7/08 . . . {using capacitive means}
- 7/082 . . . . {Height gauges}
- 7/085 . . . . {for measuring thickness of coating}
- 7/087 . . . . {for measuring of objects while moving ([G01B 7/085](#) takes precedence)}
- 7/10 . . . {using magnetic means, e.g. by measuring change of reluctance}
- 7/102 . . . . {Height gauges}
- 7/105 . . . . {for measuring thickness of coating}
- 7/107 . . . . {for measuring objects while moving ([G01B 7/105](#) takes precedence)}
- 7/12 . for measuring diameters
- 7/125 . . {of objects while moving}
- 7/13 . . Internal diameters
- 7/14 . for measuring distance or clearance between spaced objects or spaced apertures ([G01B 7/30](#) takes precedence)
- 7/142 . . {between holes on a workpiece}
- 7/144 . . {Measuring play on bearings}
- 7/146 . . {Measuring on gear teeth}
- 7/148 . . {Measuring on screw threads}
- 7/15 . . being regularly spaced
- 7/16 . for measuring deformation in a solid, e.g. by resistance strain gauge
- 7/18 . . {using change in resistance}
- 7/20 . . . {formed by printed-circuit technique}
- 7/22 . . {using change in capacitance}
- 7/24 . . using change in magnetic properties
- 7/26 . for measuring depth
- 7/28 . for measuring contours or curvatures
- 7/281 . . {for measuring contour or curvature along an axis, e.g. axial curvature of a pipeline or along a series of feeder rollers}
- 7/282 . . {for measuring roundness}
- 7/283 . . {of gears}
- 7/284 . . {of screw-threads}
- 7/285 . . {of propellers or turbine blades}
- 7/286 . . {Spherometers}
- 7/287 . . using a plurality of fixed, simultaneously operating transducers ([G01B 7/293](#) takes precedence)
- 7/293 . . for measuring radius of curvature

- 7/30 . . for measuring angles or tapers; for testing the alignment of axes
- 7/305 . . for testing perpendicularity
- 7/31 . . for testing the alignment of axes
- 7/312 . . . for measuring eccentricity, i.e. lateral shift between two parallel axes
- 7/315 . . for testing wheel alignment
- 7/32 . for measuring areas ([integrators in general G06G](#))
- 7/34 . for measuring roughness or irregularity of surfaces
- 7/345 . . {for measuring evenness}
- 9/00 Instruments as specified in the subgroups and characterised by the use of optical measuring means (arrangements for measuring particular parameters G01B 11/00)**
- 9/02 . Interferometers {for determining dimensional properties of, or relations between, measurement objects}
- 9/02001 . . {characterised by manipulating or generating specific radiation properties}
- 9/02002 . . . {Frequency variation}
- 9/02003 . . . . {by using beat frequencies generated by mixing of two or more frequencies}
- 9/02004 . . . . {by using a continuous frequency sweep or scan}
- 9/02005 . . . . {by using discrete frequency stepping or switching}
- 9/02007 . . . {Two or more frequencies or sources used for interferometric measurement ([using only beat G01B 9/02003](#))}
- 9/02008 . . . . {by using a frequency comb}
- 9/02009 . . . . {by using two or more low coherence lengths using different or varying spectral width}
- 9/0201 . . . {using temporal phase variation}
- 9/02011 . . . {using temporal polarization variation}
- 9/02012 . . . {using temporal intensity variation}
- 9/02014 . . . . {by using pulsed light}
- 9/02015 . . {characterised by a particular beam path configuration}
- 9/02016 . . . {contacting two or more objects}
- 9/02017 . . . {contacting one object several times}
- 9/02018 . . . . {Multiple-pass interferometer, e.g. double pass}
- 9/02019 . . . . {contacting different points on same face of object}
- 9/02021 . . . . {contacting different faces of object, e.g. opposite faces}
- 9/02022 . . . {contacting one object by grazing incidence}
- 9/02023 . . . {Indirect probing of object, e.g. via influence on cavity or fibre}
- 9/02024 . . . {Measuring in transmission, i.e. light traverses the object}
- 9/02025 . . . {Interference between three or more discrete surfaces}
- 9/02027 . . . {Two or more interferometric channels or interferometers}
- 9/02028 . . . . {Two or more reference or object arms in one interferometer}
- 9/02029 . . . {Combination with non-interferometric systems, i.e. for measuring the object}
- 9/0203 . . . . {With imaging systems}
- 9/02031 . . . . {With non-optical systems, e.g. tactile}
- 9/02032 . . . {generating a spatial carrier frequency, e.g. by creating lateral or angular offset between reference and object beam ([shearing interferometers G01B 9/02098](#))}
- 9/02034 . . {characterised by particularly shaped beams or wavefronts}
- 9/02035 . . . {Shaping the focal point, e.g. elongated focus}
- 9/02036 . . . . {by using chromatic effects, e.g. a wavelength dependent focal point}
- 9/02037 . . . . {by generating a transverse line focus}
- 9/02038 . . . {Shaping the wavefront, e.g. generating a spherical wavefront}
- 9/02039 . . . . {by matching the wavefront with a particular object surface shape}
- 9/02041 . . {characterised by particular imaging or detection techniques}
- 9/02042 . . . {Confocal imaging}
- 9/02043 . . . {Imaging of the Fourier or pupil or back focal plane, i.e. angle resolved imaging}
- 9/02044 . . . {Imaging in the frequency domain, e.g. by using a spectrometer}
- 9/02045 . . . {using the Doppler effect}
- 9/02047 . . . {using digital holographic imaging, e.g. lensless phase imaging without hologram in the reference path}
- 9/02048 . . . {Rough and fine measurement}
- 9/02049 . . {characterised by particular mechanical design details}
- 9/0205 . . . {of probe head}
- 9/02051 . . . {Integrated design, e.g. on-chip or monolithic}
- 9/02052 . . . {Protecting, e.g. shock absorbing, arrangements}
- 9/02054 . . . {Hand held}
- 9/02055 . . {characterised by error reduction techniques}
- 9/02056 . . . {Passive error reduction, i.e. not varying during measurement, e.g. by constructional details of optics}
- 9/02057 . . . . {by using common path configuration, i.e. reference and object path almost entirely overlapping}
- 9/02058 . . . . {by particular optical compensation or alignment elements, e.g. dispersion compensation}
- 9/02059 . . . . {Reducing effect of parasitic reflections, e.g. cyclic errors}
- 9/02061 . . . . {Reducing or preventing effect of tilt or misalignment, e.g. of object or reference mirror}
- 9/02062 . . . {Active error reduction, i.e. varying with time}
- 9/02063 . . . . {by particular alignment of focus position, e.g. dynamic focussing in optical coherence tomography}
- 9/02064 . . . . {by particular adjustment of coherence gate, i.e. adjusting position of zero path difference in low coherence interferometry}
- 9/02065 . . . . . {using a second interferometer before or after measuring interferometer}
- 9/02067 . . . . {by electronic control systems, i.e. using feedback acting on optics or light}
- 9/02068 . . . . . {Auto-alignment of optical elements}
- 9/02069 . . . . . {Synchronization of light source or manipulator and detector}



- 9/0207 . . . {Error reduction by correction of the measurement signal based on independently determined error sources, e.g. using a reference interferometer}
- 9/02071 . . . . {by measuring path difference independently from interferometer}
- 9/02072 . . . . {by calibration or testing of interferometer}
- 9/02074 . . . . {of the detector}
- 9/02075 . . . {of particular errors}
- 9/02076 . . . . {Caused by motion}
- 9/02077 . . . . {of the object}
- 9/02078 . . . . {Caused by ambiguity}
- 9/02079 . . . . {Quadrature detection, i.e. detecting relatively phase-shifted signals}
- 9/02081 . . . . . {simultaneous quadrature detection, e.g. by spatial phase shifting}
- 9/02082 . . . . {Caused by speckles}
- 9/02083 . . {characterised by particular signal processing and presentation}
- 9/02084 . . . {Processing in the Fourier or frequency domain when not imaged in the frequency domain}
- 9/02085 . . . {Combining two or more images of different regions}
- 9/02087 . . . {Combining two or more images of the same region}
- 9/02088 . . . {Matching signals with a database}
- 9/02089 . . . {Displaying the signal, e.g. for user interaction}
- 9/0209 . . {Non-tomographic low coherence interferometers, e.g. low coherence interferometry, scanning white light interferometry, optical frequency domain interferometry or reflectometry}
- 9/02091 . . {Tomographic low coherence interferometers, e.g. optical coherence tomography}
- 9/02092 . . {Self-mixing interferometers, i.e. feedback of light from object into laser cavity}
- 9/02094 . . {Speckle interferometers, i.e. for detecting changes in speckle pattern}
- 9/02095 . . . {detecting deformation from original shape}
- 9/02096 . . . {detecting a contour or curvature}
- 9/02097 . . {Self-interferometers, i.e. the object beam interfering with a shifted version of itself}
- 9/02098 . . . {shearing interferometers}
- 9/021 . . using holographic techniques
- 9/023 . . . for contour producing  
([G01B 9/025](#) - [G01B 9/029](#) take precedence)
- 9/025 . . . Double exposure technique
- 9/027 . . . in real time
- 9/029 . . . by time averaging
- 9/04 . Measuring microscopes ([microscopes in general G02B 21/00](#))
- 9/06 . Measuring telescopes ([telescopes in general G02B 23/00](#))
- 9/08 . Optical projection comparators
- 9/10 . Goniometers for measuring angles between surfaces
- 11/00** **Measuring arrangements characterised by the use of optical means (instruments of the types covered by group [G01B 9/00](#) per se [G01B 9/00](#))**
- 11/002 . {for measuring two or more coordinates}
- 11/005 . . {coordinate measuring machines}
- 11/007 . . . {feeler heads therefor}
- 11/02 . for measuring length, width or thickness  
([G01B 11/08](#) takes precedence)
- 11/022 . . {by means of tv-camera scanning}
- 11/024 . . {by means of diode-array scanning}
- 11/026 . . {by measuring distance between sensor and object ([G01B 11/0608](#) takes precedence)}
- 11/028 . . {by measuring lateral position of a boundary of the object ([G01B 11/022](#), [G01B 11/024](#), [G01B 11/04](#) take precedence)}
- 11/03 . . by measuring coordinates of points
- 11/04 . . specially adapted for measuring length or width of objects while moving
- 11/043 . . . {for measuring length}
- 11/046 . . . {for measuring width}
- 11/06 . . for measuring thickness, e.g. of sheet material  
([thickness measurement by thermal means G01B 21/085](#))
- 11/0608 . . . {Height gauges}
- 11/0616 . . . {of coating}
- 11/0625 . . . . {with measurement of absorption or reflection}
- 11/0633 . . . . . {using one or more discrete wavelengths}
- 11/0641 . . . . . {with measurement of polarization}
- 11/065 . . . . . {using one or more discrete wavelengths}
- 11/0658 . . . . . {with measurement of emissivity or reradiation}
- 11/0666 . . . . {using an exciting beam and a detection beam including surface acoustic waves [SAW]}
- 11/0675 . . . . . {using interferometry}
- 11/0683 . . . . {measurement during deposition or removal of the layer}
- 11/0691 . . . {of objects while moving ([G01B 11/0616](#) takes precedence)}
- 11/08 . for measuring diameters
- 11/10 . . of objects while moving
- 11/105 . . . {using photoelectric detection means}
- 11/12 . . internal diameters
- 11/14 . for measuring distance or clearance between spaced objects or spaced apertures ([G01B 11/26](#) takes precedence; [rangefinders G01C](#))
- 11/16 . for measuring the deformation in a solid, e.g. optical strain gauge
- 11/161 . . {by interferometric means}
- 11/162 . . . {by speckle- or shearing interferometry}
- 11/164 . . . {by holographic interferometry}
- 11/165 . . {by means of a grating deformed by the object}
- 11/167 . . {by projecting a pattern on the object}
- 11/168 . . {by means of polarisation}
- 11/18 . . {using photoelastic elements}
- 11/20 . . {using brittle lacquer}
- 11/22 . for measuring depth
- 11/24 . for measuring contours or curvatures
- 11/2408 . . {for measuring roundness}
- 11/2416 . . {of gears ([optical projection profile comparators G01B 9/08](#))}
- 11/2425 . . {of screw-threads}
- 11/2433 . . {for measuring outlines by shadow casting}
- 11/2441 . . {using interferometry}
- 11/245 . . using a plurality of fixed, simultaneously operating transducers  
([G01B 11/2408](#) - [G01B 11/2425](#), } [G01B 11/255](#) take precedence)

- 11/25 . . by projecting a pattern, e.g. {one or more lines,} moiré fringes on the object ([G01B 11/255](#) takes precedence; image analysis for depth or shape recovery [G06T 7/50](#))
- 11/2504 . . . {Calibration devices}
- 11/2509 . . . {Color coding}
- 11/2513 . . . {with several lines being projected in more than one direction, e.g. grids, patterns}
- 11/2518 . . . {Projection by scanning of the object}
- 11/2522 . . . . {the position of the object changing and being recorded}
- 11/2527 . . . . {with phase change by in-plane movement of the pattern}
- 11/2531 . . . {using several gratings, projected with variable angle of incidence on the object, and one detection device}
- 11/2536 . . . {using several gratings with variable grating pitch, projected on the object with the same angle of incidence}
- 11/254 . . . {Projection of a pattern, viewing through a pattern, e.g. moiré}
- 11/2545 . . . {with one projection direction and several detection directions, e.g. stereo}
- 11/255 . . for measuring radius of curvature {(measuring diameter [G01B 11/08](#))}
- 11/26 . . for measuring angles or tapers; for testing the alignment of axes
- 11/27 . . for testing the alignment of axes {(means for centering or aligning a light guide within a ferrule [G02B 6/3834](#))}
- 11/272 . . . {using photoelectric detection means}
- 11/275 . . for testing wheel alignment
- 11/2755 . . . {using photoelectric detection means}
- 11/28 . . for measuring areas (integrators in general [G06G](#))
- 11/285 . . {using photoelectric detection means}
- 11/30 . . for measuring roughness or irregularity of surfaces
- 11/303 . . {using photoelectric detection means}
- 11/306 . . {for measuring evenness}
- 13/00 Measuring arrangements characterised by the use of fluids {(pressure regulation [G05D 16/00](#))}**
- 13/02 . . for measuring length, width or thickness ([G01B 13/08](#) takes precedence)
- 13/03 . . by measuring coordinates of points
- 13/04 . . specially adapted for measuring length or width of objects while moving
- 13/06 . . for measuring thickness, e.g. of sheet material
- 13/065 . . . {Height gauges}
- 13/08 . . for measuring diameters
- 13/10 . . internal diameters
- 13/12 . . for measuring distance or clearance between spaced objects or spaced apertures ([G01B 13/18](#) takes precedence)
- 13/14 . . for measuring depth
- 13/16 . . for measuring contours or curvatures
- 13/18 . . for measuring angles or tapers; for testing the alignment of axes
- 13/19 . . for testing the alignment of axes
- 13/195 . . for testing wheel alignment
- 13/20 . . for measuring areas, e.g. pneumatic planimeter (integrators in general [G06G](#))
- 13/22 . . for measuring roughness or irregularity of surfaces
- 13/24 . . for measuring the deformation in a solid

- 15/00 Measuring arrangements characterised by the use of wave or particle radiation ([G01B 9/00](#), [G01B 11/00](#) take precedence; {by radar technique [G01S](#)})**
- 15/02 . . for measuring thickness
- 15/025 . . {by measuring absorption}
- 15/04 . . for measuring contours or curvatures
- 15/045 . . {by measuring absorption}
- 15/06 . . for measuring the deformation in a solid
- 15/08 . . for measuring roughness or irregularity of surfaces
- 17/00 Measuring arrangements characterised by the use of subsonic, sonic or ultrasonic vibrations {(by sonar technique [G01S 15/00](#))}**
- 17/02 . . for measuring thickness
- 17/025 . . {for measuring thickness of coating}
- 17/04 . . for measuring the deformation in a solid, e.g. by vibrating string
- 17/06 . . for measuring contours or curvatures
- 17/08 . . for measuring roughness or irregularity of surfaces
- 21/00 Measuring arrangements or details thereof in so far as they are not adapted to particular types of measuring means of the preceding groups**
- NOTE**
- Measuring arrangements or details thereof covered by two or more of groups [G01B 3/00](#) - [G01B 17/00](#) are classified in this group if no single other group can be selected as being predominantly applicable.
- 21/02 . . for measuring length, width, or thickness ([G01B 21/10](#) takes precedence)
- 21/04 . . by measuring coordinates of points
- 21/042 . . . {Calibration or calibration artifacts ([G01B 3/30](#), [G01B 9/02072](#) take precedence)}
- 21/045 . . . {Correction of measurements ([G01B 9/02055](#) takes precedence)}
- 21/047 . . . {Accessories, e.g. for positioning, for tool-setting, for measuring probes}
- 21/06 . . specially adapted for measuring length or width of objects while moving {(unwinding or rewinding apparatus incorporating length measuring devices [B65H 16/025](#))}
- 21/065 . . . {for stretchable materials}
- 21/08 . . for measuring thickness
- 21/085 . . . {using thermal means}
- 21/10 . . for measuring diameters
- 21/12 . . of objects while moving
- 21/14 . . internal diameters {(of boreholes or wells [E21B 47/08](#))}
- 21/16 . . for measuring distance of clearance between spaced objects
- 21/18 . . for measuring depth
- 21/20 . . for measuring contours or curvatures, e.g. determining profile
- 21/22 . . for measuring angles or tapers; for testing the alignment of axes
- 21/24 . . for testing alignment of axes
- 21/26 . . for testing wheel alignment
- 21/28 . . for measuring areas (integrators in general [G06G](#))
- 21/30 . . for measuring roughness or irregularity of surfaces
- 21/32 . . for measuring the deformation in a solid

<b>2210/00</b>	<b>Aspects not specifically covered by any group under <a href="#">G01B</a>, e.g. of wheel alignment, caliper-like sensors</b>	<b>2290/00</b>	<b>Aspects of interferometers not specifically covered by any group under <a href="#">G01B 9/02</a></b>
2210/10	. Wheel alignment	2290/10	. Astronomic interferometers
2210/12	. . Method or fixture for calibrating the wheel aligner	2290/15	. Cat eye, i.e. reflection always parallel to incoming beam
2210/14	. . One or more cameras or other optical devices capable of acquiring a two-dimensional image	2290/20	. Dispersive element for generating dispersion
2210/143	. . . One or more cameras on each side of a vehicle in the main embodiment	2290/25	. Fabry-Perot in interferometer, e.g. etalon, cavity
2210/146	. . . Two or more cameras imaging the same area	2290/30	. Grating as beam-splitter
2210/16	. . Active or passive device attached to the chassis of a vehicle	2290/35	. Mechanical variable delay line
2210/18	. . Specially developed for using with motorbikes or other two-wheeled vehicles	2290/40	. Non-mechanical variable delay line
2210/20	. . Vehicle in a state of translatory motion	2290/45	. Multiple detectors for detecting interferometer signals
2210/22	. . Wheels in a state of motion supported on rollers, rotating platform or other structure substantially capable of only one degree of rotational freedom	2290/50	. Pupil plane manipulation, e.g. filtering light of certain reflection angles
2210/24	. . Specially developed for using with trucks or other heavy-duty vehicles	2290/55	. Quantum effects
2210/26	. . Algorithms, instructions, databases, computerized methods and graphical user interfaces employed by a user in conjunction with the wheel aligner	2290/60	. Reference interferometer, i.e. additional interferometer not interacting with object
2210/28	. . Beam projector and related sensors, camera, inclinometer or other active sensing or projecting device	2290/65	. Spatial scanning object beam
2210/283	. . . Beam projectors and related sensors	2290/70	. Using polarization in the interferometer
2210/286	. . . . Projecting a light pattern on the wheel or vehicle body		
2210/30	. . Reference markings, reflector, scale or other passive device		
2210/303	. . . fixed to the ground or to the measuring station		
2210/306	. . . Mirror, prism or other reflector		
2210/40	. Caliper-like sensors		
2210/42	. . with one or more detectors on a single side of the object to be measured and with a backing surface of support or reference on the other side		
2210/44	. . with detectors on both sides of the object to be measured		
2210/46	. . with one or more detectors on a single side of the object to be measured and with a transmitter on the other side		
2210/48	. . for measurement of a wafer		
2210/50	. Using chromatic effects to achieve wavelength-dependent depth resolution		
2210/52	. Combining or merging partially overlapping images to an overall image		
2210/54	. Revolving an optical measuring instrument around a body		
2210/56	. Measuring geometric parameters of semiconductor structures, e.g. profile, critical dimensions or trench depth		
2210/58	. Wireless transmission of information between a sensor or probe and a control or evaluation unit		
2210/60	. Unique sensor identification		
2210/62	. Support for workpiece air film or bearing with positive or negative pressure		
2210/64	. Interconnection or interfacing through or under capping or via rear of substrate in microsensors		
2210/66	. Rock or ground anchors having deformation measuring means		