

CPC COOPERATIVE PATENT CLASSIFICATION

F05B INDEXING SCHEME RELATING TO MACHINES OR ENGINES OTHER THAN NON-POSITIVE-DISPLACEMENT MACHINES OR ENGINES, TO WIND MOTORS, TO NON-POSITIVE DISPLACEMENT PUMPS, AND TO GENERATING COMBUSTION PRODUCTS OF HIGH PRESSURE OR HIGH VELOCITY

NOTE

This subclass constitutes an internal scheme for indexing only.

2200/00 Mathematical features

- 2200/10 . Basic functions
- 2200/11 . . Sum
- 2200/12 . . Subtraction
- 2200/13 . . Product
- 2200/14 . . Division
- 2200/15 . . Inverse
- 2200/20 . Special functions
- 2200/21 . . Root
- 2200/211 . . . Square root
- 2200/212 . . . Cubic root
- 2200/22 . . Power
- 2200/221 . . . Square power
- 2200/222 . . . Cubic power
- 2200/23 . . Logarithm
- 2200/24 . . exponential
- 2200/25 . . Hyperbolic trigonometric, e.g. sinh, cosh, tanh
- 2200/26 . . trigonometric
- 2200/261 . . . Sine
- 2200/262 . . . Cosine
- 2200/263 . . . Tangent
- 2200/264 . . . Cotangent
- 2200/30 . miscellaneous
- 2200/31 . . odd
- 2200/32 . . even
- 2200/33 . . bigger/smaller
- 2200/34 . . biggest/smallest
- 2200/35 . . first
- 2200/36 . . last

2210/00 Working fluid

NOTE

Indexing codes of group [F05B 2210/00](#) can be followed by a name for a specific working fluid preceded by the "+" sign, e.g. [F05B 2210/11](#) +water.

- 2210/10 . Kind or type
- 2210/11 . . liquid, i.e. incompressible
- 2210/12 . . gaseous, i.e. compressible
- 2210/13 . . mixed, e.g. two-phase fluid
- 2210/132 . . . Pumps with means for separating and evacuating the gaseous phase
- 2210/14 . . Refrigerants with particular properties, e.g. HFC-134a
- 2210/16 . Air or water being indistinctly used as working fluid, i.e. the machine can work equally with air or water without any modification
- 2210/18 . Air and water being simultaneously used as working fluid

- 2210/20 . Properties
- 2210/30 . Flow characteristics
- 2210/301 . . with Mach-number kept constant along the flow
- 2210/302 . . Pressure kept constant along the flow
- 2210/40 . Flow geometry or direction
- 2210/401 . . upwards due to the buoyancy of compressed air
- 2210/402 . . Axial inlet and radial outlet
- 2210/403 . . Radial inlet and axial outlet
- 2210/404 . . bidirectional, i.e. in opposite, alternating directions

2220/00 Application

- 2220/10 . in ram-jet engines or ram-jet driven vehicles
- 2220/20 . within closed fluid conduits, e.g. pipes
- 2220/25 . as advertisement
- 2220/30 . in turbines
- 2220/301 . . in steam turbines
- 2220/302 . . in gas turbines
- 2220/3021 . . . for a special turbine stage
- 2220/3022 the first stage of a turbine
- 2220/3023 an intermediate stage of the turbine
- 2220/3025 the last stage of the turbine
- 2220/303 . . . for aircraft propulsion, e.g. jet engines
- 2220/304 . . . to drive unshrouded, low solidity propeller
- 2220/305 . . . to drive unshrouded, high solidity propeller
- 2220/306 . . . to drive shrouded, low solidity propeller
- 2220/307 . . . to drive shrouded, high solidity propeller
- 2220/308 . . . providing direct vertical lift
- 2220/309 . . . in a helicopter
- 2220/31 . . in ram-air turbines ("RATS")
- 2220/32 . . in water turbines
- 2220/33 . . specially adapted for the fan of turbofan engines
- 2220/40 . in turbochargers
- 2220/50 . for auxiliary power units (APU's)
- 2220/60 . making use of surplus or waste energy
- 2220/602 . . with energy recovery turbines
- 2220/604 . . for domestic central heating or production of electricity
- 2220/61 . for hydrogen and/or oxygen production
- 2220/62 . for desalination
- 2220/64 . for aeration
- 2220/70 . in combination with
- 2220/702 . . a steam turbine
- 2220/704 . . a gas turbine
- 2220/706 . . an electrical generator
- 2220/7062 . . . of the direct current (D.C.) type
- 2220/7064 . . . of the alternating current (A.C.) type
- 2220/70642 of the synchronous type
- 2220/70644 of the asynchronous type, i.e. induction type
- 2220/70646 Double fed induction generators (DFIGs)

2220/7066	. . . via a direct connection, i.e. a gearless transmission	2230/61	. . . using auxiliary equipment for lifting or holding (hoisting on to a stationary structure with provisions on the structure itself F05B 2240/916)
2220/7068	. . . equipped with permanent magnets	2230/6102	. . . carried on a floating platform
2220/707	. . . of the linear type	2230/70	. Disassembly methods
2220/708	. . Photoelectric means, i.e. photovoltaic or solar cells	2230/80	. Repairing, retrofitting or upgrading methods
2220/709	. . Piezoelectric means	2230/90	. Coating; Surface treatment (manufacture with deposition of material F05B 2220/30)
2220/80	. in supersonic vehicles excluding hypersonic vehicles or ram, scram or rocket propulsion	2240/00	Components
2220/90	. in vehicles adapted for vertical or short take off and landing (v/stol vehicles), (gas turbines providing direct vertical lift F05B 2220/308)		NOTE
2230/00	Manufacture		Components are the basic elements of construction.
	NOTE		
	Manufacture comprises also treatment, assembly or disassembly methods, repairing, handling or the like.	2240/10	. Stators
2230/10	. by removing material	2240/11	. . Shroud seal segments
2230/101	. . by electrochemical methods	2240/12	. . Fluid guiding means, e.g. vanes
2230/102	. . by spark erosion methods	2240/121	. . . Baffles or ribs
2230/103	. . using lasers	2240/122	. . . Vortex generators, turbulators, or the like, for mixing (by creating turbulence F05B 2260/222)
2230/104	. Micromachining	2240/123	. . . Nozzles
2230/20	. essentially without removing material	2240/1231 Plug nozzles
2230/21	. . by casting	2240/124	. . . Cascades, i.e. assemblies of similar profiles acting in parallel
2230/211	. . . by precision casting, e.g. microfusing or investment casting	2240/13	. . to collect or cause flow towards or away from turbines
2230/22	. . by sintering	2240/131	. . . by means of vertical structures, i.e. chimneys
2230/23	. . by permanently joining parts together	2240/132	. . . creating a vortex or tornado effect
2230/232	. . . by welding	2240/133	. . . with a convergent-divergent guiding structure, e.g. a Venturi conduit
2230/233 Electron beam welding	2240/14	. . Casings, housings, nacelles, gondels or the like, protecting or supporting assemblies within
2230/234 Laser welding	2240/142	. . . in the form of a standard ISO container
2230/235 Tig/Mig welding	2240/20	. Rotors
2230/236 Diffusion bonding	2240/201	. . using the Magnus-effect
2230/237 Brazing	2240/202	. . with adjustable area of intercepted fluid
2230/238 Soldering	2240/2021	. . . by means of telescoping blades
2230/239 Inertia or friction welding	2240/2022	. . . by means of tethering or coning blades
2230/24	. . by extrusion	2240/2023	. . . by means of radially reefing blades
2230/25	. . by forging	2240/21	. . for wind turbines
2230/26	. . by rolling	2240/211	. . . with vertical axis
2230/30	. with deposition of material	2240/212 of the Darrieus type
2230/31	. . Layer deposition	2240/213 of the Savonius type
2230/311	. . . by torch or flame spray	2240/214 of the Musgrove or "H"-type
2230/312	. . . by plasma spray	2240/215 of the panemone or "vehicle ventilator" type
2230/313	. . . by physical vapour deposition	2240/216 of the anemometer type
2230/314	. . . by chemical vapour deposition	2240/217 of the crossflow- or "Banki"- or "double action" type
2230/40	. Heat treatment	2240/218 with horizontally hinged vanes
2230/41	. . Hardening; Annealing	2240/221	. . . with horizontal axis
2230/50	. Building or constructing in particular ways	2240/2211 of the multibladed, low speed, e.g. "American farm" type
2230/502	. . using existing or "off the shelf" parts, e.g. using standardised turbocharger elements	2240/2212 perpendicular to wind direction
2230/60	. Assembly methods	2240/2213 and with the rotor downwind from the yaw pivot axis
2230/601	. . using limited numbers of standard modules which can be adapted by machining	2240/231	. . . driven by aerodynamic lift effects
2230/604	. . using positioning or alignment devices for aligning or centering, e.g. pins	2240/232 driven by drag
2230/606	. . . using maintaining alignment while permitting differential dilatation	2240/24	. . for turbines
2230/608	. . . for adjusting the position or the alignment, e.g. wedges or excenters	2240/241	. . . of impulse type
		2240/2411 Pelton type
		2240/242	. . . of reaction type
		2240/243	. . . of the Archimedes screw type

F05B

2240/244	. . . of the cross-flow, e.g. Banki, Ossberger type	2240/932	. . . which is a catamaran-like structure
2240/30	. . Characteristics of rotor blades, i.e. of any element transforming dynamic fluid energy to or from rotational energy and being attached to a rotor	2240/94	. . on a movable wheeled structure
2240/301	. . . Cross-section characteristics	2240/941	. . . which is a land vehicle
2240/302	. . . Segmented or sectional blades	2240/95	. . offshore
2240/31	. . . of changeable form or shape	2240/96	. . as part of a wind farm
2240/311	. . . flexible or elastic	2240/97	. . on a submerged structure
2240/312 capable of being reefed	2240/98	. . which is inflatable
2240/3121 around an axis orthogonal to rotor rotational axis	2240/99	. characterised by colour or colour patterns
2240/313 with adjustable flow intercepting area (F05B 2240/312 takes precedence)	2250/00	Geometry
2240/32	. . . with roughened surfaces		NOTE
2240/33	. . Shrouds which are part of or which are rotating with the rotor		Geometry indicates the shape or form of a component or the configuration or arrangement of components in a machine or in a plant.
2240/34	. . with auxiliary or secondary rotors attached to blades of main rotor	2250/02	. variable
2240/35	. Combustors or associated equipment	2250/10	. two-dimensional
2240/36	. . Fuel vaporizer	2250/11	. . triangular
2240/40	. Use of a multiplicity of similar components	2250/12	. . rectangular
2240/50	. Bearings	2250/121	. . . square
2240/51	. . magnetic	2250/13	. . trapezial
2240/511	. . . with permanent magnets	2250/131	. . . polygonal
2240/515	. . . electromagnetic	2250/132	. . . hexagonal
2240/52	. . Axial thrust bearings	2250/14	. . elliptical
2240/53	. . Hydrodynamic or hydrostatic bearings	2250/141	. . . circular
2240/54	. . Radial bearings	2250/15	. . spiral
2240/57	. Seals	2250/16	. . parabolic
2240/571	. . Brush seals	2250/17	. . hyperbolic
2240/572	. . Leaf seals	2250/18	. . patterned
2240/60	. Shafts	2250/181	. . . ridged
2240/61	. . hollow	2250/182	. . . crenellated, notched
2240/62	. . flexible	2250/183	. . . zigzag
2240/63	. . Glands for admission or removal of fluids from shafts	2250/184	. . . sinusoidal
2240/70	. Slinger plates or washers	2250/19	. . machined; miscellaneous
2240/80	. Platforms for stationary or moving blades	2250/191	. . . perforated
2240/801	. . cooled platforms	2250/192	. . . beveled
2240/90	. Mounting on supporting structures or systems	2250/193	. . . milled
2240/91	. . on a stationary structure	2250/20	. three-dimensional
2240/911	. . . already existing for a prior purpose	2250/21	. . pyramidal
2240/9111 which is a chimney	2250/22	. . parallelepipedic
2240/9112 which is a building	2250/221	. . . cubic
2240/9113 which is a roadway, rail track, or the like for recovering energy from moving vehicles	2250/23	. . prismatic
2240/912	. . . on a tower	2250/231	. . . cylindrical
2240/9121 on a lattice tower	2250/232	. . . conical
2240/913	. . . on a mast	2250/24	. . ellipsoidal
2240/914	. . . on an inflatable structure	2250/241	. . . spherical
2240/915	. . . which is vertically adjustable	2250/25	. . helical
2240/9151 telescopically	2250/26	. . paraboloidal
2240/9152 by being hinged	2250/27	. . hyperboloidal
2240/91521 at ground level	2250/28	. . patterned
2240/916	. . . with provision for hoisting onto the structure	2250/281	. . . threaded
2240/917	. . . attached to cables	2250/282	. . . Cubic pattern
2240/92	. . on an airborne structure	2250/283	. . . Honeycomb
2240/921	. . . kept aloft due to aerodynamic effects	2250/29	. . machined; miscellaneous
2240/922	. . . kept aloft due to buoyancy effects	2250/291	. . . hollowed
2240/923	. . . which is a vehicle	2250/292	. . . tapered
2240/93	. . on a structure floating on a liquid surface	2250/293	. . . lathed, e.g. rotation symmetrical
2240/931	. . . which is a vehicle	2250/30	. Arrangement of components
		2250/31	. . according to the direction of their main axis or their axis of rotation
		2250/311	. . . the axes being in line
		2250/312	. . . the axes being parallel to each other

2250/313	. . . the axes being perpendicular to each other	2260/211	. . by intercooling, e.g. during a compression cycle
2250/314	. . . the axes being inclined in relation to each other	2260/212	. . . by water injection
2250/315	. . . the main axis being substantially vertical	2260/221	. . Improvement of heat transfer
2250/32	. . according to their shape	2260/222	. . . by creating turbulence (vortex generators, turbulators or the like for mixing F05B 2240/122)
2250/321	. . . asymptotic	2260/224	. . . by increasing the heat transfer surface
2250/322	. . . tangential	2260/2241 using fins or ribs
2250/323	. . . convergent	2260/231	. . Preventing heat transfer
2250/324	. . . divergent	2260/232	. . characterised by the cooling medium
2250/33	. . symmetrical	2260/233	. . . the medium being steam
2250/34	. . translated	2260/24	. . for draft enhancement in chimneys, using solar or other heat sources
2250/35	. . rotated	2260/30	. . Retaining components in desired mutual position
2250/36	. . in inner-outer relationship, e.g. shaft-bearing arrangements	2260/301	. . Retaining bolts or nuts
2250/40	. Movement of component	2260/3011	. . . of the frangible or shear type
2250/41	. . with one degree of freedom	2260/302	. . by means of magnetic or electromagnetic forces
2250/411	. . . in rotation	2260/303	. . with a bayonet coupling
2250/42	. . with two degrees of freedom	2260/304	. . Balancing of radial or axial forces on regenerative rotors
2250/43	. . with three degrees of freedom	2260/305	. . Reducing friction between regenerative impeller discs and casing walls
2250/50	. Inlet or outlet	2260/40	. Transmission of power
2250/501	. . Inlet	2260/402	. . through friction drives
2250/5011	. . . augmenting, i.e. with intercepting fluid flow cross sectional area greater than the rest of the machine behind the inlet	2260/4021	. . . through belt drives
2250/5012	. . . concentrating only, i.e. with intercepting fluid flow cross sectional area not greater than the rest of the machine behind the inlet	2260/4022	. . . through endless chains
2250/502	. . Outlet	2260/4023	. . . through a friction clutch
2250/503	. . of regenerative pumps	2260/403	. . through the shape of the drive components
2250/60	. Structure; Surface texture	2260/4031	. . . as in toothed gearing
2250/61	. . corrugated	2260/40311 of the epicyclic, planetary or differential type
2250/611	. . . undulated	2260/404	. . through magnetic drive coupling
2250/62	. . smooth	2260/4041	. . . the driven magnets encircling the driver magnets
2250/621	. . . polished	2260/406	. . through hydraulic systems
2250/70	. Shape	2260/407	. . through piezoelectric conversion
2250/71	. . curved	2260/408	. . through magnetohydrodynamic conversion
2250/711	. . . convex	2260/42	. Storage of energy
2250/712	. . . concave	2260/421	. . in the form of rotational kinetic energy, e.g. in flywheels
2250/713	. . . inflexed	2260/50	. Kinematic linkage, i.e. transmission of position
2250/72	. . symmetric	2260/502	. . involving springs
2250/73	. . asymmetric	2260/503	. . using gears
2250/80	. Size or power range of the machines	2260/5032	. . . of the bevel or angled type
2250/82	. . Micromachines	2260/504	. . using flat or V-belts and pulleys
2250/84	. . Nanomachines (Nanotechnology for interacting, sensing or actuating B82Y 15/00)	2260/505	. . using chains and sprockets; using toothed belts
2250/86	. . Megamachines	2260/506	. . using cams or eccentrics
2260/00	Function	2260/507	. . using servos, independent actuators, etc.
2260/02	. Transport, e.g. specific adaptations or devices for conveyance (transport of wind turbines or equipments therefore F03D 13/40)	2260/60	. Fluid transfer
2260/10	. Particular cycles	2260/601	. . using an ejector or a jet pump
2260/20	. Heat transfer, e.g. cooling	2260/602	. . Drainage
2260/201	. . by impingement of a fluid	2260/603	. . . of leakage having past a seal (seals F05B 2240/57 ; glands F05B 2240/63)
2260/202	. . by film cooling	2260/604	. . Vortex non-clogging type pumps
2260/203	. . by transpiration cooling	2260/63	. . Preventing clogging or obstruction of flow paths by dirt, dust, or foreign particles
2260/205	. . Cooling fluid recirculation, i.e. after having cooled one or more components the cooling fluid is recovered and used elsewhere for other purposes	2260/64	. . Aeration, ventilation, dehumidification or moisture removal of closed spaces
2260/207	. . using a phase changing mass, (e.g. heat absorbing by melting or boiling)	2260/70	. Adjusting of angle of incidence or attack of rotating blades
2260/208	. . using heat pipes	2260/71	. . as a function of flow velocity
2260/209	. . using vortex tubes	2260/72	. . by turning around an axis parallel to the rotor centre line

- 2260/74 . . by turning around an axis perpendicular the rotor centre line
- 2260/75 . . the adjusting mechanism not using auxiliary power sources ("servos")
- 2260/76 . . the adjusting mechanism using auxiliary power sources
- 2260/77 . . the adjusting mechanism driven or triggered by centrifugal forces
- 2260/78 . . the adjusting mechanism driven or triggered by aerodynamic forces
- 2260/79 . . Bearing, support or actuation arrangements therefor
- 2260/80 . Diagnostics
- 2260/82 . Forecasts
- 2260/821 . . Parameter estimation or prediction
- 2260/8211 . . . of the weather
- 2260/83 . Testing, e.g. methods, components or tools therefor
- 2260/84 . Modeling or simulation
- 2260/845 . Redundancy
- 2260/85 . Starting
- 2260/90 . Braking
- 2260/901 . . using aerodynamic forces, i.e. lift or drag
- 2260/9011 . . . of the tips of rotor blades
- 2260/902 . . using frictional mechanical forces
- 2260/903 . . using electrical or magnetic forces
- 2260/904 . . using hydrodynamic forces
- 2260/95 . Preventing corrosion ([coating or surface treatment F05B 2230/90](#))
- 2260/96 . Preventing, counteracting or reducing vibration or noise
- 2260/962 . . my means creating "anti-noise"
- 2260/964 . . by damping means
- 2260/966 . . by correcting static or dynamic imbalance
- 2260/97 . Reducing windage losses
- 2260/972 . . in radial flow machines
- 2260/98 . Lubrication
- 2260/99 . Radar absorption
- 2270/00 Control**
- 2270/10 . Purpose of the control system
- 2270/101 . . to control rotational speed (n)
- 2270/1011 . . . to prevent overspeed
- 2270/1012 . . . to prevent underspeed
- 2270/1013 . . . of different spools or shafts
- 2270/1014 . . . to keep rotational speed constant
- 2270/1016 . . in variable speed operation
- 2270/102 . . to control acceleration (u)
- 2270/1021 . . . by keeping it below damagingly high values
- 2270/1022 . . . by making it as high as possible
- 2270/103 . . to affect the output of the engine
- 2270/1031 . . . Thrust
- 2270/1032 . . . Torque
- 2270/1033 . . . Power (if explicitly mentioned)
- 2270/104 . . to match engine to driven device
- 2270/1041 . . . in particular the electrical frequency of driven generator
- 2270/105 . . to improve fuel economy
- 2270/1051 . . . in particular at idling speed
- 2270/106 . . to produce clean exhaust gases
- 2270/1061 . . . with as little smoke as possible
- 2270/1062 . . . with as little NOx's as possible
- 2270/1063 . . . by monitoring combustion conditions
- 2270/1064 indirectly, at the exhaust
- 2270/107 . . to cope with emergencies
- 2270/1071 . . . in particular sudden load loss
- 2270/10711 applying a low voltage ride through method
- 2270/1072 . . . in particular blow-out and relight
- 2270/1073 . . . of one engine in a multi-engine system
- 2270/1074 . . . by using back-up controls
- 2270/1075 . . . by temporary overriding set control limits
- 2270/1076 . . . caused by water or hail ingestion
- 2270/108 . . to cope with, or avoid, compressor flow instabilities
- 2270/1081 . . . Compressor surge or stall
- 2270/10812 caused by working fluid flow velocity profile distortion
- 2270/10815 due to high angle of attack of aircraft
- 2270/10817 due to compressor degradation
- 2270/109 . . to prolong engine life
- 2270/1091 . . . by limiting temperatures
- 2270/1095 . . . by limiting mechanical stresses
- 2270/1097 . . . by preventing reverse rotation
- 2270/11 . . to maintain desired vehicle trajectory parameters
- 2270/1101 . . . Altitude
- 2270/1102 . . . Speed or Mach number
- 2270/111 . . to control two or more engines simultaneously
- 2270/15 . . to control thermoacoustic behaviour in the combustion chambers ([counteracting noise or vibration F05B 2260/96](#))
- 2270/16 . . to control water or steam injection
- 2270/17 . . to avoid excessive deflection of the blades
- 2270/18 . . to control buoyancy
- 2270/19 . . to avoid stroboscopic flicker shadow on surroundings
- 2270/20 . . to optimise the performance of a machine
- 2270/30 . Control parameters, e.g. input parameters
- 2270/301 . . Pressure
- 2270/3011 . . . Inlet
- 2270/3013 . . . Outlet
- 2270/3015 . . . differential
- 2270/303 . . Temperature
- 2270/3032 . . . excessive temperatures, e.g. caused by overheating
- 2270/304 . . Spool rotational speed
- 2270/305 . . Tolerances
- 2270/309 . . Rate of change of parameters
- 2270/31 . . Fuel schedule for stage combustors
- 2270/32 . . Wind speeds
- 2270/3201 . . . "cut-off" or "shut-down" wind speed
- 2270/321 . . Wind directions
- 2270/322 . . the detection or prediction of a wind gust
- 2270/323 . . Air humidity
- 2270/324 . . Air pressure
- 2270/325 . . Air temperature
- 2270/326 . . Rotor angle
- 2270/327 . . Rotor or generator speeds
- 2270/328 . . Blade pitch angle
- 2270/329 . . Azimuth or yaw angle
- 2270/33 . . Proximity of blade to tower
- 2270/331 . . Mechanical loads
- 2270/332 . . Maximum loads or fatigue criteria
- 2270/333 . . Noise or sound levels
- 2270/334 . . Vibration measurements
- 2270/335 . . Output power or torque

2270/336	. . Blade lift measurements	2280/10308	. . . Lead
2270/337	. . Electrical grid status parameters, e.g. voltage, frequency or power demand	2280/10309	. . . Tin
2270/40	. Type of control system	2280/1031	. . . Zinc
2270/402	. . passive or reactive, e.g. using large wind vanes	2280/10311	. . . Mercury
2270/404	. . active, predictive, or anticipative	2280/104	. . Noble metals
2270/50	. Control logic embodiment by	2280/1041	. . . Silver
2270/502	. . electrical means, e.g. relays or switches	2280/1042	. . . Gold
2270/504	. . electronic means, e.g. electronic tubes, transistors or IC's within an electronic circuit	2280/1043	. . . Platinum group, e.g. Pt, Ir
2270/506	. . hydraulic means, e.g. hydraulic valves within a hydraulic circuit	2280/1044	. . . Palladium
2270/508	. . mechanical means, e.g. levers, gears or cams	2280/1045	. . . Ruthenium
2270/60	. Control system actuates through	2280/1046	. . . Osmium
2270/602	. . electrical actuators	2280/1047	. . . Iridium
2270/604	. . hydraulic actuators	2280/1048	. . . Rhodium
2270/605	. . Pneumatic actuators	2280/105	. . Copper
2270/606	. . mechanical actuators (F05B 2270/602 takes precedence)	2280/106	. . Rare earth metals, e.g. Sc, Y
2270/70	. Type of control algorithm	2280/107	. . Alloys
2270/701	. . proportional	2280/1071	. . . Steel alloys
2270/702	. . differential	2280/1072	. . Copper alloys
2270/703	. . integral	2280/10721	. . . Bronze
2270/704	. . proportional-differential	2280/10722	. . . Phosphor-bronze alloy
2270/705	. . proportional-integral	2280/10723	. . . Nickel-Copper alloy, e.g. monel
2270/706	. . proportional-integral-differential	2280/1073	. . Aluminium alloy, e.g. AlCuMgPb
2270/707	. . fuzzy logic	2280/1074	. . Alloys not otherwise provided for
2270/708	. . with comparison tables	2280/10741	. . . Superalloys
2270/709	. . with neural networks	2280/10742	. . . Heat stable alloys
2270/80	. Devices generating input signals, e.g. transducers, sensors, cameras or strain gauges	2280/10743	. . . Ni - Si alloys
2270/802	. . Calibration thereof	2280/10744	. . . Metal-aluminide intermetallic compounds
2270/803	. . Sampling thereof	2280/20	. Inorganic materials, e.g. non-metallic materials
2270/804	. . Optical devices	2280/2001	. . Glass
2270/8041	. . . Cameras	2280/20011	. . . MIBA
2270/8042	. . . Lidar systems	2280/20012	. . . Quartz
2270/805	. . Radars	2280/2002	. . Phosphor
2270/806	. . Sonars	2280/2003	. . Silicon
2270/807	. . Accelerometers	2280/2004	. . Ceramics; Oxides
2270/808	. . Strain gauges; Load cells	2280/20041	. . . Aluminium oxides
2270/809	. . Encoders	2280/20042	. . . Zinc oxides
2270/81	. . Microphones	2280/20043	. . . Zirconium oxides
2270/821	. . Displacement measuring means, e.g. inductive	2280/2005	. . Non-oxide ceramics
2280/00	Materials; Properties thereof	2280/2006	. . Carbon, e.g. graphite
2280/10	. Inorganic materials, e.g. metals	2280/2007	. . Carbides
2280/101	. . Iron	2280/20071	. . . of silicon
2280/1011	. . Cast iron	2280/20072	. . . of titanium, e.g. TiB
2280/102	. . Light metals	2280/20073	. . . of wolfram, e.g. tungsten carbide
2280/1021	. . . Aluminium	2280/2008	. . Nitrides
2280/1022	. . . Beryllium	2280/20081	. . . of aluminium
2280/1023	. . . Boron	2280/20082	. . . of boron
2280/1024	. . . Lithium	2280/20083	. . . of silicon
2280/1025	. . . Magnesium	2280/20084	. . . of titanium
2280/103	. . Heavy metals	2280/20085	. . . of zirconium
2280/10301	. . . Refractory metals, e.g. V, W	2280/2009	. . Sulfides
2280/10302	. . . Chromium	2280/20091	. . . of molybdenum
2280/10303	. . . Molybdenum	2280/201	. . Sapphire
2280/10304	. . . Titanium	2280/2011	. . Aluminium titanate
2280/10305	. . . Zirconium	2280/2013	. . Silica
2280/10306	. . . Hafnium	2280/2014	. . Arsenic
2280/10307	. . . Manganese	2280/2015	. . Antimony
		2280/2016	. . Bismuth
		2280/2017	. . Barium
		2280/30	. Inorganic materials not otherwise provided for
		2280/40	. Organic materials
		2280/4001	. . Leather

- 2280/4002 . . Cellulosic materials, e.g. wood
- 2280/4003 . . Synthetic polymers, e.g. plastics; Rubber
- 2280/4004 . . Rubber
- 2280/4005 . . PTFE [PolyTetraFluorEthylene]
- 2280/4006 . . Polyamides, e.g. NYLON
- 2280/4007 . . Thermoplastics
- 2280/4008 . . Polyamides, e.g. Aurum
- 2280/4009 . . Polyetherketones, e.g. PEEK
- 2280/401 . . Silicon polymers
- 2280/4011 . . Organic materials not otherwise provided for
- 2280/50 . Intrinsic material properties or characteristics
- 2280/5001 . . Elasticity
- 2280/5002 . . Thermal properties
- 2280/5003 . . Expansivity
- 2280/50031 . . . similar
- 2280/50032 . . . dissimilar
- 2280/5004 . . Heat transfer
- 2280/5005 . . Reflective properties
- 2280/5006 . . Shape memory
- 2280/5007 . . Hardness
- 2280/5008 . . Magnetic properties
- 2280/5009 . . non-magnetic
- 2280/501 . . Self lubricating materials; Solid lubricants
- 2280/5011 . . Surface roughness
- 2280/60 . Properties or characteristics given to material by treatment or manufacturing
- 2280/6001 . . Fabrics
- 2280/6002 . . . Woven fabrics
- 2280/6003 . . Composites; e.g. fibre-reinforced
- 2280/6004 . . amorphous
- 2280/6005 . . crystalline
- 2280/6006 . . Directionally-solidified crystalline structures
- 2280/6007 . . monocrystalline
- 2280/6008 . . Structures
- 2280/6009 . . Grain size
- 2280/601 . . Syntactic
- 2280/6011 . . Coating
- 2280/6012 . . Foam
- 2280/6013 . . Fibres
- 2280/6014 . . Filler
- 2280/6015 . . Resin
- 2280/70 . Treatments or modification of materials
- 2280/701 . . Heat treatments
- 2280/702 . . Reinforcements