

CPC COOPERATIVE PATENT CLASSIFICATION

H ELECTRICITY

(NOTE omitted)

H01 BASIC ELECTRIC ELEMENTS

(NOTE omitted)

H01F MAGNETS; INDUCTANCES; TRANSFORMERS; SELECTION OF MATERIALS FOR THEIR MAGNETIC PROPERTIES (ceramics based on ferrites [C04B 35/26](#); alloys [C22C](#); {construction of loading coils [H01B](#)} ; thermomagnetic devices [H01L 37/00](#); loudspeakers, microphones, gramophone pick-ups or like acoustic electromechanical transducers [H04R](#))

NOTE

In this subclass, inductances and transformers are regarded as being "for power supply" if they are intended for this purpose even in systems operating at frequencies above 60 cycles/sec.

- | | |
|---|---|
| <p>1/00 Magnets or magnetic bodies characterised by the magnetic materials therefor; Selection of materials for their magnetic properties</p> <p>1/0009 . {Antiferromagnetic materials, i.e. materials exhibiting a Néel transition temperature (H01F 1/0036 takes precedence)}</p> <p>WARNING</p> <p>This groups is not complete pending the completion of reclassification; see provisionally also H01F 1/00 - H01F 1/447</p> <p>1/0018 . {Diamagnetic or paramagnetic materials, i.e. materials with low susceptibility and no hysteresis (H01F 1/0036 takes precedence)}</p> <p>1/0027 . {Thick magnetic films (forming thick magnetic films H01F 41/16; magnetic record carriers G11B 5/70)}</p> <p>NOTE</p> <p>Group H01F 1/0036 takes precedence over groups H01F 1/09, H01F 1/11, H01F 1/20, H01F 1/33 and H01F 1/36</p> <p>1/0036 . {showing low dimensional magnetism, i.e. spin rearrangements due to a restriction of dimensions, e.g. showing giant magnetoresistivity, (H01F 1/153, H01F 1/42 and H01F 10/00 take precedence; magnetoresistive sensors G01D 5/16, G01R 33/06; magnetoresistive recording G11B 5/39; magnetic-field-controlled resistors H01L 43/08)}</p> <p>1/0045 . . {Zero dimensional, e.g. nanoparticles, soft nanoparticles for medical/biological use (preparation of fullerenes in general C01B 32/15)}</p> <p>1/0054 . . . {Coated nanoparticles, e.g. nanoparticles coated with organic surfactant}</p> <p>1/0063 . . . {in a non-magnetic matrix, e.g. granular solids (granular films H01F 10/007)}</p> <p>1/0072 . . {one dimensional, i.e. linear or dendritic nanostructures}</p> <p>1/0081 . . . {in a non-magnetic matrix, e.g. Fe-nanowires in a nanoporous membrane}</p> | <p>1/009 . . {bidimensional, e.g. nanoscale period nanomagnet arrays (H01F 10/007 takes precedence)}</p> <p>1/01 . . of inorganic materials (H01F 1/44 takes precedence)</p> <p>1/012 . . {adapted for magnetic entropy change by magnetocaloric effect, e.g. used as magnetic refrigerating material (refrigeration systems using magnetic effects F25B 21/00)}</p> <p>1/015 . . . {Metals or alloys}</p> <p>1/017 . . . {Compounds}</p> <p>1/03 . . characterised by their coercivity { (H01F 1/40 takes precedence)}</p> <p>1/0302 . . . {characterised by unspecified or heterogeneous hardness or specially adapted for magnetic hardness transitions}</p> <p>1/0304 {adapted for large Barkhausen jumps or domain wall rotations, e.g. WIEGAND or MATTEUCCI effect (H01F 1/143 and H01F 1/15391 take precedence)}</p> <p>1/0306 {Metals or alloys, e.g. LAVES phase alloys of the MgCu₂-type (H01F 1/0304 takes precedence)}</p> <p>1/0308 {with magnetic shape memory [MSM], i.e. with lattice transformations driven by a magnetic field, e.g. Heusler alloys}</p> <p>1/0311 {Compounds (H01F 1/0304 takes precedence)}</p> <p>1/0313 {Oxidic compounds}</p> <p>1/0315 {Ferrites}</p> <p>1/0317 {Manganites}</p> <p>1/032 . . . of hard-magnetic materials</p> <p>1/04 metals or alloys</p> <p>1/047 Alloys characterised by their composition</p> <p>NOTE</p> <p>In groups H01F 1/053 - H01F 1/059, an alloy is classified in the last appropriate place</p> <p>1/053 containing rare earth metals</p> <p>1/0533 {in a bonding agent}</p> <p>1/0536 {sintered}</p> |
|---|---|

1/055 and magnetic transition metals, e.g. SmCo_5
1/0551 {in the form of particles, e.g. rapid quenched powders or ribbon flakes}
1/0552 {with a protective layer}
1/0553 {obtained by reduction or by hydrogen decrepitation or embrittlement}
1/0555 {pressed, sintered or bonded together}
1/0556 {pressed}
1/0557 {sintered}
1/0558 {bonded together}
1/057 and IIIa elements, e.g. $\text{Nd}_2\text{Fe}_{14}\text{B}$
1/0571 {in the form of particles, e.g. rapid quenched powders or ribbon flakes}
1/0572 {with a protective layer}
1/0573 {obtained by reduction or by hydrogen decrepitation or embrittlement}
1/0574 {obtained by liquid dynamic compaction}
1/0575 {pressed, sintered or bonded together}
1/0576 {pressed, e.g. hot working}
1/0577 {sintered}
1/0578 {bonded together}
1/0579 {with exchange spin coupling between hard and soft nanophases, e.g. nanocomposite spring magnets}
1/058 and IVa elements, e.g. $\text{Gd}_2\text{Fe}_{14}\text{C}$
1/059 and Va elements, e.g. $\text{Sm}_2\text{Fe}_{17}\text{N}_2$
1/0593 {of tetragonal ThMn_{12} -structure}
1/0596 {of rhombic or rhombohedral $\text{Th}_2\text{Zn}_{17}$ structure or hexagonal $\text{Th}_2\text{Ni}_{17}$ structure}
1/06 in the form of particles, e.g. powder (H01F 1/047 takes precedence; record carriers G11B 5/70605)
1/061 {with a protective layer}
1/063 {with a non magnetic core}
1/065 {obtained by a reduction}
1/066 {obtained by liquid dynamic compaction}
1/068 {having a L10 crystallographic structure, e.g. $[\text{Co,Fe}][\text{Pt,Pd}]$ (nano)particles}
<u>WARNING</u>	
This groups is not complete pending the completion of reclassification; see provisionally also H01F 1/06 - H01F 1/066	
1/08 pressed, sintered, or bound together
1/083 {in a bonding agent}
1/086 {sintered}
1/09 mixtures of metallic and non-metallic particles; metallic particles having oxide skin

1/10 non-metallic substances, e.g. ferrites {, e.g. $[(\text{Ba,Sr})\text{O}(\text{Fe}_2\text{O}_3)_6]$ ferrites with hexagonal structure}
1/11 in the form of particles {(for magnetic record carriers G11B 5/70626)}
1/111 {with a non-magnetic core}
1/112 {with a skin (H01F 1/113 takes precedence)}
1/113 in a bonding agent
1/117 Flexible bodies
1/12 of soft-magnetic materials
1/14 metals or alloys
1/143 {in the form of wires (H01F 1/147 takes precedence)}
1/147 Alloys characterised by their composition {(treatment thereof for enhancing their electromagnetic properties C21D 8/12)}
<u>NOTE</u>	
In groups H01F 1/14708 - H01F 1/15391 , an alloy is classified in the last appropriate place	
1/14708 {Fe-Ni based alloys (pure Fe or Ni H01F 1/14 , H01F 1/16 or H01F 1/20)}
1/14716 {in the form of sheets}
1/14725 {with insulating coating}
1/14733 {in the form of particles}
1/14741 {pressed, sintered or bonded together}
1/1475 {the particles being insulated}
1/14758 {by macromolecular organic substances}
1/14766 {Fe-Si based alloys}
1/14775 {in the form of sheets}
1/14783 {with insulating coating}
1/14791 {Fe-Si-Al based alloys, e.g. Sendust}
1/153 Amorphous metallic alloys, e.g. glassy metals {(making ferrous amorphous alloys C22C 33/003)}
1/15308 {based on Fe/Ni (H01F 1/15325 takes precedence)}
1/15316 {based on Co (H01F 1/15325 takes precedence)}
1/15325 {containing rare earths}
1/15333 {containing nanocrystallites, e.g. obtained by annealing}
1/15341 {Preparation processes therefor}
1/1535 {by powder metallurgy, e.g. spark erosion}
1/15358 {Making agglomerates therefrom, e.g. by pressing}
1/15366 {using a binder}
1/15375 {using polymers}
1/15383 {Applying coatings thereon (H01F 1/15366 takes precedence)}
1/15391 {Elongated structures, e.g. wires}
1/16 in the form of sheets (H01F 1/147 takes precedence)
1/18 with insulating coating
1/20 in the form of particles, e.g. powder (H01F 1/147 takes precedence)
1/22 pressed, sintered, or bound together

1/24	the particles being insulated	2003/005	. {Magnetic cores for receiving several windings with perpendicular axes, e.g. for antennae or inductive power transfer}
1/26	by macromolecular organic substances	3/02	. made from sheets
1/28	dispersed or suspended in a bonding agent	3/04	. made from strips or ribbons
1/33	mixtures of metallic and non-metallic particles; metallic particles having oxide skin	3/06	. made from wires
1/34	non-metallic substances, e.g. ferrites	3/08	. made from powder (powder coatings on sheets H01F 3/02 ; on strips or ribbons H01F 3/04 ; on wires H01F 3/06)
1/342	{Oxides (H01F 1/36 and H01F 1/38 take precedence)}	3/10	. Composite arrangements of magnetic circuits
1/344	{Ferrites, e.g. having a cubic spinel structure (X ₂ O)(Y ₂ 3+O ₃), e.g. magnetite Fe ₃ O ₄ }	2003/103	. {Magnetic circuits with permanent magnets}
1/346	{[(TO ₄) ₃] with T= Si, Al, Fe, Ga (H01F 10/24 takes precedence; Faraday rotators G02F 1/09)}	2003/106	. {Magnetic circuits using combinations of different magnetic materials}
1/348	{Hexaferrites with decreased hardness or anisotropy, i.e. with increased permeability in the microwave (GHz) range, e.g. having a hexagonal crystallographic structure}	3/12	. Magnetic shunt paths
1/36	in the form of particles (H01F 1/346 , H01F 1/348 and H01F 1/38 take precedence)}	3/14	. Constrictions; Gaps, e.g. air-gaps (in magnetic shunt paths H01F 3/12)
1/37	in a bonding agent	5/00	Coils (superconducting coils H01F 6/06 ; fixed inductances of the signal type H01F 17/00)
1/375	Flexible bodies	5/003	. {Printed circuit coils}
1/38	amorphous, e.g. amorphous oxides	2005/006	. {with conical spiral form}
1/40	of magnetic semiconductor materials, e.g. CdCr ₂ S ₄ (devices using galvano-magnetic or similar effects H01L 43/00)	5/02	. wound on non-magnetic supports, e.g. formers
1/401	{diluted}	2005/022	. {wound on formers with several winding chambers separated by flanges, e.g. for high voltage applications}
NOTE			2005/025	. {wound on coaxial arrangement of two or more formers}
In group H01F 1/401 , a diluted magnetic semiconductor (DMS) is classified in the last appropriate place			2005/027	. {wound on formers for receiving several coils with perpendicular winding axes, e.g. for antennae or inductive power transfer}
1/402	{of II-VI type, e.g. Zn _{1-x} Cr _x Se}	5/04	. Arrangements of electric connections to coils, e.g. leads
1/404	{of III-V type, e.g. In _{1-x} Mn _x As}	2005/043	. {having multiple pin terminals, e.g. arranged in two parallel lines at both sides of the coil}
1/405	{of IV type, e.g. Ge _{1-x} Mn _x }	2005/046	. {Details of formers and pin terminals related to mounting on printed circuits}
1/407	{Diluted non-magnetic ions in a magnetic cation-sublattice, e.g. perovskites, La _{1-x} (Ba,Sr) _x MnO ₃ }	5/06	. Insulation of windings
1/408	{half-metallic, i.e. having only one electronic spin direction at the Fermi level, e.g. CrO ₂ , Heusler alloys (H01F 10/1936 takes precedence)}	6/00	Superconducting magnets; Superconducting coils (magnetic resonance assemblies using superconducting coil systems G01R 33/3815)
1/42	of organic or organo-metallic materials {, e.g. graphene} (H01F 1/44 takes precedence)	2006/001	. {Constructive details of inductive current limiters}
1/44	of magnetic liquids, e.g. ferrofluids (particles in a bonding agent H01F 1/28, H01F 1/36, H01F 1/37)	6/003	. {Methods and means for discharging superconductive storage (superconducting alloys C22C ; static memories with superconducting elements G11C 11/44 ; superconducting circuit breakers with contacts H01H 33/004 ; superconducting material H01L 39/00 ; power cryotons H01L 39/20 ; superconducting switches for low power H03K 17/92)}
1/442	{the magnetic component being a metal or alloy, e.g. Fe (H01F 1/447 takes precedence)}	6/005	. {Methods and means for increasing the stored energy in superconductive coils by increments (flux pumps)}
1/445	{the magnetic component being a compound, e.g. Fe ₃ O ₄ (H01F 1/447 takes precedence)}	6/006	. {Supplying energising or de-energising current; Flux pumps}
1/447	{characterised by magnetoviscosity, e.g. magnetorheological, magnetorheototropic, magnetodilatant liquids (electrorheological fluids C10M 171/001)}	6/008	. {Electric circuit arrangements for energising superconductive electromagnets}
3/00	Cores, Yokes, or armatures (magnetic materials H01F 1/00 ; permanent magnets H01F 7/02)		6/02	. Quenching; Protection arrangements during quenching (protection circuits H02H 7/001)
			6/04	. Cooling
			6/06	. Coils, e.g. winding, insulating, terminating or casing arrangements therefor

- 6/065 . . {Feed-through bushings, terminals and joints (leading of conductors or axes through casings of transformers [H01F 27/04](#))}
- 7/00 Magnets** (superconducting magnets [H01F 6/00](#); for separation of solid materials or fluids [B03C 1/00](#); for bench or like work-holders [B23B 31/28](#), [B23Q 3/00](#); work-holding devices [B25B 11/00](#); lifting magnets [B66C 1/00](#); {operating or controlling locks using permanent magnets [E05B 47/0038](#); devices for holding a wing, e.g. door or window, by magnetic or electromagnetic attraction [E05C 19/16](#); relieving load or bearings using magnetic means [F16C 39/06](#)} ; for electric meters [G01R](#); for relays [H01H](#); {for electric discharge tubes [H01J](#), e.g. [H01J 3/24](#), [H01J 23/10](#), [H01J 29/68](#)} ; for dynamo-electric machines [H02K](#))
- 7/02 . Permanent magnets {[PM]}
- 7/0205 . . {Magnetic circuits with PM in general}
- 7/021 . . . {Construction of PM ([H01F 7/0278](#) takes precedence; PM compositions [H01F 1/032](#))}
- 7/0215 {Flexible forms, sheets}
- 7/0221 . . . {Mounting means for PM, supporting, coating, encapsulating PM}
- 7/0226 . . . {PM with variable field strength ([H01F 7/0284](#) takes precedence)}
- 7/0231 . . {Magnetic circuits with PM for power or force generation}
- 7/0236 . . . {Magnetic suspension or levitation (for vehicles [B60L 13/04](#); magnetic bearings [F16C 39/063](#))}
- 7/0242 . . . {Magnetic drives, magnetic coupling devices}
- 7/0247 . . . {Orientating, locating, transporting arrangements}
- 7/0252 . . . {PM holding devices ([H01F 7/021](#), [H01F 7/0215](#), [H01F 7/0226](#) take precedence)}
- 7/0257 {Lifting, pick-up magnetic objects}
- 7/0263 {Closures, bags, bands, engagement devices with male and female parts}
- 7/0268 {Magnetic cylinders}
- 7/0273 . . {Magnetic circuits with PM for magnetic field generation}
- 7/0278 . . . {for generating uniform fields, focusing, deflecting electrically charged particles (for magnetic separation by Lorentz force [B03C 1/023](#); specially adapted for NMR applications [G01R 33/383](#))}
- 7/0284 {using a trimmable or adjustable magnetic circuit, e.g. for a symmetric dipole or quadrupole magnetic field}
- 7/0289 . . . {Transducers, loudspeakers, moving coil arrangements}
- 7/0294 . . . {Detection, inspection, magnetic treatment}
- 7/04 . . Means for releasing the attractive force
- 7/06 . Electromagnets; Actuators including electromagnets {(electric coils [H01F 5/00](#); devices for holding workpieces using electric force [B23Q 3/15](#); load-engaging elements for lifting articles electromagnetically [B66C 1/06](#); electromagnetic couplings [F16D 27/00](#); magnetic brakes [F16D 63/002](#); electromagnetically operated valves [F16K 11/24](#), [F16K 31/00](#); analysing materials by magnetic means [G01N 27/72](#), [G01N 27/80](#); electromagnets for winding mechanical clocks [G04C 1/02](#); electromagnetic relays [H01H 51/00](#); windings for salient poles of dynamo-electric machines [H02K 3/18](#); electromagnets for telegraphic communication [H04L](#); for arc lamps [H05B 31/28](#))}
- 2007/062 . . {Details of terminals or connectors for electromagnets}
- 7/064 . . {Circuit arrangements for actuating electromagnets (circuit arrangements for obtaining special operating characteristics [H01F 7/18](#); driving circuits for electromagnets making use of a switching regulator [H01H 47/325](#))}
- 7/066 . . {Electromagnets with movable winding}
- 2007/068 . . {using printed circuit coils}
- 7/08 . . with armatures
- 7/081 . . . {Magnetic constructions}
- 2007/083 {External yoke surrounding the coil bobbin, e.g. made of bent magnetic sheet}
- 2007/085 {Yoke or polar piece between coil bobbin and armature having a gap, e.g. filled with nonmagnetic material}
- 2007/086 {Structural details of the armature}
- 7/088 . . . {provided with means for absorbing shocks}
- 7/10 . . . specially adapted for alternating current
- 7/11 reducing or eliminating the effects of eddy currents
- 7/12 having anti-chattering arrangements
- 7/1205 {having short-circuited conductors (electromagnetic relays provided with short-circuited conducting sleeves [H01H 47/00](#))}
- 7/121 . . . Guiding or setting position of armatures, e.g. retaining armatures in their end position
- 7/122 by permanent magnets {([H01F 7/1615](#), [H01F 7/1646](#) take precedence)}
- 7/123 by ancillary coil
- 7/124 by mechanical latch, e.g. detent
- 7/126 . . . Supporting or mounting
- 7/127 . . . Assembling
- 7/128 . . . Encapsulating, encasing or sealing
- 7/129 of armatures
- 7/13 . . . characterised by pulling-force characteristics
- 7/14 . . . Pivoting armatures ([H01F 7/17](#) takes precedence)
- 7/145 {Rotary electromagnets with variable gap (with fixed gap or torque motors [H02K 26/00](#))}
- 7/16 . . . Rectilinearly-movable armatures ([H01F 7/17](#) takes precedence)
- 7/1607 {Armatures entering the winding}
- 7/1615 {Armatures or stationary parts of magnetic circuit having permanent magnet}
- 7/1623 {Armatures having T-form}

2007/163	{with axial bearing}	7/202	{Electromagnets for high magnetic field strength (for superconducting electromagnets H01F 6/00 ; for transformers or inductances without a magnetic core H01F 30/08)}
7/1638	{Armatures not entering the winding}	7/204	{Circuits for energising or de-energising}
7/1646	{Armatures or stationary parts of magnetic circuit having permanent magnet}	7/206	{Electromagnets for lifting, handling or transporting of magnetic pieces or material (electromagnets for guidance of vehicles, workpieces B65G 21/2009 ; for magnetic suspension or levitation H02N 15/00)}
7/1653	{Magnetic circuit having axially spaced pole-pieces}	2007/208	{combined with permanent magnets}
2007/1661	{Electromagnets or actuators with anti-stick disc}	10/00		Thin magnetic films, e.g. of one-domain structure (magnetic record carriers G11B 5/00 ; thin-film magnetic stores G11C)
2007/1669	{Armatures actuated by current pulse, e.g. bistable actuators}	10/002	{Antiferromagnetic thin films, i.e. films exhibiting a Néel transition temperature (H01F 10/3218 and H01F 10/3268 take precedence)}
2007/1676	{Means for avoiding or reducing eddy currents in the magnetic circuit, e.g. radial slots}			WARNING This groups is not complete pending the completion of reclassification; see provisionally also H01F 10/00 - H01F 10/30
2007/1684	{Armature position measurement using coils}	10/005	{organic or organo-metallic films, e.g. monomolecular films obtained by Langmuir-Blodgett technique, graphene}
2007/1692	{Electromagnets or actuators with two coils}	10/007	{ultrathin or granular films (H01F 10/005 and H01F 10/3227 take precedence; applying ultrathin or granular layers to substrates H01F 41/301)}
7/17	Pivoting and rectilinearly-movable armatures	10/06	characterised by the coupling or physical contact with connecting or interacting conductors
7/18	Circuit arrangements for obtaining desired operating characteristics, e.g. for slow operation, for sequential energisation of windings, for high-speed energisation of windings	10/08	characterised by magnetic layers (H01F 10/32 takes precedence) ; applying thin magnetic films to substrates H01F 41/14)
7/1805	{Circuit arrangements for holding the operation of electromagnets or for holding the armature in attracted position with reduced energising current (for holding relay armature in attracted position with reduced energising current H01H 47/04 ; quick energising of electro-dynamic machines H02P 9/08 ; for quickly de-energising of dynamo-electric generators H02P 9/123)}	10/10	characterised by the composition
7/1811	{demagnetising upon switching off, removing residual magnetism}	10/12	being metals or alloys (intermetallic compounds H01F 10/18)
7/1816	{making use of an energy accumulator (for relays H01H 47/043)}	10/123	{having a L10 crystallographic structure, e.g. [Co,Fe][Pt,Pd] thin films}
2007/1822	{using a capacitor to produce a boost voltage}			WARNING This groups is not complete pending the completion of reclassification; see provisionally also H01F 10/16
7/1827	{by changing number of serially-connected turns or windings (for relays H01H 47/06)}	10/126	{containing rare earth metals (H01F 10/133 takes precedence)}
7/1833	{by changing number of parallel-connected turns or windings (for relays H01H 47/08)}	10/13	Amorphous metallic alloys, e.g. glassy metals (H01F 10/3204 takes precedence)}
7/1838	{by switching-in or -out impedance (for relays H01H 47/10)}			NOTE In this group, amorphous metallic alloys are classified in the last appropriate place
7/1844	{Monitoring or fail-safe circuits (for relays H01H 47/002)}	10/131	{containing iron or nickel}
2007/185	{with armature position measurement}	10/132	{containing cobalt}
2007/1855	{using a stored table to deduce one variable from another}	10/133	{containing rare earth metals}
2007/1861	{using derivative of measured variable}	10/135	{containing transition metals}
2007/1866	{with regulation loop}	10/136	{containing iron}
7/1872	{Bistable or bidirectional current devices (relays H01H 47/226)}	10/137	{containing cobalt}
7/1877	{controlling a plurality of loads}	10/138	{containing nanocrystallites, e.g. obtained by annealing}
7/1883	{by steepening leading and trailing edges of magnetisation pulse, e.g. printer drivers}			
2007/1888	{using pulse width modulation}			
2007/1894	{minimizing impact energy on closure of magnetic circuit}			
7/20	without armatures (cores H01F 3/00 ; coils H01F 5/00 ; {shaping metal by applying magnetic forces B21D 26/14 ; electromagnets specially adapted for NMR applications G01R 33/381)}			

- 10/14 containing iron or nickel ([H01F 10/126](#) , [H01F 10/13](#), [H01F 10/16](#) take precedence)
- NOTE**
- In this group, alloys containing iron or nickel are classified in the last appropriate place
- 10/142 {containing Si}
- 10/145 {containing Al, e.g. SENDUST}
- 10/147 {with lattice under strain, e.g. expanded by interstitial nitrogen ([H01F 10/26](#) - [H01F 10/30](#) take precedence)}
- 10/16 containing cobalt ([H01F 10/126](#) , [H01F 10/13](#) take precedence)
- 10/18 . . . being compounds
- 10/187 Amorphous compounds { ([H01F 10/3204](#) takes precedence)}
- 10/193 Magnetic semiconductor compounds { (in general [H01F 1/40](#); multilayers, e.g. superlattices [H01F 10/3213](#))}
- 10/1933 {Perovskites}
- WARNING**
- This groups is not complete pending the completion of reclassification; see provisionally also [H01F 10/193](#)
- 10/1936 {Half-metallic, e.g. epitaxial CrO₂ or NiMnSb films}
- 10/20 Ferrites
- 10/205 {Hexagonal ferrites}
- 10/22 Orthoferrites {, e.g. RFeO₃ (R= rare earth element) with orthorhombic structure}
- 10/24 Garnets { (in general [H01F 1/346](#); multilayers, e.g. superlattices [H01F 10/3209](#); applying magnetic garnet films to substrates by sputtering [H01F 41/186](#))}
- 10/245 {Modifications for enhancing interaction with electromagnetic wave energy}
- 10/26 . characterised by the substrate or intermediate layers { ([H01F 10/06](#) and [H01F 10/32](#) take precedence)}
- 10/265 . . {Magnetic multilayers non exchange-coupled ([H01F 10/32](#) takes precedence)}
- WARNING**
- This groups is not complete pending the completion of reclassification; see provisionally also [H01F 10/00](#) - [H01F 10/30](#)
- 10/28 . . characterised by the composition of the substrate
- 10/30 . . characterised by the composition of the intermediate layers {, e.g. seed, buffer, template, diffusion preventing, cap layers ([H01F 10/06](#) and [H01F 10/32](#) take precedence)}
- 10/32 . Spin-exchange-coupled multilayers, e.g. nanostructured superlattices { (applying spin-exchange-coupled multilayers to substrates [H01F 41/302](#))}
- 10/3204 . . {Exchange coupling of amorphous multilayers}
- 10/3209 . . {Exchange coupling of garnet multilayers}
- 10/3213 . . {Exchange coupling of magnetic semiconductor multilayers, e.g. MnSe/ZnSe superlattices (semiconductor materials for use in semiconductor devices [H01L 29/12](#))}
- 10/3218 . . {Exchange coupling of magnetic films via an antiferromagnetic interface ([H01F 10/3268](#) takes precedence)}
- 10/3222 . . {Exchange coupled hard/soft multilayers, e.g. CoPt/Co or NiFe/CoSm (nanocomposite spring magnets [H01F 1/0579](#))}
- 10/3227 . . {Exchange coupling via one or more magnetisable ultrathin or granular films}
- 10/3231 . . . {via a non-magnetic spacer}
- 10/3236 {made of a noble metal, e.g.(Co/Pt) n multilayers having perpendicular anisotropy ([H01F 10/3286](#) takes precedence)}
- 10/324 . . {Exchange coupling of magnetic film pairs via a very thin non-magnetic spacer, e.g. by exchange with conduction electrons of the spacer}
- 10/3245 . . . {the spacer being superconductive}
- 10/325 . . . {the spacer being noble metal}
- 10/3254 . . . {the spacer being semiconducting or insulating, e.g. for spin tunnel junction [STJ]}
- 10/3259 {Spin-exchange-coupled multilayers comprising at least a nanooxide layer [NOL], e.g. with a NOL spacer}
- 10/3263 . . . {the exchange coupling being symmetric, e.g. for dual spin valve, e.g. NiO/Co/Cu/Co/Cu/Co/NiO}
- 10/3268 . . . {the exchange coupling being asymmetric, e.g. by use of additional pinning, by using antiferromagnetic or ferromagnetic coupling interface, i.e. so-called spin-valve [SV] structure, e.g. NiFe/Cu/NiFe/FeMn}
- 10/3272 {by use of anti-parallel coupled [APC] ferromagnetic layers, e.g. artificial ferrimagnets [AFI], artificial [AAF] or synthetic [SAF] anti-ferromagnets}
- 10/3277 {by use of artificial ferrimagnets [AFI] only}
- 10/3281 {only by use of asymmetry of the magnetic film pair itself, i.e. so-called pseudospin valve [PSV] structure, e.g. NiFe/Cu/Co}
- 10/3286 . . . {Spin-exchange coupled multilayers having at least one layer with perpendicular magnetic anisotropy}
- 10/329 . . . {Spin-exchange coupled multilayers wherein the magnetisation of the free layer is switched by a spin-polarised current, e.g. spin torque effect}
- 10/3295 . . . {Spin-exchange coupled multilayers wherein the magnetic pinned or free layers are laminated without anti-parallel coupling within the pinned and free layers}
- 13/00 Apparatus or processes for magnetising or demagnetising** { (devices for holding workpieces using magnetic or electric force acting directly on the workpieces [B23Q 3/15](#)) ; for degaussing ships [B63G 9/06](#); for clocks or watches [G04D 9/00](#); {recording or erasing of information on magnetic record carriers [G11B 5/00](#) ; demagnetising arrangements for colour television [H04N 9/29](#)}
- 13/003 . {Methods and devices for magnetising permanent magnets (permanent magnets [H01F 7/02](#))}

13/006	. {Methods and devices for demagnetising of magnetic bodies, e.g. workpieces, sheet material (for erasing of information on magnetic record carriers G11B 5/00)}	19/08	. . Transformers having magnetic bias, e.g. for handling pulses
17/00	Fixed inductances of the signal type (coils in general H01F 5/00 {inductors without a potential-jump or surface barrier specially adapted for integrated circuits, details thereof and multistep manufacturing processes therefor H01L 28/10 })	2019/085	. . . {Transformer for galvanic isolation}
17/0006	. {Printed inductances (printed coils for dynamo-electric machines H02K 3/26 ; printed circuits H05K)}	21/00	Variable inductances or transformers of the signal type (H01F 36/00 takes precedence)
17/0013	. . {with stacked layers (H01F 27/2804 takes precedence)}	21/005	. {Inductances without magnetic core}
2017/002	. . . {Details of via holes for interconnecting the layers}	21/02	. continuously variable, e.g. variometers
2017/0026	. . . {Multilayer LC-filter}	21/04	. . by relative movement of turns or parts of windings
17/0033	. . {with the coil helically wound around a magnetic core}	21/06	. . by movement of core or part of core relative to the windings as a whole
2017/004	. . {with the coil helically wound around an axis without a core}	21/065	. . . {Measures for obtaining a desired relation between the position of the core and the inductance}
2017/0046	. . {with a conductive path having a bridge}	21/08	. . by varying the permeability of the core, e.g. by varying magnetic bias
2017/0053	. . {with means to reduce eddy currents}	21/10	. . by means of a movable shield
2017/006	. . {flexible printed inductors}	21/12	. discontinuously variable, e.g. tapped
2017/0066	. . {with a magnetic layer}	2021/125	. . {Printed variable inductor with taps, e.g. for VCO}
2017/0073	. . {with a special conductive pattern, e.g. flat spiral}	27/00	Details of transformers or inductances, in general
2017/008	. . {Electric or magnetic shielding of printed inductances}	27/002	. {Arrangements provided on the transformer facilitating its transport}
2017/0086	. . {on semiconductor substrate (inductors for integrated circuits H01L 28/10)}	27/004	. {Arrangements for interchanging inductances, transformers or coils thereof}
2017/0093	. {Common mode choke coil}	27/006	. {with special arrangement or spacing of turns of the winding(s), e.g. to produce desired self-resonance}
17/02	. without magnetic core	27/008	. {with temperature compensation}
17/03	. . with ceramic former	27/02	. Casings
17/04	. with magnetic core	27/022	. . {Encapsulation}
17/041	. . {Means for preventing rotation or displacement of the core}	27/025	. . {Constructional details relating to cooling}
17/043	. . {with two, usually identical or nearly identical parts enclosing completely the coil (pot cores)}	27/027	. . {specially adapted for combination of signal type inductors or transformers with electronic circuits, e.g. mounting on printed circuit boards}
17/045	. . {with core of cylindric geometry and coil wound along its longitudinal axis, i.e. rod or drum core}	27/04	. . Leading of conductors or axes through casings, e.g. for tap-changing arrangements
2017/046	. . . {helical coil made of flat wire, e.g. with smaller extension of wire cross section in the direction of the longitudinal axis}	27/06	. Mounting, supporting or suspending transformers, reactors or choke coils {not being of the signal type}
2017/048	. . {with encapsulating core, e.g. made of resin and magnetic powder}	2027/065	. . {Mounting on printed circuit boards}
17/06	. . with core substantially closed in itself, e.g. toroid	27/08	. Cooling (heat-transfer elements F28F); Ventilating (structural details of casings H01F 27/02)
17/062	. . . {Toroidal core with turns of coil around it}	27/085	. . {Cooling by ambient air}
2017/065	. . . {Core mounted around conductor to absorb noise, e.g. EMI filter}	27/10	. . Liquid cooling
2017/067	. . . {Core with two or more holes to lead through conductor}	27/105	. . . {Cooling by special liquid or by liquid of particular composition}
17/08	. . . Loading coils for telecommunication circuits	27/12	. . . Oil cooling
19/00	Fixed transformers or mutual inductances of the signal type (H01F 36/00 takes precedence)	27/125 {Cooling by synthetic insulating and incombustible liquid}
19/02	. Audio-frequency transformers or mutual inductances, i.e. not suitable for handling frequencies considerably beyond the audio range	27/14 Expansion chambers; Oil conservators; Gas cushions; Arrangements for purifying, drying, or filling
19/04	. Transformers or mutual inductances suitable for handling frequencies considerably beyond the audio range (resonant circuits H03H)	27/16 Water cooling
19/06	. . Broad-band transformers, e.g. suitable for handling frequencies well down into the audio range	27/18 by evaporating liquids
		27/20	. . Cooling by special gases or non-ambient air
		27/22	. . Cooling by heat conduction through solid or powdered fillings
		27/23	. Corrosion protection
		27/24	. Magnetic cores
		27/245	. . made from sheets, e.g. grain-oriented (H01F 27/26 takes precedence)
		27/2455	. . . {using bent laminations}

- 27/25 . . . made from strips or ribbons ([H01F 27/26 takes precedence](#))
- 27/255 . . . made from particles ([H01F 27/26 takes precedence](#))
- 27/26 . . . Fastening parts of the core together; Fastening or mounting the core on casing or support ([on coil H01F 27/30](#))
- 27/263 . . . {Fastening parts of the core together}
- 27/266 . . . {Fastening or mounting the core on casing or support ([on coil H01F 27/30](#))}
- 27/28 . . Coils; Windings; Conductive connections
- 27/2804 . . . {Printed windings}
- 2027/2809 . . . {on stacked layers}
- 2027/2814 . . . {with only part of the coil or of the winding in the printed circuit board, e.g. the remaining coil or winding sections can be made of wires or sheets}
- 2027/2819 . . . {Planar transformers with printed windings, e.g. surrounded by two cores and to be mounted on printed circuit}
- 27/2823 . . . {Wires ([H01F 27/2866 takes precedence](#))}
- 27/2828 . . . {Construction of conductive connections, of leads}
- 2027/2833 . . . {using coaxial cable as wire}
- 2027/2838 . . . {using transposed wires}
- 2027/2842 . . . {Wire coils wound in conical zigzag to reduce voltage between winding turns}
- 27/2847 . . . {Sheets; Strips ([H01F 27/2866 takes precedence](#))}
- 27/2852 . . . {Construction of conductive connections, of leads}
- 2027/2857 . . . {Coil formed from wound foil conductor}
- 2027/2861 . . . {Coil formed by folding a blank}
- 27/2866 . . . {Combination of wires and sheets}
- 27/2871 . . . {Pancake coils}
- 27/2876 . . . {Cooling ([cooling transformers and inductances in general H01F 27/08](#))}
- 27/288 . . . {Shielding}
- 27/2885 . . . {with shields or electrodes ([shields or electrodes for pancake coils H01F 27/2871; construction of electric or magnetic shields or screens H01F 27/36](#))}
- 27/289 . . . {with auxiliary windings ([for pancake coils H01F 27/2871](#))}
- 27/2895 . . . {Windings disposed upon ring cores}
- 27/29 . . . Terminals; Tapping arrangements {for signal inductances}
- 27/292 . . . {Surface mounted devices}
- 2027/295 {with flexible terminals}
- 2027/297 . . . {with pin-like terminal to be inserted in hole of printed path}
- 27/30 . . . Fastening or clamping coils, windings, or parts thereof together; Fastening or mounting coils or windings on core, casing, or other support
- 27/303 . . . {Clamping coils, windings or parts thereof together}
- 27/306 . . . {Fastening or mounting coils or windings on core, casing or other support}
- 27/32 . . . Insulating of coils, windings, or parts thereof
- 27/321 . . . {using a fluid for insulating purposes only}
- 27/322 . . . {the insulation forming channels for circulation of the fluid}
- 27/323 . . . {Insulation between winding turns, between winding layers}
- 27/324 . . . {Insulation between coil and core, between different winding sections, around the coil; Other insulation structures}
- 27/325 {Coil bobbins ([formers for coils in general H01F 5/02](#))}
- 27/326 {specifically adapted for discharge lamp ballasts}
- 27/327 . . . {Encapsulating or impregnating ([encapsulating coil and core H01F 27/022](#))}
- 2027/328 {Dry-type transformer with encapsulated foil winding, e.g. windings coaxially arranged on core legs with spacers for cooling and with three phases}
- 2027/329 . . . {Insulation with semiconducting layer, e.g. to reduce corona effect}
- 27/33 . . Arrangements for noise damping
- 27/34 . . Special means for preventing or reducing unwanted electric or magnetic effects, e.g. no-load losses, reactive currents, harmonics, oscillations, leakage fields
- 27/341 . . . {Preventing or reducing no-load losses or reactive currents}
- 27/343 . . . {Preventing or reducing surge voltages; oscillations}
- 27/345 . . . {using auxiliary conductors}
- 27/346 . . . {Preventing or reducing leakage fields ([using magnetic shields H01F 27/365; using auxiliary windings H01F 27/38](#))}
- 2027/348 . . . {Preventing eddy currents}
- 27/36 . . . Electric or magnetic shields or screens ([movable for varying inductance H01F 21/10](#))
- 27/362 . . . {Electric shields or screens}
- 27/365 . . . {Magnetic shields or screens}
- 27/367 {using non-magnetic screens}
- 27/38 . . . Auxiliary core members; Auxiliary coils or windings
- 27/385 . . . {for reducing harmonics}
- 27/40 . . Structural association with built-in electric component, e.g. fuse
- 27/402 . . . {Association of measuring or protective means}
- 2027/404 . . . {Protective devices specially adapted for fluid filled transformers}
- 2027/406 . . . {Temperature sensor or protection}
- 2027/408 . . . {Association with diode or rectifier}
- 27/42 . . Circuits specially adapted for the purpose of modifying, or compensating for, electric characteristics of transformers, reactors, or choke coils ([circuits for controlling transformers, reactors or choke coils, for the purpose of obtaining a desired output H02P 13/00; impedance networks H03H](#))
- 27/422 . . . {for instrument transformers}
- 27/425 . . . {for voltage transformers}
- 27/427 . . . {for current transformers}
- 29/00** **Variable transformers or inductances not covered by group [H01F 21/00](#) {[tap change devices H01H 9/0005](#)}**
- 29/02 . . with tapplings on coil or winding; with provision for rearrangement or interconnection of windings
- 29/025 . . . {Constructional details of transformers or reactors with tapping on coil or windings}
- 29/04 . . having provision for tap-changing without interrupting the load current

29/06	• with current collector gliding or rolling on or along winding	38/14	• Inductive couplings {(for charging batteries from ac mains by converters H02J 7/025)}
29/08	• with core, coil, winding, or shield movable to offset variation of voltage or phase shift, e.g. induction regulators	2038/143	• • {for signals}
29/10	• • having movable part of magnetic circuit {(high leakage transformers H01F 38/08 ; dynamo-electric machines with movable part of magnetic circuit H02K 23/44 , H02K 23/48)}	2038/146	• • {in combination with capacitive coupling}
29/12	• • having movable coil, winding, or part thereof; having movable shield	38/16	• Cascade transformers, e.g. for use with extra high tension
29/14	• with variable magnetic bias {(amplitude modulation by means of variable impedance element H03C 1/08) ; magnetic amplifiers H03F ; {circuits for automatic telephonic communication H04M 3/00)}	38/18	• Rotary transformers
2029/143	• • {with control winding for generating magnetic bias}	38/20	• Instruments transformers
29/146	• • {Constructional details}	38/22	• • for single phase ac
30/00	Fixed transformers not covered by group H01F 19/00	38/24	• • • Voltage transformers
30/02	• Auto-transformers	38/26	• • • • Constructions
30/04	• having two or more secondary windings, each supplying a separate load, e.g. for radio set power supplies	38/28	• • • Current transformers
30/06	• characterised by the structure	38/30	• • • • Constructions
30/08	• • without magnetic core	2038/305	• • • • • {with toroidal magnetic core}
30/10	• • Single-phase transformers (H01F 30/16 takes precedence)	38/32	• • • • Circuit arrangements
30/12	• • Two-phase, three-phase or polyphase transformers	38/34	• • • Combined voltage and current transformers
30/14	• • • for changing the number of phases	38/36	• • • • Constructions
30/16	• • Toroidal transformers	38/38	• • for polyphase ac
36/00	Transformers with superconductive windings or with windings operating at cryogenic temperature (superconducting magnets or superconducting coils H01F 6/00)	38/40	• • for dc
37/00	Fixed inductances not covered by group H01F 17/00	38/42	• Flyback transformers
37/005	• {without magnetic core}	2038/423	• • {with adjusting potentiometers}
38/00	Adaptations of transformers or inductances for specific applications or functions	2038/426	• • {with gap in transformer core}
2038/003	• {High frequency transformer for microwave oven}	41/00	Apparatus or processes specially adapted for manufacturing or assembling magnets, inductances or transformers; Apparatus or processes specially adapted for manufacturing materials characterised by their magnetic properties
2038/006	• {matrix transformer consisting of several interconnected individual transformers working as a whole}	41/005	• {Impregnating or encapsulating (insulating of windings H01F 41/12)}
38/02	• for non-linear operation	41/02	• for manufacturing cores, coils, or magnets (H01F 41/14 takes precedence; for dynamo-electric machines H02K 15/00)
38/023	• • {of inductances}	41/0206	• • {Manufacturing of magnetic cores by mechanical means (magnetic cores per se H01F 27/24)}
2038/026	• • • {non-linear inductive arrangements for converters, e.g. with additional windings}	41/0213	• • • {Manufacturing of magnetic circuits made from strip(s) or ribbon(s) (magnetic cores made by winding a ribbon H01F 27/25)}
38/04	• • for frequency changing	41/022	• • • • {by winding the strips or ribbons around a coil}
38/06	• • for changing the wave shape	41/0226	• • • • • {from amorphous ribbons}
38/08	• High-leakage transformers or inductances	41/0233	• • • {Manufacturing of magnetic circuits made from sheets (magnetic cores made from sheets H01F 27/245 ; soft magnetic alloys in the form of sheets H01F 1/16)}
38/085	• • {Welding transformers}	41/024	• • • • {Manufacturing of magnetic circuits made from deformed sheets (magnetic cores made from deformed sheets H01F 27/2455)}
38/10	• • Ballasts, e.g. for discharge lamps	41/0246	• • • {Manufacturing of magnetic circuits by moulding or by pressing powder (magnetic cores made by moulding or by pressing powder H01F 27/255 ; soft magnetic particles H01F 1/20 , H01F 1/36)}
38/12	• Ignition, e.g. for IC engines	41/0253	• • {for manufacturing permanent magnets}
2038/122	• • {with rod-shaped core}	41/026	• • • {protecting methods against environmental influences, e.g. oxygen, by surface treatment (magnetic particles with skin H01F 1/061 , H01F 1/09 , H01F 1/24 , H01F 1/33 and G11B 5/706)}
2038/125	• • {with oil insulation}	41/0266	• • • {Moulding; Pressing (H01F 41/0273 takes precedence; hard magnetic particles H01F 1/06 , H01F 1/11)}
2038/127	• • {with magnetic circuit including permanent magnet}		

- 41/0273 . . . {Imparting anisotropy (methods and devices for magnetising permanent magnets [H01F 13/003](#))}
- 41/028 {Radial anisotropy (for rotor or stator bodies [H02K 15/02](#))}
- 41/0286 . . . {Trimming}
- 41/0293 . . . {diffusion of rare earth elements, e.g. Tb, Dy or Ho, into permanent magnets}
- 41/04 . . for manufacturing coils {(coils for transformer or inductances [H01F 27/28](#))}
- 41/041 . . . {Printed circuit coils (apparatus or processes for manufacturing printed circuits in general [H05K 3/00](#))}
- 41/042 {by thin film techniques}
- 41/043 {by thick film techniques}
- 41/045 {Trimming}
- 41/046 {structurally combined with ferromagnetic material}
- 41/047 {structurally combined with superconductive material}
- 41/048 . . . {Superconductive coils}
- 41/06 . . . Coil winding
- 41/061 Winding flat conductive wires or sheets
- 41/063 with insulation
- 41/064 Winding non-flat conductive wires, e.g. rods, cables or cords
- 41/066 with insulation
- 41/068 in the form of strip material
- 41/069 Winding two or more wires, e.g. bifilar winding
- 41/07 Twisting
- 41/071 Winding coils of special form ([winding conductors onto closed formers or cores \[H01F 41/08\]\(#\)](#))
- 2041/0711 {Winding saddle or deflection coils}
- 41/073 Winding onto elongate formers
- 41/074 Winding flat coils
- 41/076 Forming taps or terminals while winding, e.g. by wrapping or soldering the wire onto pins, or by directly forming terminals from the wire
- 41/077 Deforming the cross section or shape of the winding material while winding
- 41/079 Measuring electrical characteristics while winding
- 41/08 Winding conductors onto closed formers or cores, e.g. threading conductors through toroidal cores
- 41/082 Devices for guiding or positioning the winding material on the former
- 41/084 for forming pancake coils
- 41/086 in a special configuration on the former, e.g. orthocyclic coils or open mesh coils
- 41/088 using revolving flyers
- 41/09 Winding machines having two or more work holders or formers
- 41/092 Turrets; Turntables
- 41/094 Tensioning or braking devices
- 41/096 Dispensing or feeding devices
- 41/098 Mandrels; Formers
- 41/10 . . . Connecting leads to windings ([making electric connections in general \[H01R 43/00\]\(#\)](#))
- 41/12 . . . Insulating of windings ({impregnating or encapsulating of transformers [H01F 41/005](#)}; of conductors in general [H01B 13/06](#))
- 41/122 {Insulating between turns or between winding layers}
- 41/125 {Other insulating structures; Insulating between coil and core, between different winding sections, around the coil}
- 41/127 {Encapsulating or impregnating (encapsulating coil and core [H01F 41/005](#))}
- 41/14 . . for applying magnetic films to substrates ([covering metals, or materials with metals, in general \[C23C\]\(#\); manufacturing record carriers \[G11B 5/84\]\(#\)](#))
- NOTE**
Group [H01F 41/30](#) takes precedence over groups [H01F 41/16](#) - [H01F 41/24](#), and over group [H01F 41/32](#)
- 41/16 . . the magnetic material being applied in the form of particles, e.g. by serigraphy {, i.e. forming thick magnetic films and precursors therefor, e.g. magnetisable pastes, inks, glass frits ([H01F 41/18](#) - [H01F 41/24](#) take precedence; thick magnetic films [H01F 1/0027](#))}
- 41/18 . . by cathode sputtering
- 41/183 . . . {Sputtering targets therefor}
- 41/186 . . . {for applying a magnetic garnet film (magnetic garnet materials [H01F 1/346](#); magnetic garnet films [H01F 10/24](#))}
- 41/20 . . by evaporation
- 41/205 . . . {by laser ablation, e.g. pulsed laser deposition [PLD]}
- 41/22 . . Heat treatment; Thermal decomposition; Chemical vapour deposition
- 41/24 . . from liquids
- 41/26 . . . using electric currents {, e.g. electroplating}
- 41/28 . . . by liquid phase epitaxy
- 41/30 . . for applying nanostructures, e.g. by molecular beam epitaxy [MBE]
- 41/301 . . . {for applying ultrathin or granular layers (ultrathin or granular layers [H01F 10/007](#))}
- 41/302 . . . {for applying spin-exchange-coupled multilayers, e.g. nanostructured superlattices (spin-exchange-coupled multilayers [H01F 10/32](#))}
- 41/303 {with exchange coupling adjustment of magnetic film pairs, e.g. interface modifications by reduction, oxidation}
- 41/304 {using temporary decoupling, e.g. involving blocking, Néel or Curie temperature transitions by heat treatment in presence/absence of a magnetic field}
- 41/305 {applying the spacer or adjusting its interface, e.g. in order to enable particular effect different from exchange coupling}
- 41/306 {conductive spacer}
- 41/307 {insulating or semiconductive spacer}
- 41/308 {lift-off processes, e.g. ion milling, for trimming or patterning}
- 41/309 {electroless or electrodeposition processes from plating solution}
- 41/32 . . for applying conductive, insulating or magnetic material on a magnetic film {, specially adapted for a thin magnetic film}

H01F

- 41/325 . . {applying a noble metal capping on a spin-exchange-coupled multilayer, e.g. spin filter deposition}

WARNING

This groups is not complete pending the completion of reclassification; see provisionally also [H01F 41/32](#)

- 41/34 . . in patterns, e.g. by lithography