

CPC COOPERATIVE PATENT CLASSIFICATION

H ELECTRICITY

(NOTE omitted)

H04 ELECTRIC COMMUNICATION TECHNIQUE

(NOTE omitted)

H04R LOUDSPEAKERS, MICROPHONES, GRAMOPHONE PICK-UPS OR LIKE ACOUSTIC ELECTROMECHANICAL TRANSDUCERS; DEAF-AID SETS; PUBLIC ADDRESS SYSTEMS (generating mechanical vibrations in general [B06B](#); transducers for measuring particular variables [G01](#); transducers in clocks [G04](#); producing sounds with frequency not determined by supply frequency [G10K](#); transducers in recording or reproducing heads [G11B](#); transducers in motors [H02](#))

NOTE

This subclass covers :

- loudspeakers, microphones, {acoustic} transducers {therefor} producing acoustic waves or variations of electric current or voltage, or gramophone pick-ups;
- arrangements actuated by variations of electric current or voltage for cutting grooves in records;
- circuits for the above-mentioned {loudspeakers, microphones, acoustic transducers, gramophone pick-ups or} arrangements;
- monitoring or testing {of the above-mentioned loudspeakers, microphones, acoustic transducers, gramophone pick-ups or} arrangements

1/00 Details of transducers, {loudspeakers or microphones}

1/005 . {using digitally weighted transducing elements}

1/02 . Casings; Cabinets {; Supports therefor;} Mountings therein ([H04R 1/28](#) takes precedence {; attachments for microphones [H04R 1/08](#); mounting of transducers in earpieces [H04R 1/1075](#)})

1/021 . . {incorporating only one transducer}

1/023 . . {Screens for loudspeakers}

1/025 . . {Arrangements for fixing loudspeaker transducers, e.g. in a box, furniture}

1/026 . . {Supports for loudspeaker casings}

1/028 . . {associated with devices performing functions other than acoustics, e.g. electric candles}

1/04 . . Structural association of microphone with electric circuitry therefor (in deaf-aid sets [H04R 25/00](#))

1/06 . Arranging circuit leads; Relieving strain on circuit leads

1/08 . Mouthpieces; {Microphones;} Attachments therefor

1/083 . . {Special constructions of mouthpieces}

1/086 . . . {Protective screens, e.g. all weather or wind screens}

1/10 . Earpieces; Attachments therefor {; Earphones; Monophonic headphones ([H04R 1/28](#) takes precedence; stereophonic headphones [H04R 5/033](#))}

NOTES

1. This group covers details of headphones, both of monophonic and stereophonic type.
2. When classifying in this group or in its subgroups, aspects relating to stereophonic headphones are to be classified in [H04R 5/033](#) as well

1/1008 . . {Earpieces of the supra-aural or circum-aural type}

1/1016 . . {Earpieces of the intra-aural type}

1/1025 . . {Accumulators or arrangements for charging (secondary cells per se [H01M 10/00](#); charging in general [H02J 7/00](#))}

1/1033 . . {Cables or cables storage, e.g. cable reels (cord reels per se [H02G 11/02](#); arrangements for storing and repeatedly paying-out and re-storing lengths of conductors or cables [B65H 75/34](#); extensible conductors or cables, e.g. self-coiling cords [H01B 7/06](#))}

1/1041 . . {Mechanical or electronic switches, or control elements (switches in general [H01H](#))}

1/105 . . {Earpiece supports, e.g. ear hooks (for stereophonic headphones [H04R 5/0335](#))}

1/1058 . . {Manufacture or assembly}

1/1066 . . . {Constructional aspects of the interconnection between earpiece and earpiece support (earpiece support for monophonic headphones [H04R 1/105](#); earpiece support for stereophonic headphones [H04R 5/0335](#))}

1/1075 . . . {Mountings of transducers in earphones or headphones}

1/1083 . . {Reduction of ambient noise (active noise reduction per se [G10K 11/175](#); protective devices for the ear, e.g. providing acoustic protection [A61F 11/06](#))}

1/1091 . . {Details not provided for in groups [H04R 1/1008](#) - [H04R 1/1083](#)}

1/12 . Sanitary or hygienic devices for mouthpieces or earpieces, e.g. for protecting against infection

1/14 . Throat mountings for microphones

1/16 . Mounting or connecting stylus to transducer with or without damping means

- 1/18 . . Holders for styli; Mounting holders on transducers
- 1/20 . Arrangements for obtaining desired frequency or directional characteristics (for stereophonic purpose [H04R 5/00](#))
- 1/22 . . for obtaining desired frequency characteristic only (circuit for combining transducers having different responses [H04R 3/00](#) {for hearing aids [H04R 25/407](#)})
- 1/222 . . . {for microphones ([H04R 1/24](#), [H04R 1/26](#) take precedence)}
- 1/225 . . . {for telephonic receivers}
- 1/227 . . . {using transducers reproducing the same frequency band}
- 1/24 . . . Structural combinations of separate transducers or of two parts of the same transducer and responsive respectively to two or more frequency ranges
- 1/245 {of microphones}
- 1/26 . . . Spatial arrangements of separate transducers responsive to two or more frequency ranges
- 1/265 {of microphones}
- 1/28 . . . Transducer mountings or enclosures modified by provision of mechanical or acoustic impedances, e.g. resonator, damping means {combinations of transducers with horns, i.e. front-loaded horns [H04R 1/30](#)}
- 1/2803 {for loudspeaker transducers}
- 1/2807 {Enclosures comprising vibrating or resonating arrangements (for the reduction of undesired resonances or vibrations [H04R 1/2869](#))}
- 1/2811 {for loudspeaker transducers}
- 1/2815 {of the bass reflex type}
- 1/2819 {for loudspeaker transducers}
- 1/2823 {Vents, i.e. ports, e.g. shape thereof or tuning thereof with damping material (number or position of ports [H04R 1/2815](#); vents in bandpass type enclosures [H04R 1/2846](#))}
- 1/2826 {for loudspeaker transducers}
- 1/283 {using a passive diaphragm}
- 1/2834 {for loudspeaker transducers}
- 1/2838 {of the bandpass type}
- 1/2842 {for loudspeaker transducers}
- 1/2846 {Vents, i.e. ports, e.g. shape thereof or tuning thereof with damping material (number or position of ports [H04R 1/2838](#); vents in bass reflex type enclosures [H04R 1/2823](#))}
- 1/2849 {for loudspeaker transducers}
- 1/2853 {using an acoustic labyrinth or a transmission line}
- 1/2857 {for loudspeaker transducers}
- 1/2861 {using a back-loaded horn}
- 1/2865 {for loudspeaker transducers}
- 1/2869 {Reduction of undesired resonances, i.e. standing waves within enclosure, or of undesired vibrations, i.e. of the enclosure itself}
- 1/2873 {for loudspeaker transducers}
- 1/2876 {by means of damping material, e.g. as cladding (damping material for tuning desired resonances [H04R 1/2807](#), e.g. in vents [H04R 1/2823](#), [H04R 1/2846](#))}
- 1/288 {for loudspeaker transducers}
- 1/2884 {by means of the enclosure structure, i.e. strengthening or shape of the enclosure (by means of Helmholtz resonators [H04R 1/2869](#))}
- 1/2888 {for loudspeaker transducers}
- 1/2892 {Mountings or supports for transducers}
- 1/2896 {for loudspeaker transducers}
- 1/30 . . . Combinations of transducers with horns, e.g. with mechanical matching means {, i.e. front-loaded horns} (horns in general [G10K](#); {transducer enclosures or mountings using a back-loaded horn [H04R 1/2861](#); application of horns as guiding means to obtain a predetermined directivity characteristic [H04R 1/345](#))}
- 1/32 . . for obtaining desired directional characteristic only {(specially adapted for hearing aids [H04R 25/40](#))}
- 1/323 . . . {for loudspeakers ([H04R 1/34](#) and [H04R 1/40](#) take precedence)}
- 1/326 . . . {for microphones ([H04R 1/34](#) and [H04R 1/40](#) take precedence)}
- 1/34 . . . by using a single transducer with sound reflecting, diffracting, directing or guiding means {(specially adapted for hearing aids [H04R 25/402](#))}
- 1/342 {for microphones}
- 1/345 {for loudspeakers}
- 1/347 {for obtaining a phase-shift between the front and back acoustic wave}
- 1/36 by using a single aperture of dimensions not greater than the shortest operating wavelength
- 1/38 in which sound waves act upon both sides of a diaphragm and incorporating acoustic phase-shifting means, e.g. pressure-gradient microphone
- 1/40 . . . by combining a number of identical transducers {(specially adapted for hearing aids [H04R 25/405](#))}
- 1/403 {loud-speakers}
- 1/406 {microphones}
- 1/42 . Combinations of transducers with fluid-pressure or other non-electrical amplifying means
- 1/44 . Special adaptations for subaqueous use, e.g. for hydrophone
- 1/46 . Special adaptations for use as contact microphones, e.g. on musical instrument, on stethoscope (throat mountings [H04R 1/14](#))
- 3/00 Circuits for transducers {, loudspeakers or microphones}**
- 3/002 . {Damping circuit arrangements for transducers, e.g. motional feedback circuits}
- 3/005 . {for combining the signals of two or more microphones (specially adapted for hearing aids [H04R 25/407](#))}
- 3/007 . {Protection circuits for transducers}

- 3/02 . for preventing acoustic reaction {, i.e. [acoustic oscillatory feedback \(specially adapted for hearing aids H04R 25/453\)](#)}
- 3/04 . for correcting frequency response
- 3/06 . . of electrostatic transducers
- 3/08 . . of electromagnetic transducers
- 3/10 . . of variable resistance microphones
- 3/12 . for distributing signals to two or more loudspeakers {[\(specially adapted for hearing aids H04R 25/407\)](#)}
- 3/14 . . Cross-over networks
- 5/00 Stereophonic arrangements** ([stereophonic pick-ups H04R 9/16, H04R 11/12, H04R 17/08, H04R 19/10](#))
- NOTE**
In this group, the expression "stereophonic arrangements" covers quadrasonic or similar arrangements.
- 5/02 . Spatial or constructional arrangements of loudspeakers
- 5/023 . . {[in a chair, pillow](#)}
- 5/027 . Spatial or constructional arrangements of microphones, e.g. in dummy heads
- 5/033 . Headphones for stereophonic communication {[\(details thereof, e.g. relating to batteries, cables or control elements H04R 1/10\)](#)}
- 5/0335 . . {[Earpiece support, e.g. headbands or neckrests \(for monophonic headphones H04R 1/105\)](#)}
- 5/04 . Circuit arrangements, {e.g. for selective connection of amplifier inputs/outputs to loudspeakers, for loudspeaker detection, or for adaptation of settings to personal preferences or hearing impairments [\(combinations of amplifiers H03F 3/68; stereophonic systems H04S\)](#)}
- 7/00 Diaphragms for electromechanical transducers** (in general [F16J 3/00](#)); **Cones** (for musical instruments [G10](#)) {[\(cones, diaphragms or the like, for emitting or receiving sound in general G10K 13/00; Mounting thereof\)](#)}
- 7/02 . characterised by the construction
- 7/04 . . Plane diaphragms
- 7/045 . . . {[using the distributed mode principle, i.e. whereby the acoustic radiation is emanated from uniformly distributed free bending wave vibration induced in a stiff panel and not from piston motion](#)}
- 7/06 . . . comprising a plurality of sections or layers
- 7/08 . . . comprising superposed layers separated by air or other fluid
- 7/10 . . . comprising superposed layers in contact
- 7/12 . . Non-planar diaphragms or cones
- 7/122 . . . {[comprising a plurality of sections or layers](#)}
- 7/125 {[comprising a plurality of superposed layers in contact](#)}
- 7/127 . . . {[dome-shaped](#)}
- 7/14 . . . corrugated, pleated or ribbed
- 7/16 . Mounting or tensioning of diaphragms or cones
- 7/18 . . at the periphery
- 7/20 . . . Securing diaphragm or cone resiliently to support by flexible material, springs, cords, or strands
- 7/22 . . . Clamping rim of diaphragm or cone against seating
- 7/24 . . Tensioning by means acting directly on free portions of diaphragm or cone
- 7/26 . Damping by means acting directly on free portion of diaphragm or cone ([air damping H04R 1/28](#))
- 9/00 Transducers of moving-coil, moving-strip, or moving-wire type**
- 9/02 . Details
- 9/022 . . {[Cooling arrangements](#)}
- 9/025 . . {[Magnetic circuit](#)}
- 9/027 . . . {[Air gaps using a magnetic fluid](#)}
- 9/04 . . Construction, mounting, or centering of coil
- 9/041 . . . {[Centering](#)}
- 9/042 {[by pressurised air](#)}
- 9/043 {[Inner suspension or damper, e.g. spider \(outer suspension or surround H04R 7/16\)](#)}
- 9/045 . . . {[Mounting \(H04R 9/043 takes precedence\)](#)}
- 9/046 . . . {[Construction](#)}
- 9/047 {[in which the windings of the moving coil lay in the same plane](#)}
- 9/048 {[of the ribbon type](#)}
- 9/06 . Loudspeakers
- 9/063 . . {[using a plurality of acoustic drivers \(H04R 1/24 and H04R 1/403 take precedence\)](#)}
- 9/066 . . {[using the principle of inertia](#)}
- 9/08 . Microphones
- 9/10 . Telephone receivers
- 9/12 . Gramophone pick-ups using a stylus; Recorders using a stylus
- 9/14 . . comprising two or more styli or transducers ([H04R 9/16 takes precedence](#))
- 9/16 . . signals recorded or played back by vibration of a stylus in two orthogonal directions simultaneously
- 9/18 . Resonant transducers, i.e. adapted to produce maximum output at a predetermined frequency
- 11/00 Transducers of moving-armature or moving-core type** ([acoustic diaphragm of magnetisable material directly coacting with electromagnet H04R 13/00](#))
- 11/02 . Loudspeakers
- 11/04 . Microphones
- 11/06 . Telephone receivers
- 11/08 . Gramophone pick-ups using a stylus; Recorders using a stylus
- 11/10 . . comprising two or more styli or transducers ([H04R 11/12 takes precedence](#))
- 11/12 . . signals being recorded or played back by vibration of a stylus in two orthogonal directions simultaneously
- 11/14 . Resonant transducers, i.e. adapted to produce maximum output at a predetermined frequency
- 13/00 Transducers having an acoustic diaphragm of magnetisable material directly co-acting with electromagnet**
- 13/02 . Telephone receivers
- 15/00 Magnetostrictive transducers** ([magnetostrictive elements in general H01L 41/00](#))
- 15/02 . Resonant transducers, i.e. adapted to produce maximum output at a predetermined frequency

17/00	Piezo-electric transducers; Electrostrictive transducers (piezo-electric or electrostrictive elements in general H01L 41/00 ; details of piezo-electric or electrostrictive motors, generators or positioners {H01L 41/00})	25/00	Deaf-aid sets {providing an auditory perception; Electric tinnitus maskers providing an auditory perception} (constructions of transducers per se H04R 9/00 - H04R 23/00 ; {non-electric hearing aids A61F 11/008 ; replacing direct auditory perception by another kind of perception A61F 11/04 ; electrical stimulation of auditory nerves to promote the auditory function A61N 1/36036 }; structural combination with spectacle frames G02C 11/06 ; processing of speech signals G10L 21/00)
17/005	• {using a piezo-electric polymer}		
17/02	• Microphones		
17/025	• • {using a piezo-electric polymer}		
17/04	• Gramophone pick-ups using a stylus; Recorders using a stylus		
17/06	• • comprising two or more styli or transducers (H04R 17/08 takes precedence)		
17/08	• • signals being recorded or played back by vibration of a stylus in two orthogonal directions simultaneously		
17/10	• Resonant transducers, i.e. adapted to produce maximum output at a predetermined frequency		
19/00	Electrostatic transducers		
19/005	• {using semiconductor materials}	25/02	• adapted to be supported entirely by ear
19/01	• characterised by the use of electrets	25/04	• comprising pocket amplifiers
19/013	• • {for loudspeakers}	25/30	• {Monitoring or testing of hearing aids, e.g. functioning, settings, battery power (testing arrangements for electro-acoustic transducers in general H04R 29/00 ; battery testing in general G01R 31/36)}
19/016	• • {for microphones}		
19/02	• Loudspeakers (H04R 19/01 takes precedence)	25/305	• • {Self-monitoring or self-testing}
19/04	• Microphones (H04R 19/01 takes precedence)	25/35	• {using translation techniques}
19/06	• Gramophone pick-ups using a stylus; Recorders using a stylus (H04R 19/01 takes precedence)	25/353	• • {Frequency, e.g. frequency shift or compression}
19/08	• • comprising two or more styli or transducers (H04R 19/10 takes precedence)	25/356	• • {Amplitude, e.g. amplitude shift or compression}
19/10	• • signals being recorded or played back by vibration of a stylus in two orthogonal directions simultaneously	25/40	• {Arrangements for obtaining a desired directivity characteristic}
		25/402	• • {using contructional means}
		25/405	• • {by combining a plurality of transducers}
21/00	Variable-resistance transducers (gaseous resistance transducers H04R 23/00 ; magneto-resistive transducers H04R 23/00)	25/407	• • {Circuits for combining signals of a plurality of transducers}
21/02	• Microphones	25/43	• {Electronic input selection or mixing based on input signal analysis, e.g. mixing or selection between microphone and telecoil or between microphones with different directivity characteristics (H04R 25/407 takes precedence)}
21/021	• • {with granular resistance material}		
21/023	• • {with more than one granular chamber}		
21/025	• • {disposition of the granular chamber in microphones}		
21/026	• • {in which the sound is perpendicular to the current crossing the transducer material}		
21/028	• • {with a fluid as resistance material}		
21/04	• Gramophone pick-ups using a stylus; Recorders using a stylus	25/45	• {Prevention of acoustic reaction, i.e. acoustic oscillatory feedback}
		25/453	• • {electronically (in general H04R 3/02)}
23/00	Transducers other than those covered by groups H04R 9/00 - H04R 21/00 {(diaphragms for transducers of the distributed-mode type H04R 7/045)}	25/456	• • {mechanically}
23/002	• {using electrothermic-effect transducer}	25/48	• {using constructional means for obtaining a desired frequency response (H04R 25/652 takes precedence ; in general H04R 1/22)}
23/004	• {using ionised gas}	25/50	• {Customised settings for obtaining desired overall acoustical characteristics}
23/006	• {using solid state devices (solid state devices per se H01L)}	25/502	• • {using analog signal processing}
23/008	• {using optical signals for detecting or generating sound}	25/505	• • {using digital signal processing}
23/02	• Transducers using more than one principle simultaneously	25/507	• • • {implemented by neural network or fuzzy logic}
		25/55	• {using an external connection, either wireless or wired}
		25/552	• • {Binaural}
		25/554	• • {using a wireless connection, e.g. between microphone and amplifier or using T-coils (near-field transmission in general H04B 5/00)}
		25/556	• • {External connectors, e.g. plugs or modules}

NOTE

Classification should be directed to groups [H04R 25/02](#), [H04R 25/04](#) or [H04R 25/50](#) and its subgroups, if and only if the technical subject in consideration cannot be classified elsewhere under the main group [H04R 25/00](#)

WARNING

Not complete pending a reorganization, see also [H04R 25/00](#)

- 25/558 . . {Remote control, e.g. of amplification, frequency (remote control of amplifications, tone, or bandwidth [H03G 1/02](#); remote control, e.g. for Hi-Fi systems or audio/video combinations [H04B 1/202](#); remote control in general [G05F](#))}
- 25/60 . {Mounting or interconnection of hearing aid parts, e.g. inside tips or housing, to ossicles (ear wax retarders, e.g. their mounting [H04R 25/654](#))}
- 25/602 . . {Arrangements for mounting batteries (batteries in general [H01M 2/02](#))}
- 25/604 . . {Arrangements for mounting transducers}
- 25/606 . . . {acting directly on the eardrum, the ossicles or the skull, e.g. mastoid, tooth, maxillary or mandibular bone, or mechanically stimulating the cochlea, e.g. at the oval window}
- 25/608 . . {Apparatus or processes specially adapted for mounting, assembling or interconnecting hearing aid parts inside tips, moulds or housings}
- WARNING**
Not complete pending a reorganization, see also [H04R 25/60](#) or its other subgroups
- 25/65 . {Housing parts, e.g. shells, tips or moulds, or their manufacture}
- 25/652 . . {Ear tips; Ear moulds}
- 25/654 . . . {Ear wax retarders}
- 25/656 . . . {Non-customized, universal ear tips, i.e. ear tips which are not specifically adapted to the size or shape of the ear or ear canal}
- WARNING**
Not complete pending a reorganization, see also [H04R 25/652](#)
- 25/658 . . {Manufacture of housing parts}
- WARNING**
Not complete pending a reorganization, see also [H04R 25/65](#) or its other subgroups
- 25/70 . {Adaptation of deaf aid to hearing loss, e.g. initial electronic fitting}
- 25/75 . {Electric tinnitus maskers providing an auditory perception (evaluating tinnitus [A61B 5/128](#); devices or methods to cause a change in the state of consciousness [A61M 21/00](#); masking sound in general [G10K 11/175](#))}
- WARNING**
Not complete pending a reorganization, see also [H04R 25/00](#)
- 27/00 Public address systems** (circuits for preventing acoustic reaction [H04R 3/02](#); circuits for distributing signals to loudspeakers [H04R 3/12](#); {monitoring or testing arrangements for public address systems [H04R 29/007](#)}; amplifiers [H03F](#))
- 27/02 . Amplifying systems for the deaf
- 27/04 . Electric megaphones
- 29/00 Monitoring arrangements; Testing arrangements** {(for hearing aids [H04R 25/30](#); detection of loudspeaker connection [H04R 5/04](#); sound-field adaptation dependent on speaker detection [H04S 7/308](#))}
- 29/001 . {for loudspeakers ([H04R 29/007](#) takes precedence)}
- 29/002 . . {Loudspeaker arrays}
- 29/003 . . {of the moving-coil type}
- 29/004 . {for microphones ([H04R 29/007](#) takes precedence)}
- 29/005 . . {Microphone arrays}
- 29/006 . . . {Microphone matching}
- 29/007 . {for public address systems (public address systems per se [H04R 27/00](#))}
- 29/008 . {Visual indication of individual signal levels (visual indication of stereophonic sound image [H04S 7/40](#))}
- 31/00 Apparatus or processes specially adapted for the manufacture of transducers or diaphragms therefor** {(manufacture of microstructural arrangements of deformable or non-deformable structures in general [B81C 1/00182](#))}
- 31/003 . {for diaphragms or their outer suspension}
- 31/006 . {Interconnection of transducer parts (of diaphragm and outer suspension by moulding [H04R 31/003](#))}
- 2201/00 Details of transducers, loudspeakers or microphones covered by [H04R 1/00](#) but not provided for in any of its subgroups (not used, see subgroups)**
- 2201/003 . Mems transducers or their use (of the electrostatic type [H04R 19/005](#))
- 2201/02 . Details casings, cabinets or mounting therein for transducers covered by [H04R 1/02](#) but not provided for in any of its subgroups
- 2201/021 . . Transducers or their casings adapted for mounting in or to a wall or ceiling
- 2201/023 . . Transducers incorporated in garment, rucksacks or the like
- 2201/025 . . Transducer mountings or cabinet supports enabling variable orientation of transducer of cabinet
- 2201/028 . . Structural combinations of loudspeakers with built-in power amplifiers, e.g. in the same acoustic enclosure ([H04R 2499/10](#) takes precedence; Single (sub)woofer with two or more satellite loudspeakers for mid- and high-frequency band reproduction driven via the (sub)woofer [H04R 2205/026](#))
- 2201/029 . . Manufacturing aspects of enclosures transducers
- 2201/10 . Details of earpieces, attachments therefor, earphones or monophonic headphones covered by [H04R 1/10](#) but not provided for in any of its subgroups
- 2201/103 . . Combination of monophonic or stereophonic headphones with audio players, e.g. integrated in the headphone
- 2201/105 . . Manufacture of mono- or stereophonic headphone components
- 2201/107 . . Monophonic and stereophonic headphones with microphone for two-way hands free communication
- 2201/109 . . Arrangements to adapt hands free headphones for use on both ears
- 2201/34 . Directing or guiding sound by means of a phase plug
- 2201/40 . Details of arrangements for obtaining desired directional characteristic by combining a number of identical transducers covered by [H04R 1/40](#) but not provided for in any of its subgroups
- 2201/401 . . 2D or 3D arrays of transducers

- 2201/403 . . Linear arrays of transducers
- 2201/405 . . Non-uniform arrays of transducers or a plurality of uniform arrays with different transducer spacing
- 2203/00 Details of circuits for transducers, loudspeakers or microphones covered by [H04R 3/00](#) but not provided for in any of its subgroups (not used, see subgroups)**
- 2203/12 . Beamforming aspects for stereophonic sound reproduction with loudspeaker arrays
- 2205/00 Details of stereophonic arrangements covered by [H04R 5/00](#) but not provided for in any of its subgroups (not used, see subgroups)**
- 2205/021 . Aspects relating to docking-station type assemblies to obtain an acoustical effect, e.g. the type of connection to external loudspeakers or housings, frequency improvement
- 2205/022 . Plurality of transducers corresponding to a plurality of sound channels in each earpiece of headphones or in a single enclosure
- 2205/024 . Positioning of loudspeaker enclosures for spatial sound reproduction
- 2205/026 . Single (sub)woofer with two or more satellite loudspeakers for mid- and high-frequency band reproduction driven via the (sub)woofer
- 2205/041 . Adaptation of stereophonic signal reproduction for the hearing impaired
- 2207/00 Details of diaphragms or cones for electromechanical transducers or their suspension covered by [H04R 7/00](#) but not provided for in [H04R 7/00](#) or in [H04R 2307/00](#) (not used, see subgroup)**
- 2207/021 . Diaphragm extensions, not necessarily integrally formed, e.g. skirts, rims, flanges
- 2209/00 Details of transducers of the moving-coil, moving-strip, or moving-wire type covered by [H04R 9/00](#) but not provided for in any of its subgroups (not used, see subgroups)**
- 2209/021 . Reduction of eddy currents in the magnetic circuit of electrodynamic loudspeaker transducer
- 2209/022 . Aspects regarding the stray flux internal or external to the magnetic circuit, e.g. shielding, shape of magnetic circuit, flux compensation coils
- 2209/024 . Manufacturing aspects of the magnetic circuit of loudspeaker or microphone transducers
- 2209/026 . Transducers having separately controllable opposing diaphragms, e.g. for ring-tone and voice ([H04R 2400/03](#) takes precedence)
- 2209/027 . Electrical or mechanical reduction of yoke vibration
- 2209/041 . Voice coil arrangements comprising more than one voice coil unit on the same bobbin
- 2209/043 . Short circuited voice coils driven by induction
- 2217/00 Details of magnetostrictive, piezo-electric, or electrostrictive transducers covered by [H04R 15/00](#) or [H04R 17/00](#) but not provided for in any of their subgroups (not used, see subgroup)**
- 2217/01 . Non-planar magnetostrictive, piezo-electric or electrostrictive benders
- 2217/03 . Parametric transducers where sound is generated or captured by the acoustic demodulation of amplitude modulated ultrasonic waves
- 2225/00 Details of deaf aids covered by [H04R 25/00](#), not provided for in any of its subgroups**
- 2225/021 . Behind the ear [BTE] hearing aids ([H04R 2225/63](#) takes precedence)
- 2225/023 . Completely in the canal [CIC] hearing aids
- 2225/025 . In the ear hearing aids [ITE] hearing aids
- 2225/31 . Aspects of the use of accumulators in hearing aids, e.g. rechargeable batteries or fuel cells
- 2225/33 . Aspects relating to adaptation of the battery voltage, e.g. its regulation, increase or decrease
- 2225/39 . Aspects relating to automatic logging of sound environment parameters and the performance of the hearing aid during use, e.g. histogram logging, or of user selected programs or settings in the hearing aid, e.g. usage logging
- 2225/41 . Detection or adaptation of hearing aid parameters or programs to listening situation, e.g. pub, forest
- 2225/43 . Signal processing in hearing aids to enhance the speech intelligibility
- 2225/49 . Reducing the effects of electromagnetic noise on the functioning of hearing aids, by, e.g. shielding, signal processing adaptation, selective (de)activation of electronic parts in hearing aid
- 2225/51 . Aspects of antennas and their circuitry in and for hearing aids
- 2225/53 . Hearing aid for unilateral hearing impairment using Contralateral Routing Of Signals [CROS]
- 2225/55 . Communication between hearing aids and external devices via a network for data exchange
- 2225/59 . Arrangements for selective connection between one or more amplifiers and one or more receivers within one hearing aid
- 2225/61 . Aspects relating to mechanical or electronic switches or control elements in hearing aids ([H04R 2225/43](#) takes precedence)
- 2225/63 . Aspects relating to ear hooks or their connection to the hearing aid housing or ear mould
- 2225/67 . Implantable hearing aids or parts thereof not covered by [H04R 25/606](#)
- 2225/77 . Design aspects, e.g. CAD, of hearing aid tips, moulds or housings
- 2225/81 . Aspects of electrical fitting of hearing aids related to problems arising from the emotional state of a hearing aid user, e.g. nervousness or unwillingness during fitting
- 2225/83 . Aspects of electrical fitting of hearing aids related to problems arising from growth of the hearing aid user, e.g. children
- 2227/00 Details of public address [PA] systems covered by [H04R 27/00](#) but not provided for in any of its subgroups**
- 2227/001 . Adaptation of signal processing in PA systems in dependence of presence of noise
- 2227/003 . Digital PA systems using, e.g. LAN or internet
- 2227/005 . Audio distribution systems for home, i.e. multi-room use
- 2227/007 . Electronic adaptation of audio signals to reverberation of the listening space for PA
- 2227/009 . Signal processing in [PA] systems to enhance the speech intelligibility

2231/00	Details of apparatus or processes specially adapted for the manufacture of transducers or diaphragms therefor covered by H04R 31/00, not provided for in its subgroups	2410/07	• Mechanical or electrical reduction of wind noise generated by wind passing a microphone
2231/001	• Moulding aspects of diaphragm or surround	2420/00	Details of connection covered by H04R, not provided for in its groups
2231/003	• Manufacturing aspects of the outer suspension of loudspeaker or microphone diaphragms or of their connecting aspects to said diaphragms	2420/01	• Input selection or mixing for amplifiers or loudspeakers (for hearing aids H04R 25/43)
2307/00	Details of diaphragms or cones for electromechanical transducers, their suspension or their manufacture covered by H04R 7/00 or H04R 31/003, not provided for in any of its subgroups	2420/03	• Connection circuits to selectively connect loudspeakers or headphones to amplifiers
2307/021	• Diaphragms comprising cellulose-like materials, e.g. wood, paper, linen	2420/05	• Detection of connection of loudspeakers or headphones to amplifiers
2307/023	• Diaphragms comprising ceramic-like materials, e.g. pure ceramic, glass, boride, nitride, carbide, mica and carbon materials	2420/07	• Applications of wireless loudspeakers or wireless microphones
2307/025	• Diaphragms comprising polymeric materials	2420/09	• Applications of special connectors, e.g. USB, XLR, in loudspeakers, microphones or headphones
2307/027	• Diaphragms comprising metallic materials	2430/00	Signal processing covered by H04R, not provided for in its groups
2307/029	• Diaphragms comprising fibres	2430/01	• Aspects of volume control, not necessarily automatic, in sound systems
2307/201	• Damping aspects of the outer suspension of loudspeaker diaphragms by addition of additional damping means	2430/03	• Synergistic effects of band splitting and sub-band processing
2307/204	• Material aspects of the outer suspension of loudspeaker diaphragms	2430/20	• Processing of the output signals of the acoustic transducers of an array for obtaining a desired directivity characteristic (H04R 2203/12 takes precedence)
2307/207	• Shape aspects of the outer suspension of loudspeaker diaphragms	2430/21	• • Direction finding using differential microphone array [DMA]
2400/00	Loudspeakers	2430/23	• • Direction finding using a sum-delay beam-former
NOTE	H04R 2400/00 itself is only to be used for those cases where the classification does not allow specification the type of transducer and the type is important, e.g. frequency control circuit (H04R 3/04 and subgroups) may require different circuits for microphones or for loudspeakers	2430/25	• • Array processing for suppression of unwanted side-lobes in directivity characteristics, e.g. a blocking matrix
2400/01	• Transducers used as a loudspeaker to generate sound as well as a microphone to detect sound	2440/00	Bending wave transducers covered by H04R, not provided for in its groups
2400/03	• Transducers capable of generating both sound as well as tactile vibration, e.g. as used in cellular phones	2440/01	• Acoustic transducers using travelling bending waves to generate or detect sound
2400/07	• Suspension between moving magnetic core and housing	2440/03	• Resonant bending wave transducer used as a microphone
2400/11	• Aspects regarding the frame of loudspeaker transducers	2440/05	• Aspects relating to the positioning and way or means of mounting of exciters to resonant bending wave panels
2400/13	• Use or details of compression drivers	2440/07	• Loudspeakers using bending wave resonance and piston motion to generate sound
2410/00	Microphones	2460/00	Details of hearing devices, i.e. of ear- or headphones covered by H04R 1/10 or H04R 5/033 but not provided for in any of their subgroups, or of hearing aids covered by H04R 25/00 but not provided for in any of its subgroups
NOTE	H04R 2410/00 itself is only to be used for those cases where the classification does not allow specification the type of transducer and the type is important, e.g. frequency control circuit (H04R 3/04 and subgroups) may require different circuits for microphones or for loudspeakers	2460/01	• Hearing devices using active noise cancellation
2410/01	• Noise reduction using microphones having different directional characteristics	2460/03	• Aspects of the reduction of energy consumption in hearing devices
2410/03	• Reduction of intrinsic noise in microphones	2460/05	• Electronic compensation of the occlusion effect
2410/05	• Noise reduction with a separate noise microphone	2460/07	• Use of position data from wide-area or local-area positioning systems in hearing devices, e.g. program or information selection
		2460/09	• Non-occlusive ear tips, i.e. leaving the ear canal open, for both custom and non-custom tips (H04R 2460/11 takes precedence)
		2460/11	• Aspects relating to vents, e.g. shape, orientation, acoustic properties in ear tips of hearing devices to prevent occlusion
		2460/13	• Hearing devices using bone conduction transducers
		2460/15	• Determination of the acoustic seal of ear moulds or ear tips of hearing devices

H04R

- 2460/17 . Hearing device specific tools used for storing or handling hearing devices or parts thereof, e.g. placement in the ear, replacement of cerumen barriers, repair, cleaning hearing devices
- 2499/00 Aspects covered by [H04R](#) or [H04S](#) not otherwise provided for in their subgroups**
 - 2499/01 . General technical reviews, overviews, tutorials
 - 2499/10 . General applications
 - 2499/11 . . Transducers incorporated or for use in hand-held devices, e.g. mobile phones, PDA's, camera's
 - 2499/13 . . Acoustic transducers and sound field adaptation in vehicles
 - 2499/15 . . Transducers incorporated in visual displaying devices, e.g. televisions, computer displays, laptops