

# CPC COOPERATIVE PATENT CLASSIFICATION

## B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

### TRANSPORTING

#### B67 OPENING, CLOSING {OR CLEANING} BOTTLES, JARS OR SIMILAR CONTAINERS; LIQUID HANDLING

#### B67B APPLYING CLOSURE MEMBERS TO BOTTLES JARS, OR SIMILAR CONTAINERS; OPENING CLOSED CONTAINERS (opening or closing devices attached to, or incorporated in, containers or container closures [B65D](#))

##### WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

<a href="#">B67B 7/46</a>	covered by	<a href="#">B67B 7/30-B67B 7/385</a>
<a href="#">B67B 7/48-B67B 7/52</a>	covered by	<a href="#">B67B 7/24, B67B 7/26, B67B 7/28</a>
<a href="#">B67B 7/54-B67B 7/90</a>	covered by	<a href="#">B67B 7/30-B67B 7/385</a>

2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

- |             |   |        |   |
|-------------|---|--------|---|
| <b>1/00</b> | <b>Closing bottles, jars or similar containers by applying stoppers (stoppers <a href="#">per se B65D 39/00</a>)</b>  | 3/064  | . . . from a hopper { ( <a href="#">B67B 3/061</a> takes precedence) }  |
| 1/005       | . {Feeding stoppers (in general <a href="#">B65G</a> ) }  | 3/0645 | . . . . {with means for orientating the caps to a position ready to be applied to the container}  |
| 1/03        | . Pretreatment of stoppers, e.g. cleaning, steaming, heating, impregnating or coating; Applying resilient rings to stoppers (mechanical working of cork <a href="#">B27J 5/00</a> ) | 3/10   | . . Capping heads for securing caps { ( <a href="#">B67B 3/023</a> takes precedence) }  |
| 1/04        | . by inserting threadless stoppers, e.g. corks  | 3/12   | . . . characterised by being movable axially relative to cap to deform flanges thereof, e.g. to press projecting flange rims inwardly   |
| 1/045       | . . {using hand operated devices}   | 3/14   | . . . characterised by having movable elements, e.g. hinged fingers, for applying radial pressure to the flange of the cap ( <a href="#">B67B 3/16, B67B 3/18</a> take precedence)              |
| 1/06        | . by inserting and rotating screw stoppers  | 3/16   | . . . characterised by having resilient deforming elements, e.g. resilient sleeves or collars ( <a href="#">B67B 3/18</a> takes precedence)   |
| 1/08        | . Securing stoppers, e.g. swing stoppers, which are held in position by associated pressure-applying means coacting with the bottle neck  | 3/18   | . . . characterised by being rotatable, e.g. for forming screw threads <i>in situ</i>   |
| 1/10        | . by inserting disc closures  | 3/20   | . by applying and rotating preformed threaded caps (forming threads <i>in situ</i> by resilient deforming means <a href="#">B67B 3/16</a> , by rotary capping heads <a href="#">B67B 3/18</a> ) |
| <b>3/00</b> | <b>Closing bottles, jars or similar containers by applying caps (caps <a href="#">per se B65D 41/00</a>)</b>  | 3/2006 | . . {using manually-controlled or manually operated devices}  |
| 3/003       | . {Pretreatment of caps, e.g. cleaning, steaming, heating or sterilizing}   | 3/2013 | . . {by carousel-type capping machines}   |
| 3/006       | . {Applying date marks, code marks, or the like, to caps during capping (applying marks to labels <a href="#">B65C 9/46</a> ) }   | 3/202  | . . . {using friction means for screwing the caps, e.g. belts or guides ( <a href="#">B67B 3/2026, B67B 3/2033</a> take precedence) }   |
| 3/02        | . by applying flanged caps, e.g. crown caps, and securing by deformation of flanges   | 3/2026 | . . . {comprising stationary capping heads}   |
| 3/023       | . . {using additional means for securing the cap, e.g. adhesives}   | 3/2033 | . . . {comprising carousel co-rotating capping heads}   |
| 3/026       | . . {the caps being made of thermoplastic material ( <a href="#">B67B 3/023</a> takes precedence) }   | 3/204  | . . {Linear-type capping machines}  |
| 3/04        | . . Cutting caps from strip material in capping machines (devices for registering moving strip material <a href="#">B65H 23/00</a> )  | 3/2046 | . . . {using friction means for screwing the caps, e.g. belts or wheels ( <a href="#">B67B 3/2053</a> takes precedence) }   |
| 3/06        | . . Feeding caps to capping heads   | 3/2053 | . . . {comprising capping heads}  |
| 3/061       | . . . {the caps having an asymmetric footprint, e.g. comprising a gripping lip}   |        |   |
| 3/062       | . . . from a magazine { ( <a href="#">B67B 3/061</a> takes precedence) }  |        |   |

- 3/206 . . {Means for preventing rotation of the container or cap}
- 3/2066 . . {Details of capping heads ([B67B 3/2073](#) takes precedence)}
- 3/2073 . . {comprising torque limiting means (torque limiters in wrenches or screwdrivers [B25B 23/14](#); couplings or clutches *per se* [F16D](#))}
- 3/208 . . . {Electrical means responsive to the torque applied and acting on motor control means, e.g. strain gauges or power measurement means ([B67B 3/2093](#) takes precedence)}
- 3/2086 . . . {Magnetic or electromagnetic clutches}
- 3/2093 . . . {whereby the applied torque limit is varied}
- 3/22 . by applying snap-on caps
- 3/24 . Special measures for applying and securing caps under vacuum
- 3/26 . Applications of control, warning, or safety devices in capping machinery
- 3/261 . . {Devices for controlling the tightening of threaded caps, e.g. testing the release torque (torque testers in general [G01L 5/00](#))}
- 3/262 . . {Devices for controlling the caps}
- 3/264 . . . {positioning of the caps}
- 3/265 . . . {presence of a cap}
- 3/267 . . . {positioning of the cap-label}
- 3/268 . . {devices for avoiding damage to the closing machine}
- 3/28 . Mechanisms for causing relative movement between bottle or jar and capping head
- 5/00 Applying protective or decorative covers to closures; Devices for securing bottle closures with wire (infant feeding teats with means for fastening to bottles [A61J 11/04](#))**
- 5/03 . Applying protective or decorative covers to closures, e.g. by forming *in situ*
- 5/032 . . {Dies for securing overcaps}
- 5/034 . . {the covers being elastic}
- 5/036 . . {the covers being heat-shrinkable}
- 5/038 . . {the covers being applied wet, whereby shrinkage occurs on drying}
- 5/05 . . by applying liquids, e.g. by dipping
- 5/06 . Devices for securing bottle closures with wire ([B67B 1/08](#) takes precedence)
- 6/00 Closing bottles, jars or similar containers by applying closure members, not provided for in groups [B67B 1/00](#) - [B67B 5/00](#)**
- 7/00 Hand- or power-operated devices for opening closed containers (nail pullers or extractors [B25C 11/00](#); attached to, or incorporated in, containers or container closures {[B65D 75/58](#), [B65D 77/30](#)})**
- 7/02 . for removing stoppers
- 7/04 . . Cork-screws
- 7/0405 . . . {Power-operated cork-screws, e.g. operated by an electric motor}
- 7/0411 . . . {without supporting means for assisting the pulling action}
- 7/0417 . . . {with supporting means for assisting the pulling action}
- 7/0423 . . . . {of wine-waiter, i.e. sommelier type}
- 7/0429 . . . . {having means for varying the effective lever arm length}
- 7/0435 . . . . {with a pantograph extracting mechanism}
- 7/0441 . . . . {whereby the supporting means abut around the whole periphery of the neck of the bottle}
- 7/0447 . . . . {whereby the supporting means abut around parts of the periphery of the neck of the bottle}
- 7/0452 . . . {adapted to be mounted on walls}
- 2007/0458 . . . {Means for cutting sealing capsules}
- 2007/0464 . . . {Means for counting}
- 2007/047 . . . {Means for reducing friction}
- 2007/0476 . . . . {by coating the screw}
- 2007/0482 . . . . {by using roller-bearings}
- 2007/0488 . . . {Means for measuring temperature}
- 2007/0494 . . . {Means for varying the lever arm}
- 7/06 . . Other cork removers
- 7/063 . . . {using one or more blades to be inserted between the cork and the inner surface of the bottle neck}
- 7/066 . . . {specially adapted for opening pressurised bottles, e.g. champagne or sparkling wine bottles}
- 7/08 . . . using air or gas pressure
- 7/10 . . with means for retrieving stoppers from the interior of the container
- 7/12 . for removing disc-closures
- 7/14 . for removing tightly-fitting lids or covers, e.g. of shoe-polish tins, by gripping and rotating
- 7/15 . . finger grapple type
- 7/16 . for removing flanged caps, e.g. crown caps
- 7/162 . . {the removing device being formed by at least two articulated parts, e.g. pliers ([B67B 7/164](#) takes precedence)}
- 7/164 . . {Power-operated devices}
- 2007/166 . . {Means for attaching the opener to fingers}
- 2007/168 . . {Means for counting}
- 7/18 . for removing threaded caps ([B67B 7/14](#) takes precedence; wrenches [B25B 13/00](#))
- 7/182 . . {power-operated}
- 7/184 . . {by use of a flexible loop gripping the cap skirt or the container body by friction}
- 7/186 . . . {the loop having an adjustable length}
- 2007/188 . . {Means for attaching the opener to fingers}
- 7/20 . for breaking vacuum seals between lids or covers and bodies of preserving jars, e.g. by wedge action
- 7/22 . . incorporating loops, e.g. of wire, which are tightened around seal
- 7/24 . {Hole-piercing devices}
- 7/26 . . {combined with spouts}
- 7/28 . . . {and associated with receptacle hodlers}
- 7/30 . {Hand-operated cutting devices}
- 2007/303 . . {can openers}
- 2007/306 . . . {Means for counting}
- 7/32 . . {propelled by rotary gears or wheels around periphery of container}
- 7/34 . . {with rotatable cutters}
- 7/36 . . {adapted to be mounted on walls}
- 7/38 . {Power-operated cutting devices ([machines for domestic use with a plurality of interchangeable units \[A47J 43/06\]\(#\), \[A47J 44/00\]\(#\)](#))}
- 7/385 . . {specially adapted to be hand-held}
- 7/40 . Devices for engaging tags, strips, or tongues for opening by tearing, e.g. slotted keys for opening sardine tins

## B67B

- 7/403 . . {adapted for engaging the ring of a pull tab for opening an aperture}
- 7/406 . . . {and subsequently tearing off the top of the can}
- 7/42 . Devices for removing barrel bungs
- 7/44 . Combination tools, e.g. comprising cork-screws, can piercers, crown cap removers ([combinations of opening devices with cutting tools B26](#); with devices serving other purposes, [see appropriate subclasses, e.g. B25F; B43K 29/00](#))
- 7/92 . by breaking, e.g. for ampoules

### **2201/00 Indexing codes relating to constructional features of closing machines**

- 2201/01 . Orienting closure means
- 2201/012 . . Stoppers
- 2201/015 . . . Cylindrical stoppers
- 2201/017 . . Caps
- 2201/03 . applying two closures on a container
- 2201/06 . Details of cap feeding devices
- 2201/065 . . Use of magnets
- 2201/08 . Aseptic features
- 2201/10 . Quick or easy connection means for connecting a capping head to a spindle
- 2201/12 . Details related to spray caps, i.e. caps comprising a pump and a tube for dispensing content from a container