

# CPC COOPERATIVE PATENT CLASSIFICATION

## B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

### TRANSPORTING

#### B60 VEHICLES IN GENERAL

(NOTE omitted)

#### B60W CONJOINT CONTROL OF VEHICLE SUB-UNITS OF DIFFERENT TYPE OR DIFFERENT FUNCTION; CONTROL SYSTEMS SPECIALLY ADAPTED FOR HYBRID VEHICLES; ROAD VEHICLE DRIVE CONTROL SYSTEMS FOR PURPOSES NOT RELATED TO THE CONTROL OF A PARTICULAR SUB-UNIT

##### NOTES

1. This subclass does not cover the control of a single sub-unit; such control is classified in the relevant place for the sub-unit, e.g. [F02D](#), [F16H](#). Where a single sub-unit is controlled by means of signals or commands from other sub-units, the control of this single sub-unit is classified in the relevant place for this sub-unit. For example, the control of variable-ratio gearing by means of signals from the engine or the accelerator is classified in the subclass for gearing, [F16H](#).
2. Conjoint control of driveline units, e.g. engines, and variable-ratio gearing occurring only transiently during ratio shift and being also characterised by the control of the gearing is also classified in the subclass for gearing, [F16H](#).
3. In groups [B60W 20/00](#) - [B60W 50/00](#), the first place priority rule is applied, i.e. at each hierarchical level, classification is made in the first appropriate place.
4. When classifying in group [B60W 10/00](#), classification must also be made in groups [B60W 20/00-B60W 50/00](#) in order to identify the purpose or use of the control.
5. In this subclass, the following terms are used with the meanings indicated:
  - "conjoint control" means that a programmed or condition-responsive { main } automatic controller on board the vehicle, embodying control logic for vehicle sub-units of different type or different function, sends control signals to actuators of two or more vehicle sub-units, { three or more vehicle sub-units for groups [B60W 30/00-B60W 30/16](#) }, so that the sub-units act together to solve a particular problem or in response to a particular driving condition, { in order to improve stability, comfort or safety by managing the global dynamics of the vehicle };
  - "drive control system" means an electronic system in a road vehicle for automatically controlling the movement { by managing the global dynamics } of that vehicle in order to take certain actions { in order to improve stability, comfort or safety };
  - "road vehicle" means a { motorised passenger } vehicle normally under the control of a human driver for transportation on roads, e.g. an automobile, truck or bus;
  - "sub-unit" means one of the following vehicle systems: { driveline systems, e.g. } propulsion system, clutch system, change-speed gearing system, system for distributing drive torque between front and rear axles, axle differential system, brake system, steering system, suspension system, { and, particularly for hybrid vehicles, } energy storage means, fuel cells, or auxiliary equipment.

**10/00 Conjoint control of vehicle sub-units of different type or different function (for propulsion of purely electrically-propelled vehicles with power supplied within the vehicle [B60L 50/00](#))**

##### NOTE

When classifying in this group, each controlled sub-unit must be separately identified by a classification in a relevant place in this group.

10/02 . including control of driveline clutches  
 10/023 . . {Fluid clutches, e.g. torque converters}  
 10/026 . . {Clutches for bridging a fluid gearing, e.g. lock-up}  
 10/04 . including control of propulsion units  
 10/06 . . including control of combustion engines  
 10/08 . . including control of electric propulsion units, e.g. motors or generators  
 10/10 . including control of change-speed gearings

10/101 . . Infinitely variable gearings  
 10/103 . . . of fluid type  
 10/105 . . . of electric type  
 10/107 . . . with endless flexible members  
 10/108 . . . Friction gearings  
 10/109 . . . . of the toroid type  
 10/11 . . Stepped gearings  
 10/111 . . . with separate change-speed gear trains arranged in series  
 10/113 . . . with two input flow paths, e.g. double clutch transmission selection of one of the torque flow paths by the corresponding input clutch  
 10/115 . . . with planetary gears  
 10/119 . including control of all-wheel-driveline means, e.g. transfer gears or clutches for dividing torque between front and rear axle ([B60W 10/14](#) takes precedence)  
 10/12 . including control of differentials

10/14	. . Central differentials for dividing torque between front and rear axles	30/02	. Control of vehicle driving stability
10/16	. . Axle differentials, e.g. for dividing torque between left and right wheels	30/025	. . {related to comfort of drivers or passengers}
10/18	. including control of braking systems	30/04	. . related to roll-over prevention
10/182	. . {including control of parking brakes}	2030/041	. . . {about the pitch axis}
10/184	. . with wheel brakes	2030/043	. . . {about the roll axis}
10/188	. . . hydraulic brakes	30/045	. . Improving turning performance
10/192	. . . electric brakes	30/06	. Automatic manoeuvring for parking (controlling only the steering B62D 15/0285)
10/196	. . acting within the driveline, e.g. retarders	30/08	. {Active safety systems} predicting or avoiding probable or impending collision {or attempting to minimise its consequences}
10/198	. . with exhaust brakes	2030/082	. . {Vehicle operation after collision}
10/20	. including control of steering systems	30/085	. . Taking automatic action to adjust vehicle attitude in preparation for collision, e.g. braking for nose dropping
10/22	. including control of suspension systems	30/09	. . Taking automatic action to avoid collision, e.g. braking and steering
10/24	. including control of energy storage means	30/095	. . Predicting travel path or likelihood of collision
10/26	. . for electrical energy, e.g. batteries or capacitors	30/0953	. . . {the prediction being responsive to vehicle dynamic parameters}
10/28	. including control of fuel cells	30/0956	. . . {the prediction being responsive to traffic or environmental parameters}
10/30	. including control of auxiliary equipment, e.g. air-conditioning compressors or oil pumps	30/10	. Path keeping {(cruise control for automatically following a preceding vehicle B60W 30/165)}
<b>20/00</b>	<b>Control systems specially adapted for hybrid vehicles {(hybrid vehicle design, B60K 6/00; electric vehicles B60L)}</b>	30/12	. . Lane keeping
20/10	. Controlling the power contribution of each of the prime movers to meet required power demand	30/14	. {Adaptive} cruise control
20/11	. . using model predictive control [MPC] strategies, i.e. control methods based on models predicting performance {(utilising navigation and traffic information in the control strategy B60W 20/12)}	30/143	. . {Speed control (B60W 30/16 takes precedence)}
20/12	. . using control strategies taking into account route information {(estimation or calculation of non-directly measurable driving parameters B60W 40/00)}	30/146	. . . {Speed limiting}
20/13	. . in order to stay within battery power input or output limits; in order to prevent overcharging or battery depletion	30/16	. . Control of distance between vehicles, e.g. keeping a distance to preceding vehicle
20/14	. . . in conjunction with braking regeneration	30/162	. . . {Speed limiting therefor}
20/15	. . Control strategies specially adapted for achieving a particular effect	30/165	. . . Automatically following the path of a preceding lead vehicle, e.g. "electronic tow-bar"
20/16	. . . for reducing engine exhaust emissions	30/17	. . . with provision for special action when the preceding vehicle comes to a halt, e.g. stop and go
20/17	. . . for noise reduction	30/18	. Propelling the vehicle
20/18	. . . for avoiding ageing of fuel	30/18009	. . {related to particular drive situations}
20/19	. . . for achieving enhanced acceleration	30/18018	. . . {Start-stop drive, e.g. in a traffic jam}
20/20	. Control strategies involving selection of hybrid configuration, e.g. selection between series or parallel configuration	30/18027	. . . {Drive off, accelerating from standstill}
20/30	. Control strategies involving selection of transmission gear ratio {(control of change speed gearings, together with other vehicle sub-units B60W 10/10; HEV transmission gearing B60K 6/36; gearings and control thereof F16H)}	30/18036	. . . {Reversing}
20/40	. Controlling the engagement or disengagement of prime movers, e.g. for transition between prime movers {(power-up or power-down of the driveline B60W 30/192)}	30/18045	. . . . {Rocking, i.e. fast change between forward and reverse}
20/50	. Control strategies for responding to system failures, e.g. for fault diagnosis, failsafe operation or limp mode	30/18054	. . . {at stand still, e.g. engine in idling state (hill holding B60W 30/18118)}
<b>30/00</b>	<b>Purposes of road vehicle drive control systems not related to the control of a particular sub-unit, e.g. of systems using conjoint control of vehicle sub-units {, or advanced driver assistance systems for ensuring comfort, stability and safety or drive control systems for propelling or retarding the vehicle (anti-lock brake systems [ABS] B60T 8/00)}</b>	30/18063	. . . {Creeping}
		30/18072	. . . {Coasting}
		2030/18081	. . . . {With torque flow from driveshaft to engine, i.e. engine being driven by vehicle}
		2030/1809	. . . . {Without torque flow between driveshaft and engine, e.g. with clutch disengaged or transmission in neutral}
		30/181	. . . {Preparing for stopping}
		30/18109	. . . {Braking}
		30/18118	. . . . {Hill holding}
		30/18127	. . . . {Regenerative braking}
		30/18136	. . . . {Engine braking}
		30/18145	. . . {Cornering}
		30/18154	. . . {Approaching an intersection}
		30/18163	. . . {Lane change; Overtaking manoeuvres}
		30/18172	. . {Preventing, or responsive to skidding of wheels}

30/18181	. . {Propulsion control with common controlling member for different functions}	40/105	. . Speed
30/1819	. . {Propulsion control with control means using analogue circuits, relays or mechanical links}	40/107	. . Longitudinal acceleration
30/182	. . Selecting between different operative modes, e.g. comfort and performance modes	40/109	. . Lateral acceleration
30/184	. . Preventing damage resulting from overload or excessive wear of the driveline	40/11	. . Pitch movement
30/1843	. . . {Overheating of driveline components (B60W 30/186 takes precedence)}	40/112	. . Roll movement
30/1846	. . . {Preventing of breakage of drive line components, e.g. parts of the gearing}	40/114	. . Yaw movement
30/186	. . . excessive wear or burn out of friction elements, e.g. clutches	40/12	. related to parameters of the vehicle itself {, e.g. tyre models}
30/188	. . Controlling power parameters of the driveline, e.g. determining the required power	40/13	. . Load or weight
30/1882	. . . {characterised by the working point of the engine, e.g. by using engine output chart}	2040/1307	. . . {Load distribution on each wheel suspension}
30/1884	. . . {Avoiding stall or overspeed of the engine}	2040/1315	. . . {Location of the centre of gravity}
30/1886	. . . {Controlling power supply to auxiliary devices}	2040/1323	. . . {Moment of inertia of the vehicle body}
30/1888	. . . . {Control of power take off [PTO]}	2040/133	. . . . {about the roll axis}
30/19	. . Improvement of gear change, e.g. by synchronisation or smoothing gear shift	2040/1338	. . . . {about the pitch axis}
30/192	. . Mitigating problems related to power-up or power-down of the driveline, e.g. start-up of a cold engine	2040/1346	. . . . {about the yaw axis}
30/194	. . . related to low temperature conditions, e.g. high viscosity of hydraulic fluid	2040/1353	. . . {Moment of inertia of a sub-unit}
30/20	. . Reducing vibrations in the driveline	2040/1361	. . . . {the component being the engine}
2030/203	. . . {related or induced by the clutch}	2040/1369	. . . . {the component being the clutch}
2030/206	. . . {related or induced by the engine}	2040/1376	. . . . {the component being the transmission}
40/00	<b>Estimation or calculation of {non-directly measurable} driving parameters for road vehicle drive control systems not related to the control of a particular sub unit, {e.g. by using mathematical models}</b>	2040/1384	. . . . {the component being the wheel}
40/02	. related to ambient conditions	2040/1392	. . . {Natural frequency of components}
40/04	. . Traffic conditions	50/00	<b>Details of control systems for road vehicle drive control not related to the control of a particular sub-unit {, e.g. process diagnostic or vehicle driver interfaces}</b>
40/06	. . Road conditions	2050/0001	. {Details of the control system}
40/064	. . . Degree of grip	2050/0002	. . {Automatic control, details of type of controller or control system architecture}
40/068	. . . Road friction coefficient	2050/0003	. . . {In analogue systems, e.g. continuous systems}
40/072	. . . Curvature of the road	2050/0004	. . . {In digital systems, e.g. discrete-time systems involving sampling}
40/076	. . . Slope angle of the road	2050/0005	. . . . {Processor details or data handling, e.g. memory registers or chip architecture}
40/08	. related to drivers or passengers	2050/0006	. . . . {Digital architecture hierarchy}
2040/0809	. . {Driver authorisation; Driver identical check}	2050/0008	. . . {Feedback, closed loop systems or details of feedback error signal}
2040/0818	. . {Inactivity or incapacity of driver}	2050/0009	. . . . {Proportional differential [PD] controller}
2040/0827	. . . {due to sleepiness}	2050/001	. . . . {Proportional integral [PI] controller}
2040/0836	. . . {due to alcohol}	2050/0011	. . . . {Proportional Integral Differential [PID] controller}
2040/0845	. . . {due to drugs}	2050/0012	. . . {Feedforward or open loop systems}
2040/0854	. . . {due to driver cheating, e.g. to circumvent driver tests}	2050/0013	. . . {Optimal controllers}
2040/0863	. . . {due to erroneous selection or response of the driver}	2050/0014	. . . {Adaptive controllers}
2040/0872	. . {Driver physiology}	2050/0016	. . . {State machine analysis}
2040/0881	. . {Seat occupation; Driver or passenger presence}	2050/0017	. . . {Modal analysis, e.g. for determining system stability}
2040/089	. . {Driver voice}	2050/0018	. . . {Method for the design of a control system}
40/09	. . Driving style or behaviour	2050/0019	. . {Control system elements or transfer functions}
40/10	. related to vehicle motion	2050/002	. . . {Integrating means}
40/1005	. . {Driving resistance}	2050/0021	. . . {Differentiating means}
40/101	. . Side slip angle of tyre	2050/0022	. . . {Gains, weighting coefficients or weighting functions}
40/103	. . Side slip angle of vehicle body	2050/0024	. . . . {Variable gains}
		2050/0025	. . . . {Transfer function weighting factor}
		2050/0026	. . . {Lookup tables or parameter maps}
		2050/0027	. . . {Minimum/maximum value selectors}
		2050/0028	. . . {Mathematical models, e.g. for simulation}
		2050/0029	. . . . {Mathematical model of the driver}
		2050/0031	. . . . {Mathematical model of the vehicle}
		2050/0032	. . . . . {Quarter vehicle model, i.e. only one vehicle corner}

2050/0033	. . . . .	{Single-track, 2D vehicle model, i.e. two-wheel bicycle model}	2050/0078	. . . . .	{using Global Position System data}
2050/0034	. . . . .	{Multiple-track, 2D vehicle model, e.g. four-wheel model}	2050/0079	. . . . .	{using telemetry}
2050/0035	. . . . .	{Multiple-track, 3D vehicle model, e.g. including roll and pitch conditions}	2050/008	. . . . .	{using data transmitted between vehicles, e.g. for platooning, control of inter-vehicle distance}
2050/0036	. . . . .	{Multiple-track, 3D multi-body vehicle model, e.g. combination of models for vehicle sub-units}	2050/0081	. . . . .	{using satellite communication}
2050/0037	. . . . .	{Mathematical models of vehicle sub-units}	2050/0082	. . . . .	{for initialising the control system}
2050/0039	. . . . .	{of the propulsion unit}	2050/0083	. . . . .	{Setting, resetting, calibration}
2050/004	. . . . .	{of the clutch}	2050/0085	. . . . .	{Setting or resetting initial positions}
2050/0041	. . . . .	{of the drive line}	2050/0086	. . . . .	{Recalibrating datum positions, e.g. by using check cycles}
2050/0042	. . . . .	{Transfer function lag; delays}	2050/0087	. . . . .	{Resetting start and end points of actuator travel}
2050/0043	. . . . .	{Signal treatments, identification of variables or parameters, parameter estimation or state estimation}	2050/0088	. . . . .	{Adaptive recalibration}
2050/0044	. . . . .	{In digital systems}	2050/0089	. . . . .	{Historical data record of previous events}
2050/0045	. . . . .	{using databus protocols}	2050/009	. . . . .	{Priority selection}
2050/0047	. . . . .	{Digital-analogue (D/A) or analogue-digital (A/D) conversion}	2050/0091	. . . . .	{of control inputs}
2050/0048	. . . . .	{Addition or subtraction of signals}	2050/0093	. . . . .	{of the engine}
2050/0049	. . . . .	{Signal offset}	2050/0094	. . . . .	{of control units}
2050/005	. . . . .	{Sampling}	2050/0095	. . . . .	{Automatic control mode change}
2050/0051	. . . . .	{combined with averaging}	2050/0096	. . . . .	{Control during transition between modes}
2050/0052	. . . . .	{Filtering, filters}	50/0097	. . . . .	{Predicting future conditions}
2050/0054	. . . . .	{Cut-off filters, retarders, delaying means, dead zones, threshold values or cut-off frequency}	50/0098	. . . . .	{Details of control systems ensuring comfort, safety or stability not otherwise provided for}
2050/0055	. . . . .	{High-pass filters}	50/02	. . . . .	Ensuring safety in case of control system failures, e.g. by diagnosing, circumventing or fixing failures
2050/0056	. . . . .	{Low-pass filters}	50/0205	. . . . .	{Diagnosing or detecting failures; Failure detection models}
2050/0057	. . . . .	{Frequency analysis, spectral techniques or transforms}	2050/021	. . . . .	{Means for detecting failure or malfunction}
2050/0058	. . . . .	{Signal modulation for data transmission}	2050/0215	. . . . .	{Sensor drifts or sensor failures}
2050/0059	. . . . .	{Signal noise suppression}	2050/022	. . . . .	{Actuator failures}
2050/006	. . . . .	{Interpolation; Extrapolation}	50/0225	. . . . .	{Failure correction strategy}
2050/0062	. . . . .	{Adapting control system settings}	50/023	. . . . .	Avoiding failures by using redundant parts
2050/0063	. . . . .	{Manual parameter input, manual setting means, manual initialising or calibrating means (for vehicle control input means, control panels see <a href="#">B60K 37/00</a> )}	50/029	. . . . .	Adapting to failures or work around with other constraints, e.g. circumvention by avoiding use of failed parts
2050/0064	. . . . .	{using a remote, e.g. cordless, transmitter or receiver unit, e.g. remote keypad or mobile phone}	2050/0292	. . . . .	{Fail-safe or redundant systems, e.g. limp-home or backup systems}
2050/0065	. . . . .	{using a personalised data carrier, e.g. magnetic card, memory card or electronic ignition key}	2050/0295	. . . . .	{Inhibiting action of specific actuators or systems}
2050/0066	. . . . .	{using buttons or a keyboard connected to the on-board processor}	2050/0297	. . . . .	{Control Giving priority to different actuators or systems}
2050/0067	. . . . .	{Confirmation by the driver}	50/032	. . . . .	Fixing failures by repairing failed parts, e.g. loosening a sticking valve
2050/0068	. . . . .	{Giving intention of direction, e.g. by indicator lights, steering input}	50/035	. . . . .	Bringing the control units into a predefined state, e.g. giving priority to particular actuators
2050/007	. . . . .	{Switching between manual and automatic parameter input, and <i>vice versa</i> }	50/038	. . . . .	Limiting the input power, torque or speed
2050/0071	. . . . .	{Controller overrides driver automatically}	50/04	. . . . .	Monitoring the functioning of the control system
2050/0072	. . . . .	{Controller asks driver to take over}	2050/041	. . . . .	{Built in Test Equipment [BITE]}
2050/0073	. . . . .	{Driver overrides controller}	2050/043	. . . . .	{Testing equipment at KEY-ON}
2050/0074	. . . . .	{Driver shifts control to the controller, e.g. by pressing a button}	50/045	. . . . .	{Monitoring control system parameters}
2050/0075	. . . . .	{Automatic parameter input, automatic initialising or calibrating means}	2050/046	. . . . .	{involving external transmission of data to or from the vehicle, e.g. via telemetry, satellite, Global Positioning System [GPS]}
2050/0077	. . . . .	{involving external transmission of data to or from the vehicle}	2050/048	. . . . .	{displaying data transmitted between vehicles, e.g. for platooning, control of inter-vehicle distance}
			50/06	. . . . .	Improving the dynamic response of the control system, e.g. improving the speed of regulation or avoiding hunting or overshoot
			2050/065	. . . . .	{by reducing the computational load on the digital processor of the control computer}



50/08	. Interaction between the driver and the control system	2300/45	. Skid-steer
50/082	. . {Selecting or switching between different modes of propelling}	2300/46	. Variable track or wheelbase vehicles
50/085	. . {Changing the parameters of the control units, e.g. changing limit values, working points by control input}	2300/48	. Low or lowerable bed vehicles
50/087	. . {where the control system corrects or modifies a request from the driver}	2300/50	. Tilting frame vehicles
50/10	. . Interpretation of driver requests or demands	<b>2400/00</b>	<b>Indexing codes relating to detected, measured or calculated conditions or factors</b>
50/12	. . Limiting control by the driver depending on vehicle state, e.g. interlocking means for the control input for preventing unsafe operation	<b>2420/00</b>	<b>Indexing codes relating to the type of sensors based on the principle of their operation</b>
50/14	. . Means for informing the driver, warning the driver or prompting a driver intervention	2420/10	. Transducer, e.g. piezoelectric elements
2050/143	. . . {Alarm means (B60W 50/16 takes precedence)}	2420/20	. Resistance type, e.g. potentiometer as level indicator
2050/146	. . . {Display means}	2420/22	. Strain gauge
50/16	. . . Tactile feedback to the driver, e.g. vibration or force feedback to the driver on the steering wheel or the accelerator pedal	2420/225	. . Wheatstone bridge circuit
<b>2300/00</b>	<b>Indexing codes relating to the type of vehicle</b>	2420/24	. Capacitance type, e.g. as level indicator
2300/10	. Buses	2420/30	. Switches, e.g. mercury or ball type switches
2300/105	. . Ambulances	2420/40	. Photo or light sensitive means, e.g. infrared sensors
2300/12	. Trucks; Load vehicles	2420/403	. . Image sensing, e.g. optical camera
2300/121	. . Fork lift trucks, Clarks	2420/406	. . Fiber optic sensor
2300/123	. . Light trucks	2420/42	. Image sensing, e.g. optical camera
2300/125	. . Heavy duty trucks	2420/50	. Magnetic or electromagnetic sensors
2300/126	. . . Multi-axes trucks	2420/503	. . Hall effect or magnetoresistive, i.e. active wheel speed sensors
2300/128	. . . Silo or fluid transporting vehicles	2420/506	. . Inductive sensors, i.e. passive wheel sensors
2300/13	. Independent Multi-axe long vehicles	2420/52	. Radar, Lidar
2300/135	. . Vehicles having wheels mounted on a vertical steerable column	2420/54	. Audio sensitive means, e.g. ultrasound
2300/14	. Trailers, e.g. full trailers, caravans (relation between towing and towed vehicle B60Y 2300/28)	2420/60	. Doppler effect
2300/145	. . Semi-trailers	2420/62	. Laser
2300/15	. Agricultural vehicles	2420/90	. Single sensor for two or more measurements
2300/152	. . Tractors	2420/905	. . the sensor being an xyz axis sensor
2300/154	. . Boom carrying vehicles, e.g. for crop spraying	<b>2422/00</b>	<b>Indexing codes relating to the special location or mounting of sensors</b>
2300/156	. . Ridable lawn mowers	2422/10	. on a suspension arm
2300/158	. . Harvesters	2422/20	. on or inside a spring
2300/16	. Cranes	2422/202	. . the spring being a coil spring
2300/17	. Construction vehicles, e.g. graders, excavators	2422/205	. . the spring being a pneumatic spring
2300/18	. Four-wheel drive vehicles	2422/207	. . the spring being a leaf spring
2300/185	. . Off-road vehicles	2422/40	. on a damper
2300/26	. Military	2422/50	. on a steering column
2300/28	. Racing vehicles, e.g. Formula one cars	2422/70	. on the wheel or the tire
2300/285	. . Go-karts	2422/80	. on wheel hub bearing
2300/30	. Toys	2422/90	. on bumper, e.g. collision sensor
2300/32	. Amphibious vehicles	2422/95	. Measuring the same parameter at multiple locations of the vehicle
2300/34	. Compact city vehicles	<b>2510/00</b>	<b>Input parameters relating to a particular sub-units</b>
2300/345	. . Three wheelers not including single track vehicles	2510/02	. Clutches
2300/36	. Cycles; Motorcycles; Scooters	2510/0208	. . Clutch engagement state, e.g. engaged or disengaged
2300/362	. . Buggies; Quads	2510/0216	. . . Clutch engagement rate
2300/365	. . Scooters	2510/0225	. . . Clutch actuator position
2300/367	. . Tricycles	2510/0233	. . . of torque converter lock-up clutch
2300/38	. Wheelchairs; Perambulators	2510/0241	. . Clutch slip, i.e. difference between input and output speeds
2300/40	. Carts, e.g. trolleys	2510/025	. . . Slip change rate
2300/405	. . Golf carts	2510/0258	. . Clutch friction coefficient
2300/42	. Loading ramps	2510/0266	. . Moment of inertia
2300/43	. Snowmobile	2510/0275	. . Clutch torque
2300/44	. Tracked vehicles	2510/0283	. . Clutch input shaft speed
		2510/0291	. . Clutch temperature
		2510/06	. Combustion engines, Gas turbines
		2510/0604	. . Throttle position
		2510/0609	. . . Throttle change rate

2510/0614	. .	Position of fuel or air injector	2510/22	. .	Suspension systems
2510/0619	. . .	Air-fuel ratio	2510/222	. .	Stiffness
2510/0623	. . .	Fuel flow rate	2510/225	. .	Damping
2510/0628	. . .	Inlet air flow rate	2510/227	. .	Oscillation frequency
2510/0633	. .	Turbocharger state	2510/24	. .	Energy storage means
2510/0638	. .	Engine speed	2510/242	. . .	for electrical energy
2510/0642	. . .	Idle condition	2510/244	. . .	Charge state
2510/0647	. . .	Coasting condition	2510/246	. . .	Temperature
2510/0652	. . .	Speed change rate	2510/248	. . .	Age of storage means
2510/0657	. .	Engine torque	2510/28	. .	Fuel cells
2510/0661	. . .	Torque change rate	2510/285	. .	Temperature
2510/0666	. .	Engine power	2510/30	. .	Auxiliary equipments
2510/0671	. .	Engine manifold pressure	2510/305	. .	Power absorbed by auxiliaries
2510/0676	. .	Engine temperature			
2510/068	. .	Engine exhaust temperature	<b>2520/00</b>		<b>Input parameters relating to overall vehicle dynamics</b>
2510/0685	. .	Engine crank angle	2520/04	. .	Vehicle stop
2510/069	. .	Engine braking signal	2520/06	. .	Direction of travel
2510/0695	. .	Inertia	2520/10	. .	Longitudinal speed
2510/08	. .	Electric propulsion units	2520/105	. .	Longitudinal acceleration
2510/081	. .	Speed	2520/12	. .	Lateral speed
2510/082	. . .	Speed change rate	2520/125	. .	Lateral acceleration
2510/083	. .	Torque	2520/14	. .	Yaw
2510/084	. . .	Torque change rate	2520/16	. .	Pitch
2510/085	. .	Power	2520/18	. .	Roll
2510/086	. . .	Power change rate	2520/20	. .	Sideslip angle
2510/087	. .	Temperature	2520/22	. .	Articulation angle, e.g. between tractor and trailer
2510/088	. .	Inertia	2520/26	. .	Wheel slip
2510/09	. .	Other types of propulsion units, e.g. fluid motors, or type not specified	2520/263	. . .	Slip values between front and rear axle
2510/10	. .	Change speed gearings	2520/266	. . .	Slip values between left and right wheel
2510/1005	. .	Transmission ratio engaged	2520/28	. .	Wheel speed
2510/101	. . .	Transmission neutral state	2520/30	. .	Wheel torque
2510/1015	. .	Input shaft speed, e.g. turbine speed	2520/40	. .	Torque distribution
2510/102	. . .	Input speed change rate	2520/403	. . .	between front and rear axle
2510/1025	. .	Input torque	2520/406	. . .	between left and right wheel
2510/103	. . .	Input torque change rate			
2510/1035	. .	Input power	<b>2530/00</b>		<b>Input parameters relating to other vehicle conditions or values</b>
2510/104	. .	Output speed	2530/10	. .	Weight
2510/1045	. . .	Output speed change rate	2530/12	. .	Catalyst or filter state
2510/105	. .	Output torque	2530/14	. .	Historical data
2510/1055	. . .	Output torque change rate	2530/145	. .	Mileage
2510/106	. .	Output power	2530/16	. .	Driving resistance
2510/1065	. . .	Transmission of zero torque	2530/18	. .	Distance travelled
2510/107	. .	Temperature	2530/20	. .	Tyre data
2510/1075	. .	fluid pressure, e.g. oil pressure	2530/22	. .	Towing force
2510/108	. . .	pressure of control fluid			
2510/1085	. . .	pressure of working fluid	<b>2540/00</b>		<b>Input parameters relating to the driver</b>
2510/109	. .	Direction of power flow	2540/02	. .	Driver's voice
2510/1095	. .	Inertia	2540/04	. .	Driver selection, e.g. driver confirmation
2510/12	. .	Differentials	2540/06	. .	Ignition switch
2510/125	. .	Locking status	2540/10	. .	Accelerator pedal position
2510/18	. .	Braking system	2540/103	. . .	Accelerator thresholds, e.g. kickdown
2510/182	. .	Brake pressure, e.g. of fluid or between pad and disc	2540/106	. .	Rate of change
2510/184	. .	Brake temperature, e.g. of fluid, pads or discs	2540/12	. .	Brake pedal position
2510/186	. .	Status of parking brakes	2540/14	. .	Clutch pedal position
2510/188	. .	Parking lock mechanisms	2540/16	. .	Ratio selector position
2510/20	. .	Steering systems	2540/165	. . .	Rate of change
2510/202	. .	Steering torque	2540/18	. .	Steering angle
2510/205	. .	Steering speed	2540/20	. .	Direction indicator values
2510/207	. .	Oversteer or understeer	2540/22	. .	Psychological state; Stress level or workload
			2540/24	. .	Drug level, e.g. alcohol
			2540/26	. .	Incapacity of driver

2540/28	. Identity of driver	2710/0666	. . Engine torque
2540/30	. Driving style	2710/0672	. . . Torque change rate
<b>2550/00</b>	<b>Input parameters relating to exterior conditions</b>	2710/0677	. . Engine power
2550/10	. from obstacle detection	2710/0683	. . Engine manifold pressure
2550/12	. Ambient conditions, e.g. wind or rain	2710/0688	. . Engine temperature
2550/13	. Altitude	2710/0694	. . Engine exhaust temperature
2550/14	. Road conditions, road types or road features	2710/08	. Electric propulsion units
2550/141	. . Type of road	2710/081	. . Speed
2550/142	. . Road slope	2710/082	. . . Speed change rate
2550/143	. . Road profile	2710/083	. . Torque
2550/145	. . Road altitude	2710/085	. . . Torque change rate
2550/146	. . Road curve radius	2710/086	. . Power
2550/147	. . Road bumpiness, e.g. pavement or potholes	2710/087	. . . Power change rate
2550/148	. . Coefficient of friction	2710/088	. . Temperature
2550/16	. Country codes	2710/09	. Other types of propulsion units, e.g. fluid motors, or type not specified
2550/20	. Traffic related input parameters	2710/10	. Change speed gearings
2550/22	. . Traffic rules, e.g. traffic signs	2710/1005	. . Transmission ratio engaged
2550/30	. . Distance or speed relative to other vehicles	2710/1011	. . Input shaft speed, e.g. turbine speed
2550/302	. . . the longitudinal speed of preceding vehicle	2710/1016	. . . Input speed change rate
2550/304	. . . the lateral speed of preceding vehicle	2710/1022	. . Input torque
2550/306	. . . the position of preceding vehicle	2710/1027	. . . Input torque change rate
2550/308	. . . Distance between vehicles	2710/1033	. . Input power
2550/40	. Involving external transmission of data to or from the vehicle	2710/1038	. . Output speed
2550/402	. . for navigation systems	2710/1044	. . . Output speed change rate
2550/404	. . using telemetry	2710/105	. . Output torque
2550/406	. . using satellite communication	2710/1055	. . . Output torque change rate
2550/408	. . Data transmitted between vehicles	2710/1061	. . Output power
<b>2560/00</b>	<b>Other vehicle related input parameters not covered by groups <a href="#">B60W 2510/00</a> - <a href="#">B60W 2550/00</a></b>	2710/1066	. . . Transmission of zero torque
2560/02	. Remaining fuel quantity in tank	2710/1072	. . Temperature
2560/04	. Fuel quality, e.g. water content due to age of fuel	2710/1077	. . fluid pressure, e.g. oil pressure
2560/06	. Fuel type	2710/1083	. . . pressure of control fluid
<b>2600/00</b>	<b>Indexing codes relating to automatic control systems or control processes</b>	2710/1088	. . . pressure of working fluid
<b>2710/00</b>	<b>Output or target parameters relating to a particular sub-units</b>	2710/1094	. . Direction of power flow
2710/02	. Clutches	2710/12	. Differentials
2710/021	. . Clutch engagement state	2710/125	. . Locking status
2710/022	. . . Clutch actuator position	2710/18	. Braking system
2710/023	. . . Clutch engagement rate	2710/182	. . Brake pressure, e.g. of fluid or between pad and disc
2710/024	. . . of torque converter lock-up clutch	2710/184	. . Brake temperature, e.g. of fluid, pads or discs
2710/025	. . Clutch slip, i.e. difference between input and output speeds	2710/186	. . Status of parking brakes
2710/026	. . . Slip change rate	2710/188	. . Parking lock mechanisms
2710/027	. . Clutch torque	2710/20	. Steering systems
2710/028	. . Clutch input shaft speed	2710/202	. . Steering torque
2710/029	. . Clutch temperature	2710/205	. . Steering speed
2710/06	. Combustion engines, Gas turbines	2710/207	. . Steering angle of wheels
2710/0605	. . Throttle position	2710/22	. Suspension systems
2710/0611	. . . Throttle change rate	2710/223	. . Stiffness
2710/0616	. . Position of fuel or air injector	2710/226	. . Damping
2710/0622	. . . Air-fuel ratio	2710/24	. Energy storage means
2710/0627	. . . Fuel flow rate	2710/242	. . for electrical energy
2710/0633	. . . Inlet air flow rate	2710/244	. . . Charge state
2710/0638	. . Turbocharger state	2710/246	. . . Temperature
2710/0644	. . Engine speed	2710/248	. . . Current for loading or unloading
2710/065	. . . Idle condition	2710/28	. Fuel cells
2710/0655	. . . Coasting condition	2710/285	. . Temperature
2710/0661	. . . Speed change rate	2710/30	. Auxiliary equipments
		2710/305	. . target power to auxiliaries
		<b>2720/00</b>	<b>Output or target parameters relating to overall vehicle dynamics</b>
		2720/10	. Longitudinal speed

## B60W

- 2720/103 . . Speed profile
- 2720/106 . . Longitudinal acceleration
- 2720/12 . Lateral speed
- 2720/125 . . Lateral acceleration
- 2720/14 . Yaw
- 2720/16 . Pitch
- 2720/18 . Roll
- 2720/20 . Sideslip angle
- 2720/22 . Articulation angle, e.g. between tractor and trailer
- 2720/24 . Direction of travel
- 2720/26 . Wheel slip
- 2720/263 . . Slip values between front and rear axle
- 2720/266 . . Slip values between left and right wheel
- 2720/28 . Wheel speed
- 2720/30 . Wheel torque
- 2720/40 . Torque distribution
- 2720/403 . . between front and rear axle
- 2720/406 . . between left and right wheel

### **2750/00 Output or target parameters relating to exterior, e.g. between vehicles**

- 2750/30 . Distance or speed in relation to other vehicles
- 2750/302 . . the longitudinal speed of preceding vehicle
- 2750/304 . . the lateral speed of preceding vehicle
- 2750/306 . . the position of preceding vehicle
- 2750/308 . . the distance between vehicles
- 2750/40 . Involving external transmission of data to or from the vehicle

### **2900/00 Indexing codes relating to the purpose of, or problem solved of road vehicle drive control systems not otherwise provided for in groups** [B60W 30/00](#)