

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F15 FLUID-PRESSURE ACTUATORS; HYDRAULICS OR PNEUMATICS IN GENERAL

F15B SYSTEMS ACTING BY MEANS OF FLUIDS IN GENERAL; FLUID-PRESSURE ACTUATORS, e.g. SERVOMOTORS; DETAILS OF FLUID-PRESSURE SYSTEMS, NOT OTHERWISE PROVIDED FOR

NOTE

In this subclass, the following terms are used with the meaning stated:

- "Telemotor" means a system or device in which a substantially constant amount of fluid is trapped between an input member and an output member to act as a fluid link;
- "Servomotor" means a fluid-pressure actuator, e.g. a piston and cylinder, directly controlled by a valve or other device which is responsive to operation of an initial controlling member; "Servomotor" does not cover a telemotor. The initial controlling member may be adjacent to the servomotor or at a distance, and may be, for example a hand lever.

1/00 Installations or systems with accumulators; Supply reservoir or sump assemblies

- 1/02 . Installations or systems with accumulators
- 1/021 . . {used for damping}
- 1/022 . . {used as an emergency power source, e.g. in case of pump failure}
- 1/024 . . {used as a supplementary power source, e.g. to store energy in idle periods to balance pump load}
- 1/025 . . {used for thermal compensation, e.g. to collect expanded fluid and to return it to the system as the system fluid cools down}
- 1/027 . . having accumulator charging devices
- 1/0275 . . . {with two or more pilot valves, e.g. for independent setting of the cut-in and cut-out pressures}
- 1/033 . . . with electrical control means
- 1/04 . . Accumulators
- 1/045 . . . {Dead weight accumulators}
- 1/08 . . . using a gas cushion; Gas charging devices; Indicators or floats therefor
- 1/083 {the accumulator having a fusible plug}
- 1/086 {the gas cushion being entirely enclosed by the separating means, e.g. foam or gas-filled balls}
- 1/10 with flexible separating means
- 1/103 {the separating means being bellows}
- 1/106 {characterised by the way housing components are assembled}
- 1/12 attached at their periphery (flexible separating means in the form of a tube [F15B 1/16](#))
- 1/125 {characterised by the attachment means ([F15B 1/14](#) takes precedence)}
- 1/14 by means of a rigid annular supporting member
- 1/16 in the form of a tube
- 1/165 {in the form of a bladder}
- 1/18 Anti-extrusion means

- 1/20 fixed to the separating means
- 1/22 Liquid port constructions
- 1/24 with rigid separating means, e.g. pistons
- 1/26 . Supply reservoir or sump assemblies
- 1/265 . . {with pressurised main reservoir}

3/00 Intensifiers or fluid-pressure converters, e.g. pressure exchangers; Conveying pressure from one fluid system to another, without contact between the fluids ([fluid-driven pumps F04B 9/08](#))

5/00 Transducers converting variations of physical quantities, e.g. expressed by variations in positions of members, into fluid-pressure variations or vice versa; Varying fluid pressure as a function of variations of a plurality of fluid pressures or variations of other quantities ([F15B 9/00](#) takes precedence)

- 5/003 . {characterised by variation of the pressure in a nozzle or the like, e.g. nozzle-flapper system}
- 5/006 . {with electrical means, e.g. electropneumatic transducer ([F15B 5/003](#) takes precedence)}

Fluid-pressure actuator systems (systems peculiar to the control of a particular machine or apparatus covered in a single other class, see the class for such machine or apparatus)

NOTE

This heading relates to moving members into one or more definite positions by means of fluid pressure. Pump, motor and control features so far as not peculiar to this purpose are classified in the relevant classes.

7/00 Systems in which the movement produced is definitely related to the output of a volumetric pump; Telemotors

- 7/001 . {With multiple inputs, e.g. for dual control}
- 7/003 . {with multiple outputs}
- 7/005 . {With rotary or crank input}
- 7/006 . . {Rotary pump input}
- 7/008 . {with rotary output}

7/02	. Systems with continuously-operating input and output apparatus	11/036	. . . by means of servomotors having a plurality of working chambers
7/04	. In which the ratio between pump stroke and motor stroke varies with the resistance against the motor	11/0365 {Tandem constructions}
7/06	. Details (F15B 15/00 takes precedence)	11/04	. . for controlling the speed (F15B 11/024 takes precedence)
7/08	. . Input units; Master units	11/0406	. . . {during starting or stopping (F15B 11/048 takes precedence)}
7/10	. . Compensation of the liquid content in a system (F15B 7/08 takes precedence)	11/0413	. . . {in one direction only, with no control in the reverse direction, e.g. check valve in parallel with a throttle valve}
9/00	Servomotors with follow-up action, {e.g. obtained by feed-back control,} i.e. in which the position of the actuated member conforms with that of the controlling member	11/042	. . . by means in the feed line {, i.e. "meter in"} (F15B 11/046, F15B 11/05 take precedence)
9/02	. with servomotors of the reciprocable or oscillatable type	11/0423 {by controlling pump output or bypass, other than to maintain constant speed}
9/03	. . with electrical control means {(F15B 9/07, F15B 9/09, F15B 9/17 take precedence)}	11/0426 {by controlling the number of pumps or parallel valves switched on}
9/04	. . controlled by varying the output of a pump with variable capacity	11/044	. . . by means in the return line {, i.e. "meter out"} (F15B 11/046, F15B 11/05 take precedence)
9/06	. . controlled by means using a fluid jet	11/0445 {with counterbalance valves, e.g. to prevent overrunning or for braking}
9/07	. . . with electrical control means	11/046	. . . depending on the position of the working member
9/08	. . controlled by valves affecting the fluid feed or the fluid outlet of the servomotor (F15B 9/06 takes precedence)	11/048 with deceleration control
9/09	. . . with electrical control means	11/05	. . . specially adapted to maintain constant speed, e.g. pressure-compensated, load-responsive {(F15B 11/161 takes precedence)}
9/10	. . . in which the controlling element and the servomotor each controls a separate member, these members influencing different fluid passages or the same passage	11/055 {by adjusting the pump output or bypass}
9/12	. . . in which both the controlling element and the servomotor control the same member influencing a fluid passage and are connected to that member by means of a differential gearing	11/06	. involving features specific to the use of a compressible medium, e.g. air, steam
9/14	. with rotary servomotors	11/064	. . with devices for saving the compressible medium
9/16	. Systems essentially having two or more interacting servomotors {, e.g. multi-stage (F15B 18/00, F15B 20/00 take precedence)}	11/068	. . with valves for gradually putting pneumatic systems under pressure
9/17	. . with electrical control means	11/072	. . Combined pneumatic-hydraulic systems (F15B 11/032 takes precedence)
11/00	Servomotor systems without provision for follow-up action; {Circuits therefor} (F15B 3/00 takes precedence)	11/0725	. . . {with the driving energy being derived from a pneumatic system, a subsequent hydraulic system displacing or controlling the output element}
11/003	. {Systems with load-holding valves}	11/076	. . . with pneumatic drive or displacement and speed control or stopping by hydraulic braking
11/006	. {Hydraulic "Wheatstone bridge" circuits, i.e. with four nodes, P-A-T-B, and on-off or proportional valves in each link}	11/08	. with only one servomotor
11/02	. Systems essentially incorporating special features for controlling the speed or actuating force of an output member	11/10	. . in which the servomotor position is a function of the pressure {also pressure regulators as operating means for such systems, the device itself may be a position indicating system}
11/022	. . {in which a rapid approach stroke is followed by a slower, high-force working stroke (F15B 11/0325 takes precedence)}	11/12	. . providing distinct intermediate positions; with step-by-step action
11/024	. . by means of differential connection of the servomotor lines, e.g. regenerative circuits	11/121	. . . {providing distinct intermediate positions (F15B 11/13 takes precedence)}
2011/0243	. . . {the regenerative circuit being activated or deactivated automatically}	11/122 {by means of actuators with multiple stops}
2011/0246	. . . {with variable regeneration flow}	11/123 {by means of actuators with fluid-operated stops}
11/028	. . for controlling the actuating force (F15B 11/024 takes precedence)	11/125 {by means of digital actuators, i.e. actuators in which the total stroke is the sum of individual strokes}
11/032	. . . by means of fluid-pressure converters	11/126 {by means of actuators of the standard type with special circuit controlling means (F15B 11/125 takes precedence)}
11/0325 {the fluid-pressure converter increasing the working force after an approach stroke}	11/127	. . . {with step-by-step action}
		11/128 {by means of actuators of the standard type with special circuit controlling means}

11/13	. . . using {separate dosing} chambers of predetermined volume	13/0401	. . . { Valve members; Fluid interconnections therefor}
11/15	. . with special provision for automatic return	13/0402	. . . {for linearly sliding valves, e.g. spool valves}
11/16	. with two or more servomotors	13/0403 {a secondary valve member sliding within the main spool, e.g. for regeneration flow (F15B 13/0418 takes precedence)}
11/161	. . {with sensing of servomotor demand or load}	13/0405 {for seat valves, i.e. poppet valves}
11/162	. . . {for giving priority to particular servomotors or users}	13/0406 {for rotary valves}
11/163	. . . {for sharing the pump output equally amongst users or groups of users, e.g. using anti-saturation, pressure compensation}	13/0407 {Means for damping the valve member movement}
11/165	. . . {for adjusting the pump output or bypass in response to demand}	2013/0409 {Position sensing or feedback of the valve member}
11/166	. . . {Controlling a pilot pressure in response to the load, i.e. supply to at least one user is regulated by adjusting either the system pilot pressure or one or more of the individual pilot command pressures}	2013/041 {with two positions}
11/167	. . . {using pilot pressure to sense the demand}	2013/0412 {with three positions}
11/168	. . . {with an isolator valve (duplicating valve), i.e. at least one load sense [LS] pressure is derived from a work port load sense pressure but is not a work port pressure itself}	2013/0413 {with four or more positions}
11/17	. . using two or more pumps	2013/0414 {Dosing devices}
11/18	. . used in combination for obtaining stepwise operation of a single controlled member	13/0416	. . . {with means or adapted for load sensing}
11/183	. . . {Linear stepwise operation}	13/0417 {Load sensing elements; Internal fluid connections therefor; Anti-saturation or pressure-compensation valves}
11/186	. . . {Rotary stepwise operation}	13/0418 {Load sensing elements sliding within a hollow main valve spool}
11/20	. . controlling several interacting or sequentially-operating members	13/042	. . . operated by fluid pressure {(F15B 13/0401, F15B 13/0416 take precedence)}
11/205	. . . {the position of the actuator controlling the fluid flow to the subsequent actuator}	13/0422 {with manually-operated pilot valves, e.g. joysticks}
11/22	. . Synchronisation of the movement of two or more servomotors	13/0424 {the joysticks being provided with electrical switches or sensors}
13/00	Details of servomotor systems ({F15B 1/04, F15B 1/26, F15B 3/00, F15B 7/08, F15B 11/02, F15B 11/10,} F15B 15/00 take precedence){; Valves for servomotor systems}	13/0426 {with fluid-operated pilot valves, i.e. multiple stage valves}
2013/002	. {Modular valves, i.e. consisting of an assembly of interchangeable components}	2013/0428 {with switchable internal or external pilot pressure source}
2013/004	. . {Cartridge valves}	13/043 with electrically-controlled pilot valves
2013/006	. . {Modular components with multiple uses, e.g. kits for either normally-open or normally-closed valves, interchangeable or reprogrammable manifolds}	13/0431 {the electrical control resulting in an on-off function}
2013/008	. {Throttling member profiles}	13/0433 {the pilot valves being pressure control valves (F15B 13/0435, F15B 13/0436, F15B 13/0438 take precedence)}
13/01	. Locking-valves or other detent {i.e. load-holding} devices	13/0435 {the pilot valves being sliding valves}
13/015	. . {using an enclosed pilot flow valve}	13/0436 {the pilot valves being of the steerable jet type}
13/02	. Fluid distribution or supply devices characterised by their adaptation to the control of servomotors	13/0438 {the pilot valves being of the nozzle-flapper type}
13/021	. . {Valves for interconnecting the fluid chambers of an actuator}	13/044	. . . operated by electrically-controlled means, e.g. solenoids, torque-motors
13/022	. . {Flow-dividers; Priority valves}	13/0442 {with proportional solenoid allowing stable intermediate positions}
13/023	. . {Excess flow valves, e.g. for locking cylinders in case of hose burst}	13/0444 {with rotary electric motor}
13/024	. . {Pressure relief valves}	13/0446 {with moving coil, e.g. voice coil}
13/025	. . {Pressure reducing valves}	2013/0448 {Actuation by solenoid and permanent magnet}
13/026	. . {Pressure compensating valves}	13/06	. . for use with two or more servomotors
13/027	. . {Check valves}	13/07	. . . in distinct sequence
13/028	. . {Shuttle valves}	13/08	. . . Assemblies of units, each for the control of a single servomotor only
13/029	. . {Counterbalance valves}	13/0803 {Modular units}
13/04	. . for use with a single servomotor	13/0807 {Manifolds}
		13/081 {Laminated constructions}
		13/0814 {Monoblock manifolds}
		13/0817 {Multiblock manifolds}
		13/0821 {Attachment or sealing of modular units to each other}

13/0825 {the modular elements being mounted on a common member, e.g. on a rail}	15/103	. . . {using inflatable bodies that contract when fluid pressure is applied, e.g. pneumatic artificial muscles or McKibben-type actuators}
13/0828 {characterised by sealing means of the modular units}	15/106	. . . {the motor being of the pinching-roller type}
13/0832 {Modular valves}	15/12	. . of the oscillating-vane or curved-cylinder type
13/0835 {Cartridge type valves}	15/125	. . . {of the curved-cylinder type}
13/0839 {Stacked plate type valves}	15/14	. . of the straight-cylinder type
13/0842 {Monoblock type valves, e.g. with multiple valve spools in a common housing}	15/1404	. . . {in clusters, e.g. multiple cylinders in one block}
13/0846 {Electrical details}	15/1409	. . . {with two or more independently movable working pistons}
13/085 {Electrical controllers}	15/1414	. . . {with non-rotatable piston}
13/0853 {Electric circuit boards}	15/1419 {of non-circular cross-section}
13/0857 {Electrical connecting means, e.g. plugs, sockets}	15/1423	. . . {Component parts; Constructional details}
13/086 {Sensing means, e.g. pressure sensors}	15/1428 {Cylinders (F15B 15/1438 takes precedence)}
13/0864 {Signalling means, e.g. LEDs}	15/1433 {End caps (F15B 15/1438 takes precedence)}
13/0867 {Data bus systems}	15/1438 {Cylinder to end cap assemblies}
13/0871 {Channels for fluid}	15/1442 {End cap sealings}
13/0875 {Channels for electrical components, e.g. for cables or sensors}	15/1447 {Pistons; Piston to piston rod assemblies}
13/0878 {Assembly of modular units}	15/1452 {Piston sealings}
13/0882 {using identical modular elements}	15/1457 {Piston rods (F15B 15/1447 takes precedence)}
13/0885 {using valves combined with other components}	15/1461 {Piston rod sealings}
13/0889 {Valves combined with electrical components}	15/1466 {Hollow piston sliding over a stationary rod inside the cylinder}
13/0892 {Valves combined with fluid components}	15/1471 {Guiding means other than in the end cap (F15B 15/1466 takes precedence)}
13/0896 {using different types or sizes of valves}	15/1476 {Special return means}
13/10	. Special arrangements for operating the actuated device {with or} without using fluid pressure, e.g. for emergency use	15/148 {Lost-motion means between the piston and the output}
13/12	. Special measures for increasing the sensitivity of the system	15/1485 {Special measures for cooling or heating}
13/14	. Special measures for giving the operating person a "feeling" of the response of the actuated device	15/149	. . . {Fluid interconnections, e.g. fluid connectors, passages}
13/16	. Special measures for feedback {, e.g. by a follow-up device}	2015/1495	. . . {with screw mechanism attached to the piston}
15/00	Fluid-actuated devices for displacing a member from one position to another; Gearing associated therewith	15/16	. . . of the telescopic type
15/02	. Mechanical layout characterised by the means for converting the movement of the fluid-actuated element into movement of the finally-operated member	15/165 {with synchronisation of sections}
15/04	. . with oscillating cylinder	15/17	. . . of differential-piston type
15/06	. . for mechanically converting rectilinear movement into non- rectilinear movement	15/18	. Combined units comprising both motor and pump
15/061	. . . {by unidirectional means}	15/19	. Pyrotechnical actuators
15/063	. . . {Actuator having both linear and rotary output, i.e. dual action actuator}	15/20	. Other details {, e.g. assembly with regulating devices}
15/065	. . . {the motor being of the rack-and-pinion type}	15/202	. . {Externally-operated valves mounted in or on the actuator}
15/066	. . . {the motor being of the scotch yoke type}	15/204	. . {Control means for piston speed or actuating force without external control, e.g. control valve inside the piston (F15B 11/02 , F15B 15/22 take precedence)}
15/068	. . . {the motor being of the helical type}	2015/206	. . {Combined actuation, e.g. electric and fluid actuated}
15/08	. Characterised by the construction of the motor unit	2015/208	. . {Special fluid pressurisation means, e.g. thermal or electrolytic}
15/082	. . {the motor being of the slotted cylinder type}	15/22	. . for accelerating or decelerating the stroke
15/084	. . {the motor being of the rodless piston type, e.g. with cable, belt or chain}	15/221	. . . {for accelerating the stroke, e.g. by area increase}
15/086	. . . {with magnetic coupling}	15/222	. . . {having a piston with a piston extension or piston recess which throttles the main fluid outlet as the piston approaches its end position}
15/088	. . {the motor using combined actuation, e.g. electric and fluid actuation}	15/223	. . . {having a piston with a piston extension or piston recess which completely seals the main fluid outlet as the piston approaches its end position}
15/10	. . the motor being of diaphragm type		

15/224	. . . {having a piston which closes off fluid outlets in the cylinder bore by its own movement}	20/002	. {Electrical failure}
15/225	. . . {with valve stems operated by contact with the piston end face or with the cylinder wall}	20/004	. {Fluid pressure supply failure}
15/226	. . . {having elastic elements, e.g. springs, rubber pads}	20/005	. {Leakage; Spillage; Hose burst}
15/227	. . . {having an auxiliary cushioning piston within the main piston or the cylinder end face}	20/007	. {Overload}
15/228	. . . {having shock absorbers mounted outside the actuator housing}	20/008	. {Valve failure}
15/24	. . for restricting the stroke	21/00	Common features of fluid actuator systems; Fluid-pressure actuator systems or details thereof, not covered by any other group of this subclass
15/26	. . Locking mechanisms	21/001	. {Servomotor systems with fluidic control}
15/261	. . . {using positive interengagement, e.g. balls and grooves, for locking in the end positions}	21/003	. {Systems with different interchangeable components, e.g. using preassembled kits}
15/262	. . . {using friction, e.g. brake pads}	21/005	. {Filling or draining of fluid systems}
15/264 {Screw mechanisms attached to the piston}	21/006	. {Compensation or avoidance of ambient pressure variation}
15/265	. . . {specially adapted for rodless pistons or slotted cylinders}	21/008	. {Reduction of noise or vibration}
2015/267	. . . {Manual locking or release}	21/02	. Servomotor systems with programme control derived from a store or timing device; Control devices therefor
2015/268	. . . {Fluid supply for locking or release independent of actuator pressurisation}	21/04	. Special measures taken in connection with the properties of the fluid
15/28	. . Means for indicating the position, e.g. end of stroke	21/041	. . Removal or measurement of solid or liquid contamination, e.g. filtering
15/2807	. . . {Position switches, i.e. means for sensing of discrete positions only, e.g. limit switches}	21/042	. . Controlling the temperature of the fluid
15/2815	. . . {Position sensing, i.e. means for continuous measurement of position, e.g. LVDT}		<u>WARNING</u>
15/2823 {by a screw mechanism attached to the piston}		Group F15B 21/042 is impacted by reclassification into groups F15B 21/0423 and F15B 21/0427 .
15/283 {using a cable wrapped on a drum and attached to the piston}		Groups F15B 21/042 , F15B 21/0423 , and F15B 21/0427 should be considered in order to perform a complete search.
15/2838 {with out using position sensors, e.g. by volume flow measurement or pump speed}	21/0423	. . . Cooling
15/2846 {using detection of markings, e.g. markings on the piston rod}		<u>WARNING</u>
15/2853 {using potentiometers}		Group F15B 21/0423 is incomplete pending reclassification of documents from group F15B 21/042 .
15/2861 {using magnetic means}		Groups F15B 21/042 and F15B 21/0423 should be considered in order to perform a complete search.
15/2869 {using electromagnetic radiation, e.g. radar or microwaves}	21/0427	. . . Heating
15/2876 {using optical means, e.g. laser}		<u>WARNING</u>
15/2884 {using sound, e.g. ultrasound}		Group F15B 21/0427 is incomplete pending reclassification of documents from group F15B 21/042 .
15/2892	. . . {characterised by the attachment means}		Groups F15B 21/042 and F15B 21/0427 should be considered in order to perform a complete search.
17/00	Combinations of telemotor and servomotor systems		
17/02	. in which a telemotor operates the control member of a servomotor		
18/00	Parallel arrangements of independent servomotor systems		
19/00	Testing; {Calibrating; Fault detection or monitoring; Simulation or modelling of} fluid-pressure systems or apparatus not otherwise provided for		
19/002	. {Calibrating}	21/044	. . Removal or measurement of undissolved gas, e.g. de-aeration, venting or bleeding
19/005	. {Fault detection or monitoring}	21/045	. . Compensating for variations in viscosity or temperature
19/007	. {Simulation or modelling}	21/047	. . Preventing foaming, churning or cavitation
20/00	Safety arrangements for fluid actuator systems; Applications of safety devices in fluid actuator systems; Emergency measures for fluid actuator systems	21/048	. . Arrangements for compressed air preparation, e.g. comprising air driers, air condensers, filters, lubricators or pressure regulators
20/001	. {Double valve requiring the use of both hands simultaneously}	21/06	. Use of special fluids, e.g. liquid metal; Special adaptations of fluid-pressure systems, or control of elements therefor, to the use of such fluids
		21/065	. . {Use of electro- or magnetosensitive fluids, e.g. electrorheological fluid}

21/08	. Servomotor systems incorporating electrically operated control means (F15B 21/02, {F15B 21/065} take precedence)	2201/615	. . Assembling or methods for making ports therefor
21/082	. . {with different modes}	2211/00	Circuits for servomotor systems
21/085	. . {using a data bus, e.g. "CANBUS"}	2211/20	. Fluid pressure source, e.g. accumulator or variable axial piston pump
21/087	. . {Control strategy, e.g. with block diagram}	2211/205	. . Systems with pumps
21/10	. Delay devices or arrangements	2211/20507	. . . Type of prime mover
21/12	. Fluid oscillators or pulse generators	2211/20515 Electric motor
21/125	. . {by means of a rotating valve}	2211/20523 Internal combustion engine
21/14	. Energy-recuperation means	2211/2053	. . . Type of pump
2201/00	Accumulators	2211/20538 constant capacity
2201/20	. Accumulator cushioning means	2211/20546 variable capacity
2201/205	. . using gas	2211/20553 with pilot circuit, e.g. for controlling a swash plate
2201/21	. . using springs	2211/20561 reversible
2201/215	. . using weights	2211/20569 capable of working as pump and motor
2201/22	. . using elastic housings	2211/20576	. . . with multiple pumps
2201/30	. Accumulator separating means	2211/20584 Combinations of pumps with high and low capacity
2201/305	. . without separating means	2211/20592 Combinations of pumps for supplying high and low pressure
2201/31	. . having rigid separating means, e.g. pistons	2211/21	. . Systems with pressure sources other than pumps, e.g. with a pyrotechnical charge
2201/312	. . . Sealings therefor, e.g. piston rings	2211/212	. . . the pressure sources being accumulators
2201/315	. . having flexible separating means	2211/214	. . . the pressure sources being hydrotransformers
2201/3151	. . . the flexible separating means being diaphragms or membranes	2211/216	. . . the pressure sources being pneumatic-to-hydraulic converters
2201/3152	. . . the flexible separating means being bladders	2211/218	. . . the pressure sources being pyrotechnical charges
2201/3153	. . . the flexible separating means being bellows	2211/25	. . Pressure control functions
2201/3154	. . . the flexible separating means being completely enclosed, e.g. using gas-filled balls or foam	2211/251	. . . High pressure control
2201/3155	. . . characterised by the material of the flexible separating means	2211/252	. . . Low pressure control
2201/3156	. . . characterised by their attachment	2211/253	. . . Pressure margin control, e.g. pump pressure in relation to load pressure
2201/3157	. . . Sealings for the flexible separating means	2211/255	. . Flow control functions
2201/3158	. . . Guides for the flexible separating means, e.g. for a collapsed bladder	2211/26	. . Power control functions
2201/32	. . having multiple separating means, e.g. with an auxiliary piston sliding within a main piston, multiple membranes or combinations thereof	2211/265	. . Control of multiple pressure sources
2201/40	. Constructional details of accumulators not otherwise provided for	2211/2652	. . . without priority
2201/405	. . Housings	2211/2654	. . . one or more pressure sources having priority
2201/4053	. . . characterised by the material	2211/2656	. . . by control of the pumps
2201/4056	. . . characterised by the attachment of housing components	2211/2658	. . . by control of the prime movers
2201/41	. . Liquid ports	2211/27	. . Directional control by means of the pressure source
2201/411	. . . having valve means	2211/275	. . Control of the prime mover, e.g. hydraulic control
2201/413	. . . having multiple liquid ports	2211/30	. Directional control
2201/415	. . Gas ports	2211/305	. . characterised by the type of valves
2201/4155	. . . having valve means	2211/30505	. . . Non-return valves, i.e. check valves
2201/42	. . Heat recuperators for isothermal compression and expansion	2211/3051 Cross-check valves
2201/43	. . Anti-extrusion means	2211/30515 Load holding valves
2201/435	. . . being fixed to the separating means	2211/3052	. . . Shuttle valves
2201/50	. Monitoring, detection and testing means for accumulators	2211/30525	. . . Directional control valves, e.g. 4/3-directional control valve
2201/505	. . Testing of accumulators, e.g. for testing tightness	2211/3053 In combination with a pressure compensating valve
2201/51	. . Pressure detection	2211/30535 the pressure compensating valve is arranged between pressure source and directional control valve
2201/515	. . Position detection for separating means	2211/3054 the pressure compensating valve is arranged between directional control valve and output member
2201/60	. Assembling or methods for making accumulators	2211/30545 the pressure compensating valve is arranged between output member and directional control valve
2201/605	. . Assembling or methods for making housings therefor		
2201/61	. . Assembling or methods for making separating means therefor		

2211/3055	the pressure compensating valve is arranged between directional control valve and return line	2211/31547	having multiple pressure sources and multiple output members
2211/30555	Inlet and outlet of the pressure compensating valve being connected to the directional control valve	2211/31552	. . .	being connected to an output member and a return line
2211/3056	. . .	Assemblies of multiple valves	2211/31558	having a single output member
2211/30565	having multiple valves for a single output member, e.g. for creating higher valve function by use of multiple valves like two 2/2-valves replacing a 5/3-valve	2211/31564	having multiple output members
2211/3057	having two valves, one for each port of a double-acting output member	2211/3157	. . .	being connected to a pressure source, an output member and a return line
2211/30575	in a Wheatstone Bridge arrangement (also half bridges)	2211/31576	having a single pressure source and a single output member
2211/3058	having additional valves for interconnecting the fluid chambers of a double-acting actuator, e.g. for regeneration mode or for floating mode (directional control valves having a regenerative position F15B 2211/3133 ; directional control valves having a floating position F15B 2211/3127)	2211/31582	having multiple pressure sources and a single output member
2211/30585	having a single valve for multiple output members	2211/31588	having a single pressure source and multiple output members
2211/3059	having multiple valves for multiple output members	2211/31594	having multiple pressure sources and multiple output members
2211/30595	with additional valves between the groups of valves for multiple output members	2211/32	. .	characterised by the type of actuation
2211/31	. .	characterised by the positions of the valve element	2211/321	. . .	mechanically
2211/3105	. . .	Neutral or centre positions	2211/322	actuated by biasing means, e.g. spring-actuated
2211/3111	the pump port being closed in the centre position, e.g. so-called closed centre	2211/323	the biasing means being adjustable
2211/3116	the pump port being open in the centre position, e.g. so-called open centre	2211/324	manually, e.g. by using a lever or pedal
2211/3122	. . .	Special positions other than the pump port being connected to working ports or the working ports being connected to the return line	2211/325	actuated by an output member of the circuit
2211/3127	Floating position connecting the working ports and the return line	2211/326	with follow-up action
2211/3133	Regenerative position connecting the working ports or connecting the working ports to the pump, e.g. for high-speed approach stroke	2211/327	. . .	electrically or electronically
2211/3138	. . .	the positions being discrete	2211/328	with signal modulation, e.g. pulse width modulation [PWM]
2211/3144	. . .	the positions being continuously variable, e.g. as realised by proportional valves	2211/329	. . .	actuated by fluid pressure
2211/315	. .	characterised by the connections of the valve or valves in the circuit	2211/35	. .	Directional control combined with flow control
2211/31505	. . .	being connected to a pressure source and a return line	2211/351	. . .	Flow control by regulating means in feed line, i.e. meter-in control
2211/31511	having a single pressure source	2211/353	. . .	Flow control by regulating means in return line, i.e. meter-out control
2211/31517	having multiple pressure sources	2211/355	. .	Pilot pressure control
2211/31523	. . .	being connected to a pressure source and an output member	2211/36	. .	Pilot pressure sensing
2211/31529	having a single pressure source and a single output member	2211/365	. .	Directional control combined with flow control and pressure control
2211/31535	having multiple pressure sources and a single output member	2211/40	. .	Flow control
2211/31541	having a single pressure source and multiple output members	2211/405	. .	characterised by the type of flow control means or valve
			2211/40507	. . .	with constant throttles or orifices
			2211/40515	. . .	with variable throttles or orifices
			2211/40523	. . .	with flow dividers
			2211/4053	using valves
			2211/40538	using volumetric pumps or motors
			2211/40546	. . .	with flow combiners
			2211/40553	. . .	with pressure compensating valves
			2211/40561	the pressure compensating valve arranged upstream of the flow control means
			2211/40569	the pressure compensating valve arranged downstream of the flow control means
			2211/40576	. . .	Assemblies of multiple valves
			2211/40584	the flow control means arranged in parallel with a check valve
			2211/40592	with multiple valves in parallel flow paths,
			2211/41	. .	characterised by the positions of the valve element
			2211/411	. . .	the positions being discrete
			2211/413	. . .	the positions being continuously variable, e.g. as realised by proportional valves
			2211/415	. .	characterised by the connections of the flow control means in the circuit

2211/41509	. . .	being connected to a pressure source and a directional control valve	2211/511	. . .	the positions being discrete
2211/41518	being connected to multiple pressure sources	2211/513	. . .	the positions being continuously variable, e.g. as realised by proportional valves
2211/41527	. . .	being connected to an output member and a directional control valve	2211/515	. .	characterised by the connections of the pressure control means in the circuit
2211/41536	being connected to multiple ports of an output member	2211/5151	. . .	being connected to a pressure source and a directional control valve
2211/41545	being connected to multiple output members	2211/5152	being connected to multiple pressure sources
2211/41554	. . .	being connected to a return line and a directional control valve	2211/5153	. . .	being connected to an output member and a directional control valve
2211/41563	. . .	being connected to a pressure source and a return line	2211/5154	being connected to multiple ports of an output member
2211/41572	. . .	being connected to a pressure source and an output member	2211/5155	being connected to multiple output members
2211/41581	. . .	being connected to an output member and a return line	2211/5156	. . .	being connected to a return line and a directional control valve
2211/4159	. . .	being connected to a pressure source, an output member and a return line	2211/5157	. . .	being connected to a pressure source and a return line
2211/42	. .	characterised by the type of actuation	2211/5158	. . .	being connected to a pressure source and an output member
2211/421	. . .	mechanically	2211/5159	. . .	being connected to an output member and a return line
2211/422	actuated by biasing means, e.g. spring-actuated	2211/52	. .	characterised by the type of actuation
2211/423	manually, e.g. by using a lever or pedal	2211/521	. . .	mechanically
2211/424	actuated by an output member of the circuit	2211/522	actuated by biasing means, e.g. spring-actuated
2211/425	with follow-up action	2211/523	manually, e.g. by using a lever or pedal
2211/426	. . .	electrically or electronically	2211/524	actuated by an output member of the circuit
2211/427	with signal modulation, e.g. using pulse width modulation [PWM]	2211/525	with follow-up action
2211/428	. . .	actuated by fluid pressure	2211/526	. . .	electrically or electronically
2211/45	. .	Control of bleed-off flow, e.g. control of bypass flow to the return line	2211/527	with signal modulation, e.g. pulse width modulation [PWM]
2211/455	. .	Control of flow in the feed line, i.e. meter-in control	2211/528	. . .	actuated by fluid pressure
2211/46	. .	Control of flow in the return line, i.e. meter-out control	2211/55	. .	for limiting a pressure up to a maximum pressure, e.g. by using a pressure relief valve
2211/465	. .	Flow control with pressure compensation	2211/555	. .	for assuring a minimum pressure, e.g. by using a back pressure valve
2211/47	. .	Flow control in one direction only	2211/56	. .	Control of an upstream pressure
2211/473	. . .	without restriction in the reverse direction	2211/565	. .	Control of a downstream pressure
2211/476	. . .	the flow in the reverse direction being blocked	2211/57	. .	Control of a differential pressure
2211/50	. .	Pressure control	2211/575	. .	Pilot pressure control
2211/505	. .	characterised by the type of pressure control means	2211/5753	. . .	for closing a valve
2211/50509	. . .	the pressure control means controlling a pressure upstream of the pressure control means	2211/5756	. . .	for opening a valve
2211/50518	using pressure relief valves	2211/60	. .	Circuit components or control therefor
2211/50527	using cross-pressure relief valves	2211/605	. .	Load sensing circuits
2211/50536	using unloading valves controlling the supply pressure by diverting fluid to the return line	2211/6051	. . .	having valve means between output member and the load sensing circuit
2211/50545	using braking valves to maintain a back pressure	2211/6052	using check valves
2211/50554	. . .	the pressure control means controlling a pressure downstream of the pressure control means, e.g. pressure reducing valve	2211/6054	using shuttle valves
2211/50563	. . .	the pressure control means controlling a differential pressure	2211/6055	using pressure relief valves
2211/50572	using a pressure compensating valve for controlling the pressure difference across a flow control valve	2211/6057	using directional control valves
2211/50581	using counterbalance valves	2211/6058	. . .	with isolator valves
2211/5059	using double counterbalance valves	2211/61	. .	Secondary circuits
2211/51	. .	characterised by the positions of the valve element	2211/611	. . .	Diverting circuits, e.g. for cooling or filtering
			2211/613	. . .	Feeding circuits
			2211/615	. .	Filtering means
			2211/62	. .	Cooling or heating means
			2211/625	. .	Accumulators
			2211/63	. .	Electronic controllers
			2211/6303	. . .	using input signals
			2211/6306	representing a pressure
			2211/6309	the pressure being a pressure source supply pressure
			2211/6313	the pressure being a load pressure

2211/6316	the pressure being a pilot pressure	2211/7114	. . .	with direct connection between the chambers of different actuators
2211/632	representing a flow rate	2211/7121	the chambers being connected in series
2211/6323	the flow rate being a pressure source flow rate	2211/7128	the chambers being connected in parallel
2211/6326	the flow rate being an output member flow rate	2211/7135	. . .	Combinations of output members of different types, e.g. single-acting cylinders with rotary motors
2211/633	representing a state of the prime mover, e.g. torque or rotational speed	2211/7142	. . .	the output members being arranged in multiple groups
2211/6333	representing a state of the pressure source, e.g. swash plate angle	2211/715	. .	having braking means
2211/6336	representing a state of the output member, e.g. position, speed or acceleration	2211/72	. .	having locking means
2211/634	representing a state of a valve	2211/75	. .	Control of speed of the output member
2211/6343	representing a temperature	2211/755	. .	Control of acceleration or deceleration of the output member
2211/6346	representing a state of input means, e.g. joystick position	2211/76	. .	Control of force or torque of the output member
2211/635	. .	Circuits providing pilot pressure to pilot pressure-controlled fluid circuit elements	2211/761	. . .	Control of a negative load, i.e. of a load generating hydraulic energy
2211/6355	. . .	having valve means	2211/763	. . .	Control of torque of the output member by means of a variable capacity motor, i.e. by a secondary control on the motor
2211/65	. .	Methods of control of the load sensing pressure	2211/765	. .	Control of position or angle of the output member
2211/651	. . .	characterised by the way the load pressure is communicated to the load sensing circuit	2211/7653	. . .	at distinct positions, e.g. at the end position
2211/652	. . .	the load sensing pressure being different from the load pressure	2211/7656	. . .	with continuous position control
2211/653	. . .	the load sensing pressure being higher than the load pressure	2211/77	. .	Control of direction of movement of the output member
2211/654	. . .	the load sensing pressure being lower than the load pressure	2211/7708	. . .	in one direction only
2211/655	. .	Methods of contamination control, i.e. methods of control of the cleanliness of circuit components or of the pressure fluid	2211/7716	. . .	with automatic return
2211/66	. .	Temperature control methods	2211/7725	. . .	with automatic reciprocation
2211/665	. .	Methods of control using electronic components	2211/7733	. . .	providing vibrating movement, e.g. dither control for emptying a bucket
2211/6651	. . .	Control of the prime mover, e.g. control of the output torque or rotational speed	2211/7741	. . .	with floating mode, e.g. using a direct connection between both lines of a double-acting cylinder
2211/6652	. . .	Control of the pressure source, e.g. control of the swash plate angle	2211/775	. .	Combined control, e.g. control of speed and force for providing a high speed approach stroke with low force followed by a low speed working stroke with high force, e.g. for a hydraulic press
2211/6653	. . .	Pressure control	2211/78	. .	Control of multiple output members
2211/6654	. . .	Flow rate control	2211/781	. . .	one or more output members having priority
2211/6655	. . .	Power control, e.g. combined pressure and flow rate control	2211/782	. . .	Concurrent control, e.g. synchronisation of two or more actuators
2211/6656	. . .	Closed loop control, i.e. control using feedback	2211/783	. . .	Sequential control
2211/6657	. . .	Open loop control, i.e. control without feedback	2211/785	. .	Compensation of the difference in flow rate in closed fluid circuits using differential actuators
2211/6658	. . .	Control using different modes, e.g. four-quadrant-operation, working mode and transportation mode	2211/80	. .	Other types of control related to particular problems or conditions
2211/67	. .	Methods for controlling pilot pressure	2211/85	. .	Control during special operating conditions
2211/70	. .	Output members, e.g. hydraulic motors or cylinders or control therefor	2211/851	. . .	during starting
2211/705	. .	characterised by the type of output members or actuators	2211/853	. . .	during stopping
2211/7051	. . .	Linear output members	2211/855	. .	Testing of fluid pressure systems
2211/7052	Single-acting output members	2211/857	. .	Monitoring of fluid pressure systems
2211/7053	Double-acting output members	2211/86	. .	Control during or prevention of abnormal conditions
2211/7054	Having equal piston areas	2211/8603	. . .	the abnormal condition being an obstacle
2211/7055	having more than two chambers	2211/8606	. . .	the abnormal condition being a shock
2211/7056	Tandem cylinders	2211/8609	. . .	the abnormal condition being cavitation
2211/7057	being of the telescopic type	2211/8613	. . .	the abnormal condition being oscillations
2211/7058	. . .	Rotary output members	2211/8616	. . .	the abnormal condition being noise or vibration
2211/71	. .	Multiple output members, e.g. multiple hydraulic motors or cylinders	2211/862	. . .	the abnormal condition being electric or electronic failure
2211/7107	. . .	the output members being mechanically linked	2211/8623	Electric supply failure
			2211/8626	Electronic controller failure, e.g. software, EMV, electromagnetic interference

F15B

- 2211/863 . . . the abnormal condition being a hydraulic or pneumatic failure
- 2211/8633 Pressure source supply failure
- 2211/8636 Circuit failure, e.g. valve or hose failure
- 2211/864 Failure of an output member, e.g. actuator or motor failure
- 2211/8643 . . . the abnormal condition being a human failure
- 2211/8646 . . . the abnormal condition being hysteresis
- 2211/865 . . Prevention of failures
- 2211/87 . . Detection of failures
- 2211/875 . . Control measures for coping with failures
- 2211/8752 . . . Emergency operation mode, e.g. fail-safe operation mode
- 2211/8755 . . . Emergency shut-down
- 2211/8757 . . . using redundant components or assemblies
- 2211/88 . . Control measures for saving energy
- 2211/885 . . Control specific to the type of fluid, e.g. specific to magnetorheological fluid
- 2211/8855 . . . Compressible fluids, e.g. specific to pneumatics
- 2211/89 . . Control specific for achieving vacuum or "negative pressure"
- 2211/895 . . Manual override
- 2215/00 Fluid-actuated devices for displacing a member from one position to another**
- 2215/30 . . Constructional details thereof
- 2215/305 . . characterised by the use of special materials