

# CPC COOPERATIVE PATENT CLASSIFICATION

## H ELECTRICITY

(NOTE omitted)

## H02 GENERATION; CONVERSION OR DISTRIBUTION OF ELECTRIC POWER

## H02H EMERGENCY PROTECTIVE CIRCUIT ARRANGEMENTS (indicating or signalling undesired working conditions [G01R](#), e.g. [G01R 31/00](#), [G08B](#); locating faults along lines [G01R 31/08](#); emergency protective devices [H01H](#))

### NOTE

This subclass covers only circuit arrangements for the automatic protection of electric lines or electric machines or apparatus in the event of an undesired change from normal working conditions

### WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

- |               |  |              |  |
|---------------|--|--------------|--|
| <b>1/00</b>   | <b>Details of emergency protective circuit arrangements</b>  | <b>1/043</b> | . . {to inrush currents ( <a href="#">H02H 1/046</a> takes precedence; differential protection of transformers <a href="#">H02H 7/045</a> )}   |
| <b>1/0007</b> | . {concerning the detecting means (in general <a href="#">G01R</a> or other subclasses of <a href="#">G01</a> ; reed switches <a href="#">H01H 71/2445</a> )}  | <b>1/046</b> | . . {upon detecting saturation of current transformers (for differential protection <a href="#">H02H 3/283</a> )}  |
| <b>1/0015</b> | . . {Using arc detectors}  | <b>1/06</b>  | . Arrangements for supplying operative power {(power supply arrangements in general <a href="#">G05F</a> , <a href="#">H02M</a> )}   |
| <b>1/0023</b> | . . . {sensing non electrical parameters, e.g. by optical, pneumatic, thermal or sonic sensors}  | <b>1/063</b> | . . {primary power being supplied by fault current}  |
| <b>1/003</b>  | . . {Fault detection by injection of an auxiliary voltage (same for detection of earth fault currents <a href="#">H02H 3/17</a> ; for monitoring earth connection <a href="#">H02H 5/105</a> )}  | <b>1/066</b> | . . . {and comprising a shunt regulator}   |
| <b>1/0038</b> | . {concerning the connection of the detecting means, e.g. for reducing their number}   | <b>3/00</b>  | <b>Emergency protective circuit arrangements for automatic disconnection directly responsive to an undesired change from normal electric working condition with or without subsequent reconnection (specially adapted for specific types of electric machines or apparatus or for sectionalised protection of cable or line systems <a href="#">H02H 7/00</a>; systems for change-over to standby supply <a href="#">H02J 9/00</a>); <b>integrated protection</b> (for motors <a href="#">H02H 7/0822</a>)</b> |
| <b>1/0046</b> | . . {Commutating the detecting means in dependance of the fault, e.g. for reducing their number}   | <b>3/003</b> | . {responsive to reversal of power transmission direction (reversal of direct current <a href="#">H02H 3/18</a> )}   |
| <b>1/0053</b> | . . {Means for storing the measured quantities during a predetermined time}  | <b>3/006</b> | . {Calibration or setting of parameters}   |
| <b>1/0061</b> | . {concerning transmission of signals (transmission of measured quantities or switching orders; sectionalised protection involving signal transmission between at least two stations <a href="#">H02H 7/261</a> ; comparison of the voltage or current values at two spaced portions of a single system <a href="#">H02H 3/28</a> ; transferring the output of a sensing member to another variable <a href="#">G01D 5/00</a> ; electrical measuring arrangements using modulation of electromagnetic waves, e.g. light beams <a href="#">G01R 15/24</a> , <a href="#">G01R 15/26</a> )} | <b>3/02</b>  | . Details  |
| <b>1/0069</b> | . . {by means of light or heat rays}   | <b>3/021</b> | . . {concerning the disconnection itself, e.g. at a particular instant, particularly at zero value of current, disconnection in a predetermined order (disconnection at zero value in general <a href="#">H03K 17/18</a> )}  |
| <b>1/0076</b> | . . {by superposition on the watched current}  | <b>3/023</b> | . . . {by short-circuiting}  |
| <b>1/0084</b> | . . {by means of pilot wires or a telephone network; watching of these wires}  | <b>3/025</b> | . . {Disconnection after limiting, e.g. when limiting is not sufficient or for facilitating disconnection}   |
| <b>1/0092</b> | . {concerning the data processing means, e.g. expert systems, neural networks}   | <b>3/027</b> | . . with automatic disconnection after a predetermined time ( <a href="#">H02H 3/033</a> , <a href="#">H02H 3/06</a> take precedence ; timing in overcurrent protection circuits <a href="#">H02H 3/093</a> ; in undervoltage protection circuits <a href="#">H02H 3/247</a> ; staggered disconnection <a href="#">H02H 7/30</a> )}  |
| <b>1/04</b>   | . Arrangements for preventing response to transient abnormal conditions, e.g. to lightning {or to short duration over voltage or oscillations; Damping the influence of dc component by short circuits in ac networks}   | <b>3/033</b> | . . with several disconnections in a preferential order, {e.g. following priority of the users, load repartition} ( <a href="#">H02H 3/06</a> takes precedence)  |

- 3/04 . . with warning or supervision in addition to disconnection, e.g. for indicating that protective apparatus has functioned {(watching of pilot wires [H02H 1/0084](#); protection of protective arrangements [H02H 7/008](#); indication of the state of electronic switches [H03K 17/18](#))}
- 3/042 . . . {combined with means for locating the fault (locating faults in cables [G01R 31/08](#))}
- 3/044 . . . {Checking correct functioning of protective arrangements, e.g. by simulating a fault (for differential current circuit breakers [H02H 3/335](#))}
- 3/046 . . . {Signalling the blowing of a fuse (detecting non functioning of a lamp [H05B 47/20](#))}
- 3/048 . . . {Checking overvoltage diverters}
- 3/05 . . with means for increasing reliability, e.g. redundancy arrangements {(for logic circuits [H03K 19/003](#))}
- 3/06 . . with automatic reconnection
- 3/063 . . . {Details concerning the co-operation of many similar arrangements, e.g. in a network (sectionalised protection [H02H 7/26](#))}
- 3/066 . . . {Reconnection being a consequence of eliminating the fault which caused disconnection}
- 3/07 . . . and with permanent disconnection after a predetermined number of reconnection cycles
- 3/08 . responsive to excess current (responsive to abnormal temperature caused by excess current [H02H 5/04](#))
- 3/081 . . {and depending on the direction}
- 3/083 . . {for three-phase systems}
- 3/085 . . {making use of a thermal sensor, e.g. thermistor, heated by the excess current (also responsive to the temperature of the protected device [H02H 5/041](#), thermal images [H02H 6/00](#))}
- 3/087 . . for dc applications
- 3/093 . . with timing means {(in general [H02H 3/027](#); thermal delay [H02H 3/085](#); timing means for undervoltage protection [H02H 3/247](#))}
- 3/0935 . . . {the timing being determined by numerical means}
- 3/10 . . additionally responsive to some other abnormal electrical conditions
- 3/105 . . . {responsive to excess current and fault current to earth}
- 3/12 . responsive to underload or no-load {(for motors [H02H 7/0827](#))}
- 3/13 . . for multiphase applications, e.g. phase interruption
- 3/14 . responsive to occurrence of voltage on parts normally at earth potential {(monitoring earth connection [H02H 5/105](#))}
- 3/16 . responsive to fault current to earth, frame or mass (with balanced or differential arrangement [H02H 3/26](#) ; monitoring earth connection [H02H 5/105](#))
- 3/162 . . {for ac systems}
- 3/165 . . . {for three-phase systems}
- 3/167 . . {combined with other earth-fault protective arrangements}
- 3/17 . . by means of an auxiliary voltage injected into the installation to be protected {(using summation current transformers [H02H 3/33](#))}
- 3/18 . responsive to reversal of direct current
- 3/20 . responsive to excess voltage
- 3/202 . . {for dc systems}
- 3/205 . . {using a spark-gap as detector}
- 3/207 . . {also responsive to under-voltage (window comparators for indication [G01R 19/165](#))}
- 3/22 . . of short duration, e.g. lightning
- 3/24 . responsive to undervoltage or no-voltage {(H02H 3/207 takes precedence)}
- 3/243 . . {for DC systems}
- 3/247 . . having timing means
- 3/253 . . for multiphase applications, e.g. phase interruption
- 3/26 . responsive to difference between voltages or between currents; responsive to phase angle between voltages or between currents
- 3/265 . . {responsive to phase angle between voltages or between currents}
- 3/28 . . involving comparison of the voltage or current values at two spaced portions of a single system, e.g. at opposite ends of one line, at input and output of apparatus {(for transformers [H02H 7/045](#))}
- 3/283 . . . {and taking into account saturation of current transformers}
- 3/286 . . . {involving comparison of similar homopolar quantities}
- 3/30 . . . using pilot wires or other signalling channel
- 3/302 . . . . {involving phase comparison}
- 3/305 . . . . {involving current comparison}
- 3/307 . . . . {involving comparison of quantities derived from a plurality of phases, e.g. homopolar quantities; using mixing transformers}
- 3/32 . . involving comparison of the voltage or current values at corresponding points in different conductors of a single system, e.g. of currents in go and return conductors
- 3/325 . . . {involving voltage comparison ([H02H 3/347](#) takes precedence)}
- 3/33 . . . using summation current transformers ([H02H 3/347](#) takes precedence)
- 3/331 . . . . {responsive to earthing of the neutral conductor ([H02H 3/338](#) takes precedence)}
- 3/332 . . . . {with means responsive to dc component in the fault current}
- 3/334 . . . . {with means to produce an artificial unbalance for other protection or monitoring reasons or remote control ([H02H 3/338](#) takes precedence)}
- 3/335 . . . . . {the main function being self testing of the device}
- 3/337 . . . . {avoiding disconnection due to reactive fault currents}
- 3/338 . . . . {also responsive to wiring error, e.g. loss of neutral, break}
- 3/34 . . . of a three-phase system
- 3/343 . . . . {using phase sequence analysers}
- 3/347 . . . . using summation current transformers
- 3/353 . . . . involving comparison of phase voltages
- 3/36 . . involving comparison of the voltage or current values at corresponding points of different systems, e.g. of parallel feeder systems
- 3/365 . . . {one of the systems simulating the other system}

3/38	• responsive to both voltage and current; responsive to phase angle between voltage and current	5/12	• responsive to undesired approach to, or touching of, live parts by living beings
3/382	• • {involving phase comparison between current and voltage or between values derived from current and voltage}	<b>6/00</b>	<b>Emergency protective circuit arrangements responsive to undesired changes from normal non-electric working conditions using simulators of the apparatus being protected, e.g. using thermal images</b>
3/385	• • {using at least one homopolar quantity}	6/005	• {using digital thermal images}
3/387	• • {using phase-sequence analysing arrangements}	<b>7/00</b>	<b>Emergency protective circuit arrangements specially adapted for specific types of electric machines or apparatus or for sectionalised protection of cable or line systems, and effecting automatic switching in the event of an undesired change from normal working conditions (structural association of protective devices with specific machines or apparatus and their protection without automatic disconnection, <a href="#">see the relevant subclass for the machine or apparatus</a>)</b>
3/40	• responsive to ratio of voltage and current	7/001	• {for superconducting apparatus, e.g. coils, lines, machines}
3/402	• • {using homopolar quantities}	7/003	• {for electrostatic apparatus}
3/405	• • {using phase sequence analysing arrangements}	7/005	• {for remote controlled apparatus; for lines connecting such apparatus}
3/407	• • {using induction relays}	7/006	• {for non-insulated low-voltage distribution systems, e.g. low-voltage halogen-lamp system}
3/42	• responsive to product of voltage and current	7/008	• {for protective arrangements according to this subclass ( <a href="#">H02H 9/042</a> , <a href="#">H02H 9/043</a> take precedence; protection of spark-gaps <a href="#">H02H 7/24</a> )}
3/422	• • {using homopolar quantities}	7/04	• for transformers
3/425	• • {using phase sequence analysing arrangements}	7/042	• • {for current transformers}
3/427	• • {using induction relays}	7/045	• • Differential protection of transformers
3/44	• responsive to the rate of change of electrical quantities	7/0455	• • • {taking into account saturation of current transformers}
3/445	• • {of DC quantities}	7/05	• • for capacitive voltage transformers, e.g. against resonant conditions
3/46	• responsive to frequency deviations	7/055	• • for tapped transformers or tap-changing means thereof
3/48	• responsive to loss of synchronism	7/06	• for dynamo-electric generators; for synchronous capacitors
3/50	• responsive to the appearance of abnormal wave forms, e.g. ac in dc installations	7/062	• • {for parallel connected generators}
3/52	• • responsive to the appearance of harmonics	7/065	• • {against excitation faults}
<b>5/00</b>	<b>Emergency protective circuit arrangements for automatic disconnection directly responsive to an undesired change from normal non-electric working conditions with or without subsequent reconnection (using simulators of the apparatus being protected <a href="#">H02H 6/00</a>; specially adapted for specific types of electric machines or apparatus or for sectionalised protection of cable or line systems <a href="#">H02H 7/00</a>)</b>	7/067	• • {on occurrence of a load dump (control on sudden change of load <a href="#">H02P 9/10</a> )}
5/005	• {responsive to ionising radiation; Nuclear-radiation circumvention circuits (radiation detectors <a href="#">G01T</a> ; nuclear-explosion detection <a href="#">G21J 5/00</a> )}	7/08	• for dynamo-electric motors
5/04	• responsive to abnormal temperature {(specially adapted for electric machines <a href="#">H02H 7/0852</a> )}	7/0805	• • {for synchronous motors}
5/041	• • {additionally responsive to excess current ( <a href="#">H02H 5/048</a> takes precedence)}	7/0811	• • {for dc motors ( <a href="#">H02H 7/0833</a> takes precedence)}
5/042	• • {using temperature dependent resistors}	7/0816	• • {concerning the starting sequence, e.g. limiting the number of starts per time unit, monitoring speed during starting}
5/043	• • • {the temperature dependent resistor being disposed parallel to a heating wire, e.g. in a heating blanket}	7/0822	• • {Integrated protection, motor control centres}
5/044	• • {using a semiconductor device to sense the temperature}	7/0827	• • {responsive to underload or no-load, e.g. pump-off control circuits for pump motors}
5/045	• • {using a thermal radiation sensor}	7/0833	• • {for electric motors with control arrangements}
5/046	• • {using a thermocouple}	7/0838	• • • {with H-bridge circuit}
5/047	• • {using a temperature responsive switch}	7/0844	• • • {Fail safe control, e.g. by comparing control signal and controlled current, isolating motor on commutation error}
5/048	• • • {additionally responsive to excess current due to heating of the switch}	7/085	• • against excessive load {( <a href="#">H02H 6/00</a> takes precedence)}
5/06	• • in oil-filled electric apparatus	7/0851	• • • {for motors actuating a movable member between two end positions, e.g. detecting an end position or obstruction by overload signal}
5/08	• responsive to abnormal fluid pressure, liquid level or liquid displacement, e.g. Buchholz relays		
5/083	• • {responsive to the entry or leakage of a liquid into an electrical appliance (moisture alarm <a href="#">G08B 21/20</a> )}		
5/086	• • {of cooling or lubricating fluids}		
5/10	• responsive to mechanical injury, e.g. rupture of line, breakage of earth connection		
5/105	• • {responsive to deterioration or interruption of earth connection (for preventing switching-on <a href="#">H02H 11/001</a> )}		

- 7/0852 . . . {directly responsive to abnormal temperature by using a temperature sensor (in a control circuit [H02H 7/0833](#))}
- 7/0853 . . . {specially adapted for motors rotating in both directions ([H02H 7/0851](#) takes precedence)}
- 7/0854 . . . {responsive to rate of change of current, couple or speed, e.g. anti-kickback protection ([H02H 7/0851](#) takes precedence)}
- 7/0855 . . . {avoiding response to transient overloads, e.g. during starting}
- 7/0856 . . . {characterised by the protection measure taken}
- 7/0857 . . . . {by lowering the mechanical load of the motor}
- 7/0858 . . . . {by reversing, cycling or reducing the power supply to the motor}
- 7/0859 . . . . {avoiding restarting after fault condition has disappeared}
- 7/09 . . against over-voltage; against reduction of voltage; against phase interruption
- 7/093 . . against increase beyond, or decrease below, a predetermined level of rotational speed ([centrifugal switches H01H 35/10](#))
- 7/097 . . against wrong direction of rotation
- 7/10 . . for converters; for rectifiers {(forming part of the control circuit of the converter, [see the relevant group in H02M](#))}
- 7/103 . . {for rotating converters}
- 7/106 . . {for dynamic converters}
- 7/12 . . for static converters or rectifiers {(for discharge lamp power supplies using static converters [H05B 41/2851](#), [H05B 41/2921](#), [H05B 41/2981](#))}
- 7/1203 . . . {Circuits independent of the type of conversion}
- 7/1206 . . . . {specially adapted to conversion cells composed of a plurality of parallel or serial connected elements}
- 7/1209 . . . {for converters using only discharge tubes}
- 7/1213 . . . {for DC-DC converters}
- 7/1216 . . . {for AC-AC converters}
- 7/122 . . . for inverters, i.e. dc/ac converters
- 7/1222 . . . . {responsive to abnormalities in the input circuit, e.g. transients in the DC input}
- 7/1225 . . . . {responsive to internal faults, e.g. shoot-through ([avoiding shoot-through H02M 1/38](#))}
- 7/1227 . . . . {responsive to abnormalities in the output circuit, e.g. short circuit}
- 7/125 . . . for rectifiers
- 7/1252 . . . . {responsive to overvoltage in input or output, e.g. by load dump}
- 7/1255 . . . . {responsive to internal faults, e.g. by monitoring ripple in output voltage}
- 7/1257 . . . . {responsive to short circuit or wrong polarity in output circuit}
- 7/127 . . . . having auxiliary control electrode to which blocking control voltages or currents are applied in case of emergency
- 7/16 . . for capacitors ([for synchronous capacitors H02H 7/06](#))
- 7/18 . . for batteries; for accumulators
- 7/20 . . for electronic equipment ([for converters H02H 7/10](#); [for electric measuring instruments G01R 1/36](#); [for dc voltage or current semiconductor regulators G05F 1/569](#); [for amplifiers H03F 1/52](#); [for electronic switching circuits H03K 17/08](#))
- 7/205 . . {for controlled semi-conductors which are not included in a specific circuit arrangement}
- 7/22 . . for distribution gear, e.g. bus-bar systems; for switching devices {(detecting mechanical or electrical defects in gas-insulated switchgears [H02B 13/065](#))}
- 7/222 . . {for switches}
- 7/224 . . . {Anti-pump circuits}
- 7/226 . . {for wires or cables, e.g. heating wires}
- 7/228 . . {for covered wires or cables}
- 7/24 . . for spark-gap arresters
- 7/26 . . Sectionalised protection of cable or line systems, e.g. for disconnecting a section on which a short-circuit, earth fault, or arc discharge has occurred ([locating faults in cables G01R 31/08](#))
- 7/261 . . {involving signal transmission between at least two stations ([transmission of signals in general H02H 1/0061](#))}
- 7/262 . . . {involving transmissions of switching or blocking orders}
- 7/263 . . . {involving transmissions of measured values (comparison of currents or voltages using pilot wires [H02H 3/30](#))}
- 7/265 . . {making use of travelling wave theory}
- 7/266 . . {involving switching on a spare supply ([in general H02J 9/00](#))}
- 7/267 . . {for parallel lines and wires}
- 7/268 . . {for dc systems}
- 7/28 . . for meshed systems
- 7/30 . . Staggered disconnection
- 9/00 Emergency protective circuit arrangements for limiting excess current or voltage without disconnection** (structural association of protective devices with specific machines or apparatus, [see the relevant subclass for the machine or apparatus](#))
- 9/001 . . {limiting speed of change of electric quantities, e.g. soft switching on or off ([progressive control of electronic switches for eliminating interferences H03K 17/16](#))}
- 9/002 . . {limiting inrush current on switching on of inductive loads subjected to remanence, e.g. transformers}
- 9/004 . . {in connection with live-insertion of plug-in units ([involving communication with a central processing unit G06F 13/40](#))}
- 9/005 . . {avoiding undesired transient conditions}
- 9/007 . . {avoiding or damping oscillations, e.g. ferroresonance or travelling waves}
- 9/008 . . {Intrinsically safe circuits}
- 9/02 . . responsive to excess current {(current limitation for voltage regulators [G05F 1/573](#); [disconnection after limiting H02H 3/025](#))}
- 9/021 . . {Current limitation using saturable reactors ([H02H 9/023](#) takes precedence)}
- 9/023 . . {Current limitation using superconducting elements}
- 9/025 . . {Current limitation using field effect transistors}

- 9/026 . . {Current limitation using PTC resistors, i.e. resistors with a large positive temperature coefficient}
- 9/028 . . {Current limitation by detuning a series resonant circuit ([H02H 9/021](#), [H02H 9/023](#) take precedence)}
- 9/04 . responsive to excess voltage ([lightning arrestors H01C 7/12](#), [H01C 8/04](#), [H01G 9/18](#), [H01T](#))
- 9/041 . . {using a short-circuiting device}
- 9/042 . . {comprising means to limit the absorbed power or indicate damaged over-voltage protection device}
- 9/043 . . {Protection of over-voltage protection device by short-circuiting}
- 9/044 . . {Physical layout, materials not provided for elsewhere ([varistors H01C 7/12](#); [Ovshinsky devices H01L 45/00](#); [spark-gaps H01T](#))}
- 9/045 . . {adapted to a particular application and not provided for elsewhere}
- 9/046 . . . {responsive to excess voltage appearing at terminals of integrated circuits ([protection by specific structural integration design H01L 27/0248](#))}
- 9/047 . . . {Free-wheeling circuits}
- 9/048 . . {Anti-latching or quenching devices, i.e. bringing the protection device back to its normal state after a protection action}
- 9/049 . . {Circuit arrangements for limiting the number of protection devices}
- 9/06 . . using spark-gap arresters
- 9/08 . Limitation or suppression of earth fault currents, e.g. Petersen coil

**11/00 Emergency protective circuit arrangements for preventing the switching-on in case an undesired electric working condition might result**

- 11/001 . {in case of incorrect or interrupted earth connection ([disconnection by breaking of earth connection H02H 5/105](#))}
- 11/002 . {in case of inverted polarity or connection; with switching for obtaining correct connection}
- 11/003 . . {using a field effect transistor as protecting element in one of the supply lines}
- 11/004 . {in case of incorrect phase sequence; with switching for obtaining correct phase sequence ([protection of motors against wrong direction of rotation H02H 7/097](#))}
- 11/005 . {in case of too low isolation resistance, too high load, short-circuit; earth fault}
- 11/006 . {in case of too high or too low voltage}
- 11/007 . . {involving automatic switching for adapting the protected apparatus to the supply voltage}
- 11/008 . {preventing unsafe switching operations in substations ([Schaltfehlerschutz](#))}