

CPC COOPERATIVE PATENT CLASSIFICATION

H ELECTRICITY

(NOTE omitted)

H02 GENERATION; CONVERSION OR DISTRIBUTION OF ELECTRIC POWER

H02K DYNAMO-ELECTRIC MACHINES (dynamo-electric relays [H01H 53/00](#); conversion of DC or AC input power into surge output power {[H03K 3/53](#)})

NOTES

1. This subclass covers the structural adaptation of dynamo-electric machines for the purpose of their control.
2. This subclass does not cover starting, regulating, electronically commutating, braking, or otherwise controlling motors, generators or dynamo-electric converters, in general, which is covered by subclass [H02P](#).
3. Attention is drawn to the Notes following the titles of class [B81](#) and subclass [B81B](#) relating to "microstructural devices" and "microstructural systems".
4. Group [H02K 16/00](#) takes precedence over groups [H02K 17/00](#) - [H02K 53/00](#).
{This Note corresponds to IPC Note (1) relating to [H02K 17/00](#) - [H02K 53/00](#).}
5. {In this subclass, it is desirable to add the indexing codes of [H02K 2201/00](#)-[H02K 2213/12](#).}

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Details of the magnetic circuit (magnetic circuits for relays H01H 50/16)	1/223	. . . {Rotor cores with windings and permanent magnets (for additional excitation in synchronous motors or generators H02K 21/042 ; in synchronous motors having additional short-circuited winding for starting as an asynchronous motor H02K 21/46)}
1/02	. characterised by the magnetic material		
1/04	. characterised by the material used for insulating the magnetic circuit or parts thereof		
1/06	. characterised by the shape, form or construction		
1/08	. . Salient poles	1/24	. . . Rotor cores with salient poles {; Variable reluctance rotors}
1/10	. . . Commutating poles		
1/12	. . Stationary parts of the magnetic circuit	1/243 {of the claw-pole type}
1/14	. . . Stator cores with salient poles	1/246 {Variable reluctance rotors}
1/141 {consisting of C-shaped cores}	1/26	. . . Rotor cores with slots for windings
1/143 {of the horse-shoe type}	1/265 {Shape, form or location of the slots}
1/145 {having an annular coil, e.g. of the claw-pole type}	1/27	. . . Rotor cores with permanent magnets
1/146 {consisting of a generally annular yoke with salient poles}	1/2706 Inner rotors
1/148 {Sectional cores (H02K 1/141 takes precedence)}	1/2713 the magnetisation axis of the magnets being axial, e.g. claw-pole type
1/16	. . . Stator cores with slots for windings	1/272 the magnetisation axis of the magnets being perpendicular to the rotor axis
1/165 {Shape, form or location of the slots}	1/2726 the rotor consisting of a single magnet or two or more axially juxtaposed single magnets
1/17	. . . Stator cores with permanent magnets		
1/18	. . . Means for mounting or fastening magnetic stationary parts on to, or to, the stator structures	1/2733 Annular magnets
1/182 {to stators axially facing the rotor, i.e. with axial or conical air gap}	1/274 the rotor consisting of two or more circumferentially positioned magnets
1/185 {to outer stators}	1/2746 the rotor consisting of magnets arranged with the same polarity, e.g. consequent pole type
1/187 {to inner stators}		
1/20	. . . with channels or ducts for flow of cooling medium	1/2753 the rotor consisting of magnets or groups of magnets arranged with alternating polarity
1/22	. . Rotating parts of the magnetic circuit	1/276 Magnets embedded in the magnetic core, e.g. interior permanent magnets [IPM]
		1/2766 {having a flux concentration effect}

1/2773 {consisting of tangentially magnetized radial magnets}

1/278 Surface mounted magnets; Inset magnets

WARNING

Group [H02K 1/278](#) is impacted by reclassification into groups [H02K 1/2781](#) and [H02K 1/2783](#).

Groups [H02K 1/278](#), [H02K 1/2781](#) and [H02K 1/2783](#) should be considered in order to perform a complete search.

1/2781 Magnets shaped to vary the mechanical air gap between the magnets and the stator

WARNING

Group [H02K 1/2781](#) is incomplete pending reclassification of documents from group [H02K 1/278](#).

Groups [H02K 1/278](#) and [H02K 1/2781](#) should be considered in order to perform a complete search.

1/2783 with magnets arranged in Halbach arrays

WARNING

Group [H02K 1/2783](#) is incomplete pending reclassification of documents from group [H02K 1/278](#).

Groups [H02K 1/278](#) and [H02K 1/2783](#) should be considered in order to perform a complete search.

1/2786 Outer rotors

WARNING

Group [H02K 1/2786](#) is impacted by reclassification into groups [H02K 1/2787](#), [H02K 1/2788](#), [H02K 1/2789](#), [H02K 1/279](#), [H02K 1/2791](#), [H02K 1/27915](#) and [H02K 1/2792](#).

All groups listed in this Warning should be considered in order to perform a complete search.

1/2787 the magnetisation axis of the magnets being perpendicular to the rotor axis

WARNING

Groups [H02K 1/2787](#), [H02K 1/2788](#), [H02K 1/2789](#), [H02K 1/279](#), [H02K 1/2791](#), [H02K 1/27915](#) and [H02K 1/2792](#) are incomplete pending reclassification of documents from group [H02K 1/2786](#).

All groups listed in this Warning should be considered in order to perform a complete search.

1/2788 the rotor consisting of a single magnet or two or more axially juxtaposed single magnets

1/2789 the rotor consisting of two or more circumferentially positioned magnets

1/279 Magnets embedded in the magnetic core

1/2791 Surface mounted magnets; Inset magnets

1/27915 Magnets shaped to vary the mechanical air gap between the magnets and the stator

1/2792 with magnets arranged in Halbach arrays

1/2793 Rotors axially facing stators

WARNING

Group [H02K 1/2793](#) is impacted by reclassification into groups [H02K 1/2795](#), [H02K 1/2796](#) and [H02K 1/2798](#).

All groups listed in this Warning should be considered in order to perform a complete search.

1/2795 the rotor consisting of two or more circumferentially positioned magnets

WARNING

Groups [H02K 1/2795](#), [H02K 1/2796](#) and [H02K 1/2798](#) are incomplete pending reclassification of documents from group [H02K 1/2793](#).

All groups listed in this Warning should be considered in order to perform a complete search.

1/2796 where both axial sides of the rotor face a stator

1/2798 where both axial sides of the stator face a rotor

1/28 . . . Means for mounting or fastening rotating magnetic parts on to, or to, the rotor structures

1/30 using intermediate parts, e.g. spiders

1/32 . . . with channels or ducts for flow of cooling medium

1/325 {between salient poles}

1/34 . . Reciprocating, oscillating or vibrating parts of the magnetic circuit

3/00 Details of windings

3/02 . Windings characterised by the conductor material

3/04 . Windings characterised by the conductor shape, form or construction, e.g. with bar conductors

3/12 . . arranged in slots

3/14 . . . with transposed conductors, e.g. twisted conductors

3/16 . . . for auxiliary purposes, e.g. damping or commutating

3/18 . . Windings for salient poles

3/20 . . . for auxiliary purposes, e.g. damping or commutating

3/22 . . consisting of hollow conductors

3/24 . . with channels or ducts for cooling medium between the conductors

3/26 . . consisting of printed conductors

- 3/28 . . Layout of windings or of connections between windings ([windings for pole-changing H02K 17/06, H02K 17/14, H02K 19/12, H02K 19/32](#))
- 3/30 . Windings characterised by the insulating material
- 3/32 . Windings characterised by the shape, form or construction of the insulation
- 3/325 . . {for windings on salient poles, such as claw-shaped poles}
- 3/34 . . between conductors or between conductor and core, e.g. slot insulation
- 3/345 . . . {between conductor and core, e.g. slot insulation}
- 3/38 . . around winding heads, equalising connectors, or connections thereto
- 3/40 . . for high voltage, e.g. affording protection against corona discharges
- 3/42 . Means for preventing or reducing eddy-current losses in the winding heads, e.g. by shielding
- 3/44 . Protection against moisture or chemical attack; Windings specially adapted for operation in liquid or gas
- 3/46 . Fastening of windings on the stator or rotor structure
- 3/47 . . Air-gap windings, i.e. iron-free windings
- 3/48 . . in slots
- 3/487 . . . Slot-closing devices
- 3/493 magnetic
- 3/50 . . Fastening of winding heads, equalising connectors, or connections thereto
- 3/505 . . . {for large machine windings, e.g. bar windings ([H02K 3/51 takes precedence](#))}
- 3/51 . . . applicable to rotors only
- 3/52 . . Fastening salient pole windings or connections thereto
- 3/521 . . . {applicable to stators only}
- 3/522 {for generally annular cores with salient poles}
- 3/524 {for U-shaped, E-shaped or similarly shaped cores}
- 3/525 {Annular coils, e.g. for cores of the claw-pole type}
- 3/527 . . . {applicable to rotors only}
- 3/528 {of the claw-pole type}
- 5/00 Casings; Enclosures; Supports**
- 5/02 . Casings or enclosures characterised by the material thereof
- 5/04 . Casings or enclosures characterised by the shape, form or construction thereof
- 5/06 . . Cast metal casings
- 5/08 . . Insulating casings
- 5/10 . . with arrangements for protection from ingress, e.g. water or fingers
- 5/12 . . specially adapted for operating in liquid or gas ([combined with cooling arrangements H02K 9/00](#))
- 5/124 . . . Sealing of shafts
- 5/128 . . . using air-gap sleeves or air-gap discs
- 5/1282 {the partition wall in the air-gap being non cylindrical}
- 5/1285 {of the submersible type}
- 5/132 . . . Submersible electric motors ([H02K 5/128 takes precedence](#))
- 5/136 . . . explosion-proof
- 5/14 . . Means for supporting or protecting brushes or brush holders
- 5/141 . . . {for cooperation with slip-rings}
- 5/143 . . . {for cooperation with commutators}
- 5/145 {Fixedly supported brushes or brush holders, e.g. leaf or leaf-mounted brushes}
- 5/146 {Pivotally supported brushes or brush holders}
- 5/148 {Slidably supported brushes}
- 5/15 . . Mounting arrangements for bearing-shields or end plates
- 5/16 . . Means for supporting bearings, e.g. insulating supports or means for fitting bearings in the bearing-shields ([magnetic bearings H02K 7/09](#))
- 5/161 . . . {radially supporting the rotary shaft at both ends of the rotor ([H02K 5/165, H02K 5/167, H02K 5/173 take precedence](#))}
- 5/163 . . . {radially supporting the rotary shaft at only one end of the rotor ([H02K 5/165, H02K 5/167, H02K 5/173 take precedence](#))}
- 5/165 . . . {radially supporting the rotor around a fixed spindle; radially supporting the rotor directly ([H02K 5/167, H02K 5/173 take precedence](#))}
- 5/167 . . . using sliding-contact or spherical cap bearings
- 5/1672 {radially supporting the rotary shaft at both ends of the rotor ([H02K 5/1677 takes precedence](#))}
- 5/1675 {radially supporting the rotary shaft at only one end of the rotor ([H02K 5/1677 takes precedence](#))}
- 5/1677 {radially supporting the rotor around a fixed spindle; radially supporting the rotor directly}
- 5/173 . . . using bearings with rolling contact, e.g. ball bearings
- 5/1732 {radially supporting the rotary shaft at both ends of the rotor ([H02K 5/1737 takes precedence](#))}
- 5/1735 {radially supporting the rotary shaft at only one end of the rotor ([H02K 5/1737 takes precedence](#))}
- 5/1737 {radially supporting the rotor around a fixed spindle; radially supporting the rotor directly}
- 5/18 . . with ribs or fins for improving heat transfer
- 5/20 . . with channels or ducts for flow of cooling medium

WARNING

Group [H02K 5/20](#) is impacted by reclassification into groups [H02K 5/203](#) and [H02K 5/207](#).

Groups [H02K 5/20](#), [H02K 5/203](#), and [H02K 5/207](#) should be considered in order to perform a complete search.

- 5/203 . . . {specially adapted for liquids, e.g. cooling jackets}

WARNING

Group [H02K 5/203](#) is incomplete pending reclassification of documents from group [H02K 5/20](#).

Groups [H02K 5/20](#) and [H02K 5/203](#) should be considered in order to perform a complete search.

- 5/207 . . . {with openings in the casing specially adapted for ambient air}

WARNING

Group [H02K 5/207](#) is incomplete pending reclassification of documents from group [H02K 5/20](#).

Groups [H02K 5/20](#) and [H02K 5/207](#) should be considered in order to perform a complete search.

- 5/22 . . Auxiliary parts of casings not covered by groups [H02K 5/06-H02K 5/20](#), e.g. shaped to form connection boxes or terminal boxes

- 5/225 . . . {Terminal boxes or connection arrangements (specially adapted for submersible motors [H02K 5/132](#))}

- 5/24 . specially adapted for suppression or reduction of noise or vibrations

- 5/26 . Means for adjusting casings relative to their supports

7/00 Arrangements for handling mechanical energy structurally associated with dynamo-electric machines, e.g. structural association with mechanical driving motors or auxiliary dynamo-electric machines

- 7/003 . {Couplings; Details of shafts (means for mounting rotors on shafts [H02K 1/28](#))}

- 7/006 . {Structural association of a motor or generator with the drive train of a motor vehicle}

- 7/02 . Additional mass for increasing inertia, e.g. flywheels

- 7/025 . . {for power storage}

- 7/04 . Balancing means

- 7/06 . Means for converting reciprocating motion into rotary motion or *vice versa*

- 7/061 . . {using rotary unbalanced masses (for generating mechanical vibrations in general [B06B 1/16](#))}

- 7/063 . . . {integrally combined with motor parts, e.g. motors with eccentric rotors}

- 7/065 . . Electromechanical oscillators; Vibrating magnetic drives

- 7/07 . . using pawls and ratchet wheels

- 7/075 . . using crankshafts or eccentrics

- 7/08 . Structural association with bearings

- 7/081 . . {specially adapted for worm gear drives ([H02K 7/09](#) takes precedence)}

- 7/083 . . {radially supporting the rotary shaft at both ends of the rotor ([H02K 7/086](#), [H02K 7/09](#) take precedence)}

- 7/085 . . {radially supporting the rotary shaft at only one end of the rotor ([H02K 7/086](#), [H02K 7/09](#) take precedence)}

- 7/086 . . {radially supporting the rotor around a fixed spindle; radially supporting the rotor directly ([H02K 7/09](#) takes precedence)}

- 7/088 . . . {radially supporting the rotor directly}

- 7/09 . . with magnetic bearings

- 7/10 . Structural association with clutches, brakes, gears, pulleys or mechanical starters

NOTE

{Group [H02K 7/12](#) takes precedence over groups [H02K 7/102](#) - [H02K 7/118](#)}

- 7/1004 . . {with pulleys}

- 7/1008 . . . {structurally associated with the machine rotor ([H02K 7/1012](#) takes precedence)}

- 7/1012 . . . {Machine arranged inside the pulley}

- 7/1016 {Machine of the outer rotor type}

- 7/102 . . with friction brakes

- 7/1021 . . . {Magnetically influenced friction brakes}

- 7/1023 {using electromagnets}

- 7/1025 {using axial electromagnets with generally annular air gap}

- 7/1026 {using stray fields}

- 7/1028 {axially attracting the brake armature in the frontal area of the magnetic core}

- 7/104 . . with eddy-current brakes

- 7/106 . . with dynamo-electric brakes

- 7/108 . . with friction clutches

- 7/1085 . . . {Magnetically influenced friction clutches}

- 7/11 . . with dynamo-electric clutches

- 7/112 . . with friction clutches in combination with brakes

- 7/1125 . . . {Magnetically influenced friction clutches and brakes}

- 7/114 . . with dynamo-electric clutches in combination with brakes

- 7/116 . . with gears

- 7/1163 . . . {where at least two gears have non-parallel axes without having orbital motion}

- 7/1166 {comprising worm and worm-wheel (structural association with bearings specially adapted for worm gear drives [H02K 7/081](#))}

- 7/118 . . with starting devices

- 7/1185 . . . {with a mechanical one-way direction control, i.e. with means for reversing the direction of rotation of the rotor}

- 7/12 . . with auxiliary limited movement of stators, rotors or core parts, e.g. rotors axially movable for the purpose of clutching or braking

- 7/125 . . . {magnetically influenced}

- 7/14 . Structural association with mechanical loads, e.g. with hand-held machine tools or fans (with fan or impeller for cooling the machine [H02K 9/06](#))

- 7/145 . . {Hand-held machine tool}

- 7/16 . . for operation above the critical speed of vibration of the rotating parts

- 7/18 . Structural association of electric generators with mechanical driving motors, e.g. with turbines

- 7/1807 . . {Rotary generators ([H02K 7/006](#) takes precedence)}

- 7/1815 . . . {structurally associated with reciprocating piston engines (general aspects of generating sets, e.g. housing, [F02B 63/04](#))}

- 7/1823 . . . {structurally associated with turbines or similar engines}
- 7/183 {wherein the turbine is a wind turbine (adaptation of a wind turbine to an electric generator [F03D 9/25](#))}
- 7/1838 {Generators mounted in a nacelle or similar structure of a horizontal axis wind turbine}
- 7/1846 . . . {structurally associated with wheels or associated parts (dynamos arranged in the wheel hub of cycles [B62J 6/12](#))}
- 7/1853 . . . {driven by intermittent forces}
- 7/1861 . . . {driven by animals or vehicles ([H02K 7/1853](#) takes precedence)}
- 7/1869 . . {Linear generators; sectional generators}
- 7/1876 . . . {with reciprocating, linearly oscillating or vibrating parts}
- 7/1884 {structurally associated with free piston engines}
- 7/1892 . . {Generators with parts oscillating or vibrating about an axis}
- 7/20 . Structural association with auxiliary dynamo-electric machines, e.g. with electric starter motors or exciters
- 9/00 Arrangements for cooling or ventilating (channels or ducts in parts of the magnetic circuit [H02K 1/20](#), [H02K 1/32](#); channels or ducts in or between conductors [H02K 3/22](#), [H02K 3/24](#))**
- 9/02 . by ambient air flowing through the machine
- 9/04 . . having means for generating a flow of cooling medium
- 9/06 . . . with fans or impellers driven by the machine shaft
- 9/08 . by gaseous cooling medium circulating wholly within the machine casing ([H02K 9/10](#) takes precedence)
- 9/10 . by gaseous cooling medium flowing in closed circuit, a part of which is external to the machine casing
- 9/12 . . wherein the cooling medium circulates freely within the casing
- 9/14 . wherein gaseous cooling medium circulates between the machine casing and a surrounding mantle
- 9/16 . . wherein the cooling medium circulates through ducts or tubes within the casing
- 9/18 . . wherein the external part of the closed circuit comprises a heat exchanger structurally associated with the machine casing
- 9/19 . for machines with closed casing and closed-circuit cooling using a liquid cooling medium, e.g. oil
- WARNING**
Group [H02K 9/19](#) is impacted by reclassification into group [H02K 9/197](#).
Groups [H02K 9/19](#) and [H02K 9/197](#) should be considered in order to perform a complete search.
- 9/193 . . with provision for replenishing the cooling medium; with means for preventing leakage of the cooling medium

- 9/197 . . in which the rotor or stator space is fluid-tight, e.g. to provide for different cooling media for rotor and stator

WARNING

Group [H02K 9/197](#) is incomplete pending reclassification of documents from group [H02K 9/19](#).

Groups [H02K 9/19](#) and [H02K 9/197](#) should be considered in order to perform a complete search.

- 9/20 . . wherein the cooling medium vaporises within the machine casing

WARNING

Group [H02K 9/20](#) is impacted by reclassification into group [H02K 9/225](#).

Groups [H02K 9/20](#) and [H02K 9/225](#) should be considered in order to perform a complete search.

- 9/22 . by solid heat conducting material embedded in, or arranged in contact with, the stator or rotor, e.g. heat bridges

WARNING

Group [H02K 9/22](#) is impacted by reclassification into groups [H02K 9/223](#), [H02K 9/225](#), and [H02K 9/227](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 9/223 . . {Heat bridges}

WARNING

Group [H02K 9/223](#) is incomplete pending reclassification of documents from group [H02K 9/22](#).

Groups [H02K 9/22](#) and [H02K 9/223](#) should be considered in order to perform a complete search.

- 9/225 . . {Heat pipes}

WARNING

Group [H02K 9/225](#) is incomplete pending reclassification of documents from groups [H02K 9/20](#) and [H02K 9/22](#).

Groups [H02K 9/20](#), [H02K 9/22](#), and [H02K 9/225](#) should be considered in order to perform a complete search.

- 9/227 . . {Heat sinks}

WARNING

Group [H02K 9/227](#) is incomplete pending reclassification of documents from group [H02K 9/22](#).

Groups [H02K 9/22](#) and [H02K 9/227](#) should be considered in order to perform a complete search.

- 9/24 . Protection against failure of cooling arrangements, e.g. due to loss of cooling medium or due to interruption of the circulation of cooling medium

- 9/26 . Structural association of machines with devices for cleaning or drying cooling medium, e.g. with filters
- 9/28 . Cooling of commutators, slip-rings or brushes e.g. by ventilating
- 11/00 Structural association of dynamo-electric machines with electric components or with devices for shielding, monitoring or protection (casings, enclosures or supports H02K 5/00)**
- 11/0094 . {Structural association with other electrical or electronic devices}
- 11/01 . for shielding from electromagnetic fields {, i.e. structural association with shields} (means for preventing or reducing eddy-current losses in the winding heads by shielding H02K 3/42)
- 11/012 . . {Shields associated with rotating parts, e.g. rotor cores or rotary shafts}
- 11/014 . . {Shields associated with stationary parts, e.g. stator cores}
- 11/0141 . . . {Shields associated with casings, enclosures or brackets}
- 11/02 . for suppression of electromagnetic interference
- 11/026 . . Suppressors associated with brushes, brush holders or their supports
- 11/028 . . Suppressors associated with the rotor
- 11/04 . for rectification
- 11/042 . . Rectifiers associated with rotating parts, e.g. rotor cores or rotary shafts
- 11/044 . . {in motors (H02K 11/042 takes precedence)}
- (Frozen)
- WARNING**
- Group H02K 11/044 is no longer used for the classification of documents as of August 1, 2021.
- The content of this group is being reclassified into groups H02K 11/049 and H02K 11/05.
- Groups H02K 11/044, H02K 11/049 and H02K 11/05 should be considered in order to perform a complete search.
- 11/046 . . {in generators (H02K 11/042 takes precedence)}
- (Frozen)
- WARNING**
- Group H02K 11/046 is no longer used for the classification of documents as of August 1, 2021.
- The content of this group is being reclassified into groups H02K 11/049 and H02K 11/05.
- Groups H02K 11/046, H02K 11/049 and H02K 11/05 should be considered in order to perform a complete search.
- 11/048 . . . {Rectifiers combined with drive circuits in starter-generators}
- (Frozen)
- WARNING**
- Group H02K 11/048 is no longer used for the classification of documents as of August 1, 2021.
- The content of this group is being reclassified into groups H02K 11/049 and H02K 11/05.
- Groups H02K 11/048, H02K 11/049 and H02K 11/05 should be considered in order to perform a complete search.
- 11/049 . . Rectifiers associated with stationary parts, e.g. stator cores
- WARNING**
- Groups H02K 11/049 and H02K 11/05 are incomplete pending reclassification of documents from groups H02K 11/044, H02K 11/046 and H02K 11/048.
- All groups listed in this Warning should be considered in order to perform a complete search.
- 11/05 . . . Rectifiers associated with casings, enclosures or brackets
- 11/20 . for measuring, monitoring, testing, protecting or switching (rectifiers H02K 11/04; power electronics H02K 11/33)
- 11/21 . . Devices for sensing speed or position, or actuated thereby (specially adapted for machines having non-mechanical commutating devices H02K 29/06, H02K 29/14)
- 11/215 . . . Magnetic effect devices, e.g. Hall-effect or magneto-resistive elements
- 11/22 . . . Optical devices
- 11/225 . . . Detecting coils
- 11/23 . . . Mechanically-actuated centrifugal switches
- 11/24 . . Devices for sensing torque, or actuated thereby (H02K 11/27 takes precedence)
- 11/25 . . Devices for sensing temperature, or actuated thereby
- 11/26 . . Devices for sensing voltage, or actuated thereby, e.g. overvoltage protection devices
- 11/27 . . Devices for sensing current, or actuated thereby (overcurrent protection responsive to temperature of the machines or parts thereof, e.g. windings, H02K 11/25)
- 11/28 . . Manual switches
- 11/30 . Structural association with control circuits or drive circuits
- 11/33 . . Drive circuits, e.g. power electronics (H02K 11/38 takes precedence)
- 11/35 . . Devices for recording or transmitting machine parameters, e.g. memory chips or radio transmitters for diagnosis
- 11/38 . . Control circuits or drive circuits associated with geared commutator motors of the worm-and-wheel type
- 11/40 . Structural association with grounding devices
- 13/00 Structural associations of current collectors with motors or generators, e.g. brush mounting plates or connections to windings (supporting or protecting brushes or brush holders in motor casings or enclosures H02K 5/14); Disposition of current collectors in motors or generators; Arrangements for improving commutation**
- 13/003 . {Structural associations of slip-rings}
- 13/006 . {Structural associations of commutators}
- 13/02 . Connections between slip-rings and windings
- 13/04 . Connections between commutator segments and windings
- 13/06 . . Resistive connections, e.g. by high-resistance chokes or by transistors
- 13/08 . . Segments formed by extensions of the winding

- 13/10 . Arrangements of brushes or commutators specially adapted for improving commutation
- 13/105 . . {Spark suppressors associated with the commutator}
- 13/12 . Arrangements for producing an axial reciprocation of the rotor and its associated current collector part, e.g. for polishing commutator surfaces
- 13/14 . Circuit arrangements for improvement of commutation, e.g. by use of unidirectionally conductive elements
- 15/00 Methods or apparatus specially adapted for manufacturing, assembling, maintaining or repairing of dynamo-electric machines**
- 15/0006 . {Disassembling, repairing or modifying dynamo-electric machines (repairing of cooling fluid boxes [H02K 15/0093](#))}
- 15/0012 . {Manufacturing cage rotors}
- 15/0018 . {Applying slot closure means in the core; Manufacture of slot closure means}
- 15/0025 . {Shaping or compacting conductors or winding heads after the installation of the winding in the core or machine (methods or apparatus for simultaneously twisting a plurality of hairpins prior to mounting [H02K 15/0428](#)); Applying fastening means on winding heads}
- 15/0031 . . {Shaping or compacting conductors in slots or around salient poles ([H02K 15/005](#) takes precedence)}
- 15/0037 . . {Shaping or compacting winding heads ([H02K 15/005](#), [H02K 15/0087](#) and [H02K 15/0428](#) take precedence)}
- 15/0043 . . . {Applying fastening means on winding heads (fastening by applying resin, glue, varnish and similar means [H02K 15/12](#))}
- 15/005 . . {by means of electrodynamic forces}
- 15/0056 . {Manufacturing winding connections}
- 15/0062 . . {Manufacturing the terminal arrangement *per se*; Connecting the terminals to an external circuit}
- 15/0068 . . {Connecting winding sections; Forming leads; Connecting leads to terminals}
- 15/0081 . . . {for form-wound windings}
- 15/0087 {characterised by the method or apparatus for simultaneously twisting a plurality of hairpins open ends after insertion into the machine (for simultaneously twisting a plurality of hairpins prior to mounting into the machine [H02K 15/0428](#))}
- 15/0093 {Manufacturing or repairing cooling fluid boxes, i.e. terminals of fluid cooled windings ensuring both electrical and fluid connection}
- 15/02 . of stator or rotor bodies
- 15/022 . . {with salient poles or claw-shaped poles}
- 15/024 . . {with slots}
- 15/026 . . . {Wound cores}
- 15/028 . . . {for fastening to casing or support, respectively to shaft or hub}
- 15/03 . . having permanent magnets
- 15/04 . of windings, prior to mounting into machines ([insulating windings H02K 15/10](#), [H02K 15/12](#))
- 15/0407 . . {Windings manufactured by etching, printing or stamping the complete coil}
- 15/0414 . . {Windings consisting of separate elements, e.g. bars, hairpins, segments, half coils}
- 15/0421 {consisting of single conductors, e.g. hairpins}
- 15/0428 {characterised by the method or apparatus for simultaneously twisting a plurality of hairpins (for simultaneously twisting a plurality of hairpins open ends after insertion into the machine [H02K 15/0087](#))}
- 15/0435 . . {Wound windings}
- 15/0442 . . . {Loop windings (manufacturing of windings consisting of overlapped loops [H02K 15/0464](#))}
- 15/045 {Form wound coils}
- 15/0464 . . . {Lap windings (when on diagonally wound hollow coils [H02K 15/0492](#))}
- 15/0471 {manufactured by flattening a spiral winding}
- 15/0478 . . . {Wave windings, undulated windings (when on diagonally wound hollow coils [H02K 15/0492](#))}
- 15/0485 {manufactured by shaping an annular winding}
- 15/0492 . . . {Diagonally wound hollow coils}
- 15/06 . Embedding prefabricated windings in machines
- 15/061 . . {Air-gap windings}
- 15/062 . . {Windings in slots; salient pole windings}
- 15/063 . . . {Windings for large electric machines, e.g. bar windings (windings consisting of cables [H02K 15/065](#))}
- 15/064 . . . {Windings consisting of separate segments, e.g. hairpin windings ([H02K 15/063](#) takes precedence)}
- 15/065 . . . {Windings consisting of complete sections, e.g. coils, waves (windings for large electric machines other than those consisting of cables [H02K 15/063](#))}
- 15/066 {inserted perpendicularly to the axis of the slots or inter-polar channels}
- 15/067 {inserted in parallel to the axis of the slots or inter-polar channels}
- 15/068 {Strippers}
- 15/08 . Forming windings by laying conductors into or around core parts
- 15/085 . . by laying conductors into slotted stators
- 15/09 . . by laying conductors into slotted rotors
- 15/095 . . by laying conductors around salient poles
- 15/10 . Applying solid insulation to windings, stators or rotors
- 15/105 . . {to the windings}
- 15/12 . Impregnating, heating or drying of windings, stators, rotors or machines
- 15/125 . . {Heating or drying of machines in operational state, e.g. standstill heating}
- 15/14 . Casings; Enclosures; Supports
- 15/16 . Centering rotors within the stator; Balancing rotors
- 15/165 . . {Balancing the rotor}
- 16/00 Machines with more than one rotor or stator** {(machines for transmitting mechanical power from a driving shaft to a driven shaft and comprising structurally interrelated motor and generator parts [H02K 51/00](#); permanent magnet machines with multiple rotors or stators relatively rotated for vectorially combining the excitation fields or the armature voltages [H02K 21/029](#))}

16/005	<ul style="list-style-type: none"> • {Machines with only rotors, e.g. counter-rotating rotors (DC commutator machines or universal AC/DC commutator motors having a rotating armature and a rotating excitation field H02K 23/60)} 	19/08	<ul style="list-style-type: none"> • . . . Motors having windings on the stator and a smooth rotor without windings of material with large hysteresis, e.g. hysteresis motors
16/02	<ul style="list-style-type: none"> • Machines with one stator and two {or more} rotors 	19/10	<ul style="list-style-type: none"> • . . . for multi-phase current
16/025	<ul style="list-style-type: none"> • . . {with rotors and moving stators connected in a cascade (cascade arrangement of an asynchronous motor with another dynamo-electric motor or converter H02K 17/34)} 	19/103	<ul style="list-style-type: none"> • . . . {Motors having windings on the stator and a variable reluctance soft-iron rotor without windings}
16/04	<ul style="list-style-type: none"> • Machines with one rotor and two stators 	19/106	<ul style="list-style-type: none"> • . . . {Motors having windings in the stator and a smooth rotor of material with large hysteresis without windings}
17/00	Asynchronous induction motors; Asynchronous induction generators	19/12	<ul style="list-style-type: none"> • . . . characterised by the arrangement of exciting windings, e.g. for self-excitation, compounding or pole-changing
17/02	<ul style="list-style-type: none"> • Asynchronous induction motors 	19/14	<ul style="list-style-type: none"> • . . having additional short-circuited windings for starting as asynchronous motors
17/04	<ul style="list-style-type: none"> • . . for single phase current 	19/16	<ul style="list-style-type: none"> • Synchronous generators
17/06	<ul style="list-style-type: none"> • . . . having windings arranged for permitting pole-changing 	19/18	<ul style="list-style-type: none"> • . . having windings each turn of which co-operates only with poles of one polarity, e.g. homopolar generators
17/08	<ul style="list-style-type: none"> • . . . Motors with auxiliary phase obtained by externally fed auxiliary windings, e.g. capacitor motors 	19/20	<ul style="list-style-type: none"> • . . . with variable-reluctance soft-iron rotors without winding
17/10	<ul style="list-style-type: none"> • . . . Motors with auxiliary phase obtained by split-pole carrying short-circuited windings 	19/22	<ul style="list-style-type: none"> • . . having windings each turn of which co-operates alternately with poles of opposite polarity, e.g. heteropolar generators
17/12	<ul style="list-style-type: none"> • . . for multi-phase current 	19/24	<ul style="list-style-type: none"> • . . . with variable-reluctance soft-iron rotors without winding
17/14	<ul style="list-style-type: none"> • . . . having windings arranged for permitting pole-changing 	19/26	<ul style="list-style-type: none"> • . . characterised by the arrangement of exciting windings
17/16	<ul style="list-style-type: none"> • . . having rotors with internally short-circuited windings, e.g. cage rotors 	19/28	<ul style="list-style-type: none"> • . . . for self-excitation
17/165	<ul style="list-style-type: none"> • . . . {characterised by the squirrel-cage or other short-circuited windings} 	19/30	<ul style="list-style-type: none"> • . . . for compounding
17/18	<ul style="list-style-type: none"> • . . . having double-cage or multiple-cage rotors 	19/32	<ul style="list-style-type: none"> • . . . for pole-changing
17/185	<ul style="list-style-type: none"> • {characterised by the double- or multiple cage windings} 	19/34	<ul style="list-style-type: none"> • . . Generators with two or more outputs
17/20	<ul style="list-style-type: none"> • . . . having deep-bar rotors 	19/36	<ul style="list-style-type: none"> • . . Structural association of synchronous generators with auxiliary electric devices influencing the characteristic of the generator or controlling the generator, e.g. with impedances or switches
17/205	<ul style="list-style-type: none"> • {characterised by the deep-bar windings} 	19/365	<ul style="list-style-type: none"> • . . . {with a voltage regulator}
17/22	<ul style="list-style-type: none"> • . . having rotors with windings connected to slip-rings 	19/38	<ul style="list-style-type: none"> • . . Structural association of synchronous generators with exciting machines
17/24	<ul style="list-style-type: none"> • . . . in which both stator and rotor are fed with AC 	21/00	Synchronous motors having permanent magnets; Synchronous generators having permanent magnets
17/26	<ul style="list-style-type: none"> • . . having rotors or stators designed to permit synchronous operation 	21/02	<ul style="list-style-type: none"> • Details
17/28	<ul style="list-style-type: none"> • . . having compensating winding for improving phase angle 	21/021	<ul style="list-style-type: none"> • . . {Means for mechanical adjustment of the excitation flux}
17/30	<ul style="list-style-type: none"> • . . Structural association of asynchronous induction motors with auxiliary electric devices influencing the characteristics of the motor or controlling the motor, e.g. with impedances or switches 	21/022	<ul style="list-style-type: none"> • . . . {by modifying the relative position between field and armature, e.g. between rotor and stator (vectorial combination of field or armature sections H02K 21/029)}
17/32	<ul style="list-style-type: none"> • . . Structural association of asynchronous induction motors with auxiliary mechanical devices, e.g. with clutches or brakes 	21/023	<ul style="list-style-type: none"> • {by varying the amount of superposition, i.e. the overlap, of field and armature}
17/34	<ul style="list-style-type: none"> • . . Cascade arrangement of an asynchronous motor with another dynamo-electric motor or converter 	21/024	<ul style="list-style-type: none"> • {Radial air gap machines}
17/36	<ul style="list-style-type: none"> • . . . with another asynchronous induction motor 	21/025	<ul style="list-style-type: none"> • {by varying the thickness of the air gap between field and armature}
17/38	<ul style="list-style-type: none"> • . . . with a commutator machine 	21/026	<ul style="list-style-type: none"> • {Axial air gap machines}
17/40	<ul style="list-style-type: none"> • . . . with a rotary AC/DC converter 	21/027	<ul style="list-style-type: none"> • {Conical air gap machines}
17/42	<ul style="list-style-type: none"> • Asynchronous induction generators (H02K 17/02 takes precedence) 	21/028	<ul style="list-style-type: none"> • . . . {by modifying the magnetic circuit within the field or the armature, e.g. by using shunts, by adjusting the magnets position, by vectorial combination of field or armature sections}
17/44	<ul style="list-style-type: none"> • . . Structural association with exciting machines 	21/029	<ul style="list-style-type: none"> • {Vectorial combination of the fluxes generated by a plurality of field sections or of the voltages induced in a plurality of armature sections}
19/00	Synchronous motors or generators (having permanent magnets H02K 21/00)		
19/02	<ul style="list-style-type: none"> • Synchronous motors 		
19/04	<ul style="list-style-type: none"> • . . for single-phase current 		
19/06	<ul style="list-style-type: none"> • . . . Motors having windings on the stator and a variable-reluctance soft-iron rotor without windings, e.g. inductor motors 		

21/04	. . Windings on magnets for additional excitation { ; Windings and magnets for additional excitation }	23/04	. . having permanent magnet excitation
21/042	. . . { with permanent magnets and field winding both rotating }	23/06	. . having shunt connection of excitation windings
21/044 { Rotor of the claw pole type }	23/08	. . having series connection of excitation windings
21/046	. . . { with rotating permanent magnets and stationary field winding }	23/10	. . having compound connection of excitation windings
21/048 { Rotor of the claw pole type }	23/12	. . having excitation produced by current sources independent of the armature circuit
21/10	. . Rotating armatures	23/14	. . having high-speed excitation or de-excitation, e.g. by neutralising the remanent excitation field
21/12	. with stationary armatures and rotating magnets	23/16	. . having angularly adjustable excitation field, e.g. by pole reversing or pole switching
21/125	. . { having an annular armature coil (H02K 21/14 - H02K 21/24 take precedence) }	23/18	. . having displaceable main or auxiliary brushes
21/14	. . with magnets rotating within the armatures	23/20	. . having additional brushes spaced intermediately of the main brushes on the commutator, e.g. cross-field machines, metadynes, amplidynes or other armature-reaction excited machines
21/145	. . . { having an annular armature coil (with homopolar co-operation H02K 21/20) }	23/22	. . having compensating or damping windings
21/16	. . . having annular armature cores with salient poles (with homopolar co-operation H02K 21/20)	23/24	. . having commutating-pole windings
21/18	. . . having horse-shoe armature cores (with homopolar co-operation H02K 21/20)	23/26	. characterised by the armature windings
21/185 { with the axis of the rotor perpendicular to the plane of the armature }	23/28	. . having open windings, i.e. not closed within the armatures
21/20	. . . having windings each turn of which co-operates only with poles of one polarity, e.g. homopolar machine	23/30	. . having lap or loop windings
21/22	. . with magnets rotating around the armatures, e.g. flywheel magnetos	23/32	. . having wave or undulating windings
21/222	. . . { Flywheel magnetos }	23/34	. . having mixed windings
21/225 { having I-shaped, E-shaped or similarly shaped armature cores }	23/36	. . having two or more windings; having two or more commutators; having two or more stators
21/227	. . . { having an annular armature coil }	23/38	. . having winding or connection for improving commutation, e.g. equipotential connection
21/24	. . with magnets axially facing the armatures, e.g. hub-type cycle dynamos	23/40	. characterised by the arrangement of the magnet circuits
21/26	. with rotating armatures and stationary magnets	23/405	. . { Machines with a special form of the pole shoes }
21/28	. . with armatures rotating within the magnets	23/42	. . having split poles, i.e. zones for varying reluctance by gaps in poles or by poles with different spacing of the air gap
21/30	. . . having annular armature cores with salient poles (with homopolar co-operation H02K 21/36)	23/44	. . having movable, e.g. turnable, iron parts
21/32	. . . having horse-shoe magnets (with homopolar co-operation H02K 21/36)	23/46	. . having stationary shunts, i.e. magnetic cross flux
21/325 { with the axis of the rotating armature perpendicular to the plane of the magnet }	23/48	. . having adjustable armatures
21/34	. . . having bell-shaped or bar-shaped magnets, e.g. for cycle lighting (with homopolar co-operation H02K 21/36)	23/50	. Generators with two or more outputs
21/36	. . . with homopolar co-operation	23/52	. Motors acting also as generators, e.g. starting motors used as generators for ignition or lighting
21/38	. with rotating flux distributors, and armatures and magnets both stationary	23/54	. Disc armature motors or generators
21/40	. . with flux distributors rotating around the magnets and within the armatures	23/56	. Motors or generators having iron cores separated from armature winding
21/42	. . with flux distributors rotating around the armatures and within the magnets	23/58	. Motors or generators without iron cores
21/44	. . with armature windings wound upon the magnets	23/60	. Motors or generators having rotating armatures and rotating excitation field
21/46	. Motors having additional short-circuited winding for starting as an asynchronous motor	23/62	. Motors or generators with stationary armatures and rotating excitation field
21/48	. Generators with two or more outputs	23/64	. Motors specially adapted for running on DC or AC by choice
23/00	DC commutator motors or generators having mechanical commutator; Universal AC/DC commutator motors	23/66	. Structural association with auxiliary electric devices influencing the characteristic of, or controlling, the machine, e.g. with impedances or switches
23/02	. characterised by arrangement for exciting	23/68	. Structural association with auxiliary mechanical devices, e.g. with clutches or brakes
23/023	. . { having short-circuited brushes }	24/00	Machines adapted for the instantaneous transmission or reception of the angular displacement of rotating parts, e.g. synchro, selsyn
23/026	. . { having an irregular distribution of the exciting winding or of the excitation over the poles }	25/00	DC interrupter motors or generators
		26/00	Machines adapted to function as torque motors, i.e. to exert a torque when stalled

27/00	AC commutator motors or generators having mechanical commutator	33/14	<ul style="list-style-type: none"> wherein the alternate energisation and de-energisation of the two coil systems are effected or controlled by movement of the armatures
27/02	<ul style="list-style-type: none"> characterised by the armature winding 	33/16	<ul style="list-style-type: none"> with polarised armatures moving in alternate directions by reversal or energisation of a single coil system
27/04	<ul style="list-style-type: none"> having single-phase operation in series or shunt connection 	33/18	<ul style="list-style-type: none"> with coil systems moving upon intermittent or reversed energisation thereof by interaction with a fixed field system, e.g. permanent magnets
27/06	<ul style="list-style-type: none"> with a single or multiple short-circuited commutator, e.g. repulsion motor 	35/00	Generators with reciprocating, oscillating or vibrating coil system, magnet, armature or other part of the magnetic circuit (arrangements for handling mechanical energy structurally associated with generators H02K 7/00, e.g. H02K 7/06)
27/08	<ul style="list-style-type: none"> with multiple-fed armature 	35/02	<ul style="list-style-type: none"> with moving magnets and stationary coil systems
27/10	<ul style="list-style-type: none"> with switching devices for different modes of operation, e.g. repulsion-induction motor 	35/04	<ul style="list-style-type: none"> with moving coil systems and stationary magnets
27/12	<ul style="list-style-type: none"> having multi-phase operation 	35/06	<ul style="list-style-type: none"> with moving flux distributors, and both coil systems and magnets stationary
27/14	<ul style="list-style-type: none"> in series connection 	37/00	Motors with rotor rotating step by step and without interrupter or commutator driven by the rotor, e.g. stepping motors
27/16	<ul style="list-style-type: none"> in shunt connection with stator feeding 	37/02	<ul style="list-style-type: none"> of variable reluctance type
27/18	<ul style="list-style-type: none"> in shunt connection with rotor feeding 	37/04	<ul style="list-style-type: none"> with rotors situated within the stators
27/20	<ul style="list-style-type: none"> Structural association with a speed regulating device 	37/06	<ul style="list-style-type: none"> with rotors situated around the stators
27/22	<ul style="list-style-type: none"> having means for improving commutation, e.g. auxiliary fields, double windings, double brushes 	37/08	<ul style="list-style-type: none"> with rotors axially facing the stators
27/24	<ul style="list-style-type: none"> having two or more commutators 	37/10	<ul style="list-style-type: none"> of permanent magnet type (H02K 37/02 takes precedence)
27/26	<ul style="list-style-type: none"> having disc armature 	37/12	<ul style="list-style-type: none"> with stationary armatures and rotating magnets
27/28	<ul style="list-style-type: none"> Structural association with auxiliary electric devices influencing the characteristic of the machine or controlling the machine 	37/125	<ul style="list-style-type: none"> {Magnet axially facing armature}
27/30	<ul style="list-style-type: none"> Structural association with auxiliary mechanical devices, e.g. with clutches or brakes 	37/14	<ul style="list-style-type: none"> with magnets rotating within the armatures
29/00	Motors or generators having non-mechanical commutating devices, e.g. discharge tubes or semiconductor devices	37/16	<ul style="list-style-type: none"> having horseshoe armature cores
29/03	<ul style="list-style-type: none"> with a magnetic circuit specially adapted for avoiding torque ripples or self-starting problems 	37/18	<ul style="list-style-type: none"> of homopolar type
29/06	<ul style="list-style-type: none"> with position sensing devices (H02K 29/03 takes precedence) 	37/20	<ul style="list-style-type: none"> with rotating flux distributors, the armatures and magnets both being stationary
29/08	<ul style="list-style-type: none"> using magnetic effect devices, e.g. Hall-plates, magneto-resistors (H02K 29/12 takes precedence) 	37/22	<ul style="list-style-type: none"> Damping units
29/10	<ul style="list-style-type: none"> using light effect devices 	37/24	<ul style="list-style-type: none"> Structural association with auxiliary mechanical devices
29/12	<ul style="list-style-type: none"> using detecting coils {using the machine windings as detecting coil} 	39/00	Generators specially adapted for producing a desired non-sinusoidal waveform
29/14	<ul style="list-style-type: none"> with speed sensing devices (H02K 29/03 takes precedence) 	41/00	Propulsion systems in which a rigid body is moved along a path due to dynamo-electric interaction between the body and a magnetic field travelling along the path {(electromagnetic launchers F41B 6/00)}
31/00	Acyclic motors or generators, i.e. DC machines having drum or disc armatures with continuous current collectors	41/02	<ul style="list-style-type: none"> Linear motors; Sectional motors
31/02	<ul style="list-style-type: none"> with solid-contact collectors 	41/025	<ul style="list-style-type: none"> Asynchronous motors
31/04	<ul style="list-style-type: none"> with at least one liquid-contact collector 	41/03	<ul style="list-style-type: none"> Synchronous motors; Motors moving step by step; Reluctance motors (H02K 41/035 takes precedence)
33/00	Motors with reciprocating, oscillating or vibrating magnet, armature or coil system (arrangements for handling mechanical energy structurally associated with motors H02K 7/00, e.g. H02K 7/06)	41/031	<ul style="list-style-type: none"> {of the permanent magnet type}
33/02	<ul style="list-style-type: none"> with armatures moved one way by energisation of a single coil system and returned by mechanical force, e.g. by springs 	41/033	<ul style="list-style-type: none"> {with armature and magnets on one member, the other member being a flux distributor}
33/04	<ul style="list-style-type: none"> wherein the frequency of operation is determined by the frequency of uninterrupted AC energisation 	41/035	<ul style="list-style-type: none"> DC motors; Unipolar motors
33/06	<ul style="list-style-type: none"> with polarised armatures 	41/0352	<ul style="list-style-type: none"> {Unipolar motors}
33/08	<ul style="list-style-type: none"> with DC energisation superimposed on AC energisation 	41/0354	<ul style="list-style-type: none"> {Lorentz force motors, e.g. voice coil motors}
33/10	<ul style="list-style-type: none"> wherein the alternate energisation and de-energisation of the single coil system is effected or controlled by movement of the armatures 	41/0356	<ul style="list-style-type: none"> {moving along a straight path}
33/12	<ul style="list-style-type: none"> with armatures moving in alternate directions by alternate energisation of two coil systems 	41/0358	<ul style="list-style-type: none"> {moving along a curvilinear path}

- 41/06 . Rolling motors, i.e. motors having the rotor axis parallel to the stator axis and following a circular path as the rotor rolls around the inside or outside of the stator {; Nutating motors, i.e. having the rotor axis parallel to the stator axis inclined with respect to the stator axis and performing a nutational movement as the rotor rolls on the stator}
- 41/065 . . {Nutating motors}
- 44/00 Machines in which the dynamo-electric interaction between a plasma or flow of conductive liquid or of fluid-borne conductive or magnetic particles and a coil system or magnetic field converts energy of mass flow into electrical energy or vice versa**
- 44/02 . Electrodynamic pumps
- 44/04 . . Conduction pumps
- 44/06 . . Induction pumps
- 44/08 . Magnetohydrodynamic [MHD] generators
- 44/085 . . {with conducting liquids}
- 44/10 . . Constructional details of electrodes
- 44/12 . . Constructional details of fluid channels
- 44/14 . . . Circular or screw-shaped channels
- 44/16 . . Constructional details of the magnetic circuits
- 44/18 . . for generating AC power
- 44/20 . . . by changing the polarity of the magnetic field
- 44/22 . . . by changing the conductivity of the fluid
- 44/24 . . . by reversing the direction of fluid
- 44/26 . . . by creating a travelling magnetic field
- 44/28 . Association of MHD generators with conventional generators (nuclear power plants including a MHD generator G21D 7/02)
- 47/00 Dynamo-electric converters**
- 47/02 . AC/DC converters or vice versa
- 47/04 . . Motor/generators
- 47/06 . . Cascade converters
- 47/08 . . Single-armature converters
- 47/10 . . . with booster machines on the AC side
- 47/12 . DC/DC converters
- 47/14 . . Motor/generators
- 47/16 . . Single-armature converters, e.g. metadyne
- 47/18 . AC/AC converters
- 47/20 . . Motor/generators
- 47/22 . . Single-armature frequency converters with or without phase-number conversion
- 47/24 . . . having windings for different numbers of poles
- 47/26 . . . operating as under- or over-synchronously running asynchronous induction machines, e.g. cascade arrangement of asynchronous and synchronous machines
- 47/28 . . . operating as commutator machines with added slip-rings
- 47/30 . . Single-armature phase-number converters without frequency conversion
- 49/00 Dynamo-electric clutches; Dynamo-electric brakes**
- 49/02 . of the asynchronous induction type
- 49/04 . . of the eddy-current hysteresis type
- 49/043 . . . {with a radial airgap}
- 49/046 . . . {with an axial airgap}
- 49/06 . of the synchronous type (H02K 49/10 takes precedence)
- 49/065 . . {hysteresis type}
- 49/08 . of the collector armature type
- 49/10 . of the permanent-magnet type
- 49/102 . . {Magnetic gearings, i.e. assembly of gears, linear or rotary, by which motion is magnetically transferred without physical contact (magnetized gearings with physical contact F16H 13/12, F16H 49/005)}
- 49/104 . . {Magnetic couplings consisting of only two coaxial rotary elements, i.e. the driving element and the driven element}
- 49/106 . . . {with a radial air gap}
- 49/108 . . . {with an axial air gap}
- 49/12 . of the acyclic type
- 51/00 Dynamo-electric gears, i.e. dynamo-electric means for transmitting mechanical power from a driving shaft to a driven shaft and comprising structurally interrelated motor and generator parts**
- 53/00 Alleged dynamo-electric perpetua mobilia**
- 55/00 Dynamo-electric machines having windings operating at cryogenic temperatures**
- 55/02 . of the synchronous type
- 55/04 . . with rotating field windings
- 55/06 . of the homopolar type
- 99/00 Subject matter not provided for in other groups of this subclass**
- 99/10 . {Generators}
- 99/20 . {Motors}
- 2201/00 Specific aspects not provided for in the other groups of this subclass relating to the magnetic circuits**
- 2201/03 . Machines characterised by aspects of the air-gap between rotor and stator
- 2201/06 . Magnetic cores, or permanent magnets characterised by their skew
- 2201/09 . Magnetic cores comprising laminations characterised by being fastened by caulking
- 2201/12 . Transversal flux machines
- 2201/15 . Sectional machines
- 2201/18 . Machines moving with multiple degrees of freedom
- 2203/00 Specific aspects not provided for in the other groups of this subclass relating to the windings**
- 2203/03 . Machines characterised by the wiring boards, i.e. printed circuit boards or similar structures for connecting the winding terminations
- 2203/06 . Machines characterised by the wiring leads, i.e. conducting wires for connecting the winding terminations
- 2203/09 . Machines characterised by wiring elements other than wires, e.g. bus rings, for connecting the winding terminations
- 2203/12 . Machines characterised by the bobbins for supporting the windings
- 2203/15 . Machines characterised by cable windings, e.g. high-voltage cables, ribbon cables
- 2205/00 Specific aspects not provided for in the other groups of this subclass relating to casings, enclosures, supports**
- 2205/03 . Machines characterised by thrust bearings
- 2205/06 . Machines characterised by means for keeping the brushes in a retracted position during assembly

H02K

- 2205/09 . Machines characterised by drain passages or by venting, breathing or pressure compensating means
- 2205/12 . Machines characterised by means for reducing windage losses or windage noise
- 2207/00 Specific aspects not provided for in the other groups of this subclass relating to arrangements for handling mechanical energy**
- 2207/03 . Tubular motors, i.e. rotary motors mounted inside a tube, e.g. for blinds
- 2209/00 Specific aspects not provided for in the other groups of this subclass relating to systems for cooling or ventilating**
- 2211/00 Specific aspects not provided for in the other groups of this subclass relating to measuring or protective devices or electric components**
- 2211/03 . Machines characterised by circuit boards, e.g. pcb
- 2213/00 Specific aspects, not otherwise provided for and not covered by codes
[H02K 2201/00](#) - [H02K 2211/00](#)**
- 2213/03 . Machines characterised by numerical values, ranges, mathematical expressions or similar information
- 2213/06 . Machines characterised by the presence of fail safe, back up, redundant or other similar emergency arrangements
- 2213/09 . Machines characterised by the presence of elements which are subject to variation, e.g. adjustable bearings, reconfigurable windings, variable pitch ventilators
- 2213/12 . Machines characterised by the modularity of some components
- 2215/00 Specific aspects not provided for in other groups of this subclass relating to methods or apparatus specially adapted for manufacturing, assembling, maintaining or repairing of dynamo-electric machines**