

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F15 FLUID-PRESSURE ACTUATORS; HYDRAULICS OR PNEUMATICS IN GENERAL

F15B SYSTEMS ACTING BY MEANS OF FLUIDS IN GENERAL; FLUID-PRESSURE ACTUATORS, e.g. SERVOMOTORS; DETAILS OF FLUID-PRESSURE SYSTEMS, NOT OTHERWISE PROVIDED FOR

NOTE

In this subclass, the following terms are used with the meaning stated:

- "Telemotor" means a system or device in which a substantially constant amount of fluid is trapped between an input member and an output member to act as a fluid link;
- "Servomotor" means a fluid-pressure actuator, e.g. a piston and cylinder, directly controlled by a valve or other device which is responsive to operation of an initial controlling member; "Servomotor" does not cover a telemotor. The initial controlling member may be adjacent to the servomotor or at a distance, and may be, for example a hand lever.

1/00 Installations or systems with accumulators; Supply reservoir or sump assemblies

- 1/02 . Installations or systems with accumulators
- 1/021 . . {used for damping}
- 1/022 . . {used as an emergency power source, e.g. in case of pump failure}
- 1/024 . . {used as a supplementary power source, e.g. to store energy in idle periods to balance pump load}
- 1/025 . . {used for thermal compensation, e.g. to collect expanded fluid and to return it to the system as the system fluid cools down}
- 1/027 . . having accumulator charging devices
- 1/0275 . . . {with two or more pilot valves, e.g. for independent setting of the cut-in and cut-out pressures}
- 1/033 . . . with electrical control means
- 1/04 . . Accumulators
- 1/045 . . . {Dead weight accumulators}
- 1/08 . . . using a gas cushion; Gas charging devices; Indicators or floats therefor
- 1/083 {the accumulator having a fusible plug}
- 1/086 {the gas cushion being entirely enclosed by the separating means, e.g. foam or gas-filled balls}
- 1/10 with flexible separating means
- 1/103 {the separating means being bellows}
- 1/106 {characterised by the way housing components are assembled}
- 1/12 attached at their periphery (flexible separating means in the form of a tube [F15B 1/16](#))
- 1/125 {characterised by the attachment means ([F15B 1/14](#) takes precedence)}
- 1/14 by means of a rigid annular supporting member
- 1/16 in the form of a tube
- 1/165 {in the form of a bladder}
- 1/18 Anti-extrusion means

- 1/20 fixed to the separating means
- 1/22 Liquid port constructions
- 1/24 with rigid separating means, e.g. pistons
- 1/26 . Supply reservoir or sump assemblies
- 1/265 . . {with pressurised main reservoir}

3/00 Intensifiers or fluid-pressure converters, e.g. pressure exchangers; Conveying pressure from one fluid system to another, without contact between the fluids {[\(fluid-driven pumps F04B 9/08\)](#)}

5/00 Transducers converting variations of physical quantities, e.g. expressed by variations in positions of members, into fluid-pressure variations or vice versa; Varying fluid pressure as a function of variations of a plurality of fluid pressures or variations of other quantities ([F15B 9/00](#) takes precedence)

- 5/003 . {characterised by variation of the pressure in a nozzle or the like, e.g. nozzle-flapper system}
- 5/006 . {with electrical means, e.g. electropneumatic transducer ([F15B 5/003](#) takes precedence)}

Fluid-pressure actuator systems (systems peculiar to the control of a particular machine or apparatus covered in a single other class, see the class for such machine or apparatus)

NOTE

This heading relates to moving members into one or more definite positions by means of fluid pressure. Pump, motor and control features so far as not peculiar to this purpose are classified in the relevant classes.

7/00 Systems in which the movement produced is definitely related to the output of a volumetric pump; Telemotors

- 7/001 . {With multiple inputs, e.g. for dual control}
- 7/003 . {with multiple outputs}
- 7/005 . {With rotary or crank input}
- 7/006 . . {Rotary pump input}
- 7/008 . {with rotary output}

| | | | |
|--------------|--|---------|--|
| 7/02 | • Systems with continuously-operating input and output apparatus | 11/036 | • • • by means of servomotors having a plurality of working chambers |
| 7/04 | • In which the ratio between pump stroke and motor stroke varies with the resistance against the motor | 11/0365 | • • • • {Tandem constructions} |
| 7/06 | • Details (F15B 15/00 takes precedence) | 11/04 | • • for controlling the speed (F15B 11/024 takes precedence) |
| 7/08 | • • Input units; Master units | 11/0406 | • • • {during starting or stopping (F15B 11/048 takes precedence)} |
| 7/10 | • • Compensation of the liquid content in a system (F15B 7/08 takes precedence) | 11/0413 | • • • {in one direction only, with no control in the reverse direction, e.g. check valve in parallel with a throttle valve} |
| 9/00 | Servomotors with follow-up action, {e.g. obtained by feed-back control,} i.e. in which the position of the actuated member conforms with that of the controlling member | 11/042 | • • • by means in the feed line {, i.e. "meter in"} (F15B 11/046, F15B 11/05 take precedence) |
| 9/02 | • with servomotors of the reciprocable or oscillatable type | 11/0423 | • • • • {by controlling pump output or bypass, other than to maintain constant speed} |
| 9/03 | • • with electrical control means {(F15B 9/07, F15B 9/09, F15B 9/17 take precedence)} | 11/0426 | • • • • {by controlling the number of pumps or parallel valves switched on} |
| 9/04 | • • controlled by varying the output of a pump with variable capacity | 11/044 | • • • by means in the return line {, i.e. "meter out"} (F15B 11/046, F15B 11/05 take precedence) |
| 9/06 | • • controlled by means using a fluid jet | 11/0445 | • • • • {with counterbalance valves, e.g. to prevent overrunning or for braking} |
| 9/07 | • • • with electrical control means | 11/046 | • • • depending on the position of the working member |
| 9/08 | • • controlled by valves affecting the fluid feed or the fluid outlet of the servomotor (F15B 9/06 takes precedence) | 11/048 | • • • • with deceleration control |
| 9/09 | • • • with electrical control means | 11/05 | • • • specially adapted to maintain constant speed, e.g. pressure-compensated, load-responsive {(F15B 11/161 takes precedence)} |
| 9/10 | • • • in which the controlling element and the servomotor each controls a separate member, these members influencing different fluid passages or the same passage | 11/055 | • • • • {by adjusting the pump output or bypass} |
| 9/12 | • • • in which both the controlling element and the servomotor control the same member influencing a fluid passage and are connected to that member by means of a differential gearing | 11/06 | • involving features specific to the use of a compressible medium, e.g. air, steam |
| 9/14 | • with rotary servomotors | 11/064 | • • with devices for saving the compressible medium |
| 9/16 | • Systems essentially having two or more interacting servomotors {, e.g. multi-stage (F15B 18/00, F15B 20/00 take precedence)} | 11/068 | • • with valves for gradually putting pneumatic systems under pressure |
| 9/17 | • • with electrical control means | 11/072 | • • Combined pneumatic-hydraulic systems (F15B 11/032 takes precedence) |
| 11/00 | Servomotor systems without provision for follow-up action; {Circuits therefor} (F15B 3/00 takes precedence) | 11/0725 | • • • {with the driving energy being derived from a pneumatic system, a subsequent hydraulic system displacing or controlling the output element} |
| 11/003 | • {Systems with load-holding valves} | 11/076 | • • • with pneumatic drive or displacement and speed control or stopping by hydraulic braking |
| 11/006 | • {Hydraulic "Wheatstone bridge" circuits, i.e. with four nodes, P-A-T-B, and on-off or proportional valves in each link} | 11/08 | • with only one servomotor |
| 11/02 | • Systems essentially incorporating special features for controlling the speed or actuating force of an output member | 11/10 | • • in which the servomotor position is a function of the pressure {also pressure regulators as operating means for such systems, the device itself may be a position indicating system} |
| 11/022 | • • {in which a rapid approach stroke is followed by a slower, high-force working stroke (F15B 11/0325 takes precedence)} | 11/12 | • • providing distinct intermediate positions; with step-by-step action |
| 11/024 | • • by means of differential connection of the servomotor lines, e.g. regenerative circuits | 11/121 | • • • {providing distinct intermediate positions (F15B 11/13 takes precedence)} |
| 2011/0243 | • • • {the regenerative circuit being activated or deactivated automatically} | 11/122 | • • • • {by means of actuators with multiple stops} |
| 2011/0246 | • • • {with variable regeneration flow} | 11/123 | • • • • {by means of actuators with fluid-operated stops} |
| 11/028 | • • for controlling the actuating force (F15B 11/024 takes precedence) | 11/125 | • • • • {by means of digital actuators, i.e. actuators in which the total stroke is the sum of individual strokes} |
| 11/032 | • • • by means of fluid-pressure converters | 11/126 | • • • • {by means of actuators of the standard type with special circuit controlling means (F15B 11/125 takes precedence)} |
| 11/0325 | • • • • {the fluid-pressure converter increasing the working force after an approach stroke} | 11/127 | • • • • {with step-by-step action} |
| | | 11/128 | • • • • {by means of actuators of the standard type with special circuit controlling means} |

| | | | |
|--------------|--|-----------|--|
| 11/13 | . . . using {separate dosing} chambers of predetermined volume | 13/0401 | . . . { Valve members; Fluid interconnections therefor} |
| 11/15 | . . with special provision for automatic return | 13/0402 | . . . {for linearly sliding valves, e.g. spool valves} |
| 11/16 | . with two or more servomotors | 13/0403 | {a secondary valve member sliding within the main spool, e.g. for regeneration flow (F15B 13/0418 takes precedence)} |
| 11/161 | . . {with sensing of servomotor demand or load} | 13/0405 | {for seat valves, i.e. poppet valves} |
| 11/162 | . . . {for giving priority to particular servomotors or users} | 13/0406 | {for rotary valves} |
| 11/163 | . . . {for sharing the pump output equally amongst users or groups of users, e.g. using anti-saturation, pressure compensation} | 13/0407 | {Means for damping the valve member movement} |
| 11/165 | . . . {for adjusting the pump output or bypass in response to demand} | 2013/0409 | {Position sensing or feedback of the valve member} |
| 11/166 | . . . {Controlling a pilot pressure in response to the load, i.e. supply to at least one user is regulated by adjusting either the system pilot pressure or one or more of the individual pilot command pressures} | 2013/041 | {with two positions} |
| 11/167 | . . . {using pilot pressure to sense the demand} | 2013/0412 | {with three positions} |
| 11/168 | . . . {with an isolator valve (duplicating valve), i.e. at least one load sense [LS] pressure is derived from a work port load sense pressure but is not a work port pressure itself} | 2013/0413 | {with four or more positions} |
| 11/17 | . . using two or more pumps | 2013/0414 | {Dosing devices} |
| 11/18 | . . used in combination for obtaining stepwise operation of a single controlled member | 13/0416 | . . . {with means or adapted for load sensing} |
| 11/183 | . . . {Linear stepwise operation} | 13/0417 | {Load sensing elements; Internal fluid connections therefor; Anti-saturation or pressure-compensation valves} |
| 11/186 | . . . {Rotary stepwise operation} | 13/0418 | {Load sensing elements sliding within a hollow main valve spool} |
| 11/20 | . . controlling several interacting or sequentially-operating members | 13/042 | . . . operated by fluid pressure {(F15B 13/0401, F15B 13/0416 take precedence)} |
| 11/205 | . . . {the position of the actuator controlling the fluid flow to the subsequent actuator} | 13/0422 | {with manually-operated pilot valves, e.g. joysticks} |
| 11/22 | . . Synchronisation of the movement of two or more servomotors | 13/0424 | {the joysticks being provided with electrical switches or sensors} |
| 13/00 | Details of servomotor systems ({F15B 1/04, F15B 1/26, F15B 3/00, F15B 7/08, F15B 11/02, F15B 11/10,} F15B 15/00 take precedence){; Valves for servomotor systems} | 13/0426 | {with fluid-operated pilot valves, i.e. multiple stage valves} |
| 2013/002 | . {Modular valves, i.e. consisting of an assembly of interchangeable components} | 2013/0428 | {with switchable internal or external pilot pressure source} |
| 2013/004 | . . {Cartridge valves} | 13/043 | with electrically-controlled pilot valves |
| 2013/006 | . . {Modular components with multiple uses, e.g. kits for either normally-open or normally-closed valves, interchangeable or reprogrammable manifolds} | 13/0431 | {the electrical control resulting in an on-off function} |
| 2013/008 | . {Throttling member profiles} | 13/0433 | {the pilot valves being pressure control valves (F15B 13/0435, F15B 13/0436, F15B 13/0438 take precedence)} |
| 13/01 | . Locking-valves or other detent {i.e. load-holding} devices | 13/0435 | {the pilot valves being sliding valves} |
| 13/015 | . . {using an enclosed pilot flow valve} | 13/0436 | {the pilot valves being of the steerable jet type} |
| 13/02 | . Fluid distribution or supply devices characterised by their adaptation to the control of servomotors | 13/0438 | {the pilot valves being of the nozzle-flapper type} |
| 13/021 | . . {Valves for interconnecting the fluid chambers of an actuator} | 13/044 | . . . operated by electrically-controlled means, e.g. solenoids, torque-motors |
| 13/022 | . . {Flow-dividers; Priority valves} | 13/0442 | {with proportional solenoid allowing stable intermediate positions} |
| 13/023 | . . {Excess flow valves, e.g. for locking cylinders in case of hose burst} | 13/0444 | {with rotary electric motor} |
| 13/024 | . . {Pressure relief valves} | 13/0446 | {with moving coil, e.g. voice coil} |
| 13/025 | . . {Pressure reducing valves} | 2013/0448 | {Actuation by solenoid and permanent magnet} |
| 13/026 | . . {Pressure compensating valves} | 13/06 | . . for use with two or more servomotors |
| 13/027 | . . {Check valves} | 13/07 | . . . in distinct sequence |
| 13/028 | . . {Shuttle valves} | 13/08 | . . . Assemblies of units, each for the control of a single servomotor only |
| 13/029 | . . {Counterbalance valves} | 13/0803 | {Modular units} |
| 13/04 | . . for use with a single servomotor | 13/0807 | {Manifolds} |
| | | 13/081 | {Laminated constructions} |
| | | 13/0814 | {Monoblock manifolds} |
| | | 13/0817 | {Multiblock manifolds} |
| | | 13/0821 | {Attachment or sealing of modular units to each other} |

| | | | |
|--------------|---|-----------|---|
| 13/0825 | {the modular elements being mounted on a common member, e.g. on a rail} | 15/103 | . . . {using inflatable bodies that contract when fluid pressure is applied, e.g. pneumatic artificial muscles or McKibben-type actuators} |
| 13/0828 | {characterised by sealing means of the modular units} | 15/106 | . . . {the motor being of the pinching-roller type} |
| 13/0832 | {Modular valves} | 15/12 | . . of the oscillating-vane or curved-cylinder type |
| 13/0835 | {Cartridge type valves} | 15/125 | . . . {of the curved-cylinder type} |
| 13/0839 | {Stacked plate type valves} | 15/14 | . . of the straight-cylinder type |
| 13/0842 | {Monoblock type valves, e.g. with multiple valve spools in a common housing} | 15/1404 | . . . {in clusters, e.g. multiple cylinders in one block} |
| 13/0846 | {Electrical details} | 15/1409 | . . . {with two or more independently movable working pistons} |
| 13/085 | {Electrical controllers} | 15/1414 | . . . {with non-rotatable piston} |
| 13/0853 | {Electric circuit boards} | 15/1419 | {of non-circular cross-section} |
| 13/0857 | {Electrical connecting means, e.g. plugs, sockets} | 15/1423 | . . . {Component parts; Constructional details} |
| 13/086 | {Sensing means, e.g. pressure sensors} | 15/1428 | {Cylinders (F15B 15/1438 takes precedence)} |
| 13/0864 | {Signalling means, e.g. LEDs} | 15/1433 | {End caps (F15B 15/1438 takes precedence)} |
| 13/0867 | {Data bus systems} | 15/1438 | {Cylinder to end cap assemblies} |
| 13/0871 | {Channels for fluid} | 15/1442 | {End cap sealings} |
| 13/0875 | {Channels for electrical components, e.g. for cables or sensors} | 15/1447 | {Pistons; Piston to piston rod assemblies} |
| 13/0878 | {Assembly of modular units} | 15/1452 | {Piston sealings} |
| 13/0882 | {using identical modular elements} | 15/1457 | {Piston rods (F15B 15/1447 takes precedence)} |
| 13/0885 | {using valves combined with other components} | 15/1461 | {Piston rod sealings} |
| 13/0889 | {Valves combined with electrical components} | 15/1466 | {Hollow piston sliding over a stationary rod inside the cylinder} |
| 13/0892 | {Valves combined with fluid components} | 15/1471 | {Guiding means other than in the end cap (F15B 15/1466 takes precedence)} |
| 13/0896 | {using different types or sizes of valves} | 15/1476 | {Special return means} |
| 13/10 | . Special arrangements for operating the actuated device {with or} without using fluid pressure, e.g. for emergency use | 15/148 | {Lost-motion means between the piston and the output} |
| 13/12 | . Special measures for increasing the sensitivity of the system | 15/1485 | {Special measures for cooling or heating} |
| 13/14 | . Special measures for giving the operating person a "feeling" of the response of the actuated device | 15/149 | . . . {Fluid interconnections, e.g. fluid connectors, passages} |
| 13/16 | . Special measures for feedback {, e.g. by a follow-up device} | 2015/1495 | . . . {with screw mechanism attached to the piston} |
| 15/00 | Fluid-actuated devices for displacing a member from one position to another; Gearing associated therewith | 15/16 | . . . of the telescopic type |
| 15/02 | . Mechanical layout characterised by the means for converting the movement of the fluid-actuated element into movement of the finally-operated member | 15/165 | {with synchronisation of sections} |
| 15/04 | . . with oscillating cylinder | 15/17 | . . . of differential-piston type |
| 15/06 | . . for mechanically converting rectilinear movement into non- rectilinear movement | 15/18 | . Combined units comprising both motor and pump |
| 15/061 | . . . {by unidirectional means} | 15/19 | . Pyrotechnical actuators |
| 15/063 | . . . {Actuator having both linear and rotary output, i.e. dual action actuator} | 15/20 | . Other details {, e.g. assembly with regulating devices} |
| 15/065 | . . . {the motor being of the rack-and-pinion type} | 15/202 | . . {Externally-operated valves mounted in or on the actuator} |
| 15/066 | . . . {the motor being of the scotch yoke type} | 15/204 | . . {Control means for piston speed or actuating force without external control, e.g. control valve inside the piston (F15B 11/02 , F15B 15/22 take precedence)} |
| 15/068 | . . . {the motor being of the helical type} | 2015/206 | . . {Combined actuation, e.g. electric and fluid actuated} |
| 15/08 | . Characterised by the construction of the motor unit | 2015/208 | . . {Special fluid pressurisation means, e.g. thermal or electrolytic} |
| 15/082 | . . {the motor being of the slotted cylinder type} | 15/22 | . . for accelerating or decelerating the stroke |
| 15/084 | . . {the motor being of the rodless piston type, e.g. with cable, belt or chain} | 15/221 | . . . {for accelerating the stroke, e.g. by area increase} |
| 15/086 | . . . {with magnetic coupling} | 15/222 | . . . {having a piston with a piston extension or piston recess which throttles the main fluid outlet as the piston approaches its end position} |
| 15/088 | . . {the motor using combined actuation, e.g. electric and fluid actuation} | 15/223 | . . . {having a piston with a piston extension or piston recess which completely seals the main fluid outlet as the piston approaches its end position} |
| 15/10 | . . the motor being of diaphragm type | | |

| | | | |
|--------------|--|----------------|---|
| 15/224 | . . . {having a piston which closes off fluid outlets in the cylinder bore by its own movement} | 20/002 | . {Electrical failure} |
| 15/225 | . . . {with valve stems operated by contact with the piston end face or with the cylinder wall} | 20/004 | . {Fluid pressure supply failure} |
| 15/226 | . . . {having elastic elements, e.g. springs, rubber pads} | 20/005 | . {Leakage; Spillage; Hose burst} |
| 15/227 | . . . {having an auxiliary cushioning piston within the main piston or the cylinder end face} | 20/007 | . {Overload} |
| 15/228 | . . . {having shock absorbers mounted outside the actuator housing} | 20/008 | . {Valve failure} |
| 15/24 | . . for restricting the stroke | 21/00 | Common features of fluid actuator systems; Fluid-pressure actuator systems or details thereof, not covered by any other group of this subclass |
| 15/26 | . . Locking mechanisms | 21/001 | . {Servomotor systems with fluidic control} |
| 15/261 | . . . {using positive interengagement, e.g. balls and grooves, for locking in the end positions} | 21/003 | . {Systems with different interchangeable components, e.g. using preassembled kits} |
| 15/262 | . . . {using friction, e.g. brake pads} | 21/005 | . {Filling or draining of fluid systems} |
| 15/264 | {Screw mechanisms attached to the piston} | 21/006 | . {Compensation or avoidance of ambient pressure variation} |
| 15/265 | . . . {specially adapted for rodless pistons or slotted cylinders} | 21/008 | . {Reduction of noise or vibration} |
| 2015/267 | . . . {Manual locking or release} | 21/02 | . Servomotor systems with programme control derived from a store or timing device; Control devices therefor |
| 2015/268 | . . . {Fluid supply for locking or release independent of actuator pressurisation} | 21/04 | . Special measures taken in connection with the properties of the fluid |
| 15/28 | . . Means for indicating the position, e.g. end of stroke | 21/041 | . . Removal or measurement of solid or liquid contamination, e.g. filtering |
| 15/2807 | . . . {Position switches, i.e. means for sensing of discrete positions only, e.g. limit switches} | 21/042 | . . Controlling the temperature of the fluid |
| 15/2815 | . . . {Position sensing, i.e. means for continuous measurement of position, e.g. LVDT} | 21/0423 | . . . Cooling |
| 15/2823 | {by a screw mechanism attached to the piston} | 21/0427 | . . . Heating |
| 15/283 | {using a cable wrapped on a drum and attached to the piston} | 21/044 | . . Removal or measurement of undissolved gas, e.g. de-aeration, venting or bleeding |
| 15/2838 | {with out using position sensors, e.g. by volume flow measurement or pump speed} | 21/045 | . . Compensating for variations in viscosity or temperature |
| 15/2846 | {using detection of markings, e.g. markings on the piston rod} | 21/047 | . . Preventing foaming, churning or cavitation |
| 15/2853 | {using potentiometers} | 21/048 | . . Arrangements for compressed air preparation, e.g. comprising air driers, air condensers, filters, lubricators or pressure regulators |
| 15/2861 | {using magnetic means} | 21/06 | . Use of special fluids, e.g. liquid metal; Special adaptations of fluid-pressure systems, or control of elements therefor, to the use of such fluids |
| 15/2869 | {using electromagnetic radiation, e.g. radar or microwaves} | 21/065 | . . {Use of electro- or magnetosensitive fluids, e.g. electrorheological fluid} |
| 15/2876 | {using optical means, e.g. laser} | 21/08 | . Servomotor systems incorporating electrically operated control means (F15B 21/02 , F15B 21/065 take precedence) |
| 15/2884 | {using sound, e.g. ultrasound} | 21/082 | . . {with different modes} |
| 15/2892 | . . . {characterised by the attachment means} | 21/085 | . . {using a data bus, e.g. "CANBUS"} |
| 17/00 | Combinations of telemotor and servomotor systems | 21/087 | . . {Control strategy, e.g. with block diagram} |
| 17/02 | . in which a telemotor operates the control member of a servomotor | 21/10 | . Delay devices or arrangements |
| 18/00 | Parallel arrangements of independent servomotor systems | 21/12 | . Fluid oscillators or pulse generators |
| 19/00 | Testing; {Calibrating; Fault detection or monitoring; Simulation or modelling of} fluid-pressure systems or apparatus not otherwise provided for | 21/125 | . . {by means of a rotating valve} |
| 19/002 | . {Calibrating} | 21/14 | . Energy-recuperation means |
| 19/005 | . {Fault detection or monitoring} | 2201/00 | Accumulators |
| 19/007 | . {Simulation or modelling} | 2201/20 | . Accumulator cushioning means |
| 20/00 | Safety arrangements for fluid actuator systems; Applications of safety devices in fluid actuator systems; Emergency measures for fluid actuator systems | 2201/205 | . . using gas |
| 20/001 | . {Double valve requiring the use of both hands simultaneously} | 2201/21 | . . using springs |
| | | 2201/215 | . . using weights |
| | | 2201/22 | . . using elastic housings |
| | | 2201/30 | . Accumulator separating means |
| | | 2201/305 | . . without separating means |
| | | 2201/31 | . . having rigid separating means, e.g. pistons |
| | | 2201/312 | . . . Sealings therefor, e.g. piston rings |
| | | 2201/315 | . . having flexible separating means |
| | | 2201/3151 | . . . the flexible separating means being diaphragms or membranes |
| | | 2201/3152 | . . . the flexible separating means being bladders |

| | | | |
|----------------|--|------------|--|
| 2201/3153 | . . . the flexible separating means being bellows | 2211/216 | . . . the pressure sources being pneumatic-to-hydraulic converters |
| 2201/3154 | . . . the flexible separating means being completely enclosed, e.g. using gas-filled balls or foam | 2211/218 | . . . the pressure sources being pyrotechnical charges |
| 2201/3155 | . . . characterised by the material of the flexible separating means | 2211/25 | . . Pressure control functions |
| 2201/3156 | . . . characterised by their attachment | 2211/251 | . . . High pressure control |
| 2201/3157 | . . . Sealings for the flexible separating means | 2211/252 | . . . Low pressure control |
| 2201/3158 | . . . Guides for the flexible separating means, e.g. for a collapsed bladder | 2211/253 | . . . Pressure margin control, e.g. pump pressure in relation to load pressure |
| 2201/32 | . . having multiple separating means, e.g. with an auxiliary piston sliding within a main piston, multiple membranes or combinations thereof | 2211/255 | . . Flow control functions |
| 2201/40 | . Constructional details of accumulators not otherwise provided for | 2211/26 | . . Power control functions |
| 2201/405 | . . Housings | 2211/265 | . . Control of multiple pressure sources |
| 2201/4053 | . . . characterised by the material | 2211/2652 | . . . without priority |
| 2201/4056 | . . . characterised by the attachment of housing components | 2211/2654 | . . . one or more pressure sources having priority |
| 2201/41 | . . Liquid ports | 2211/2656 | . . . by control of the pumps |
| 2201/411 | . . . having valve means | 2211/2658 | . . . by control of the prime movers |
| 2201/413 | . . . having multiple liquid ports | 2211/27 | . . Directional control by means of the pressure source |
| 2201/415 | . . Gas ports | 2211/275 | . . Control of the prime mover, e.g. hydraulic control |
| 2201/4155 | . . . having valve means | 2211/30 | . Directional control |
| 2201/42 | . . Heat recuperators for isothermal compression and expansion | 2211/305 | . . characterised by the type of valves |
| 2201/43 | . . Anti-extrusion means | 2211/30505 | . . . Non-return valves, i.e. check valves |
| 2201/435 | . . . being fixed to the separating means | 2211/3051 | Cross-check valves |
| 2201/50 | . Monitoring, detection and testing means for accumulators | 2211/30515 | Load holding valves |
| 2201/505 | . . Testing of accumulators, e.g. for testing tightness | 2211/3052 | . . . Shuttle valves |
| 2201/51 | . . Pressure detection | 2211/30525 | . . . Directional control valves, e.g. 4/3-directional control valve |
| 2201/515 | . . Position detection for separating means | 2211/3053 | In combination with a pressure compensating valve |
| 2201/60 | . Assembling or methods for making accumulators | 2211/30535 | the pressure compensating valve is arranged between pressure source and directional control valve |
| 2201/605 | . . Assembling or methods for making housings therefor | 2211/3054 | the pressure compensating valve is arranged between directional control valve and output member |
| 2201/61 | . . Assembling or methods for making separating means therefor | 2211/30545 | the pressure compensating valve is arranged between output member and directional control valve |
| 2201/615 | . . Assembling or methods for making ports therefor | 2211/3055 | the pressure compensating valve is arranged between directional control valve and return line |
| 2211/00 | Circuits for servomotor systems | 2211/30555 | Inlet and outlet of the pressure compensating valve being connected to the directional control valve |
| 2211/20 | . Fluid pressure source, e.g. accumulator or variable axial piston pump | 2211/3056 | . . . Assemblies of multiple valves |
| 2211/205 | . . Systems with pumps | 2211/30565 | having multiple valves for a single output member, e.g. for creating higher valve function by use of multiple valves like two 2/2-valves replacing a 5/3-valve |
| 2211/20507 | . . . Type of prime mover | 2211/3057 | having two valves, one for each port of a double-acting output member |
| 2211/20515 | Electric motor | 2211/30575 | in a Wheatstone Bridge arrangement (also half bridges) |
| 2211/20523 | Internal combustion engine | 2211/3058 | having additional valves for interconnecting the fluid chambers of a double-acting actuator, e.g. for regeneration mode or for floating mode (directional control valves having a regenerative position F15B 2211/3133 ; directional control valves having a floating position F15B 2211/3127) |
| 2211/2053 | Type of pump | 2211/30585 | having a single valve for multiple output members |
| 2211/20538 | constant capacity | | |
| 2211/20546 | variable capacity | | |
| 2211/20553 | with pilot circuit, e.g. for controlling a swash plate | | |
| 2211/20561 | reversible | | |
| 2211/20569 | capable of working as pump and motor | | |
| 2211/20576 | with multiple pumps | | |
| 2211/20584 | Combinations of pumps with high and low capacity | | |
| 2211/20592 | Combinations of pumps for supplying high and low pressure | | |
| 2211/21 | . . Systems with pressure sources other than pumps, e.g. with a pyrotechnical charge | | |
| 2211/212 | . . . the pressure sources being accumulators | | |
| 2211/214 | . . . the pressure sources being hydrotransformers | | |

| | | | | | |
|------------|-----------|---|------------|-----------|--|
| 2211/3059 | | having multiple valves for multiple output members | 2211/328 | | with signal modulation, e.g. pulse width modulation [PWM] |
| 2211/30595 | | with additional valves between the groups of valves for multiple output members | 2211/329 | . . . | actuated by fluid pressure |
| 2211/31 | . . | characterised by the positions of the valve element | 2211/35 | . . | Directional control combined with flow control |
| 2211/3105 | . . . | Neutral or centre positions | 2211/351 | . . . | Flow control by regulating means in feed line, i.e. meter-in control |
| 2211/3111 | | the pump port being closed in the centre position, e.g. so-called closed centre | 2211/353 | . . . | Flow control by regulating means in return line, i.e. meter-out control |
| 2211/3116 | | the pump port being open in the centre position, e.g. so-called open centre | 2211/355 | . . | Pilot pressure control |
| 2211/3122 | . . . | Special positions other than the pump port being connected to working ports or the working ports being connected to the return line | 2211/36 | . . | Pilot pressure sensing |
| 2211/3127 | | Floating position connecting the working ports and the return line | 2211/365 | . . | Directional control combined with flow control and pressure control |
| 2211/3133 | | Regenerative position connecting the working ports or connecting the working ports to the pump, e.g. for high-speed approach stroke | 2211/40 | . . | Flow control |
| 2211/3138 | . . . | the positions being discrete | 2211/405 | . . | characterised by the type of flow control means or valve |
| 2211/3144 | . . . | the positions being continuously variable, e.g. as realised by proportional valves | 2211/40507 | . . . | with constant throttles or orifices |
| 2211/315 | . . | characterised by the connections of the valve or valves in the circuit | 2211/40515 | . . . | with variable throttles or orifices |
| 2211/31505 | . . . | being connected to a pressure source and a return line | 2211/40523 | . . . | with flow dividers |
| 2211/31511 | | having a single pressure source | 2211/4053 | | using valves |
| 2211/31517 | | having multiple pressure sources | 2211/40538 | | using volumetric pumps or motors |
| 2211/31523 | . . . | being connected to a pressure source and an output member | 2211/40546 | . . . | with flow combiners |
| 2211/31529 | | having a single pressure source and a single output member | 2211/40553 | . . . | with pressure compensating valves |
| 2211/31535 | | having multiple pressure sources and a single output member | 2211/40561 | | the pressure compensating valve arranged upstream of the flow control means |
| 2211/31541 | | having a single pressure source and multiple output members | 2211/40569 | | the pressure compensating valve arranged downstream of the flow control means |
| 2211/31547 | | having multiple pressure sources and multiple output members | 2211/40576 | . . . | Assemblies of multiple valves |
| 2211/31552 | . . . | being connected to an output member and a return line | 2211/40584 | | the flow control means arranged in parallel with a check valve |
| 2211/31558 | | having a single output member | 2211/40592 | | with multiple valves in parallel flow paths, |
| 2211/31564 | | having multiple output members | 2211/41 | . . | characterised by the positions of the valve element |
| 2211/3157 | . . . | being connected to a pressure source, an output member and a return line | 2211/411 | . . . | the positions being discrete |
| 2211/31576 | | having a single pressure source and a single output member | 2211/413 | . . . | the positions being continuously variable, e.g. as realised by proportional valves |
| 2211/31582 | | having multiple pressure sources and a single output member | 2211/415 | . . | characterised by the connections of the flow control means in the circuit |
| 2211/31588 | | having a single pressure source and multiple output members | 2211/41509 | . . . | being connected to a pressure source and a directional control valve |
| 2211/31594 | | having multiple pressure sources and multiple output members | 2211/41518 | | being connected to multiple pressure sources |
| 2211/32 | . . | characterised by the type of actuation | 2211/41527 | . . . | being connected to an output member and a directional control valve |
| 2211/321 | . . . | mechanically | 2211/41536 | | being connected to multiple ports of an output member |
| 2211/322 | | actuated by biasing means, e.g. spring-actuated | 2211/41545 | | being connected to multiple output members |
| 2211/323 | | the biasing means being adjustable | 2211/41554 | . . . | being connected to a return line and a directional control valve |
| 2211/324 | | manually, e.g. by using a lever or pedal | 2211/41563 | . . . | being connected to a pressure source and a return line |
| 2211/325 | | actuated by an output member of the circuit | 2211/41572 | . . . | being connected to a pressure source and an output member |
| 2211/326 | | with follow-up action | 2211/41581 | . . . | being connected to an output member and a return line |
| 2211/327 | . . . | electrically or electronically | 2211/4159 | . . . | being connected to a pressure source, an output member and a return line |
| | | | 2211/42 | . . | characterised by the type of actuation |
| | | | 2211/421 | . . . | mechanically |
| | | | 2211/422 | | actuated by biasing means, e.g. spring-actuated |
| | | | 2211/423 | | manually, e.g. by using a lever or pedal |
| | | | 2211/424 | | actuated by an output member of the circuit |
| | | | 2211/425 | | with follow-up action |
| | | | 2211/426 | . . . | electrically or electronically |

| | | | |
|------------|--|-----------|--|
| 2211/427 | with signal modulation, e.g. using pulse width modulation [PWM] | 2211/524 | actuated by an output member of the circuit |
| 2211/428 | actuated by fluid pressure | 2211/525 | with follow-up action |
| 2211/45 | . . Control of bleed-off flow, e.g. control of bypass flow to the return line | 2211/526 | electrically or electronically |
| 2211/455 | . . Control of flow in the feed line, i.e. meter-in control | 2211/527 | with signal modulation, e.g. pulse width modulation [PWM] |
| 2211/46 | . . Control of flow in the return line, i.e. meter-out control | 2211/528 | actuated by fluid pressure |
| 2211/465 | . . Flow control with pressure compensation | 2211/55 | . . for limiting a pressure up to a maximum pressure, e.g. by using a pressure relief valve |
| 2211/47 | . . Flow control in one direction only | 2211/555 | . . for assuring a minimum pressure, e.g. by using a back pressure valve |
| 2211/473 | without restriction in the reverse direction | 2211/56 | . . Control of an upstream pressure |
| 2211/476 | the flow in the reverse direction being blocked | 2211/565 | . . Control of a downstream pressure |
| 2211/50 | . Pressure control | 2211/57 | . . Control of a differential pressure |
| 2211/505 | . . characterised by the type of pressure control means | 2211/575 | . . Pilot pressure control |
| 2211/50509 | the pressure control means controlling a pressure upstream of the pressure control means | 2211/5753 | for closing a valve |
| 2211/50518 | using pressure relief valves | 2211/5756 | for opening a valve |
| 2211/50527 | using cross-pressure relief valves | 2211/60 | . Circuit components or control therefor |
| 2211/50536 | using unloading valves controlling the supply pressure by diverting fluid to the return line | 2211/605 | . . Load sensing circuits |
| 2211/50545 | using braking valves to maintain a back pressure | 2211/6051 | having valve means between output member and the load sensing circuit |
| 2211/50554 | the pressure control means controlling a pressure downstream of the pressure control means, e.g. pressure reducing valve | 2211/6052 | using check valves |
| 2211/50563 | the pressure control means controlling a differential pressure | 2211/6054 | using shuttle valves |
| 2211/50572 | using a pressure compensating valve for controlling the pressure difference across a flow control valve | 2211/6055 | using pressure relief valves |
| 2211/50581 | using counterbalance valves | 2211/6057 | using directional control valves |
| 2211/5059 | using double counterbalance valves | 2211/6058 | with isolator valves |
| 2211/51 | . . characterised by the positions of the valve element | 2211/61 | . . Secondary circuits |
| 2211/511 | the positions being discrete | 2211/611 | Diverting circuits, e.g. for cooling or filtering |
| 2211/513 | the positions being continuously variable, e.g. as realised by proportional valves | 2211/613 | Feeding circuits |
| 2211/515 | . . characterised by the connections of the pressure control means in the circuit | 2211/615 | . . Filtering means |
| 2211/5151 | being connected to a pressure source and a directional control valve | 2211/62 | . . Cooling or heating means |
| 2211/5152 | being connected to multiple pressure sources | 2211/625 | . . Accumulators |
| 2211/5153 | being connected to an output member and a directional control valve | 2211/63 | . . Electronic controllers |
| 2211/5154 | being connected to multiple ports of an output member | 2211/6303 | using input signals |
| 2211/5155 | being connected to multiple output members | 2211/6306 | representing a pressure |
| 2211/5156 | being connected to a return line and a directional control valve | 2211/6309 | the pressure being a pressure source supply pressure |
| 2211/5157 | being connected to a pressure source and a return line | 2211/6313 | the pressure being a load pressure |
| 2211/5158 | being connected to a pressure source and an output member | 2211/6316 | the pressure being a pilot pressure |
| 2211/5159 | being connected to an output member and a return line | 2211/632 | representing a flow rate |
| 2211/52 | . . characterised by the type of actuation | 2211/6323 | the flow rate being a pressure source flow rate |
| 2211/521 | mechanically | 2211/6326 | the flow rate being an output member flow rate |
| 2211/522 | actuated by biasing means, e.g. spring-actuated | 2211/633 | representing a state of the prime mover, e.g. torque or rotational speed |
| 2211/523 | manually, e.g. by using a lever or pedal | 2211/6333 | representing a state of the pressure source, e.g. swash plate angle |
| | | 2211/6336 | representing a state of the output member, e.g. position, speed or acceleration |
| | | 2211/634 | representing a state of a valve |
| | | 2211/6343 | representing a temperature |
| | | 2211/6346 | representing a state of input means, e.g. joystick position |
| | | 2211/635 | . . Circuits providing pilot pressure to pilot pressure-controlled fluid circuit elements |
| | | 2211/6355 | having valve means |
| | | 2211/65 | . . Methods of control of the load sensing pressure |
| | | 2211/651 | characterised by the way the load pressure is communicated to the load sensing circuit |
| | | 2211/652 | the load sensing pressure being different from the load pressure |
| | | 2211/653 | the load sensing pressure being higher than the load pressure |

| | | | |
|-----------|---|----------------|--|
| 2211/654 | . . . the load sensing pressure being lower than the load pressure | 2211/7716 | . . . with automatic return |
| 2211/655 | . . Methods of contamination control, i.e. methods of control of the cleanliness of circuit components or of the pressure fluid | 2211/7725 | . . . with automatic reciprocation |
| 2211/66 | . . Temperature control methods | 2211/7733 | . . . providing vibrating movement, e.g. dither control for emptying a bucket |
| 2211/665 | . . Methods of control using electronic components | 2211/7741 | . . . with floating mode, e.g. using a direct connection between both lines of a double-acting cylinder |
| 2211/6651 | . . . Control of the prime mover, e.g. control of the output torque or rotational speed | 2211/775 | . . Combined control, e.g. control of speed and force for providing a high speed approach stroke with low force followed by a low speed working stroke with high force, e.g. for a hydraulic press |
| 2211/6652 | . . . Control of the pressure source, e.g. control of the swash plate angle | 2211/78 | . . Control of multiple output members |
| 2211/6653 | . . . Pressure control | 2211/781 | . . . one or more output members having priority |
| 2211/6654 | . . . Flow rate control | 2211/782 | . . . Concurrent control, e.g. synchronisation of two or more actuators |
| 2211/6655 | . . . Power control, e.g. combined pressure and flow rate control | 2211/783 | . . . Sequential control |
| 2211/6656 | . . . Closed loop control, i.e. control using feedback | 2211/785 | . . Compensation of the difference in flow rate in closed fluid circuits using differential actuators |
| 2211/6657 | . . . Open loop control, i.e. control without feedback | 2211/80 | . Other types of control related to particular problems or conditions |
| 2211/6658 | . . . Control using different modes, e.g. four-quadrant-operation, working mode and transportation mode | 2211/85 | . . Control during special operating conditions |
| 2211/67 | . . Methods for controlling pilot pressure | 2211/851 | . . . during starting |
| 2211/70 | . Output members, e.g. hydraulic motors or cylinders or control therefor | 2211/853 | . . . during stopping |
| 2211/705 | . . characterised by the type of output members or actuators | 2211/855 | . . Testing of fluid pressure systems |
| 2211/7051 | . . . Linear output members | 2211/857 | . . Monitoring of fluid pressure systems |
| 2211/7052 | Single-acting output members | 2211/86 | . . Control during or prevention of abnormal conditions |
| 2211/7053 | Double-acting output members | 2211/8603 | . . . the abnormal condition being an obstacle |
| 2211/7054 | Having equal piston areas | 2211/8606 | . . . the abnormal condition being a shock |
| 2211/7055 | having more than two chambers | 2211/8609 | . . . the abnormal condition being cavitation |
| 2211/7056 | Tandem cylinders | 2211/8613 | . . . the abnormal condition being oscillations |
| 2211/7057 | being of the telescopic type | 2211/8616 | . . . the abnormal condition being noise or vibration |
| 2211/7058 | . . . Rotary output members | 2211/862 | . . . the abnormal condition being electric or electronic failure |
| 2211/71 | . . Multiple output members, e.g. multiple hydraulic motors or cylinders | 2211/8623 | Electric supply failure |
| 2211/7107 | . . . the output members being mechanically linked | 2211/8626 | Electronic controller failure, e.g. software, EMV, electromagnetic interference |
| 2211/7114 | . . . with direct connection between the chambers of different actuators | 2211/863 | . . . the abnormal condition being a hydraulic or pneumatic failure |
| 2211/7121 | the chambers being connected in series | 2211/8633 | Pressure source supply failure |
| 2211/7128 | the chambers being connected in parallel | 2211/8636 | Circuit failure, e.g. valve or hose failure |
| 2211/7135 | . . . Combinations of output members of different types, e.g. single-acting cylinders with rotary motors | 2211/864 | Failure of an output member, e.g. actuator or motor failure |
| 2211/7142 | . . . the output members being arranged in multiple groups | 2211/8643 | . . . the abnormal condition being a human failure |
| 2211/715 | . . having braking means | 2211/8646 | . . . the abnormal condition being hysteresis |
| 2211/72 | . . having locking means | 2211/865 | . . Prevention of failures |
| 2211/75 | . . Control of speed of the output member | 2211/87 | . . Detection of failures |
| 2211/755 | . . Control of acceleration or deceleration of the output member | 2211/875 | . . Control measures for coping with failures |
| 2211/76 | . . Control of force or torque of the output member | 2211/8752 | . . . Emergency operation mode, e.g. fail-safe operation mode |
| 2211/761 | . . . Control of a negative load, i.e. of a load generating hydraulic energy | 2211/8755 | . . . Emergency shut-down |
| 2211/763 | . . . Control of torque of the output member by means of a variable capacity motor, i.e. by a secondary control on the motor | 2211/8757 | . . . using redundant components or assemblies |
| 2211/765 | . . Control of position or angle of the output member | 2211/88 | . . Control measures for saving energy |
| 2211/7653 | . . . at distinct positions, e.g. at the end position | 2211/885 | . . Control specific to the type of fluid, e.g. specific to magnetorheological fluid |
| 2211/7656 | . . . with continuous position control | 2211/8855 | . . . Compressible fluids, e.g. specific to pneumatics |
| 2211/77 | . . Control of direction of movement of the output member | 2211/89 | . . Control specific for achieving vacuum or "negative pressure" |
| 2211/7708 | . . . in one direction only | 2211/895 | . . Manual override |
| | | 2215/00 | Fluid-actuated devices for displacing a member from one position to another |
| | | 2215/30 | . Constructional details thereof |

2215/305 . . characterised by the use of special materials