

# CPC COOPERATIVE PATENT CLASSIFICATION

## H ELECTRICITY

(NOTE omitted)

## H01 ELECTRIC ELEMENTS

(NOTES omitted)

## H01F MAGNETS; INDUCTANCES; TRANSFORMERS; SELECTION OF MATERIALS FOR THEIR MAGNETIC PROPERTIES (ceramics based on ferrites [C04B 35/26](#); alloys [C22C](#) {; construction of loading coils [H01B](#)}; loudspeakers, microphones, gramophone pick-ups or like acoustic electromechanical transducers [H04R](#); thermomagnetic devices [H10N 15/00](#))

### NOTE

In this subclass, inductances and transformers are regarded as being "for power supply" if they are intended for this purpose even in systems operating at frequencies above 60 cycles/sec.

### WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

### 1/00 Magnets or magnetic bodies characterised by the magnetic materials therefor; Selection of materials for their magnetic properties

#### NOTES

1. Attention is drawn to Note (3) after the title of section [C](#), which Note indicates to which version of the periodic table of chemical elements the IPC refers. In this group, the Periodic System used is the 8 group system indicated by Roman numerals in the Periodic Table thereunder.

2. {Group [H01F 1/0036](#) takes precedence over groups [H01F 1/09](#), [H01F 1/11](#), [H01F 1/20](#), [H01F 1/33](#) and [H01F 1/36](#)}

- 1/0009 . {Antiferromagnetic materials, i.e. materials exhibiting a Néel transition temperature ([H01F 1/0036](#) takes precedence)}
- 1/0018 . {Diamagnetic or paramagnetic materials, i.e. materials with low susceptibility and no hysteresis ([H01F 1/0036](#) takes precedence)}
- 1/0027 . {Thick magnetic films (forming thick magnetic films [H01F 41/16](#))}
- 1/0036 . {showing low dimensional magnetism, i.e. spin rearrangements due to a restriction of dimensions, e.g. showing giant magnetoresistivity, ([H01F 1/153](#), [H01F 1/42](#) and [H01F 10/00](#) take precedence; magnetoresistive sensors [G01D 5/16](#), [G01R 33/06](#); magnetoresistive recording [G11B 5/39](#); magnetic-field-controlled resistors [H10N 50/10](#))}
- 1/0045 . . {Zero dimensional, e.g. nanoparticles, soft nanoparticles for medical/biological use (preparation of fullerenes in general [C01B 32/15](#))}
- 1/0054 . . . {Coated nanoparticles, e.g. nanoparticles coated with organic surfactant}
- 1/0063 . . . {in a non-magnetic matrix, e.g. granular solids (granular films [H01F 10/007](#))}
- 1/0072 . . {one dimensional, i.e. linear or dendritic nanostructures}

- 1/0081 . . . {in a non-magnetic matrix, e.g. Fe-nanowires in a nanoporous membrane}
- 1/009 . . {bidimensional, e.g. nanoscale period nanomagnet arrays ([H01F 10/007](#) takes precedence)}
- 1/01 . of inorganic materials ([H01F 1/44](#) takes precedence)
- 1/012 . . {adapted for magnetic entropy change by magnetocaloric effect, e.g. used as magnetic refrigerating material (refrigeration systems using magnetic effects [F25B 21/00](#))}
- 1/015 . . . {Metals or alloys}
- 1/017 . . . {Compounds}
- 1/03 . . characterised by their coercivity {([H01F 1/40](#) takes precedence)}
- 1/0302 . . . {characterised by unspecified or heterogeneous hardness or specially adapted for magnetic hardness transitions}
- 1/0304 . . . . {adapted for large Barkhausen jumps or domain wall rotations, e.g. WIEGAND or MATTEUCCI effect ([H01F 1/143](#) and [H01F 1/15391](#) take precedence)}
- 1/0306 . . . . {Metals or alloys, e.g. LAVES phase alloys of the MgCu<sub>2</sub>-type ([H01F 1/0304](#) takes precedence)}
- 1/0308 . . . . . {with magnetic shape memory [MSM], i.e. with lattice transformations driven by a magnetic field, e.g. Heusler alloys}
- 1/0311 . . . . {Compounds ([H01F 1/0304](#) takes precedence)}
- 1/0313 . . . . . {Oxidic compounds}
- 1/0315 . . . . . {Ferrites}
- 1/0317 . . . . . {Manganites}
- 1/032 . . . of hard-magnetic materials
- 1/04 . . . . metals or alloys

1/047 . . . . . Alloys characterised by their composition

**NOTE**

In groups [H01F 1/053](#) - [H01F 1/059](#), an alloy is classified in the last appropriate place

1/053 . . . . . containing rare earth metals  
 1/0533 . . . . . {in a bonding agent}  
 1/0536 . . . . . {sintered}  
 1/055 . . . . . and magnetic transition metals, e.g.  $\text{SmCo}_5$   
 1/0551 . . . . . {in the form of particles, e.g. rapid quenched powders or ribbon flakes}  
 1/0552 . . . . . {with a protective layer}  
 1/0553 . . . . . {obtained by reduction or by hydrogen decrepitation or embrittlement}  
 1/0555 . . . . . {pressed, sintered or bonded together}  
 1/0556 . . . . . {pressed}  
 1/0557 . . . . . {sintered}  
 1/0558 . . . . . {bonded together}  
 1/057 . . . . . and IIIa elements, e.g.  $\text{Nd}_2\text{Fe}_{14}\text{B}$   
 1/0571 . . . . . {in the form of particles, e.g. rapid quenched powders or ribbon flakes}  
 1/0572 . . . . . {with a protective layer}  
 1/0573 . . . . . {obtained by reduction or by hydrogen decrepitation or embrittlement}  
 1/0574 . . . . . {obtained by liquid dynamic compaction}  
 1/0575 . . . . . {pressed, sintered or bonded together}  
 1/0576 . . . . . {pressed, e.g. hot working}  
 1/0577 . . . . . {sintered}  
 1/0578 . . . . . {bonded together}  
 1/0579 . . . . . {with exchange spin coupling between hard and soft nanophases, e.g. nanocomposite spring magnets}  
 1/058 . . . . . and IVa elements, e.g.  $\text{Gd}_2\text{Fe}_{14}\text{C}$   
 1/059 . . . . . and Va elements, e.g.  $\text{Sm}_2\text{Fe}_{17}\text{N}_2$   
 1/0593 . . . . . {of tetragonal  $\text{ThMn}_{12}$ -structure}  
 1/0596 . . . . . {of rhombic or rhombohedral  $\text{Th}_2\text{Zn}_{17}$  structure or hexagonal  $\text{Th}_2\text{Ni}_{17}$  structure}  
 1/06 . . . . . in the form of particles, e.g. powder ([H01F 1/047](#) takes precedence {; record carriers [G11B 5/70605](#)})  
 1/061 . . . . . {with a protective layer}  
 1/063 . . . . . {with a non magnetic core}  
 1/065 . . . . . {obtained by a reduction}  
 1/066 . . . . . {obtained by liquid dynamic compaction}  
 1/068 . . . . . {having a L10 crystallographic structure, e.g.  $[\text{Co,Fe}][\text{Pt,Pd}]$  (nano)particles}  
 1/08 . . . . . pressed, sintered, or bound together  
 1/083 . . . . . {in a bonding agent}  
 1/086 . . . . . {sintered}

1/09 . . . . . mixtures of metallic and non-metallic particles; metallic particles having oxide skin  
 1/10 . . . . . non-metallic substances, e.g. ferrites {, e.g.  $[(\text{Ba,Sr})\text{O}(\text{Fe}_2\text{O}_3)_6]$  ferrites with hexagonal structure}  
 1/11 . . . . . in the form of particles {(for magnetic record carriers [G11B 5/70626](#))}  
 1/111 . . . . . {with a non-magnetic core}  
 1/112 . . . . . {with a skin ([H01F 1/113](#) takes precedence)}  
 1/113 . . . . . in a bonding agent  
 1/117 . . . . . Flexible bodies  
 1/12 . . . . . of soft-magnetic materials  
 1/14 . . . . . metals or alloys  
 1/143 . . . . . {in the form of wires ([H01F 1/147](#) takes precedence)}  
 1/147 . . . . . Alloys characterised by their composition {(treatment thereof for enhancing their electromagnetic properties [C21D 8/12](#))}

**NOTE**

In groups [H01F 1/14708](#) - [H01F 1/15391](#), an alloy is classified in the last appropriate place

1/14708 . . . . . {Fe-Ni based alloys (pure Fe or Ni [H01F 1/14](#), [H01F 1/16](#) or [H01F 1/20](#))}  
 1/14716 . . . . . {in the form of sheets}  
 1/14725 . . . . . {with insulating coating}  
 1/14733 . . . . . {in the form of particles}  
 1/14741 . . . . . {pressed, sintered or bonded together}  
 1/1475 . . . . . {the particles being insulated}  
 1/14758 . . . . . {by macromolecular organic substances}  
 1/14766 . . . . . {Fe-Si based alloys}  
 1/14775 . . . . . {in the form of sheets}  
 1/14783 . . . . . {with insulating coating}  
 1/14791 . . . . . {Fe-Si-Al based alloys, e.g. Sendust}  
 1/153 . . . . . Amorphous metallic alloys, e.g. glassy metals {(making ferrous amorphous alloys [C22C 33/003](#))}  
 1/15308 . . . . . {based on Fe/Ni ([H01F 1/15325](#) takes precedence)}  
 1/15316 . . . . . {based on Co ([H01F 1/15325](#) takes precedence)}  
 1/15325 . . . . . {containing rare earths}  
 1/15333 . . . . . {containing nanocrystallites, e.g. obtained by annealing}  
 1/15341 . . . . . {Preparation processes therefor}  
 1/1535 . . . . . {by powder metallurgy, e.g. spark erosion}  
 1/15358 . . . . . {Making agglomerates therefrom, e.g. by pressing}  
 1/15366 . . . . . {using a binder}  
 1/15375 . . . . . {using polymers}  
 1/15383 . . . . . {Applying coatings thereon ([H01F 1/15366](#) takes precedence)}  
 1/15391 . . . . . {Elongated structures, e.g. wires}  
 1/16 . . . . . in the form of sheets ([H01F 1/147](#) takes precedence)  
 1/18 . . . . . with insulating coating

- 1/20 . . . . . in the form of particles, e.g. powder  
([H01F 1/147](#) takes precedence)
- 1/22 . . . . . pressed, sintered, or bound together
- 1/24 . . . . . the particles being insulated
- 1/26 . . . . . by macromolecular organic substances
- 1/28 . . . . . dispersed or suspended in a bonding agent
- 1/33 . . . . . mixtures of metallic and non-metallic particles; metallic particles having oxide skin
- 1/34 . . . . . non-metallic substances, e.g. ferrites
- 1/342 . . . . . {Oxides ([H01F 1/36](#) and [H01F 1/38](#) take precedence)}
- 1/344 . . . . . {Ferrites, e.g. having a cubic spinel structure (X<sub>2</sub>+O)(Y<sub>2</sub>+O<sub>3</sub>), e.g. magnetite Fe<sub>3</sub>O<sub>4</sub>}
- 1/346 . . . . . {[ (TO<sub>4</sub>)<sub>3</sub>] with T= Si, Al, Fe, Ga  
([H01F 10/24](#) takes precedence;  
Faraday rotators [G02F 1/09](#))}
- 1/348 . . . . . {Hexaferrites with decreased hardness or anisotropy, i.e. with increased permeability in the microwave (GHz) range, e.g. having a hexagonal crystallographic structure}
- 1/36 . . . . . in the form of particles ([H01F 1/346](#),  
[H01F 1/348](#) and [H01F 1/38](#) take precedence)}
- 1/37 . . . . . in a bonding agent
- 1/375 . . . . . Flexible bodies
- 1/38 . . . . . amorphous, e.g. amorphous oxides
- 1/40 . . . . . of magnetic semiconductor materials, e.g. CdCr<sub>2</sub>S<sub>4</sub> (devices using galvano-magnetic or similar effects [H10N 50/00](#))
- 1/401 . . . . . {diluted}

**NOTE**

In group [H01F 1/401](#), a diluted magnetic semiconductor (DMS) is classified in the last appropriate place

- 1/402 . . . . . {of II-VI type, e.g. Zn<sub>1-x</sub>Cr<sub>x</sub>Se}
- 1/404 . . . . . {of III-V type, e.g. In<sub>1-x</sub>Mn<sub>x</sub>As}
- 1/405 . . . . . {of IV type, e.g. Ge<sub>1-x</sub>Mn<sub>x</sub>}
- 1/407 . . . . . {Diluted non-magnetic ions in a magnetic cation-sublattice, e.g. perovskites, La<sub>1-x</sub>(Ba,Sr)<sub>x</sub>MnO<sub>3</sub>}
- 1/408 . . . . . {half-metallic, i.e. having only one electronic spin direction at the Fermi level, e.g. CrO<sub>2</sub>, Heusler alloys ([H01F 10/1936](#) takes precedence)}
- 1/42 . . . . . of organic or organo-metallic materials {, e.g. graphene}([H01F 1/44](#) takes precedence)
- 1/44 . . . . . of magnetic liquids, e.g. ferrofluids (particles in a bonding agent [H01F 1/28](#), [H01F 1/36](#),  
([H01F 1/37](#))}
- 1/442 . . . . . {the magnetic component being a metal or alloy, e.g. Fe ([H01F 1/447](#) takes precedence)}
- 1/445 . . . . . {the magnetic component being a compound, e.g. Fe<sub>3</sub>O<sub>4</sub> ([H01F 1/447](#) takes precedence)}
- 1/447 . . . . . {characterised by magnetoviscosity, e.g. magnetorheological, magnetorheotropic, magnetodilatant liquids (electrorheological fluids [C10M 171/001](#))}

**3/00**

**Cores, Yokes, or armatures** (magnetic materials [H01F 1/00](#); permanent magnets [H01F 7/02](#))

- 2003/005 . . . {Magnetic cores for receiving several windings with perpendicular axes, e.g. for antennae or inductive power transfer}
- 3/02 . . . made from sheets
- 3/04 . . . made from strips or ribbons
- 3/06 . . . made from wires
- 3/08 . . . made from powder (powder coatings on sheets [H01F 3/02](#); on strips or ribbons [H01F 3/04](#); on wires [H01F 3/06](#))
- 3/10 . . . Composite arrangements of magnetic circuits
- 2003/103 . . . {Magnetic circuits with permanent magnets}
- 2003/106 . . . {Magnetic circuits using combinations of different magnetic materials}
- 3/12 . . . Magnetic shunt paths
- 3/14 . . . Constrictions; Gaps, e.g. air-gaps (in magnetic shunt paths [H01F 3/12](#))

**5/00**

**Coils** (superconducting coils [H01F 6/06](#); fixed inductances of the signal type [H01F 17/00](#))

- 5/003 . . . {Printed circuit coils}
- 2005/006 . . . {with conical spiral form}
- 5/02 . . . wound on non-magnetic supports, e.g. formers
- 2005/022 . . . {wound on formers with several winding chambers separated by flanges, e.g. for high voltage applications}
- 2005/025 . . . {wound on coaxial arrangement of two or more formers}
- 2005/027 . . . {wound on formers for receiving several coils with perpendicular winding axes, e.g. for antennae or inductive power transfer}
- 5/04 . . . Arrangements of electric connections to coils, e.g. leads
- 2005/043 . . . {having multiple pin terminals, e.g. arranged in two parallel lines at both sides of the coil}
- 2005/046 . . . {Details of formers and pin terminals related to mounting on printed circuits}
- 5/06 . . . Insulation of windings

**6/00**

**Superconducting magnets; Superconducting coils** {(magnetic resonance assemblies using superconducting coil systems [G01R 33/3815](#))}

- 2006/001 . . . {Constructive details of inductive current limiters}
- 6/003 . . . {Methods and means for discharging superconductive storage (superconducting alloys [C22C](#); static memories with superconducting elements [G11C 11/44](#); superconducting circuit breakers with contacts [H01H 33/004](#); superconducting switches for low power [H03K 17/92](#); superconducting material [H10N 60/00](#); power cryotons [H10N 60/355](#))}
- 6/005 . . . {Methods and means for increasing the stored energy in superconductive coils by increments (flux pumps)}
- 6/006 . . . {Supplying energising or de-energising current; Flux pumps}
- 6/008 . . . {Electric circuit arrangements for energising superconductive electromagnets}
- 6/02 . . . Quenching; Protection arrangements during quenching {(protection circuits [H02H 7/001](#))}
- 6/04 . . . Cooling
- 6/06 . . . Coils, e.g. winding, insulating, terminating or casing arrangements therefor

- 6/065 . . {Feed-through bushings, terminals and joints (leading of conductors or axes through casings of transformers [H01F 27/04](#))}
- 7/00 Magnets** (superconducting magnets [H01F 6/00](#); for separation of solid materials or fluids [B03C 1/00](#); for bench or like work-holders [B23B 31/28](#), [B23Q 3/00](#); work-holding devices [B25B 11/00](#); lifting magnets [B66C 1/00](#); {operating or controlling locks using permanent magnets [E05B 47/0038](#); devices for holding a wing, e.g. door or window, by magnetic or electromagnetic attraction [E05C 19/16](#); relieving load or bearings using magnetic means [F16C 39/06](#)} ; for electric meters [G01R](#); for relays [H01H](#); {for electric discharge tubes [H01J](#), e.g. [H01J 3/24](#), [H01J 23/10](#), [H01J 29/68](#)} ; for dynamo-electric machines [H02K](#))
- 7/02 . Permanent magnets {[PM]}
- 7/0205 . . {Magnetic circuits with PM in general}
- 7/021 . . . {Construction of PM ([H01F 7/0278](#) takes precedence; PM compositions [H01F 1/032](#))}
- 7/0215 . . . . {Flexible forms, sheets}
- 7/0221 . . . {Mounting means for PM, supporting, coating, encapsulating PM}
- 7/0226 . . . {PM with variable field strength ([H01F 7/0284](#) takes precedence)}
- 7/0231 . . {Magnetic circuits with PM for power or force generation}
- 7/0236 . . . {Magnetic suspension or levitation (for vehicles [B60L 13/04](#); magnetic bearings [F16C 39/063](#))}
- 7/0242 . . . {Magnetic drives, magnetic coupling devices}
- 7/0247 . . . {Orientating, locating, transporting arrangements}
- 7/0252 . . . {PM holding devices ([H01F 7/021](#), [H01F 7/0215](#), [H01F 7/0226](#) take precedence)}
- 7/0257 . . . . {Lifting, pick-up magnetic objects}
- 7/0263 . . . . {Closures, bags, bands, engagement devices with male and female parts}
- 7/0268 . . . . {Magnetic cylinders}
- 7/0273 . . {Magnetic circuits with PM for magnetic field generation}
- 7/0278 . . . {for generating uniform fields, focusing, deflecting electrically charged particles (for magnetic separation by Lorentz force [B03C 1/023](#); specially adapted for NMR applications [G01R 33/383](#))}
- 7/0284 . . . . {using a trimmable or adjustable magnetic circuit, e.g. for a symmetric dipole or quadrupole magnetic field}
- 7/0289 . . . {Transducers, loudspeakers, moving coil arrangements}
- 7/0294 . . . {Detection, inspection, magnetic treatment}
- 7/04 . . Means for releasing the attractive force
- 7/06 . Electromagnets; Actuators including electromagnets {(electric coils [H01F 5/00](#); devices for holding workpieces using electric force [B23Q 3/15](#); load-engaging elements for lifting articles electromagnetically [B66C 1/06](#); electromagnetic couplings [F16D 27/00](#); magnetic brakes [F16D 63/002](#); electromagnetically operated valves [F16K 11/24](#), [F16K 31/00](#); analysing materials by magnetic means [G01N 27/72](#), [G01N 27/80](#); electromagnets for winding mechanical clocks [G04C 1/02](#); electromagnetic relays [H01H 51/00](#); windings for salient poles of dynamo-electric machines [H02K 3/18](#); electromagnets for telegraphic communication [H04L](#); for arc lamps [H05B 31/28](#))}
- 2007/062 . . {Details of terminals or connectors for electromagnets}
- 7/064 . . {Circuit arrangements for actuating electromagnets (circuit arrangements for obtaining special operating characteristics [H01F 7/18](#); driving circuits for electromagnets making use of a switching regulator [H01H 47/325](#))}
- 7/066 . . {Electromagnets with movable winding}
- 2007/068 . . {using printed circuit coils}
- 7/08 . . with armatures
- 7/081 . . . {Magnetic constructions}
- 2007/083 . . . . {External yoke surrounding the coil bobbin, e.g. made of bent magnetic sheet}
- 2007/085 . . . . {Yoke or polar piece between coil bobbin and armature having a gap, e.g. filled with nonmagnetic material}
- 2007/086 . . . . {Structural details of the armature}
- 7/088 . . . {provided with means for absorbing shocks}
- 7/10 . . . specially adapted for alternating current
- 7/11 . . . . reducing or eliminating the effects of eddy currents
- 7/12 . . . . having anti-chattering arrangements
- 7/1205 . . . . {having short-circuited conductors (electromagnetic relays provided with short-circuited conducting sleeves [H01H 47/00](#))}
- 7/121 . . . Guiding or setting position of armatures, e.g. retaining armatures in their end position
- 7/122 . . . . by permanent magnets {([H01F 7/1615](#), [H01F 7/1646](#) take precedence)}
- 7/123 . . . . by ancillary coil
- 7/124 . . . . by mechanical latch, e.g. detent
- 7/126 . . . Supporting or mounting
- 7/127 . . . Assembling
- 7/128 . . . Encapsulating, encasing or sealing
- 7/129 . . . . of armatures
- 7/13 . . . characterised by pulling-force characteristics
- 7/14 . . . Pivoting armatures ([H01F 7/17](#) takes precedence)
- 7/145 . . . . {Rotary electromagnets with variable gap (with fixed gap or torque motors [H02K 26/00](#))}
- 7/16 . . . Rectilinearly-movable armatures ([H01F 7/17](#) takes precedence)
- 7/1607 . . . . {Armatures entering the winding}
- 7/1615 . . . . . {Armatures or stationary parts of magnetic circuit having permanent magnet}
- 7/1623 . . . . . {Armatures having T-form}

2007/163	. . . . .	{with axial bearing}	7/202	. . . . .	{Electromagnets for high magnetic field strength (for superconducting electromagnets <a href="#">H01F 6/00</a> ; for transformers or inductances without a magnetic core <a href="#">H01F 30/08</a> )}
7/1638	. . . . .	{Armatures not entering the winding}	7/204	. . . . .	{Circuits for energising or de-energising}
7/1646	. . . . .	{Armatures or stationary parts of magnetic circuit having permanent magnet}	7/206	. . . . .	{Electromagnets for lifting, handling or transporting of magnetic pieces or material (electromagnets for guidance of vehicles, workpieces <a href="#">B65G 21/2009</a> ; for magnetic suspension or levitation <a href="#">H02N 15/00</a> )}
7/1653	. . . . .	{Magnetic circuit having axially spaced pole-pieces}	2007/208	. . . . .	{combined with permanent magnets}
2007/1661	. . . . .	{Electromagnets or actuators with anti-stick disc}	<b>10/00</b>		<b>Thin magnetic films, e.g. of one-domain structure (magnetic record carriers <a href="#">G11B 5/00</a>; thin-film magnetic stores <a href="#">G11C</a>)</b>
2007/1669	. . . . .	{Armatures actuated by current pulse, e.g. bistable actuators}	10/002	. . . . .	{Antiferromagnetic thin films, i.e. films exhibiting a Néel transition temperature ( <a href="#">H01F 10/3218</a> and <a href="#">H01F 10/3268</a> take precedence)}
2007/1676	. . . . .	{Means for avoiding or reducing eddy currents in the magnetic circuit, e.g. radial slots}	10/005	. . . . .	{organic or organo-metallic films, e.g. monomolecular films obtained by Langmuir-Blodgett technique, graphene}
2007/1684	. . . . .	{Armature position measurement using coils}	10/007	. . . . .	{ultrathin or granular films ( <a href="#">H01F 10/005</a> and <a href="#">H01F 10/3227</a> take precedence; applying ultrathin or granular layers to substrates <a href="#">H01F 41/301</a> )}
2007/1692	. . . . .	{Electromagnets or actuators with two coils}	10/06	. . . . .	characterised by the coupling or physical contact with connecting or interacting conductors
7/17	. . . . .	Pivoting and rectilinearly-movable armatures	10/08	. . . . .	characterised by magnetic layers ( <a href="#">H01F 10/32</a> takes precedence) ; applying thin magnetic films to substrates <a href="#">H01F 41/14</a> )
7/18	. . . . .	Circuit arrangements for obtaining desired operating characteristics, e.g. for slow operation, for sequential energisation of windings, for high-speed energisation of windings	10/10	. . . . .	characterised by the composition
7/1805	. . . . .	{Circuit arrangements for holding the operation of electromagnets or for holding the armature in attracted position with reduced energising current (for holding relay armature in attracted position with reduced energising current <a href="#">H01H 47/04</a> ; quick energising of electro-dynamic machines <a href="#">H02P 9/08</a> ; for quickly de-energising of dynamo-electric generators <a href="#">H02P 9/123</a> )}	10/12	. . . . .	being metals or alloys (intermetallic compounds <a href="#">H01F 10/18</a> )
7/1811	. . . . .	{demagnetising upon switching off, removing residual magnetism}	10/123	. . . . .	{having a L10 crystallographic structure, e.g. [Co,Fe][Pt,Pd] thin films}
7/1816	. . . . .	{making use of an energy accumulator (for relays <a href="#">H01H 47/043</a> )}	10/126	. . . . .	{containing rare earth metals ( <a href="#">H01F 10/133</a> takes precedence)}
2007/1822	. . . . .	{using a capacitor to produce a boost voltage}	10/13	. . . . .	Amorphous metallic alloys, e.g. glassy metals ( <a href="#">H01F 10/3204</a> takes precedence)
7/1827	. . . . .	{by changing number of serially-connected turns or windings (for relays <a href="#">H01H 47/06</a> )}	<b>NOTE</b>		
7/1833	. . . . .	{by changing number of parallel-connected turns or windings (for relays <a href="#">H01H 47/08</a> )}	In this group, amorphous metallic alloys are classified in the last appropriate place		
7/1838	. . . . .	{by switching-in or -out impedance (for relays <a href="#">H01H 47/10</a> )}	10/131	. . . . .	{containing iron or nickel}
7/1844	. . . . .	{Monitoring or fail-safe circuits (for relays <a href="#">H01H 47/002</a> )}	10/132	. . . . .	{containing cobalt}
2007/185	. . . . .	{with armature position measurement}	10/133	. . . . .	{containing rare earth metals}
2007/1855	. . . . .	{using a stored table to deduce one variable from another}	10/135	. . . . .	{containing transition metals}
2007/1861	. . . . .	{using derivative of measured variable}	10/136	. . . . .	{containing iron}
2007/1866	. . . . .	{with regulation loop}	10/137	. . . . .	{containing cobalt}
7/1872	. . . . .	{Bistable or bidirectional current devices (relays <a href="#">H01H 47/226</a> )}	10/138	. . . . .	{containing nanocrystallites, e.g. obtained by annealing}
7/1877	. . . . .	{controlling a plurality of loads}	10/14	. . . . .	containing iron or nickel ( <a href="#">H01F 10/126</a> , <a href="#">H01F 10/13</a> , <a href="#">H01F 10/16</a> take precedence)
7/1883	. . . . .	{by steepening leading and trailing edges of magnetisation pulse, e.g. printer drivers}	<b>NOTE</b>		
2007/1888	. . . . .	{using pulse width modulation}	In this group, alloys containing iron or nickel are classified in the last appropriate place		
2007/1894	. . . . .	{minimizing impact energy on closure of magnetic circuit}	10/142	. . . . .	{containing Si}
7/20	. . . . .	without armatures (cores <a href="#">H01F 3/00</a> ; coils <a href="#">H01F 5/00</a> ; shaping metal by applying magnetic forces <a href="#">B21D 26/14</a> ; electromagnets specially adapted for NMR applications <a href="#">G01R 33/381</a> )	10/145	. . . . .	{containing Al, e.g. SENDUST}
			10/147	. . . . .	{with lattice under strain, e.g. expanded by interstitial nitrogen ( <a href="#">H01F 10/26</a> - <a href="#">H01F 10/30</a> take precedence)}

- 10/16 . . . . containing cobalt ([H01F 10/126](#) ,  
[H01F 10/13](#) take precedence)
- 10/18 . . . . being compounds
- 10/187 . . . . Amorphous compounds ([H01F 10/3204](#)  
takes precedence)
- 10/193 . . . . Magnetic semiconductor compounds  
{(in general [H01F 1/40](#); multilayers, e.g.  
superlattices [H01F 10/3213](#))}
- 10/1933 . . . . {Perovskites}
- 10/1936 . . . . {Half-metallic, e.g. epitaxial CrO<sub>2</sub> or  
NiMnSb films}
- 10/20 . . . . Ferrites
- 10/205 . . . . {Hexagonal ferrites}
- 10/22 . . . . Orthoferrites {, e.g. RFeO<sub>3</sub> (R= rare earth  
element) with orthorhombic structure}
- 10/24 . . . . Garnets {(in general [H01F 1/346](#);  
multilayers, e.g. superlattices  
[H01F 10/3209](#); applying magnetic  
garnet films to substrates by sputtering  
[H01F 41/186](#))}
- 10/245 . . . . {Modifications for enhancing  
interaction with electromagnetic wave  
energy}
- 10/26 . characterised by the substrate or intermediate layers  
{([H01F 10/06](#) and [H01F 10/32](#) take precedence)}
- 10/265 . . {Magnetic multilayers non exchange-coupled  
([H01F 10/32](#) takes precedence)}
- 10/28 . . characterised by the composition of the substrate
- 10/30 . . characterised by the composition of the  
intermediate layers {, e.g. seed, buffer, template,  
diffusion preventing, cap layers ([H01F 10/06](#) and  
[H01F 10/32](#) take precedence)}
- 10/32 . Spin-exchange-coupled multilayers, e.g.  
nanostructured superlattices {(applying spin-  
exchange-coupled multilayers to substrates  
[H01F 41/302](#))}
- 10/3204 . . {Exchange coupling of amorphous multilayers}
- 10/3209 . . {Exchange coupling of garnet multilayers}
- 10/3213 . . {Exchange coupling of magnetic semiconductor  
multilayers, e.g. MnSe/ZnSe superlattices  
(semiconductor materials for use in  
semiconductor devices [H01L 29/12](#))}
- 10/3218 . . {Exchange coupling of magnetic films via an  
antiferromagnetic interface ([H01F 10/3268](#) takes  
precedence)}
- 10/3222 . . {Exchange coupled hard/soft multilayers, e.g.  
CoPt/Co or NiFe/CoSm (nanocomposite spring  
magnets [H01F 1/0579](#))}
- 10/3227 . . {Exchange coupling via one or more  
magnetisable ultrathin or granular films}
- 10/3231 . . . {via a non-magnetic spacer}
- 10/3236 . . . . {made of a noble metal, e.g.(Co/Pt) n  
multilayers having perpendicular anisotropy  
([H01F 10/3286](#) takes precedence)}
- 10/324 . . {Exchange coupling of magnetic film pairs via a  
very thin non-magnetic spacer, e.g. by exchange  
with conduction electrons of the spacer}
- 10/3245 . . . {the spacer being superconductive}
- 10/325 . . . {the spacer being noble metal}
- 10/3254 . . . {the spacer being semiconducting or insulating,  
e.g. for spin tunnel junction [STJ]}
- 10/3259 . . . . {Spin-exchange-coupled multilayers  
comprising at least a nanooxide layer [NOL],  
e.g. with a NOL spacer}
- 10/3263 . . . {the exchange coupling being symmetric, e.g.  
for dual spin valve, e.g. NiO/Co/Cu/Co/Cu/Co/  
NiO}
- 10/3268 . . . {the exchange coupling being asymmetric,  
e.g. by use of additional pinning, by using  
antiferromagnetic or ferromagnetic coupling  
interface, i.e. so-called spin-valve [SV]  
structure, e.g. NiFe/Cu/NiFe/FeMn}
- 10/3272 . . . . {by use of anti-parallel coupled [APC]  
ferromagnetic layers, e.g. artificial  
ferrimagnets [AFI], artificial [AAF] or  
synthetic [SAF] anti-ferromagnets}
- 10/3277 . . . . {by use of artificial ferrimagnets [AFI]  
only}
- 10/3281 . . . . {only by use of asymmetry of the magnetic  
film pair itself, i.e. so-called pseudospin  
valve [PSV] structure, e.g. NiFe/Cu/Co}
- 10/3286 . . . {Spin-exchange coupled multilayers having  
at least one layer with perpendicular magnetic  
anisotropy}
- 10/329 . . . {Spin-exchange coupled multilayers wherein  
the magnetisation of the free layer is switched  
by a spin-polarised current, e.g. spin torque  
effect}
- 10/3295 . . . {Spin-exchange coupled multilayers wherein  
the magnetic pinned or free layers are  
laminated without anti-parallel coupling within  
the pinned and free layers}
- 13/00 Apparatus or processes for magnetising or  
demagnetising** ({devices for holding workpieces  
using magnetic or electric force acting directly  
on the workpieces [B23Q 3/15](#) ; for degaussing  
ships [B63G 9/06](#); for clocks or watches [G04D 9/00](#);  
{recording or erasing of information on magnetic  
record carriers [G11B 5/00](#) ; demagnetising  
arrangements for colour television [H04N 9/29](#))}
- 13/003 . {Methods and devices for magnetising permanent  
magnets (permanent magnets [H01F 7/02](#))}
- 13/006 . {Methods and devices for demagnetising of  
magnetic bodies, e.g. workpieces, sheet material  
(for erasing of information on magnetic record  
carriers [G11B 5/00](#))}
- 17/00 Fixed inductances of the signal type** (coils in  
general [H01F 5/00](#) {inductors without a potential-  
jump or surface barrier specially adapted for  
integrated circuits, details thereof and multistep  
manufacturing processes therefor [H01L 28/10](#)})
- 17/0006 . {Printed inductances (printed coils for dynamo-  
electric machines [H02K 3/26](#); printed circuits  
[H05K](#))}
- 17/0013 . . {with stacked layers}
- 2017/002 . . . {Details of via holes for interconnecting the  
layers}
- 2017/0026 . . . {Multilayer LC-filter}
- 17/0033 . . {with the coil helically wound around a magnetic  
core}
- 2017/004 . . {with the coil helically wound around an axis  
without a core}
- 2017/0046 . . {with a conductive path having a bridge}
- 2017/0053 . . {with means to reduce eddy currents}
- 2017/006 . . {flexible printed inductors}
- 2017/0066 . . {with a magnetic layer}
- 2017/0073 . . {with a special conductive pattern, e.g. flat spiral}

2017/008	. . {Electric or magnetic shielding of printed inductances}	27/006	. {with special arrangement or spacing of turns of the winding(s), e.g. to produce desired self-resonance}
2017/0086	. . {on semiconductor substrate (inductors for integrated circuits <a href="#">H01L 28/10</a> )}	27/008	. {with temperature compensation}
2017/0093	. {Common mode choke coil}	27/02	. Casings
17/02	. without magnetic core	27/022	. . {Encapsulation}
17/03	. . with ceramic former	27/025	. . {Constructional details relating to cooling}
17/04	. with magnetic core	27/027	. . {specially adapted for combination of signal type inductors or transformers with electronic circuits, e.g. mounting on printed circuit boards}
17/041	. . {Means for preventing rotation or displacement of the core}	27/04	. . Leading of conductors or axles through casings, e.g. for tap-changing arrangements
17/043	. . {with two, usually identical or nearly identical parts enclosing completely the coil (pot cores)}	27/06	. Mounting, supporting or suspending transformers, reactors or choke coils {not being of the signal type}
17/045	. . {with core of cylindric geometry and coil wound along its longitudinal axis, i.e. rod or drum core}	2027/065	. . {Mounting on printed circuit boards}
2017/046	. . . {helical coil made of flat wire, e.g. with smaller extension of wire cross section in the direction of the longitudinal axis}	27/08	. Cooling ( <a href="#">heat-transfer elements F28F</a> ); Ventilating ( <a href="#">structural details of casings H01F 27/02</a> )
2017/048	. . {with encapsulating core, e.g. made of resin and magnetic powder}	27/085	. . {Cooling by ambient air}
17/06	. . with core substantially closed in itself, e.g. toroid	27/10	. . Liquid cooling
17/062	. . . {Toroidal core with turns of coil around it}	27/105	. . . {Cooling by special liquid or by liquid of particular composition}
2017/065	. . . {Core mounted around conductor to absorb noise, e.g. EMI filter}	27/12	. . . Oil cooling
2017/067	. . . {Core with two or more holes to lead through conductor}	27/125	. . . . {Cooling by synthetic insulating and incombustible liquid}
17/08	. . . Loading coils for telecommunication circuits	27/14	. . . . Expansion chambers; Oil conservators; Gas cushions; Arrangements for purifying, drying, or filling
<b>19/00</b>	<b>Fixed transformers or mutual inductances of the signal type (<a href="#">H01F 36/00</a> takes precedence)</b>	27/16	. . . Water cooling
19/02	. Audio-frequency transformers or mutual inductances, i.e. not suitable for handling frequencies considerably beyond the audio range	27/18	. . . by evaporating liquids
19/04	. Transformers or mutual inductances suitable for handling frequencies considerably beyond the audio range ( <a href="#">resonant circuits H03H</a> )	27/20	. . Cooling by special gases or non-ambient air
19/06	. . Broad-band transformers, e.g. suitable for handling frequencies well down into the audio range	27/22	. . Cooling by heat conduction through solid or powdered fillings
19/08	. . Transformers having magnetic bias, e.g. for handling pulses	27/23	. Corrosion protection
2019/085	. . . {Transformer for galvanic isolation}	27/24	. Magnetic cores
<b>21/00</b>	<b>Variable inductances or transformers of the signal type (<a href="#">H01F 36/00</a> takes precedence)</b>	27/245	. . made from sheets, e.g. grain-oriented ( <a href="#">H01F 27/26</a> takes precedence)
21/005	. {Inductances without magnetic core}	27/2455	. . . {using bent laminations}
21/02	. continuously variable, e.g. variometers	27/25	. . made from strips or ribbons ( <a href="#">H01F 27/26</a> takes precedence)
21/04	. . by relative movement of turns or parts of windings	27/255	. . made from particles ( <a href="#">H01F 27/26</a> takes precedence)
21/06	. . by movement of core or part of core relative to the windings as a whole	27/26	. . Fastening parts of the core together; Fastening or mounting the core on casing or support ( <a href="#">on coil H01F 27/30</a> )
21/065	. . . {Measures for obtaining a desired relation between the position of the core and the inductance}	27/263	. . . {Fastening parts of the core together}
21/08	. . by varying the permeability of the core, e.g. by varying magnetic bias	27/266	. . . {Fastening or mounting the core on casing or support ( <a href="#">on coil H01F 27/30</a> )}
21/10	. . by means of a movable shield	27/28	. Coils; Windings; Conductive connections
21/12	. discontinuously variable, e.g. tapped	27/2804	. . {Printed windings}
2021/125	. . {Printed variable inductor with taps, e.g. for VCO}	2027/2809	. . . {on stacked layers}
<b>27/00</b>	<b>Details of transformers or inductances, in general</b>	2027/2814	. . . {with only part of the coil or of the winding in the printed circuit board, e.g. the remaining coil or winding sections can be made of wires or sheets}
27/002	. {Arrangements provided on the transformer facilitating its transport}	2027/2819	. . . {Planar transformers with printed windings, e.g. surrounded by two cores and to be mounted on printed circuit}
27/004	. {Arrangements for interchanging inductances, transformers or coils thereof}	27/2823	. . {Wires ( <a href="#">H01F 27/2866</a> takes precedence)}
		27/2828	. . . {Construction of conductive connections, of leads}
		2027/2833	. . . {using coaxial cable as wire}
		2027/2838	. . . {using transposed wires}

- 2027/2842 . . . {Wire coils wound in conical zigzag to reduce voltage between winding turns}
- 27/2847 . . {Sheets; Strips ([H01F 27/2866](#) takes precedence)}
- 27/2852 . . . {Construction of conductive connections, of leads}
- 2027/2857 . . . {Coil formed from wound foil conductor}
- 2027/2861 . . . {Coil formed by folding a blank}
- 27/2866 . . {Combination of wires and sheets}
- 27/2871 . . {Pancake coils}
- 27/2876 . . {Cooling ([cooling transformers and inductances in general H01F 27/08](#))}
- 27/288 . . {Shielding}
- 27/2885 . . . {with shields or electrodes ([shields or electrodes for pancake coils H01F 27/2871](#); [construction of electric or magnetic shields or screens H01F 27/36](#))}
- 27/289 . . . {with auxiliary windings ([for pancake coils H01F 27/2871](#))}
- 27/2895 . . {Windings disposed upon ring cores}
- 27/29 . . Terminals; Tapping arrangements {for signal inductances}
- 27/292 . . . {Surface mounted devices}
- 2027/295 . . . . {with flexible terminals}
- 2027/297 . . . {with pin-like terminal to be inserted in hole of printed path}
- 27/30 . . Fastening or clamping coils, windings, or parts thereof together; Fastening or mounting coils or windings on core, casing, or other support
- 27/303 . . . {Clamping coils, windings or parts thereof together}
- 27/306 . . . {Fastening or mounting coils or windings on core, casing or other support}
- 27/32 . . Insulating of coils, windings, or parts thereof
- 27/321 . . . {using a fluid for insulating purposes only}
- 27/322 . . . {the insulation forming channels for circulation of the fluid}
- 27/323 . . . {Insulation between winding turns, between winding layers}
- 27/324 . . . {Insulation between coil and core, between different winding sections, around the coil; Other insulation structures}
- 27/325 . . . . {Coil bobbins ([formers for coils in general H01F 5/02](#))}
- 27/326 . . . . {specifically adapted for discharge lamp ballasts}
- 27/327 . . . {Encapsulating or impregnating ([encapsulating coil and core H01F 27/022](#))}
- 2027/328 . . . . {Dry-type transformer with encapsulated foil winding, e.g. windings coaxially arranged on core legs with spacers for cooling and with three phases}
- 2027/329 . . . {Insulation with semiconducting layer, e.g. to reduce corona effect}
- 27/33 . . Arrangements for noise damping
- 27/34 . . Special means for preventing or reducing unwanted electric or magnetic effects, e.g. no-load losses, reactive currents, harmonics, oscillations, leakage fields
- 27/341 . . {Preventing or reducing no-load losses or reactive currents}
- 27/343 . . {Preventing or reducing surge voltages; oscillations}
- 27/345 . . . {using auxiliary conductors}
- 27/346 . . {Preventing or reducing leakage fields ([using magnetic shields H01F 27/36](#); [using auxiliary windings H01F 27/38](#))}
- 2027/348 . . {Preventing eddy currents}
- 27/36 . . Electric or magnetic shields or screens ([movable for varying inductance H01F 21/10](#))
- 27/361 . . . {made of combinations of electrically conductive material and ferromagnetic material}
- 27/363 . . . {made of electrically conductive material}
- 27/366 . . . {made of ferromagnetic material}
- 27/38 . . Auxiliary core members; Auxiliary coils or windings
- 27/385 . . . {for reducing harmonics}
- 27/40 . . Structural association with built-in electric component, e.g. fuse
- 27/402 . . {Association of measuring or protective means}
- 2027/404 . . . {Protective devices specially adapted for fluid filled transformers}
- 2027/406 . . . {Temperature sensor or protection}
- 2027/408 . . {Association with diode or rectifier}
- 27/42 . . Circuits specially adapted for the purpose of modifying, or compensating for, electric characteristics of transformers, reactors, or choke coils ([circuits for controlling transformers, reactors or choke coils, for the purpose of obtaining a desired output H02P 13/00](#); [impedance networks H03H](#))
- 27/422 . . {for instrument transformers}
- 27/425 . . . {for voltage transformers}
- 27/427 . . . {for current transformers}
- 29/00** **Variable transformers or inductances not covered by group [H01F 21/00](#) {[tap change devices H01H 9/0005](#)}**
- 29/02 . . with tappings on coil or winding; with provision for rearrangement or interconnection of windings
- 29/025 . . {Constructional details of transformers or reactors with tapping on coil or windings}
- 29/04 . . having provision for tap-changing without interrupting the load current
- 29/06 . . with current collector gliding or rolling on or along winding
- 29/08 . . with core, coil, winding, or shield movable to offset variation of voltage or phase shift, e.g. induction regulators
- 29/10 . . having movable part of magnetic circuit ([high leakage transformers H01F 38/08](#); [dynamo-electric machines with movable part of magnetic circuit H02K 23/44](#), [H02K 23/48](#))
- 29/12 . . having movable coil, winding, or part thereof; having movable shield
- 29/14 . . with variable magnetic bias ([amplitude modulation by means of variable impedance element H03C 1/08](#)) ; [magnetic amplifiers H03F](#); [circuits for automatic telephonic communication H04M 3/00](#))
- 2029/143 . . {with control winding for generating magnetic bias}
- 29/146 . . {Constructional details}
- 30/00** **Fixed transformers not covered by group [H01F 19/00](#)**
- 30/02 . . Auto-transformers

30/04	• having two or more secondary windings, each supplying a separate load, e.g. for radio set power supplies	41/00	<b>Apparatus or processes specially adapted for manufacturing or assembling magnets, inductances or transformers; Apparatus or processes specially adapted for manufacturing materials characterised by their magnetic properties</b>
30/06	• characterised by the structure		<b>NOTE</b>
30/08	• . without magnetic core		Group <a href="#">H01F 41/30</a> takes precedence over groups <a href="#">H01F 41/16</a> - <a href="#">H01F 41/24</a> {, and over group <a href="#">H01F 41/32</a> .
30/10	• . Single-phase transformers ( <a href="#">H01F 30/16</a> takes precedence)		This Note corresponds to IPC Note (1) relating to <a href="#">H01F 41/16</a> - <a href="#">H01F 41/24</a> , <a href="#">H01F 41/32</a> .)
30/12	• . Two-phase, three-phase or polyphase transformers		
30/14	• . . for changing the number of phases		
30/16	• . Toroidal transformers		
36/00	<b>Transformers with superconductive windings or with windings operating at cryogenic temperature (superconducting magnets or superconducting coils <a href="#">H01F 6/00</a>)</b>	41/005	• {Impregnating or encapsulating (insulating of windings <a href="#">H01F 41/12</a> )}
37/00	<b>Fixed inductances not covered by group <a href="#">H01F 17/00</a></b>	41/02	• for manufacturing cores, coils, or magnets ( <a href="#">H01F 41/14</a> takes precedence; for dynamo-electric machines <a href="#">H02K 15/00</a> )
37/005	• {without magnetic core}	41/0206	• . {Manufacturing of magnetic cores by mechanical means (magnetic cores per se <a href="#">H01F 27/24</a> )}
38/00	<b>Adaptations of transformers or inductances for specific applications or functions</b>	41/0213	• . . {Manufacturing of magnetic circuits made from strip(s) or ribbon(s) (magnetic cores made by winding a ribbon <a href="#">H01F 27/25</a> )}
2038/003	• {High frequency transformer for microwave oven}	41/022	• . . . {by winding the strips or ribbons around a coil}
2038/006	• {matrix transformer consisting of several interconnected individual transformers working as a whole}	41/0226	• . . . . {from amorphous ribbons}
38/02	• for non-linear operation	41/0233	• . . {Manufacturing of magnetic circuits made from sheets (magnetic cores made from sheets <a href="#">H01F 27/245</a> ; soft magnetic alloys in the form of sheets <a href="#">H01F 1/16</a> )}
38/023	• . {of inductances}	41/024	• . . . . {Manufacturing of magnetic circuits made from deformed sheets (magnetic cores made from deformed sheets <a href="#">H01F 27/2455</a> )}
2038/026	• . . {non-linear inductive arrangements for converters, e.g. with additional windings}	41/0246	• . . {Manufacturing of magnetic circuits by moulding or by pressing powder (magnetic cores made by moulding or by pressing powder <a href="#">H01F 27/255</a> ; soft magnetic particles <a href="#">H01F 1/20</a> , <a href="#">H01F 1/36</a> )}
38/04	• . for frequency changing	41/0253	• . {for manufacturing permanent magnets}
38/06	• . for changing the wave shape	41/026	• . . {protecting methods against environmental influences, e.g. oxygen, by surface treatment (magnetic particles with skin <a href="#">H01F 1/061</a> , <a href="#">H01F 1/09</a> , <a href="#">H01F 1/24</a> , <a href="#">H01F 1/33</a> and <a href="#">G11B 5/706</a> )}
38/08	• High-leakage transformers or inductances	41/0266	• . . {Moulding; Pressing ( <a href="#">H01F 41/0273</a> takes precedence; hard magnetic particles <a href="#">H01F 1/06</a> , <a href="#">H01F 1/11</a> )}
38/085	• . {Welding transformers}	41/0273	• . . {Imparting anisotropy (methods and devices for magnetising permanent magnets <a href="#">H01F 13/003</a> )}
38/10	• . Ballasts, e.g. for discharge lamps	41/028	• . . . {Radial anisotropy (for rotor or stator bodies <a href="#">H02K 15/02</a> )}
38/12	• Ignition, e.g. for IC engines	41/0286	• . . {Trimming}
2038/122	• . {with rod-shaped core}	41/0293	• . . {diffusion of rare earth elements, e.g. Tb, Dy or Ho, into permanent magnets}
2038/125	• . {with oil insulation}	41/04	• . for manufacturing coils {(coils for transformer or inductances <a href="#">H01F 27/28</a> )}
2038/127	• . {with magnetic circuit including permanent magnet}	41/041	• . . {Printed circuit coils (apparatus or processes for manufacturing printed circuits in general <a href="#">H05K 3/00</a> )}
38/14	• Inductive couplings {(for wireless supply or distribution of electric power using inductive coupling <a href="#">H02J 50/10</a> )}	41/042	• . . . . {by thin film techniques}
2038/143	• . {for signals}	41/043	• . . . . {by thick film techniques}
2038/146	• . {in combination with capacitive coupling}	41/045	• . . . . {Trimming}
38/16	• Cascade transformers, e.g. for use with extra high tension		
38/18	• Rotary transformers		
38/20	• Instruments transformers		
38/22	• . for single phase ac		
38/24	• . . Voltage transformers		
38/26	• . . . Constructions		
38/28	• . . . Current transformers		
38/30	• . . . Constructions		
2038/305	• . . . . {with toroidal magnetic core}		
38/32	• . . . . Circuit arrangements		
38/34	• . . . Combined voltage and current transformers		
38/36	• . . . Constructions		
38/38	• . for polyphase ac		
38/40	• . for dc		
38/42	• Flyback transformers		
2038/423	• . {with adjusting potentiometers}		
2038/426	• . {with gap in transformer core}		

41/046	. . . . {structurally combined with ferromagnetic material}	41/186	. . . {for applying a magnetic garnet film (magnetic garnet materials <a href="#">H01F 1/346</a> ; magnetic garnet films <a href="#">H01F 10/24</a> )}
41/047	. . . . {structurally combined with superconductive material}	41/20	. . by evaporation
41/048	. . . {Superconductive coils}	41/205	. . . {by laser ablation, e.g. pulsed laser deposition [PLD]}
41/06	. . . Coil winding	41/22	. . Heat treatment; Thermal decomposition; Chemical vapour deposition
41/061	. . . . Winding flat conductive wires or sheets	41/24	. . from liquids
41/063	. . . . . with insulation	41/26	. . . using electric currents {, e.g. electroplating}
41/064	. . . . Winding non-flat conductive wires, e.g. rods, cables or cords	41/28	. . . by liquid phase epitaxy
41/066	. . . . . with insulation	41/30	. . for applying nanostructures, e.g. by molecular beam epitaxy [MBE]
41/068	. . . . . in the form of strip material	41/301	. . . {for applying ultrathin or granular layers (ultrathin or granular layers <a href="#">H01F 10/007</a> )}
41/069	. . . . . Winding two or more wires, e.g. bifilar winding	41/302	. . . {for applying spin-exchange-coupled multilayers, e.g. nanostructured superlattices (spin-exchange-coupled multilayers <a href="#">H01F 10/32</a> )}
41/07	. . . . . Twisting	41/303	. . . . {with exchange coupling adjustment of magnetic film pairs, e.g. interface modifications by reduction, oxidation}
41/071	. . . . Winding coils of special form ( <a href="#">winding conductors onto closed formers or cores H01F 41/08</a> )	41/304	. . . . . {using temporary decoupling, e.g. involving blocking, Néel or Curie temperature transitions by heat treatment in presence/absence of a magnetic field}
2041/0711	. . . . . {Winding saddle or deflection coils}	41/305	. . . . . {applying the spacer or adjusting its interface, e.g. in order to enable particular effect different from exchange coupling}
41/073	. . . . . Winding onto elongate formers	41/306	. . . . . {conductive spacer}
41/074	. . . . . Winding flat coils	41/307	. . . . . {insulating or semiconductive spacer}
41/076	. . . . Forming taps or terminals while winding, e.g. by wrapping or soldering the wire onto pins, or by directly forming terminals from the wire	41/308	. . . . . {lift-off processes, e.g. ion milling, for trimming or patterning}
41/077	. . . . Deforming the cross section or shape of the winding material while winding	41/309	. . . . . {electroless or electrodeposition processes from plating solution}
41/079	. . . . Measuring electrical characteristics while winding	41/32	. . for applying conductive, insulating or magnetic material on a magnetic film {, specially adapted for a thin magnetic film}
41/08	. . . . Winding conductors onto closed formers or cores, e.g. threading conductors through toroidal cores	41/325	. . {applying a noble metal capping on a spin-exchange-coupled multilayer, e.g. spin filter deposition}
41/082	. . . . Devices for guiding or positioning the winding material on the former	41/34	. . in patterns, e.g. by lithography
41/084	. . . . . for forming pancake coils		
41/086	. . . . . in a special configuration on the former, e.g. orthocyclic coils or open mesh coils		
41/088	. . . . . using revolving flyers		
41/09	. . . . Winding machines having two or more work holders or formers		
41/092	. . . . . Turrets; Turntables		
41/094	. . . . Tensioning or braking devices		
41/096	. . . . Dispensing or feeding devices		
41/098	. . . . Mandrels; Formers		
41/10	. . . Connecting leads to windings ( <a href="#">making electric connections in general H01R 43/00</a> )		
41/12	. . . Insulating of windings ({ <a href="#">impregnating or encapsulating of transformers H01F 41/005</a> }; <a href="#">of conductors in general H01B 13/06</a> )		
41/122	. . . . {Insulating between turns or between winding layers}		
41/125	. . . . {Other insulating structures; Insulating between coil and core, between different winding sections, around the coil}		
41/127	. . . . {Encapsulating or impregnating ( <a href="#">encapsulating coil and core H01F 41/005</a> )}		
41/14	. . for applying magnetic films to substrates		
41/16	. . the magnetic material being applied in the form of particles, e.g. by serigraphy {, to form thick magnetic films or precursors therefor} ( <a href="#">H01F 41/18</a> {- <a href="#">H01F 41/24</a> } take precedence)		
41/18	. . by cathode sputtering		
41/183	. . . {Sputtering targets therefor}		