

# CPC COOPERATIVE PATENT CLASSIFICATION

## E FIXED CONSTRUCTIONS

### BUILDING

#### E05 LOCKS; KEYS; WINDOW OR DOOR FITTINGS; SAFES

(NOTE omitted)

#### E05F DEVICES FOR MOVING WINGS INTO OPEN OR CLOSED POSITION; CHECKS FOR WINGS; WING FITTINGS NOT OTHERWISE PROVIDED FOR, CONCERNED WITH THE FUNCTIONING OF THE WING

##### NOTE

In this subclass, the following terms are used with the meanings indicated:

- "closer" or "opener" includes devices for assisting wing-movement or for wing-counterbalancing.

##### WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Closers or openers for wings, not otherwise provided for in this subclass	1/1041	. . . {with a coil spring perpendicular to the pivot axis ( <a href="#">E05F 1/1246</a> takes precedence)}
1/002	. {controlled by automatically acting means (for powered-operated mechanisms <a href="#">E05F 15/70</a> )}	1/105	. . . . {with a compression spring}
1/004	. . {by thermostats, rain, wind or noise ( <a href="#">E05F 1/006</a> takes precedence)}	1/1058	. . . . . {for counterbalancing}
1/006	. . {by emergency conditions, e.g. fire (operating or controlling mechanisms for physical fire-barriers <a href="#">A62C 2/24</a> )}	1/1066	. . . . . {with a traction spring}
1/008	. . {by time control}	1/1075	. . . . . {for counterbalancing}
1/02	. gravity-actuated {, e.g. by use of counterweights}	1/1083	. . . {with a leaf or similar spring ( <a href="#">E05F 1/1284</a> takes precedence)}
1/025	. . {with rectilinearly-moving counterweights}	1/1091	. . . {with a gas spring ( <a href="#">E05F 1/1292</a> takes precedence)}
1/04	. . for wings which lift during movement {, operated by their own weight}	1/12	. . . Mechanisms in the shape of hinges or pivots, operated by springs {(for hinges with two or more pins <a href="#">E05D 3/06</a> )}
1/043	. . . {with cams, helical tracks ( <a href="#">E05F 1/061</a> takes precedence)}	1/1207	. . . . {with a coil spring parallel with the pivot axis}
1/046	. . . {with rectilinearly-inclined tracks for sliding wings}	1/1215	. . . . . {with a canted-coil torsion spring}
1/06	. . . Mechanisms in the shape of hinges or pivots, operated by the weight of the wing	1/1223	. . . . . {with a compression or traction spring}
1/061	. . . . {with cams or helical tracks}	1/123	. . . . . {with a torsion bar}
1/063	. . . . . {with complementary, substantially identical and slidably cooperating cam surfaces ( <a href="#">E05F 1/066</a> takes precedence)}	1/1238	. . . . . {specially adapted for vehicles}
1/065	. . . . . {Cam-and-wheel arrangements}	1/1246	. . . . {with a coil spring perpendicular to the pivot axis}
1/066	. . . . . {Helical grooves, slots, threads or the like}	1/1253	. . . . . {with a compression spring}
1/068	. . . . . {with inclined pivot-axes}	1/1261	. . . . . {for counterbalancing}
1/08	. spring-actuated {, e.g. for horizontally sliding wings (counterbalancing sliding or lifting wings <a href="#">E05D</a> ; springs per se <a href="#">F16F</a> , e.g. gas-springs <a href="#">F16F 9/00</a> )}	1/1269	. . . . . {with a traction spring}
1/10	. . for swinging wings {, e.g. counterbalance (spring-assisted actuation of lids or covers of refuse receptacles <a href="#">B65F 1/1623</a> )}	1/1276	. . . . . {for counterbalancing}
1/1008	. . . {with a coil spring parallel with the pivot axis ( <a href="#">E05F 1/1207</a> takes precedence)}	1/1284	. . . . . {with a leaf or similar spring}
1/1016	. . . . {with a canted-coil torsion spring}	1/1292	. . . . . {with a gas spring}
1/1025	. . . . {with a compression or traction spring}	1/14	. . . with double-acting springs, e.g. for closing and opening or checking and closing {no material}
1/1033	. . . {with a torsion bar ( <a href="#">E05F 1/123</a> takes precedence)}	1/16	. . for sliding wings
		3/00	Closers or openers with braking devices, e.g. checks; Construction of pneumatic or liquid braking devices (construction of non-pneumatic or non-liquid braking devices <a href="#">E05F 5/00</a> ; friction devices in hinges <a href="#">E05D 11/08</a> )
		3/02	. with pneumatic piston brakes (rotary type <a href="#">E05F 3/14</a> )
		3/04	. with liquid piston brakes (rotary type <a href="#">E05F 3/14</a> )

3/06	. . in which a torsion spring rotates a member around an axis perpendicular to the axis of the piston	5/04	. . hand-operated {, e.g. removable}; operated by centrifugal action {or by high closing speed}
3/08	. . in which a torsion spring rotates a member around an axis arranged in the direction of the axis of the piston	2005/043	. . . {operated by centrifugal action at high closing speed}
3/10	. . with a spring, other than a torsion spring, and a piston, the axes of which are the same or lie in the same direction	2005/046	. . . {hand operated}
3/102	. . . {with rack-and-pinion transmission between driving shaft and piston within the closer housing}	5/06	. Buffers {or stops limiting opening of swinging wings, e.g. floor or wall stops} (E05F 5/02 takes precedence)
3/104	. . . {with cam-and-slide transmission between driving shaft and piston within the closer housing}	5/08	. . with springs
3/106	. . . {with crank-arm transmission between driving shaft and piston within the closer housing}	5/10	. . with piston brakes
3/108	. . . {with piston rod protruding from the closer housing; Telescoping closers}	5/12	. specially for preventing the closing of a wing before another wing has been closed
3/12	. . Special devices controlling the circulation of the liquid, e.g. valve arrangement ({E05F 3/223 takes precedence}; valves per se F16K)	<b>7/00</b>	<b>Accessories for wings not provided for in other groups of this subclass (specially adapted for furniture A47B 95/00; door-lifters B66F, E04F 21/00; knobs or handles E05B)</b>
3/14	. with fluid brakes of the rotary type	7/005	. {Aligning devices for wings}
3/16	. with friction brakes	7/02	. for raising wings before being turned {(before sliding E05D 15/565)}
3/18	. with counteracting springs (double-acting springs E05F 1/14)	7/04	. Arrangements affording protection against rattling (with buffering action E05F 5/00)
3/20	. in hinges	7/06	. Devices for taking the weight of the wing, arranged away from the hinge axis
3/22	. Additional arrangements for closers, e.g. for holding the wing in opened or other position	7/08	. Special means for transmitting movements between vertical and horizontal sliding bars, rods, or cables {(E05D 15/5208 takes precedence)}
3/221	. . {Mechanical power-locks, e.g. for holding the wing open or for free-moving zones}	<b>Operating mechanisms for wings (for safeguarding bank teller windows E05G 5/00; for interconnected louvres E06B 7/086; for blinds or roll-type closures E06B 9/00)</b>	
3/222	. . . {electrically operated (E05F 3/223 takes precedence)}	<b>9/00</b>	<b>Means for operating wings by hand rods not guided in or on the frame, including those which also operate the fastening (bolts or fastening devices for wings E05C)</b>
3/223	. . {Hydraulic power-locks, e.g. with electrically operated hydraulic valves}	<b>11/00</b>	<b>Man-operated mechanisms for operating wings, including those which also operate the fastening (connecting mechanisms for a plurality of wings E05F 17/00)</b>
3/224	. . {for assisting in opening the wing}	11/02	. for wings in general, e.g. fanlights (E05F 11/36 takes precedence; for windows to be lowered vertically E05F 11/38; for doors E05F 11/54)
3/225	. . {mounted at the bottom of wings, e.g. details related to seals, covers, connections to the wings, embedding in the floor}	11/04	. . with cords, chains or cables
3/226	. . . {with means to adjust the closed position of the wing}	11/06	. . . in guide-channels
3/227	. . {mounted at the top of wings, e.g. details related to closer housings, covers, end caps or rails therefor}	11/08	. . with longitudinally-moving bars guided, e.g. by pivoted links, in or on the frame
2003/228	. . {Arrangements where the end of the closer arm is sliding in a track}	11/10	. . . Mechanisms by which a handle moves the bar
<b>5/00</b>	<b>Braking devices, e.g. checks; Stops; Buffers (construction of pneumatic or liquid braking devices E05F 3/00; braking devices, buffers or end stops on drawers for tables, cabinets or like furniture A47B 88/473; combined with devices for holding wings open E05C 17/00; devices for limiting opening of wings or for holding wings open by a movable member extending between frame and wing E05C 17/04)</b>	11/12	. . . Mechanisms by which the bar shifts the wing
5/003	. {for sliding wings (E05D 13/04 takes precedence)}	11/14	. . . . directly, i.e. without links, shifting the wing, e.g. by rack and gear or pin and slot
5/006	. {for hinges having a cup-shaped fixing part, e.g. for attachment to cabinets or furniture}	11/145	. . . . . {by pin and slot}
5/02	. specially for preventing the slamming of {swinging} wings {during final closing movement, e.g. jamb stops}	11/16	. . . . shifting the wing by pivotally-connected members {(moving) in a plane perpendicular to the pivot axis of the wing}
5/022	. . {specially adapted for vehicles, e.g. for hoods or trunks}	11/18	. . . . . consisting of a lever, e.g. an angle lever, only {no material}
5/025	. . . {specially adapted for vehicle doors}	11/20	. . . . . consisting of a lever, e.g. an angle lever, and only one additional link {no material}
5/027	. . {with closing action}	11/22	. . . . . consisting of a lever, e.g. an angle lever, and two or more additional links in series {no material}
		11/24	. . . . shifting the wing by pivotally-connected members {(moving) in a plane parallel to the pivot axis of the wing}

11/26	. . . . . consisting of a lever, e.g. an angle lever, only {no material}	15/41	. . Detection by monitoring transmitted force or torque ( <a href="#">E05F 15/48 takes precedence</a> ); Safety couplings with activation dependent upon torque or force, e.g. slip couplings
11/28	. . . . . consisting of a lever, e.g. an angle lever, and one or more additional links {no material}	15/42	. . Detection using safety edges
11/30	. . . . . consisting of links in rhomb-form {no material}	15/43	. . . responsive to disruption of energy beams, e.g. light or sound
11/32	. . with rotary bars guided in the frame ( <a href="#">E05F 11/34 takes precedence</a> )	15/431	. . . . . {specially adapted for vehicle windows or roofs}
11/34	. . with screw mechanisms	2015/432	. . . . . {with acoustical sensors}
11/36	. specially designed for passing through a wall	2015/433	. . . . . {using reflection from the obstruction}
11/38	. for sliding windows, e.g. vehicle windows, to be opened or closed by vertical movement	2015/434	. . . . . {with optical sensors}
11/382	. . {for vehicle windows ( <a href="#">E05F 11/40 - E05F 11/52 take precedence</a> )}	2015/435	. . . . . {by interruption of the beam}
11/385	. . . {Fixing of window glass to the carrier of the operating mechanism}	2015/436	. . . . . {the beam being parallel to the wing edge}
2011/387	. . . . . {using arrangements in the window glass, e.g. holes}	2015/437	. . . . . {the beam being perpendicular to the wing edge}
11/40	. . operated by screw mechanism	15/44	. . . responsive to changes in electrical conductivity
11/405	. . . {for vehicle windows}	15/443	. . . . . {specially adapted for vehicle windows or roofs}
11/42	. . operated by rack bars and toothed wheels {or other push-pull mechanisms}	2015/447	. . . . . {using switches in serial arrangement}
11/423	. . . {for vehicle windows}	15/46	. . . responsive to changes in electrical capacitance
11/426	. . . . . {Flexible rack-and-pinion arrangements}	15/47	. . . responsive to changes in fluid pressure
11/44	. . operated by one or more lifting arms	15/48	. . . by transmission of mechanical forces, e.g. rigid or movable members
11/445	. . . {for vehicle windows}	2015/483	. . . {for detection during opening}
11/46	. . operated by lazy-tongs mechanism	2015/487	. . . {Fault detection of safety edges}
11/465	. . . {for vehicle windows}	15/49	. . specially adapted for mechanisms operated by fluid pressure, e.g. detection by monitoring transmitted fluid pressure ( <a href="#">E05F 15/47 takes precedence</a> )
11/48	. . operated by cords or chains {or other flexible elongated pulling elements, e.g. tapes}	15/50	. using fluid-pressure actuators
11/481	. . . {for vehicle windows}	15/51	. . for folding wings
11/483	. . . . . {by cables}	15/53	. . for swinging wings
11/485	. . . . . {with cable tensioners}	15/54	. . . operated by linear actuators acting on a helical track coaxial with the swinging axis
11/486	. . . . . {with one cable connection to the window glass}	15/56	. . for horizontally-sliding wings
11/488	. . . . . {with two cable connections to the window glass}	15/565	. . . {for railway-cars}
11/50	. . Crank gear with clutches or retaining brakes, for operating window mechanisms	15/57	. . for vertically-sliding wings
11/505	. . . {for vehicle windows}	15/59	. . . for overhead wings
11/52	. . combined with means for producing an additional movement, e.g. a horizontal or a rotary movement	15/60	. using electrical actuators
11/525	. . . {for vehicle windows}	15/603	. . using rotary electromotors
11/53	. for sliding windows, e.g. vehicle windows, to be opened or closed by horizontal movement	15/605	. . . for folding wings
11/535	. . {for vehicle windows}	15/608	. . . for revolving wings
11/54	. for doors	15/611	. . . for swinging wings
13/00	<b>Mechanisms operated by the movement or weight of a person or vehicle (through power-operated wing-operating mechanisms <a href="#">E05F 15/00</a>)</b>	15/614	. . . . . operated by meshing gear wheels, one of which being mounted at the wing pivot axis; operated by a motor acting directly on the wing pivot axis
13/02	. by devices, e.g. lever arms, affected by the movement of the user	15/616	. . . . . operated by push-pull mechanisms
13/04	. by platforms lowered by the weight of the user	15/619	. . . . . using flexible or rigid rack-and-pinion arrangements
15/00	<b>Power-operated mechanisms for wings (motor-operated accessories in locks for completing closing or initiating opening of a wing <a href="#">E05B 17/00</a>)</b>	15/622	. . . . . using screw-and-nut mechanisms
15/40	. Safety devices, e.g. detection of obstructions or end positions	15/624	. . . . . using friction wheels
		15/627	. . . . . operated by flexible elongated pulling elements, e.g. belts, chains or cables ( <a href="#">using flexible elongated push-pull mechanisms <a href="#">E05F 15/619</a></a> )
		15/63	. . . . . operated by swinging arms
		2015/631	. . . . . {the end of the arm sliding in a track; Slider arms therefor}
		15/632	. . . for horizontally-sliding wings

15/635	. . . . . operated by push-pull mechanisms, e.g. flexible or rigid rack-and-pinion arrangements ( <a href="#">E05F 15/652 takes precedence</a> )	17/002	. {for wings which lie one behind the other when closed}
15/638	. . . . . allowing or involving a secondary movement of the wing, e.g. rotational or transversal	17/004	. {for wings which abut when closed}
15/641	. . . . . operated by friction wheels	2017/005	. {for sliding wings}
15/643	. . . . . operated by flexible elongated pulling elements, e.g. belts, chains or cables ( <a href="#">by flexible elongated push-pull mechanisms E05F 15/635</a> )	2017/007	. . {with means for interlocking the wings}
15/646	. . . . . allowing or involving a secondary movement of the wing, e.g. rotational or transversal	2017/008	. {for swinging wings}
15/649	. . . . . operated by swinging arms	<hr/>	
15/652	. . . . . operated by screw-and-nut mechanisms	<b>2700/00</b>	<b>Operating mechanisms for sliding windows</b>
15/655	. . . . . specially adapted for vehicle wings	2700/02	. Devices for moving and locking sliding windows
15/657	. . . . . enabling manual drive, e.g. in case of power failure	2700/04	. Devices for blocking sliding windows in general
15/659	. . . . . Control circuits therefor		
15/662	. . . . . Motor units therefor, e.g. geared motors		
15/665	. . . . . for vertically-sliding wings		
15/668	. . . . . for overhead wings		
15/67	. . . . . operated by flexible or rigid rack-and-pinion arrangements		
15/673	. . . . . operated by screw-and-nut mechanisms		
15/676	. . . . . operated by friction wheels		
15/678	. . . . . operated by swinging lever arms		
15/681	. . . . . operated by flexible elongated pulling elements, e.g. belts		
15/684	. . . . . by chains		
15/686	. . . . . by cables or ropes		
15/689	. . . . . specially adapted for vehicle windows		
15/692	. . . . . enabling manual drive, e.g. in case of power failure		
15/695	. . . . . Control circuits therefor		
15/697	. . . . . Motor units therefor, e.g. geared motors		
15/70	. with automatic actuation		
15/71	. . responsive to temperature changes, rain, wind or noise		
15/72	. . responsive to emergency conditions, e.g. fire		
15/73	. . responsive to movement or presence of persons or objects		
15/74	. . . using photoelectric cells		
15/75	. . . responsive to the weight or other physical contact of a person or object		
15/76	. . . responsive to devices carried by persons or objects, e.g. magnets or reflectors ( <a href="#">E05F 15/77 takes precedence</a> )		
2015/763	. . . {using acoustical sensors}		
2015/765	. . . {using optical sensors ( <a href="#">using photoelectric cells E05F 15/74</a> )}		
2015/767	. . . {using cameras}		
15/77	. . using wireless control		
15/78	. . . using light beams		
15/79	. . using time control		
<b>17/00</b>	<b>Special devices for shifting a plurality of wings operated simultaneously (<a href="#">for simultaneously moving a plurality of interconnected ventilating lamellae E06B 7/086</a>)</b>		
17/001	. {of prison cell doors}		