

PATSTAT Online

User Manual

Revision Sheet

Version	Date	Revision Description	Scope
2.21	21/04/2025	SQL functions contains() and freetext() are no longer available (former section 6.2.3 "Text index for long text fields" deleted)	PISE version 2.9.0 and subsequent
2.20	12/03/2020	Small editorial changes and clarifications	PISE version 2.6.0 2019 Autumn Edition
2.19	04/10/2019	Change to MS SQL Server 2017	PISE version 2.5.7 2019 Spring Edition
2.18	20/05/2019	Adding text indexes (see section 6.2.3) Adding new charts "Top elements" and "Timeline" in Statistics menu; Rework of section 9.6 "Viewing and interacting with a chart"	PISE version 2.5.4 2019 Spring Edition
2.17	01/10/2017	Adding Beginner's interface for querying; Renaming of some windows	PISE version 2.4.4; 2018 Spring and Autumn Edition
2.16	03/05/2017	Adapting product names; minor corrections	PISE version 2.4.2; 2018 Spring Edition
2.15	02/05/2017	Updates for the new PATSTAT version; Improvements to the cross reference chart	PISE version 2.4.2; 2018 Spring Edition
2.14	29/10/2017	Updates for the new PATSTAT version	PISE version 2.3.6; 2017 Autumn Edition
2.13	12/05/2017	Complete editorial review; Minor GUI adaptations ;	PISE version 2.3.3; 2017 Spring Edition
2.12	18/09/2016	Subset Download: tables of PATSTAT Biblio and PATSTAT Register can be freely combined; The Result List in the Result window now contains also the APPLN_ID; minor corrections	PISE version 2.2.9; 2016 Spring Edition
2.11	09/06/2016	Discussion forum is available via the Help menu; Tables are grouped to "Worldwide" and "EP Register" Smaller improvements of the user interface;	PISE version 2.2.8; 2016 Spring Edition
2.10	04/04/2016	Training Set feature from Patent Indicator chart has been removed	PISE version 2.2.6; 2015 Autumn Edition
2.9	21/12/2015	Tableau Chart Download feature removed; Simplification of "Subset download" form; Allow all CPC symbols in Cross Reference chart; Allow spaces in user defined list of Cross Reference chart; Minor user interface changes;	PISE version 2.2.4; 2015 Autumn Edition
2.8	15/09/2015	Minor clarifications; Addition of data scope in section 3.	PISE version 2.2.3; 2015 Spring Edition
2.7	19/06/2015	Removal of Names tab in Preferences menu;	PISE version 2.2.1; 2015 Spring Edition

2.6	08/06/2015	MySQL has been replaced by MS SQL Server; Query plan can be retrieved (see Search window); Some download features are now available in multiple windows; Descriptive error messages in the Download Manager;	PISE version 2.2.0; 2014 Autumn Edition
2.5	04/12/2014	Replace references to the PISE User Manual by adding sections for download, print and help functions. Amend Names tab in Preferences menu.	PISE version 2.0.4; 2014 Autumn Edition
2.4	14/07/2014	User Interface now based on HTML5; 3D-charts discontinued; Integrated most of the content of the PISE user manual in this document;	PISE version 2.0.0; 2014 Spring Edition
2.3	11/06/2014	Chart creation is now limited to the most recent query; Clarification of the parameters of the Patent Indicator chart;	PISE version 1.4.11; 2014 Spring Edition
2.2	22/04/2014	PATSTAT Public has been removed	PISE version 1.4.9; PATSTAT edition Oct2013
2.1	25/02/2014	Introduced limitation of max. length of a query. Changed limitation of max. number of applications for PATSTAT subset and Tableau Chart Download	PISE version 1.4.9; PATSTAT edition Oct2013
2.0	10/01/2014	Restructuring of this document; Description of Additional Attributes moved to PATSTAT Data Catalog; Download of Tableau Charts; Machine Translation	PISE version 1.4.8; PATSTAT edition Oct2013
1.8	13/06/2013	ECLA is replaced by CPC; removed / renamed auxiliary tables;	PISE version 1.4.6; PATSTAT edition April2013
1.7	04/04/2013	Amended Subset Download; Increased limit for Download of Result Table in Table window; Minor changes;	PISE version 1.4.5; PATSTAT edition April2013
1.6	03/01/2013	Addition of tool tips in "Tables" sub-window of "Search" window	PISE version 1.4.3; PATSTAT edition Oct2012
1.5	05/12/2012	Smaller corrections. Addition of OECD HAN name and bubble charts	PISE version 1.4.2 PATSTAT Oct2012
1.4	27/04/2012	Full SQL Support; EEE-PPAT harmonized name	PISE version 1.4.0 PATSTAT Oct2011 & PATSTAT April2012
1.3.1	10/04/2012	Update of Sample Queries (Annex)	PISE version 1.3.0 PATSTAT Oct2011
1.3	27/01/2012		PISE version 1.3.0 PATSTAT Oct2011
1.2	10/01/2012		PISE version 1.1.2 PATSTAT Oct2011

1.1	17/12/2011		PISE version 1.1,0 PATSTAT Oct2011
1.0	05/10/2011	First version	PISE version 1.0.1, 20110718; PATSTAT 2011/04

Table of contents

1. Introduction	8
1.1. About the PATSTAT Online User Manual.....	8
1.2. About PATSTAT	8
1.3. Accessing PATSTAT Online	9
1.4. Business use	10
1.5. User support	11
2. Getting started.....	12
3. Data content	16
4. Window layout / Top toolbar	17
4.1. Adapting the window layout	17
4.2. Top toolbar	17
4.3. Global window structure	17
5. Search window – Beginner mode	19
5.1. General behaviour	20
5.2. Query parameters	21
5.3. Data retrieved	21
6. Search window – Expert mode	23
6.1. Sub-window "Tables": Browse the database structure	23
6.2. Sub-windows "Query" and "Messages": Create and execute a query	24
6.2.1. Query language SQL and MS SQL Server	24
6.2.2. SQL restrictions in PATSTAT Online	25
6.2.3. Edit a query	25
6.2.4. Execute a query	26
6.2.5. Show the estimated query plan	27
6.3. Sub-window "History": Manage the query history	27
6.3.1. Saving and re-loading multiple queries	28
7. Table window.....	31
7.1. Sub-window "Query" and "Messages"	31
7.2. Sub-window "Result Table"	31
8. Application window	33
8.1. Sub-windows "Query" and "Messages"	33
8.2. Sub-window "Result List"	33
8.3. Sub-window "Application"	34

9. Statistics window	36
9.1. Configure statistics	37
9.2. Chart: Top elements	37
9.2.1. Business use	37
9.2.2. Example	37
9.2.3. Customisation	39
9.3. Chart: Time line	40
9.3.1. Business use	40
9.3.2. Example	40
9.3.3. Customisation	40
9.4. Chart: Cross reference analysis	41
9.4.1. Business use	41
9.4.2. Example	41
9.4.3. Customisation	42
9.5. Chart: Patent indicator	47
9.5.1. Business use	47
9.5.2. Example	47
9.5.3. Customization	49
9.6. Viewing and interacting with a chart	50
9.6.1. General interaction features	51
9.6.2. Scrolling and paging	51
9.6.3. Sorting	52
9.6.4. Filtering	52
9.6.5. Drill down / drill up	53
9.6.5.1. Drilling in the Top elements chart	53
9.6.5.2. Drilling in the Timeline chart	54
9.6.6. Change size or colour	54
9.6.7. Follow links to access external databases	55
9.7. Downloading, reloading and printing charts	56
9.8. Sub-window "My statistics"	57
10. User Preferences	58
10.1. General preferences	58
10.2. Document content	59
11. Download	60
11.1. General procedure and download limits	60
11.2. Download the query history	62
11.3. Download a result table	63
11.4. Download a subset of PATSTAT	63
11.4.1. Requesting a download	64
11.4.2. Using the download	65
11.5. Download a result list	67
11.6. Download an application	67
12. Print	69

13. Help	70
14. Annex I: References.....	71
15. Annex II: Glossary.....	72
16. Annex III: Theoretical foundation of Patent Indicator	73
17. Annex IV: Name types	74

1. Introduction

1.1. About the PATSTAT Online User Manual

This manual provides information on the use of **PATSTAT Online**:

- how to query the PATSTAT database
- how to display, download and print the results
- how to do statistical analysis and visualisation
- how to download a subset of PATSTAT for local processing

Chapter 1 introduces this document, PATSTAT data and PATSTAT Online.

Chapter 2 outlines how to make a basic query and to view your results.

Chapter 3 describes the scope of the data and introduces an essential reference document: the PATSTAT Data Catalog.

Chapters 4-13 inform the user about details of the functionalities of the product.

The Annexes include further resources and give additional information.

1.2. About PATSTAT

PATSTAT consists of 2 data sets:

- **PATSTAT Global**
has a worldwide coverage and contains bibliographic information about applications and publications as well as legal information about patents.
- **PATSTAT EP Register**
corresponds to the EPO's European Patent Register. It contains detailed and historical bibliographic, procedural and legal data for European patents.

PATSTAT has been designed to facilitate statistical patent analysis of any complexity. With PATSTAT Online you can obtain tailor-made results that you can subsequently analyse and visualise according to your needs.

New editions of PATSTAT data are available twice a year, in spring and autumn.

PATSTAT data is available via an online product or as a bulk data product:

- **PATSTAT Online**
PATSTAT data is accessible via PISE, the EPO's **Patent Information Services for Experts**. A graphical user interface is provided for access to the data using SQL queries. A form based query interface is available for a limited set of typical queries. Also, some special features for statistical analysis, visualisation and data download are included.

Each user of PATSTAT Online has access to both PATSTAT data sets: PATSTAT Global and PATSTAT EP Register. They can be freely combined.

- **PATSTAT as bulk data set**

For unlimited flexibility, PATSTAT data can be loaded locally at the user's site. It is up to the user or his IT department to implement a database of his choice and to populate it with PATSTAT bulk data, to write SQL queries, to retrieve and/or manipulate the data, using a database management system of his choice.

Subscribers of PATSTAT data will be provided with the bulk data and also scripts to create the recommended database structure.

1.3. Accessing PATSTAT Online

You can access PATSTAT Online via the platform "Patent Information Services for Experts". It is a web application based on HTML5 which requires with the following Internet browsers:

- Internet Explorer 10 or later
- Firefox 18 or later
- Chrome 24 or later
- Safari 6 or later

There are two annual PATSTAT editions, the Spring Edition and the Autumn Edition. Generally, the two most recent editions of PATSTAT Online are available.

The application is accessible via <https://www.epo.org/patstat> by clicking the button "Open PATSTAT Online" located in the centre of the web page.

PATSTAT Online is a subscription-based database requiring a username and password provided by the EPO.

- To get a free one month trial access, follow the link "Test PATSTAT Online for free".
- To subscribe to PATSTAT Online, go to the order form by clicking the button "Order".

Once you have identified yourself with your username and password in the welcome screen, you can select your PATSTAT version from the database list.

Log in – for Global Patent Index and PATSTAT Online

Username Password

☒ Remember username and password [Forgotten login details?](#)




Database		Edition	
	EP full-text search	EPAB 2025/16	info
	EP Bulletin search	BULL 2025/16	info
	Global Patent Index	GPI 2025/16	info
	PATSTAT Online	PATSTAT 2024 Autumn	info
	PATSTAT Online	PATSTAT 2024 Spring	info

Figure 1: Welcome screen

The image above shows the list of databases before you have logged in. All subscription-based databases have a padlock icon in the left column.

1.4. Business use

PATSTAT is a database for statistical analysis of worldwide patent data. It is used by leading international organisations (e.g. OECD, Eurostat), universities, patent offices and large corporations for the purpose of gaining insight into patent information.

In the beginning PATSTAT was distributed exclusively as a bulk data product and customers had to load the data on their own databases (i.e. MS SQL Server, Oracle, MySQL) to produce the statistics.

PATSTAT Online aims at reducing the barrier for patent statistics by improving the access to information and providing easy-to-use charts and powerful download features. The goal is to help shed some light on patent information and stimulate insight from the statistical analysis that remains hidden when analysing document by document.

It enables you to get insight into your portfolio of global patent data like:

- Visualising filing trends (development of industry sectors over time)
- Finding the companies most active in certain industries (IPCs)
- Identifying new combinations of technology (IPC-IPC cross reference)
- Sorting results according to patent indicators (number of citations)

PATSTAT data is linkable to other databases on harmonised names (for better company statistics), regionalisation (for improved insight into localisation of inventions) and sector allocation (for categorisation of applicants into universities, private companies, individuals etc.). Some harmonized name and sector allocation data has already been integrated into PATSTAT Online (cf. PATSTAT Data Catalog). More databases can be requested from third parties (OECD, Eurostat, etc.).

1.5. User support

Should you want to contact the EPO user support, please use the following links:

- [PATSTAT access, subscription or prices](#)
- [other PATSTAT-related points](#)

2. Getting started

This section contains a brief step-by-step description from the launch of PATSTAT Online to the display of documents matching your first search:

- 1 Launch PATSTAT Online from <https://www.epo.org/patstat> by clicking the button **Open PATSTAT Online** located in the middle of the web page.
- 2 Login with your username and password provided by the EPO and select "PATSTAT Online" in the list of databases on the welcome screen.
- 3 The Search window is now displayed.




Figure 2: Search window

In the query edit zone type (or copy & paste) your first query e.g.

```
select *
from tls201_appln
where appln_auth = 'AT'
and ipr_type = 'PI'
and (appln_filing_year = 2005
    or appln_filing_year = 2006)
```

The query is written in SQL (structured Query Language), which is widely used to work with relational databases.

Not obligatory, but it is recommended to split the query into several lines for better readability, as shown above.

This query retrieves all patent applications filed in 2005 or 2006 at the Austrian authority ("PI" stands for patent invention, so utility models are excluded). Click the Search button or press the **Ctrl + Enter** keys simultaneously to run your first query:




Figure 3: Run a query

④ Once the number of retrieved rows is displayed in the message sub-window, you can leave the **Search window** and go to other windows.




Figure 4: The query has been processed successfully; Switch between windows

⑤ Click the **Table** link to see the result of your query:

Result table															1 / 59 701	
Row	appln_id	appln_auth	appln_nr	appln_kind	appln_filing_date	appln_filing_year	appln_nr_epod...	appln_nr_origi...	lpr_type	internat_appln_id	int_phase	reg_phase	nat_phase	earliest_filing...	ear	
1	803596	AT	132005	A	2005-01-05	2005	AT20050000013	0001305	PI	0	N	N	Y	2004-03-02	200	
2	807331	AT	142005	A	2005-01-05	2005	AT20050000014	0001405	PI	0	N	N	Y	2005-01-05	200	
3	807332	AT	142006	A	2006-01-05	2006	AT20060000014	0001406	PI	0	N	N	Y	2006-01-05	200	
4	810876	AT	162005	A	2005-01-05	2005	AT20050000015	0001505	PI	0	N	N	Y	2005-01-05	200	
5	810877	AT	162006	A	2006-01-05	2006	AT20060000015	0001506	PI	0	N	N	Y	2006-01-05	200	
6	814420	AT	162005	A	2005-01-07	2005	AT20050000016	0001605	PI	0	N	N	Y	2005-01-07	200	
7	814421	AT	162006	A	2006-01-05	2006	AT20060000016	0001606	PI	0	N	N	Y	2006-01-05	200	
8	818152	AT	172006	A	2006-01-05	2006	AT20060000017	0001706	PI	0	N	N	Y	2006-01-05	200	
9	821948	AT	182005	A	2005-01-10	2005	AT20050000018	0001805	PI	0	N	N	Y	2005-01-10	200	
10	821949	AT	182006	A	2006-01-05	2006	AT20060000018	A 18/2006	PI	0	N	N	Y	2006-01-05	200	
11	734075	AT	542006	A	2006-01-13	2006	AT20060000054	0005406	PI	0	N	N	Y	2005-01-14	200	
12	736879	AT	552005	A	2005-01-14	2005	AT20050000055	0005505	PI	0	N	N	Y	2005-01-14	200	
13	739682	AT	562005	A	2005-01-14	2005	AT20050000056	0005605	PI	0	N	N	Y	2005-01-14	200	
14	742392	AT	572005	A	2005-01-14	2005	AT20050000057	0005705	PI	0	N	N	Y	2005-01-14	200	
15	747853	AT	592006	A	2006-01-16	2006	AT20060000059	0005906	PI	0	N	N	Y	2006-01-16	200	
16	804601	AT	802005	A	2005-01-19	2005	AT20050000080	0008005	PI	0	N	N	Y	2005-01-19	200	

⑥ You may follow the **Application** link to go to the **Application window** where the result list containing the application number and some information about the selected application are displayed.

Home
Preferences
Download
Print
Help
Search
Table
Application
Statistics
mkracker is using PATSTAT 2018 Spring
Log out

Query
58 674 applications (58 674 rows)

```

from us201_appln
where appln_auth = 'AT'
and ipr_type = 'PI'
and (appln_filing_year = 2005
or appln_filing_year = 2006)

```

Messages

```

13:42:49 [SELECT - 58 674 row(s), 108.241 secs, server #0] Result set
fetched
14:21:07 [Result list, 1.287 secs, server #0] Data fetched
14:21:29 [Result list, 0.376 secs, server #0] Data fetched
14:21:43 [Result list, 0.464 secs, server #0] Data fetched

```

Result list
1 / 58 674

appln_id	Application
1094642	AT 05009124 T 20050426
55459369	AT 06114517 T 20060524
56758032	AT 05018216 T 20050822
57858247	AT 05025299 T 20051119
273757697	AT 08002236 T 20060928
275084747	AT 06819637 T 20061120
315532168	AT 05716955 T 20050308

Application
1 / 58 674

AT 05009124 T 20050426

Title (de)
DATENLIEFEREINRICHTUNG UND VERFAHREN ZUR LIEFERUNG VON
DATEN

Application
AT 05009124 T 20050426

Publication
AT 372022 T 20070915

IPC
H04L 29/08 (2006.01)
H04M 3/42 (2006.01)
H04M 11/00 (2006.01)

7 Click on the button **Statistics** to go to the **Statistics window**. If the parameter form is displayed, click on the button **Calculate**. Otherwise click on the button **Cross-reference** at top of the window.




Figure 7: Bubble chart


As an example, a bubble chart shows the relationship between the top 20 filing years (remember: our query was restricted only to filing years 2005 and 2006 and the top 20 subclass level IPCs for the applications in your result set. You can change the size of the bubbles with a slider.

Note: You can customise the chart in various ways - see section 9.

More sample queries and further information can be found on the PATSTAT Online page of the EPO site: www.epo.org/patstat

3. Data content


PATSTAT data is implemented by a relational database. The data is structured into multiple tables each consisting of several columns. The structure of the database may change slightly from one edition of PATSTAT to the next.

 **Note:** PATSTAT Online does not contain the addresses of inventors, applicants, representatives, opponents or licensees with the exceptions of applicants in PATSTAT Global which are identified as legal entities.


4. Window layout / Top toolbar

4.1. Adapting the window layout

Each window consists of two or more sub-windows (e. g. see Search window in section 2). You can adjust the proportions of the sub-windows by dragging the horizontal and vertical dividers with the mouse. A divider is the white line between two sub-windows.

A box can also be minimised and maximised by clicking the minimise/maximise button  (located in the top right corner of each sub-window) or by double-clicking the sub-window toolbar.

4.2. Top toolbar



❶ Home: Go back to the welcome screen

❷ Menu items:

- Preferences: see section 10.
- Download: The download button is context specific. See section 11.
- Print: The print button is context specific. See section 12.
- Help: See section 13.

❸ The "Go to" links: enable the user to navigate between the Search, Table, Application and Statistics windows. Note that the Application window is not always available (see section 8 "Application window")

❹ The top toolbar on the right hand side of the screen includes

- your username
- the database identifier
- a status light indicating the server connection to the
 - green: connection ok
 - yellow: connection slow or unstable
 - red: no connection
- The "Log out" link triggers your log out and a return to the Welcome Page

4.3. Global window structure

PATSTAT Online consists of 4 main windows:

- Search window
- Table window
- Application window

- Statistics window

All these windows can be accessed via the top toolbar by selecting the appropriate tab. A white tab indicates the current active window.




Figure 8: Top toolbar with Search window as the current active window

In certain cases, the Application window cannot be accessed. In these situations the respective tab in the top toolbar is greyed out and an explanatory text is shown when the user hovers the mouse over the deactivated tab.

The **Search window** is available in 2 flavours:

- Beginner mode:
A limited set of typical information needs is implemented by a form based query interface. When selecting the query parameters a SQL query is automatically generated, which then can be executed. This query can later be refined in the query expert mode.
This mode is intended for users with no prior knowledge of SQL who want to take some SQL statement as a starting point to learn how to query with the SQL query language.
- Expert mode:
The database can be queried by using SQL.
This mode is intended for users familiar with the SQL query language.

Two tabs in the Search window, located below the top toolbar allow switching from one mode to the next.




Figure 9: Search window: Beginner and expert menu tab

The **Application window** is designed to display patent applications. Consequently,

- the Application Window cannot be shown when the last query did not retrieve an application (or in technical terms: did not retrieve an attribute APPLN_ID)
- when a query is executed within the Application Window and the query did not retrieve an APPLN_ID, then a pop-up message is appears informing the user that the system will switch to the Table Window, which can display any query result.

Each window is described in more detail in separate sections of this document.

5. Search window – Beginner mode

The beginner mode allows you to create typical queries without prior knowledge of the SQL query language, by just filling out very simple forms. Still, the data retrieved can be the basis of very powerful analysis.

Nevertheless, the full strength of the SQL query language will only be utilized in expert mode. You are highly encouraged to use the beginner interface as a starting point for gradually learning SQL. You may run first queries in the beginner interface, then slightly change them in the expert interface and later create your own queries directly in the expert interface. A PATSTAT-based SQL self-learning guide “[Using PATSTAT with SQL for beginners](#)” (downloadable from www.epo.org/patstat) may help you on the way.

The Search window in the Beginner mode consists of the single sub-window “Query”:

The screenshot shows the 'Query' window in the Beginner mode. It features a search interface with the following elements:

- Query** tab and a magnifying glass icon.
- 517 712 rows** displayed in red text.
- Subject** section with an information icon.
- I am interested in** dropdown menu (1) showing 'the chronological development of a technical field'.
- Technical field** section (2) with an information icon, an 'Add Field' button, and two rows of input fields (A01B, H05K) with 'IPC help' and 'x' buttons.
- Time period** section (3) with an information icon, 'Between' and 'and' labels, and input fields for '2000' and '2015'.
- SQL statement** section with radio buttons for 'Overview' and 'Details (to generate charts)' (3).
- SQL query text** (4):

```
SELECT DISTINCT a.appln_filing_year, a.appln_id, a.appln_auth, a.appln_nr, a.appln_kind, a.appln_filing_date
FROM tls201_appln a
JOIN tls209_appln_ipc i ON a.appln_id = i.appln_id
WHERE (i.ipc_class_symbol LIKE 'A01B%'
      OR i.ipc_class_symbol LIKE 'H05K%'
      ) -- Change IPC symbol here
AND a.appln_filing_year BETWEEN 2000 AND 2015 -- Define year range here
ORDER BY a.appln_filing_year, a.appln_id
```
- 517 712 row(s) retrieved in 6.318 seconds** (6) and 'See tab "Statistics" for the result'.
- Run query** button (5) and **Edit in expert mode** button (7).

Figure 10: Search window in Beginner mode

1 In this drop down field you select the query which most closely fits your information need. Currently 4 typical queries are defined. The information icons provide more information.

② Depending on the subject / information need you selected some fields are displayed. Here you can change the (default) query parameters.

③ Depending on the intended purpose of the query, you can select one of these options:

- Overview:

The result is quite compact. It contains an aggregation, like the numbers of applications per year. You may immediately use the result as is, e. g. by downloading it and processing it, e.g. in Excel.

- Details:

Typically the result is too large to be comprehensible so it needs to be visualised, filtered, aggregated or otherwise post-processed. You may create a chart in PATSTAT Online or download the data and process it further locally on your desktop with your preferred tools.

④ This box contains the automatically generated query which corresponds to the information need and the selections you made in the form above. The language of the query is called “SQL”.

The query is always complete and syntactically correct, so you can execute it any time.

The query in this box is read-only. To amend it, you need to go the search window in expert mode.

⑤ You may run the query in one of these ways:

- Clicking the “Run query” button below the query box
- Clicking the magnifier icon in the upper left border of the Search window
- By simultaneously pressing the keys <Ctrl>-<Enter>

⑥ After a query has been executed, some information is displayed here:

- The number of rows returned; the data rows themselves can be seen in the Table window
- A suggestions what to do next
- In case of a technical error: the error message

⑦ In case you want to modify or extend the query, you need to switch to the expert mode. You can do so in two ways:

- Clicking the “Edit in expert mode” button below the query box
- Clicking the “Expert” tab above the query window

5.1. General behaviour

- The SQL query is automatically constructed depending on the various input fields for the query parameters.

The query as displayed on the beginners interface is read only. There may be cases where you want to change a query in a way which cannot be done by the predefined input fields. For example, instead of the technology defined as the IPC subclass “B01F” you want to filter by the IPC subgroup “B01F 5/02”¹. In these cases you need to go to the expert interface to amend the query. The “Edit in expert mode”

¹ Note the 3 spaces between the letters F and 5, because the subclass 5 is always right-aligned on 4 positions.

button will automatically copy the query in the expert mode's SQL editor.

- Once a query is changed in the expert mode, it cannot be copied back to the beginners interface. The unmodified query will, however, be still available in the beginners interface.
- All queries which have been successfully executed, including the ones executed from the beginners interface, are stored in the query history (cf. section 6.3). Queries from the query history can be re-loaded and re-used, but only in the expert mode.
- The beginner interface contains several information icons, which give more explanations about specific input fields.

5.2. Query parameters

The input fields for the query parameter depend of the selected subject. Typically you have to specify one or more (up to 8) technology fields and a year range.

A technology field is represented by an IPC class, or more specifically by an IPC section / main class / subclass, which correspond to the first / the first 3 / the first 4 characters of the IPC code.

Examples are

A (IPC section)
A61 (IPC main class)
A61K (IPC subclass)

To input a technology field you may either

- enter it manually
- select it from the dropdown list
- use the assistant in the button "IPC help"

PATSTAT contains several types of dates (years), like publication date or application date. To understand which type of date is used for the subject you selected, please see the generated query.

If a field contains an invalid value, this field is displayed in red colour, an error is indicated and the icon and the button to run a query are deactivated.

5.3. Data retrieved

The data which a query retrieved can be seen in the Table window (cf. section 7). The result of a query is always a table, which can have any number of rows and any number of columns.

The actual meaning of a returned data row depends on the query. Here are just some examples. A query may retrieve

- aggregated data, usually a count of something. This is the case if you select in the beginners interface “Overview” as the purpose of your query.
- a patent application or a patent publication or a IPC symbol or any other information item
- a combination of applications, publications, IPC symbols or any other information item. As a consequence, more than 1 row of the result table may contain the same applications, publications, IPC symbols, ... and so on.

For example this is typically the case when the “Details” query is selected for “potential markets for a technology”. The result table may contain applications, which may have multiple publications. so their data is distributed over multiple rows:

Row	Technology	appln_id	publn_auth	publn_nr	publn_kind	publn_date
1	A01B	24785378	IT	AR980001	A1	1999-07-07
2	A01B	24785378	IT	1305006	B1	2001-04-10
3	A01B 1	472078475	CN	205726887	U	2016-11-30
4	A01B 1	476393666	CN	206005106	U	2017-03-15
5	A01B 1	477827524	CN	106576430	A	2017-04-26

Figure 11: One Technology (IPC) and a single application, but still 2 rows due to 2 publications of this application

- If your data contains an APPLN_ID column, you may go to the Chart Window to create a variety of charts.
- You always can download the data you retrieved (Top menu bar: menu option Download > Prepare download).

6. Search window – Expert mode

The Expert Search window is split into 4 sub-windows:




Figure 12: Expert Search window

6.1. Sub-window "Tables": Browse the database structure

All PATSTAT tables and their columns are listed here. Depending on the PATSTAT database you have subscribed to, the tables may or may not be grouped (see Figure 13: Group of tables).

If you have subscribed PATSTAT Global as well as to PATSTAT Register, then your tables will be grouped accordingly. Otherwise your subscribed tables will be simply listed.

Each group of tables can be expanded to see the individual tables by clicking the arrow on the left side of the icon.




Figure 13: Group of tables

A table can be expanded and collapsed to view its columns.




Figure 14: Sub-window "Tables" displays database tables and their columns

When you move the mouse over a table / a column, information about this item is displayed in a tool tip. Additional information on any table / any column can be found in the PATSTAT Data Catalog.




Figure 15: Tool tip of a table





Figure 16: Tool tip of a column

6.2. Sub-windows "Query" and "Messages": Create and execute a query

6.2.1. Query language SQL and MS SQL Server

You enter your SQL query in the Query sub-window. SQL (T-SQL) is the de facto standard in accessing highly structured databases like PATSTAT.

Note: Due to technical restrictions some rarely-used T-SQL constructs are not supported.

 **Note:** There is a considerable difference between SQL and the Boolean query languages for document databases, like EPO's Espacenet or GPI (Global Patent Index). A Boolean query is in fact a list of comparisons of search criteria and search values, combined by AND or OR. The concept of SQL is very different. If you are not familiar with SQL, there are numerous resources on the Internet or your bookstore. SQL is a very powerful language, but it is also quite easy to with some simple queries. Sample queries and a SQL self-study course specifically designed for SQL beginners using PATSTAT Online can be downloaded from www.epo.org/patstat

6.2.2. SQL restrictions in PATSTAT Online

You can retrieve data with PATSTAT Online but adding, removing or changing of data is not possible.

In PATSTAT Online all SQL queries must start with `SELECT` ...

6.2.3. Edit a query

You can enter a query in the query sub-window in several ways:

- A query can be typed.
- Tables and columns can be dragged from the Table sub-window and dropped into the query sub-window
- A query can be dragged from the search history and dropped
- A query can be loaded from a previously created query file (see section 6.3)
- A query can be pasted from the clipboard or an external application
- A query can be created by filling out the form of the beginner mode (see section 5)

While editing a query, the keywords are coloured blue, table and attribute names are coloured red and comments are coloured green, but table and attribute aliases are not coloured. Therefore, if the query terms are not coloured automatically as described, then in all probability the query contains a syntax error.

An auto-completion feature helps you to write table and attribute names. This feature can be switched off (see section 10.1 General preferences):




Figure 17: Auto-complete feature

There are several ways to make a query easier to read:


- You can break a query into several lines by pressing the `Enter` key.
- You can use indentations by inserting a TAB character by pressing the `Tab` key.
- You can use comments to add any text, e. g. to add notes or a short description which will help others to understand the query. Comments are ignored when processing a query, but will be saved in the query history.

There are 2 types of comments in MS SQL Server:

- `/* Everything here is a comment */`
- `-- Comment till the end of the line`

The maximum length of the query is 10 000 characters.

6.2.4. Execute a query


You start a query by pressing the `<Ctrl><Return>`-keys simultaneously or by clicking the icon  on the upper border of the Query sub-window. If a part of this query is selected (e.g. with the mouse), then only this query selection is executed.

Error messages as well as successful executions are reported in the Messages sub-window.


Error messages will be displayed when:

- The query contains a syntax error or a wrong table, column name or function name
- The complexity of the query is too high (see section 6.2.6) e.g., the JOIN condition might be missing, so trillions of rows would be retrieved.
- You do not have the privileges for the operation, e.g. because it is not a SELECT clause

6.2.5. Show the estimated query plan

 **Note:** This section is intended for SQL experts.

The estimated execution plan is an estimate based upon the work of the query optimizer. To create it, you can do one of the following:

- Press the <Ctrl><lowercase L>-keys simultaneously
- Press <Ctrl> and click the Search icon 

The query will be shown as a table in the Table window. The figure shown in Row 1, Column "TotalSubtreeCosts" is the measure for query complexity. If the query is too complex, then execution will be denied.

Example:

The estimated query plan of this query ...

```
select *
from tls201_appln a
join tls207_pers_appln pa on a.appln_id = pa.appln_id
join tls206_person p on pa.person_id = p.person_id
where person_name like 'panasonic %'
```

... might look like this:

Row	StmtText	StmtId	NodeId	Parent	PhysicalOp	LogicalOp	Argument	DefinedValues	EstimateRows	EstimateIO	EstimateCPU	AvgRowSize	TotalSubtreeCost	OutputList	Warnings	Type	Parallel	EstimateExecu...
1	select * from tbl2	1	1	0	NULL	NULL	1	NULL	162433.47	NULL	NULL	NULL	485.02933	NULL	NULL	SELECT	0	NULL
2	[--Nested Loops]	1	2	1	Nested Loops	Inner Join	OUTER REFER...	NULL	162433.47	0.0	0.6789719	3032	485.02933	[a] [appln_id] [a]	NULL	PLAN_ROW	0	1.0
3	[--Nested Loops]	1	5	2	Nested Loops	Inner Join	OUTER REFER...	NULL	162433.47	0.0	0.6789719	2929	9.000394	[pa] [person_id] [...]	NULL	PLAN_ROW	0	1.0
4	[--Nested Loop]	1	8	5	Nested Loops	Inner Join	OUTER REFER...	NULL	1284.7203	0.0	0.0053701308	2916	3.9417744	[p] [person_id] [...]	NULL	PLAN_ROW	0	1.0
5	[--Index Seek]	1	11	8	Index Seek	Index Seek	OBJECT ([patsta...	[p] [person_id] [...]	1284.7203	0.000050926	0.0015701923	55	0.010621118	[p] [person_id] [...]	NULL	PLAN_ROW	0	1.0
6	[--Clustered In...	1	13	8	Clustered Index	Clustered Index	OBJECT ([patsta...	[p] [person_id] [...]	1.0	0.003125	1.581E-4	2870	3.9246526	[p] [person_id] [...]	NULL	PLAN_ROW	0	1284.7203
7	[--Clustered Ind...	1	41	5	Clustered Index	Clustered Index	OBJECT ([patsta...	[pa] [person_id] [...]	126.43488	0.003125	2.9607836E-4	19	4.3796477	[pa] [person_id] [...]	NULL	PLAN_ROW	0	1284.7203
8	[--Clustered Inde	1	42	2	Clustered Index	Clustered Index	OBJECT ([patsta...	[a] [appln_id] [a]	1.0	0.003125	1.581E-4	112	475.34995	[a] [appln_id] [a]	NULL	PLAN_ROW	0	162433.47

The total subtree cost (485.03 in the above example) is shown in the red rectangle above. For the explanation of the other information items, please see a MS SQL Server technical documentation.

6.3. Sub-window "History": Manage the query history

A query is added to the history if the corresponding query execution was successful, i.e. without syntax errors in the query.

If you double-click on a query in the History sub-window, you can load the query into the Query sub-window for re-use.

For reasons of data privacy, the query history is only stored locally on your computer.


1	2	3	4	5
ID	Database	Result	Query	
\$35	PATSTAT 201...	20 029	select * from tis201_appln where appln_auth = 'CH' and appln_filing_year between 2000 and 2008	
\$34	PATSTAT 201...	20 029	select * from tis201_appln where appln_auth = 'CH' and appln_filing_year between 2000 and 2008	
\$33	PATSTAT 201...	59 702	select * from tis201_appln where appln_auth = 'AT' and ipr_type = 'PI' and (appln_filing_year = 2005 or appln_filing_year...	
\$32	PATSTAT 201...	59 702	select * from tis201_appln where appln_auth = 'AT' and ipr_type = 'PI' and (appln_filing_year = 2005 or appln_filing_year...	
\$31	PATSTAT 201...	59 702	select * from tis201_appln where appln_auth = 'AT' and ipr_type = 'PI' and (appln_filing_year = 2005 or appln_filing_year...	

Figure 11: search history including the most recent 100 queries

- ❶ Column "ID": history query number. The most recent hundred queries are stored, therefore if the history already contains hundred queries, then a new query gets the ID \$101 and query \$1 is deleted
- ❷ Column "Database": database identifier
- ❸ Column "Result": number of rows retrieved
- ❹ Column "Query": the query that was executed
- ❺ Contextual menu (visible when right-clicking one or several selected queries of the list):
 - Item "Append selected queries": appends to the current query available in the query edit zone. Both queries are connected with a default Boolean operator defined in the user preferences
 - Item "Replace selected queries": replaces the current query available in the query edit zone with the selected ones
 - Item "Delete selected queries": deletes the selected history queries
 - Item "Print selected queries"
 - Item "Download selected queries": downloads the selected queries in a CSV file

6.3.1. Saving and re-loading multiple queries

For a complex query that may be frequently re-used, it is recommended to save it locally and load it when appropriate.

A query can be saved/loaded using the button  "Save / load query" available in the Query sub-window of the Search window.




Figure 13 - query manager: save complex queries for frequent re-use

1 The tab "Save query" enables you to save history queries in a local file named `query.QRY` by default.

Note: You can add comment to saved queries.




Figure 14 - query manager: load complex queries for frequent re-use

❶ The tab "Load query" enables you to open your query file and to select a single query that you want to load. . When clicking the button "Load query", you are asked whether you want to replace the old query or to append the loaded query to the already existing one. This latter option usually does not make much sense for SQL queries.

7. Table window

The Table window is split into 3 sub-windows:




Figure 18: Table window

7.1. Sub-window "Query" and "Messages"

The functions and features of these sub-windows are exactly the same as in the Search window.

7.2. Sub-window "Result Table"

This sub-window contains the result of the previously executed query.

Result table 1 / 59 701									
Row	appln_id	appln_auth	appln_nr	appln_kind	appln_filing_date	appln_filing_year	appln_nr_epodoc	appln_nr_origi...	ipr_
1	565891	AT	42005	A	2005-01-04	2005	AT20050000004	0000405	
2	570624	AT	52005	A	2005-01-04	2005	AT20050000005	0000505	
3	570625	AT	52006	A	2006-01-03	2006	AT20060000005	0000506	
4	711621	AT	462005	A	2005-01-13	2005	AT20050000046	0004605	
5	711622	AT	462006	A	2006-01-12	2006	AT20060000046	0004606	
6	714498	AT	472005	A	2005-01-13	2005	AT20050000047	0004705	
7	714499	AT	472006	A	2006-01-12	2006	AT20060000047	0004706	
8	717277	AT	482005	A	2005-01-13	2005	AT20050000048	0004805	
9	720109	AT	492005	A	2005-01-14	2005	AT20050000049	0004905	
10	722914	AT	502006	A	2006-01-12	2006	AT20060000050	0005006	
11	728452	AT	522006	A	2006-01-13	2006	AT20060000052	0005206	
12	731225	AT	532005	A	2005-01-14	2005	AT20050000053	0005305	
13	804601	AT	802005	A	2005-01-19	2005	AT20050000080	0008005	
14	808250	AT	812005	A	2005-01-20	2005	AT20050000081	0008105	

Figure 19: Sub-window "Result table"

Using the up and down arrow keys or the controls on top of the Result Table sub-window, you can move to the next / previous entry or scroll to the beginning or the end of the table.

If your result table contains an attribute APPLN_ID (which uniquely identifies an application), you can click on any APPLN_ID value to jump to the Application window which will display the details of the selected application.

NULL values will be displayed as the string "NULL".

8. Application window

This window is only available if the result of your last query contained an attribute "appln_id". This attribute represents applications and is required because the Result window is used to display data from individual applications.

If your query did not retrieve applications (identified by APPLN_IDs) but retrieved only inventors or other data then obviously no applications will be shown. In this case the Result window cannot be accessed.

The Result window is split into 4 sub-windows:




Figure 20: Application window

8.1. Sub-windows "Query" and "Messages"

The functions and are exactly the same as in the Search window.

8.2. Sub-window "Result List"

appln_id	Application
275390909	EP 10707859 A 20100223
422560229	CN 201420277839 U 20140528
409573077	US 201113703020 A 20110520
38740455	JP 2004517196 A 20030522
3509195	BR 0314291 A 20030916
23812363	HK 44195 A 19950323
415035924	EP 2014000381 W 20140212
405848454	EP 12842565 A 20121016
273768	EP 05727348 A 20050330
267442718	EP 2009062231 W 20090922

Figure 21: Sub-window "Result list"

All applications retrieved by the query are shown in the result list. For each application the typical identifying fields are shown.

Example: see also first line in Figure 21

Description	Source (table and column)	Example
Technical application identifier	tls201_appln.appln_id	275390909
Code of the Office	tls201_appln.appln_auth	EP
Application number	tls201_appln.appln_nr	10707859
Application kind	tls201_appln.appln_kind	A
Filing date	tls201_appln.appln_filing_date	20100223

Applications can be selected and displayed in the sub-window "Application":


- with the navigation buttons
- by clicking on the application in the Result List
- by dragging (grab an entry at a blank space, not at the text) and dropping; several applications can be displayed simultaneously. The maximal number is limited to four

8.3. Sub-window "Application"


The most important information (e. g. title, application number, publication number, IPC symbols and abstract) of an application will be displayed. Some of these information items are also links to external databases (e. g. Espacenet, WIPOs IPC search tool).

The data to be displayed can be restricted and the order of the information items can be rearranged.

The top bar of the Application sub-window contains buttons to trigger some functions. Buttons, not described here are not applicable for PATSTAT Online but only for the other databases of PISE.



❶ The 4 arrows in the icon bar enable you to navigate to the first, previous, next and last application displayed in the Result List on the lower left corner of the screen.

❷ The button  activates *Patent Translate*, which is a service that translates the title and abstract of an application. For most languages a translation can be done on the fly from and into English, German and French as well as several other languages.

When the button is clicked, a window pops up to display the title and abstract in their original language:





Figure 22: Patent Translate form

You may select the target language out of a list of available languages, start the translation with  or reset the text to the original language.

- ③ If the details of more than one (up to 4) applications are shown in the Application sub-window, you can toggle between a fixed windows layout and floating windows.
- ④ This button lets you maximize or shrink this sub-window.

9. Statistics window

The Statistics window allows you to display the results of your queries as charts.

Note: Charts can only be created for your most recent query. In addition, this most recent query must have retrieved an attribute APPLN_ID as this APPLN_ID will automatically retrieve all data necessary for the computation of the chart.

The following functions are available:

- selecting and configuring charts for the most recent query
- viewing the current or previous charts
- saving chart data in multiple formats
- loading or printing charts




Figure 23: Chart window with "My Statistics" sub-window and "Configure / view statistics" sub-window

❶ Buttons to select the type of statistical analysis and to change the default parameters (see section 9.1 "Configure statistics")

❷ Most of the screen displays the "Configure / view statistics" sub-window. The features and functions are described in more detail in section 9.6 "Viewing and interacting with a chart".

❸ The "My statistics" sub-window displays a list of previously computed analyses and the status of current task execution. The status may have one of following values:

- **created:** this is the start-up status
- **pending:** the request to prepare the chart is being queued because the maximum number of requests has already been reached. At a later stage, the status will change to **running**.
- **running:** the chart is currently under preparation

- **finished:** this is the final state of a normal operation and the chart will be displayed. This status is not explicitly shown.
- **cancelled:** if the request has been cancelled by the user (final status)
- **error:** final status in case of an abnormal operation

9.1. Configure statistics

❶ As a first step, select the type of the required analysis. At this stage, no chart will be displayed yet.




Figure 24: Drop down menu to select the type of analysis

❷ Define the parameters of the analysis. The configuration parameters vary greatly depending on the type of the analysis. Details are included in the following sub-sections.

9.2. Chart: Top elements

9.2.1. Business use

The Top element chart is a bar chart showing the number of applications of selected parameters, such as application authority or CPC classification, allowing you to gain insight on how the retrieved applications are distributed among these parameters.

9.2.2. Example

The top elements chart below shows the number of applications filed in the Swiss office between 2005 and 2015, grouped by the country of residence of the applicant.




Figure 25: Example of Top elements chart

To the right side of the chart you can see a built-in scroll bar showing the distribution of all bars in this chart on a logarithmic scale. The currently visible part is marked grey.

The IPC and the CPC system are hierarchical classification schemes, therefore, if IPCs or CPCs are used as grouping criteria, the hierarchical level to be applied can be specified. For more detail see section 9.6.5 “Drill down / drill up”.




Figure 26: Example to Top elements chart with IPC parameter

9.2.3. Customisation

The Top element bar shows the number of applications grouped by certain parameters. The parameters can be selected from the Parameters form, which is accessible from the button “Parameter” (see section 9.1 “Configure statistics”).

Parameters for Top elements	
	Application
<input type="radio"/>	Application authority
	Applicant
<input checked="" type="radio"/>	Country of residence
<input type="radio"/>	Name
<input type="radio"/>	DOCDB standardized name
<input type="radio"/>	PATSTAT standardized name
<input type="radio"/>	OECD harmonized applicant name
	Inventor
<input type="radio"/>	Country of residence
<input type="radio"/>	Name
<input type="radio"/>	DOCDB standardized name
<input type="radio"/>	PATSTAT standardized name
<input type="radio"/>	IPC
<input type="radio"/>	CPC

Calculate Cancel Help

Figure 27: Parameters form of the Top elements chart

9.3. Chart: Time line

9.3.1. Business use

The Timeline chart shows the number of applications by a certain year or month. The relevant date, e. g. the earliest filing date, can be specified in the Parameters form. It allows seeing the distribution of applications over time.

9.3.2. Example

The Timeline chart below shows the number of applications filed in the Swiss office between 2005 and 2015, grouped by country of residence of the applicant.




Figure 28: Example of a Timeline chart

The level used for counting application can be selected. It can be either “Year” or “Month”. See also section 9.1 “Configure statistics”.

9.3.3. Customisation

The timeline shows the number of applications over time. The date to be considered can be selected from the Parameters form, which is accessible from the button “Parameter” (see section 9.1 “Configure statistics”).

Parameters for Timeline ✕

	Parameter
<input checked="" type="radio"/>	Filing date
<input type="radio"/>	Earliest filing date
<input type="radio"/>	Earliest publication date

Figure 29: Parameter form of the Timeline chart

9.4. Chart: Cross reference analysis

9.4.1. Business use

Typically for analysis a data set must be broken down into smaller categories, like IPC codes or time series. This is the purpose of this cross reference analysis.

9.4.2. Example

The figure below shows a typical cross-reference chart created by PATSTAT Online. This example shows the correlation between the application year and the most frequent IPC subclasses of all applications that were filed at the Swiss Patent Office between the years 2000 and 2008.



Figure 30: Example of a cross-reference bubble chart

The figure below shows the form for changing the parameter settings according to your business requirements.

Parameters for Cross-reference

Parameter 1 (X axis) **IPC**

☒ top 20 of the search result list

☐ technical field 1 Electrical machinery, apparat...

☐ user-defined list

Parameter 2 (Y axis) **IPC**

☒ top 20 of the search result list

☐ technical field

☐ user-defined list

Harmonisation type

Comparison

☒ No comparison

☐ time from to

versus

from to

Figure 31: Parameter window for cross-reference analysis

9.4.3. Customisation

A cross reference displays at most 20 x 20 values. Less data is shown when:

- the display of the complete result set does not require a 20x20 chart or
- in cases of a special data distribution. Example: Assuming that there are more bubbles with a value of 5 or higher than a 20x20 matrix can hold but very few bubbles with a value of 6 or higher, then only the few bubbles with the value of 6 and higher would be displayed; possibly resulting in a chart being much smaller than 20x20.

Figure 32: Form to customise cross-reference analysis

❶ For a cross-reference analysis, you have to define what data to display on the X axis (parameter 1) and on the Y axis (parameter 2).

You can choose among these parameters with the option of restricting their value:

- Application Authority
Restricted by:
 - The top 20 application authorities
- Dates (filing of application, earliest publication or earliest priority).
The dates will be grouped by year or month
Restricted by:
 - Date range
(Note: The date range must not include more than 20 years / months)
- IPC
Restricted by:
 - The top 20 IPC symbols on subclass level (first 4 characters) of result set
 - The IPCs of predefined technical field
 - Use your own list of IPC symbols (see ❸ below)

- **CPC**
The same restriction options (as for IPCs) are available
- **Applicant or inventor**
Restricted by:
 - Top 20 applicants / inventors of result set
 - Applicants / inventors of some predefined industry
 - Your own list of applicant / inventors (see ❸ below)
- **Without parameter 2 (selection "none"):**
If parameter 2 is not defined, then a bar chart using parameter 1 is displayed (see figure below):




Figure 33: bar chart with parameter 1 only

Note: Certain combinations of parameters are not supported:

- Selection “Application Authority” for both parameters
- Selecting dates for both parameters

❷ When one of the parameters is an applicant or inventor, you can select the name type to be used. See section 17 “Annex IV: Name types” for an explanation of the available name types.

❸ In the parameter form you can also specify if you want to compare the number of applications of two date ranges according to the date of filing.

Below is an example in which the following cross-reference parameters on the result set described earlier in this section were used:

Parameters for Cross-reference

Parameter 1 (X axis): **IPC**

☒ top 20 of the search result list

☐ technical field: **1** Electrical machinery, apparat...

☐ user-defined list: **load**

Parameter 2 (Y axis): **Applicant (PATSTAT Standardiz...**

☒ top 20 of the search result list

☐ Industry: **10** Manufacture of Food Prod...

☐ user-defined list: **load**

Harmonisation type: **PATSTAT Standardized Name**

Comparison

☐ No comparison

☒ time

from: **2001-01** to: **2004-12**

versus

from: **2005-01** to: **2008-12**

Calculate **Cancel** **Help**

Figure 34: Parameters for cross-reference chart with time-based comparison




Figure 35: Resulting cross-reference chart with time-based comparison: red bubble indicate negative values, blue bubbles indicate positive values.

The application frequencies for both date ranges (application filing date in years 2001 - 2004 vs. application filing date in the years 2005-2008) are computed and the difference in the application numbers is displayed in the chart. Note that value of the 1st date range is subtracted from the value of the 2nd date range.

In the example, there are 8 **more** applications from the applicant PHILIPS ELECTRONIC with IPC classification A61B (DIAGNOSIS; SURGERY; IDENTIFICATION) between 2005 and 2008 than between 2001 and 2004.

The top left red bubble on the every left indicates a negative value, showing that for this combination of IPC and applicant, there are **fewer** applications between 2005 and 2008 than between 2001 and 2004.

Comparing two date ranges of different lengths is usually not recommended, because the shorter date range typically will have fewer occurrences.

Note: Certain options are not supported:

- Date ranges comparison if one or both of the parameters is a date
- Date ranges comparison on a bar chart (where one parameter is "none")

④ You can define your own list of IPC or CPC subclasses (i.e. the first 4 characters of the symbol), applicant names or inventor names to be used as parameter values.

You can either enter the values directly in the parameter field, or write the values to a file to upload.

Parameters for cross-reference

Parameter 1 (X axis) IPC

☐ top 20 of the search result list

☐ industry food, beverages

☒ user-defined list

direct key in

press "load" button to be prompted for a file

Figure 36: Enter your own list of parameter values

The values (comma separated) can be entered directly in the parameter form. In case a value contains a comma or a space, the value must be enclosed in double quotes. In all other cases, these double quotes are optional.

The same rules apply when the string is first entered into a text file to be loaded.

Examples with IPC or CPC classifications:

- A61B, A61M, B01D

Examples with names:"

- "Smith, John"
- SIEMENS, "International Business Machines", "IBM"

- ⑤ These buttons enable the following functions:
- calculate the analysis, which also creates the chart
 - cancel the form
 - display help

9.5. Chart: Patent indicator

9.5.1. Business use

Some analysis tasks require patents to be sorted according to their "value". The value of a patent might be defined differently in different contexts. However, typically the value correlates with the number of citations, DOCDB family members, applicants or inventors and also on whether the application has been granted.

The patent indicator chart allows you to compute a score based on these parameters for each application and allows you to configure the relevance and the degree to which each parameter is relevant.

Sources on the theoretical foundation of the patent indicator are listed in Annex II.

9.5.2. Example

The example patent indicator chart is based on the set of all applications filed in the Swiss Patent Office between the years 2000 to 2008; listing the applications with the highest score. In this example, the score is defined by

the number of citations *minus*
the number of applicants *plus*
20 if the patents have been granted.

The rational of this example score definition might be the indication of the high relevance of a patent when it is cited often and even more so if it has been granted. However, on the other hand, the involvement of several applicants might make the licensing complicated which may lead to a decrease in the value of a patent.

Parameters for patent indicator

Filter by technical field: all

Sort by: User defined score

Coefficients for

A-number cited (DocDB family-family citation)	1
B-size of family	0
C-number of applicants	-1
D-number of inventors	0
E-grant	20

Score calculation

$1*A + 0*B - 1*C + 0*D + 20*E$

Buttons: Save parameters, Load parameters, Calculate, Cancel, Help

Figure 37: Parameter window for the example patent indicator chart




Figure 38: Example patent indicator chart

Our example of the patent indicator chart can be interpreted as follows:

Each application is represented as a horizontal bar and identified by a representative publication. In the chart, consider the publication CH 698761 B1 published 2009-10-15 (see pop-up window in Figure 38): Its application has 153 citations, resulting in a score A of 153, so the blue part of the bar is positioned to the right of the vertical zero base line. There is a single applicant, resulting in a score C of -1. The negative part of the bar is positioned to the left of the zero base line. Since the application has been granted, a score of 20 has been added. This results in a total score of 172 (= $153 + 0 - 1 + 0 + 20$), which is displayed as a red line on the top of the bar.

In case multiple applications of the same DOCDB family have been retrieved, only one family member (the one with the oldest publication) will be displayed in the chart. Typically, all applications of one family would have the same score, anyway. De-duplicating family members has the advantage of focusing on the relevant information.

Note: When browsing through the publications, the chart is automatically scaled to the windows size. To read the value of a bar, please see the X-axis at the bottom of the chart.

9.5.3. Customization

Figure 39: Form to customise patent indicators

- ❶ You can filter your result set by choosing a specific technical field
- ❷ You can sort the result by selecting “User defined score” or by any of the coefficients (see ❸ in Figure 39: Form to customise patent indicators) .
 - In case of “User defined score” you can be flexible in defining your own score.
 - In all other cases, the selected coefficient (A – E) will be set to 1, all other to 0.
- ❸ In case you selected “Sort by: User defined score”, you can define your own score. The score is computed by a formula which you can adapt to your needs. You can enter any positive or negative value for any of the coefficients.

The formula is computed for each application:

total score =

number of DOCDB family-family citations	* user defined coefficient A +
size of DOCDB family	* user defined coefficient B +
number of applicants	* user defined coefficient C +
number of inventors	* user defined coefficient D +
if granted:	user defined value; else: 0 +
offset (can be positive or negative)	

- ❹ Here you can read the formula with all coefficients. This field is for the information of the interested user. It cannot be edited. To change the formula, change the individual coefficients (see ❸ in Figure 39: Form to customise patent indicators)

- ❺ The buttons enable the following functions:

- save the parameters as an XML file on disk and re-load the file
- calculate the analysis, which also creates the chart
- cancel the form
- display help

9.6. Viewing and interacting with a chart




Figure 40: The "View / configure statistics" sub-window has several functions including viewing the chart, changing the appearance of the chart and printing/downloading the chart data.

- 1 the chart itself
- 2 information of the analysis parameters employed
- 3 options to change the appearance of the chart
- 4 the query which retrieved the data on which the analysis is based and the size of the result set
- 5 a button to save chart data in various formats, reload it from JSON and print it
- 6 a button to display the chart in the full screen mode


Depending on the type of a chart, there are several ways to interact with it as shown below:

Interaction feature	Chart type				See section
	Top element	Timeline	Cross-reference	Patent indicator	
Full screen mode	x	x	x	x	9.6.1
Display data in pop-up window	x	x	x	x	9.6.1
Scrolling / paging	x	x		x	9.6.2
Sorting	x				9.6.3
Filtering	x	x			9.6.4
Drill down / drill up	x	x			9.6.5
Change size or colour			x	x	9.6.6
Follow links to access external databases				x	9.6.7

9.6.1. General interaction features

Depending on the chart, different features are available to help view the chart:

Features, available for all charts:

- The button  found at the far right of the "Configure / view statistics" window menu bar, toggles the display between full screen mode and normal mode.
- Pop-up window: If you hover the mouse over a data point of the chart, information on its data will appear

9.6.2. Scrolling and paging

Different chart types have different scrolling or paging options:

- **Top element:**
The vertical scroll bar at the right side of the chart shows the distribution of all bars in this chart on a logarithmic scale. So it is easy to see e.g. how long the tail of the data distribution is, even if only a small portion of the data is actually displayed.
- **Timeline:**
By clicking the left mouse button on the scroll bar and dragging the mouse you can define a time range (see grey area in Figure 41). Scrolling takes place by

moving the grey area in the scroll bar.






Figure 41: Horizontal scrollbar in the Timeline chart

- **Patent indicator:**

Use the buttons  and , positioned on the left side of the chart to go to the previous / next page of the bar chart.

9.6.3. Sorting

The list in the top element chart can be sorted by the “Rank” or by the selected parameter by clicking on the respective header label. Some examples:

Rank ▲	Applicant - Name	
1	General Electric Company	920
2	THE SWATCH GROUP RESEARCH ...	187
3	ALSTOM Technology Ltd	176
4	Maschinenfabrik Rieter AG	158
5	Seiko Instruments Inc.	154

Figure 42: Sorted ascending by rank (= length of the bar): see yellow highlight

Rank	Applicant - Name ▼	
48	Zurecon AG	7
47	Zumtobel Lighting GmbH	8
51	Zumbach Electronic AG	4
54	Ziemer Ophthalmic Systems AG	1
50	Zidatech AG	5

Figure 43: Sorted descending by applicant name: see yellow highlight

9.6.4. Filtering

Different chart types have different filter options:

- **Top element:**

If IPC or CPC has selected as parameter, you can restrict the displayed data to certain IPC / CPC section (Note: The section is the first letter of the IPC / CPC symbol). This can be done with these checkboxes:

Sections:

- ☒ A
- ☒ B
- ☒ C
- ☒ D
- ☒ E
- ☒ F
- ☒ G
- ☒ H

Figure 44: Filter for IPC / CPC sections

- **Timeline:**
By clicking the left mouse button on the scroll bar and dragging the mouse you can define a time range (see grey area in Figure 41). The data displayed in the chart is then restricted to this time range.

9.6.5. Drill down / drill up

Drilling up and drilling down means changing the level of the data displayed by going one level up or one level down. This is possible if the chart parameter has an inherent hierarchical structure. This is the case in these charts:

- **Top elements:**
IPC and CPC classification symbols can be displayed at these levels:
 - Section
 - Class
 - Subclass
 - Group
 - Subgroup
- **Timeline:**
Time can be displayed on these levels:
 - Year
 - Month

9.6.5.1. Drilling in the Top elements chart




Figure 45: Top elements chart

- 1 You may drill down by clicking on a bar. In the display option you can specify which data should be displayed after drilling down one level:

- One bar:
Only the detailed data below the clicked bar is shown. The display of the other bars will be suppressed.
- All bars:
The detailed data of all bars will be shown.

② You may also drill down / up by directly selecting the required level of the IPC / CPC. This option is only available if “All bars” is selected.

③ The currently shown level is also displayed in the header line. In this example the “Class” level is shown.

④ Unless the top level “Section” is currently displayed, a button “Drill up” is available. Clicking on it goes one level up.

9.6.5.2. Drilling in the Timeline chart




Figure 46: Display options in Timeline chart:

① You can select whether you want to see a data point per year or each month of the year.

9.6.6. Change size or colour

The size of the bubbles can be changed in the Cross-reference chart. The colours can be changed for the Cross-reference as well as for the Patent indicator chart.




Figure 47: Display options form

The appearance of the display can be customised on the fly:

❶ The slider changes the size of the bubbles.

❷ You can specify how values are represented by the size of bubbles. If you select “bubble diameter proportional to data value” the distinction between larger and smaller data values will be slightly more enhanced than with the “bubble area proportional to data value” option.
Depending on what you want to express with the chart, one or the other option might be more suitable.

❸ You can change the colours of the chart

- "Standard" displays various shades of grey (EPO colours)
- "Heat" displays various colour shades depending on the value of the data point. Brilliant and light colours are used for larger numbers, greyish colours for smaller numbers.
- "Vivid": displays a fixed set of vivid colours

This option is not available for bubble charts when the date range comparison is used because these charts will always use blue bubbles for positive data values whereas the red bubbles indicate negative data values.

9.6.7. Follow links to access external databases

The bars of the Patent Indicator chart contain publication numbers. These are in fact links to the corresponding publications in Espacenet.

If you position the mouse over a link, the cursor will display a "hand" icon. Click on a link (see Figure 48) and you will be directed to several external links (e. g. to the bibliographic data of Espacenet).




Figure 48: Publication number as link




Figure 49: Pop-up window after clicking the link

9.7. Downloading, reloading and printing charts



Figure 50: The buttons to download reload and print in the window menu bar

❶ Download button:

You can select the download format (XML, CSV and PDF) by clicking on the small arrow on the right of the download button and the label of the download button will change accordingly. When you click on the download button, you are prompted to enter a directory and a file name.


The data to be downloaded contains:

- your SQL query which provided the data for the analysis
- the chart parameters you specified
- the data of the chart (JSON and CSV only)
- the graphical representation of the chart (PDF only)

Please note that this does not download the data on which the chart is based, but the chart data which is the result of aggregate functions.

To reload the chart data at a later stage, use JSON format for your download.

The button is equivalent to the link "Download" in the top toolbar, option "Statistics chart".



❷ Upload button:

To recreate charts that you have created earlier, you can upload a JSON file you have downloaded before (see ❶).

❸ Print button:

A PDF document, with the same content as the PDF file specified in ❶, is sent to the printer.

9.8. Sub-window "My statistics"




Figure 51: "My statistics" sub-window

This sub-window contains a list of statistical analysis jobs either waiting to be computed, currently being computed or which have already been computed.

The searches and their statistical analysis / charts are displayed in a tree-like structure. A statistical analysis / chart can have status such as: running, cancelled or error assigned.

A double click on any of the chart entries re-displays the chart.

Clicking on the  symbol deletes the respective entry.

10. User Preferences

User preferences can be set in the `Preferences` menu of the main menu bar. The user preferences are stored locally on your PC / notebook.




Figure 52: Main menu bar with the Preferences menu

Not all the menu items of the Preference menu are available in all windows, as they may be greyed out (deactivated).

10.1. General preferences




Figure 53: General preferences

This form contains various settings, including the choice of the font size used in the query sub-window, the "auto-complete" for table and attribute names in the query sub-window and an option to confirm certain messages.

Remember that some options are only relevant for other boolean PISE databases, and are not available for PATSTAT Online.

Note: Instead of changing the font size in the General preferences, you could also increase the font settings or the zoom factor in your browser (browser specific function).

10.2. Document content




Figure 54: Document content preferences

There are two tabs to select the fields you want to 'show' or 'hide' when displaying or downloading an application in the Application sub-window of the Application window.

You can also define the order of these fields by dragging and dropping an entry and such re-arranging the order.

11. Download

11.1. General procedure and download limits

This function can be accessed from the user interface top toolbar.





Figure 55: Download menu in the user interface top toolbar

The Download function is available from all windows. However, the type of data you can download is context specific and depends on the window that you are in. Data that cannot be downloaded is shown in the menu, but is greyed out and disabled.

Data to download	Window				Format	See section
	Search	Table	Application	Statistics		
Query history	×				PDF, CSV	11.2
Result table		×			CSV	11.3
PATSTAT subset	×	×	×	×	CSV, MS Access (.accdb file)	11.4
Result list			×		PDF, HTML, XLS, CSV, XML	11.5
Application			×		PDF, RTF, XML	11.6
Statistics chart*, **				×	PDF, CSV, JSON	9.7

* For these downloads, the Download manager is not used. The data can be downloaded immediately.

** In the Chart window, the download function can also be invoked by the icon



Note: Certain limits apply to the amount of data which can be downloaded:

- PATSTAT subset download:
Your result set must not contain more than 100 000 applications.
- Result table download:
Not more than 700 000 rows can be downloaded.(in the subscription version).
In a free trial version no more than 10 000 rows can be downloaded.
- Result list download:
Not more than 1 500 list items (applications) can be downloaded.


- Application download:
Not more than 1 500 applications can be downloaded.

The download procedure consists of 2 steps:

1. Preparation of download file

Select the menu item `Download | Prepare download` to open the form to specify the content and the format of your download. Depending on the type of download, you may specify other parameters.


After pressing “OK”; the download preparation process begins. After a few seconds, the following text pops up at the bottom-right corner of the window:



Depending on the size and the complexity of the download, the download may take a few seconds, minutes or in rare cases even longer.

You may use the Download Manager (menu `Download | Download Manager`) at any time to check the processing status of your request.

Once the data preparation process terminates; the data is ready for download and the following message pops up (the links in bold are active):



Note: You can initiate multiple download preparation processes which you could run in parallel. And even if you log off, the download process will continue to run.

2. File download

Select the menu item `Download | Download Manager` or click on “Download managers” in the pop-ups mentioned above to display the download manager. It lists all the requested downloads regardless of whether the download has been completed, is being currently executed or awaiting execution.

3

1

2




Figure 56: Download manager

- ❶ Click the icon to start the download process.
- ❷ Click the icon to delete an item from the list.
- ❸ Click the icon to stop the preparation process.

It is recommended to download the data within 72 hours on your local computer because it will be automatically removed after that time. On starting the download process, you will receive a zipped file. The file content will depend on the type of download requested.

In case the Status field contains an error indicator, you can move the mouse over the field to see more details.




Figure 57: Error of a download, shown in Download manager

If the error message reads “Internal download error”, please inform the EPO (see section 1.5 “Contact for help, feedback and reporting of errors”)

3. File download

On your local computer

- unzip the download file
- check the summary file (availability depends on the download type)
- import the data in your application and process it as needed

11.2. Download the query history

You can download your complete query history as PDF or CSV files for documentation or archiving purposes.

The 'Prepare download' dialog box has a title bar with a close button. It contains three sections: 'What:' with a dropdown menu set to 'Query history'; 'Format:' with radio buttons for PDF, HTML, CSV (selected), and XML; and 'Range:' with radio buttons for Selection (selected), All, and From: (with empty input fields) to: (with empty input fields). At the bottom are 'OK' and 'Cancel' buttons.

Figure 58 Download "Query history" form

You can select the queries to be downloaded by:

- Selecting 1 or more rows
- Downloading all rows
- Specifying a range of line numbers, such as 1 – 5 (but *not* by specifying a Query ID, like \$22-\$26)

11.3. Download a result table

You can download the result of your query as a zipped CSV file and process it with Excel or your preferred tool. If your result contains NULL values, they will be represented by empty strings in the CSV file.

The 'Prepare download' dialog box has a title bar with a close button. It contains three sections: 'What:' with a dropdown menu set to 'Result table'; 'Format:' with radio buttons for PDF, HTML, CSV (selected), and XML; and 'Range:' with radio buttons for Selection, All, and From: (with empty input fields) to: (with empty input fields). At the bottom are 'OK' and 'Cancel' buttons.

Figure 59: Download "Result table" form

Select the queries to be downloaded by:

- Selecting 1 or more rows
- Downloading all rows
- Specifying a range of line numbers

Note: The result table can only be downloaded if it contains not more than 700 000 rows.

11.4. Download a subset of PATSTAT

This powerful function allows you to download multiple tables in a single request as the intra-table consistency of the data downloaded is automatically preserved. This

means that you can define a flexible consistent PATSTAT subset database that can be downloaded for further local processing on your PC.

11.4.1. Requesting a download

Figure 60: Download a subset of PATSTAT

❶ For each download, you can include some text of up to 250 characters. This description will be included in the summary file of the download.

❷ The data to be downloaded will be zipped into a single file. You can choose from one of these download formats:

- PATSTAT bulk data format (.csv)
The same structure as that of the full PATSTAT database delivered as bulk data twice a year. Every table will be packed as one .csv file
- MS Access
Data will be packed as an .accdb file for MS Access 2007 / 2010. Please note the MS Access restriction limits the .accdb file to the maximum size of 2 GB.

❸ This subset download function returns only the data related to the patent applications retrieved by your previous query. In PATSTAT, patent applications are identified by the attributes APPLN_ID or ID. For downloading, these attributes serve as *application seeds* because starting from them, all other information regarding the retrieved patent application can be found.

In special cases when your previous query contains multiple applications seeds, i.e. APPLN_ID and(!) ID, you have to choose which of the two applications seeds should be used to create the subset download.

If your previous query contains no application seed (neither APPLN_ID nor ID), then no subset download can be executed.

④ Select the tables you wish to download. Only tables which are part of your subscription will be displayed.

Downloaded data sets can be huge, so limit your selection to only the tables that you require for your specific purpose.

Because of dependencies between tables, in some cases specific tables are recommended to be included in the download set. This download preparation form presents the tables in a hierarchical structure to automatically take care of these dependencies.

Due to its data size table TLS203_APPLN_ABSTR cannot be selected for download.

⑤ By ticking this box, you expand your original result set. Applications are added to make all families complete. You can select the type of family (Simple family – also called DOCDB family; INPADOC family – also called extended family).

This feature is useful if you need to perform analyses based on families.

Please bear in mind that using this feature may enlarge the size of the data download considerably - so use it sensibly.

⑥ This (optional) citation expansion is executed after an (optional) family expansion (see ⑤). If this box is ticked, additional applications are included into the download set and are related to:

- direct citations of the applications to be downloaded or
- those directly cited by the applications to be downloaded

This feature is useful if you need to perform analyses on citations.

Remember that using this feature may enlarge the size of the data download considerably - so use it sensibly.

11.4.2. Using the download

You will always receive a single zip-file. However, the content of this file will depend on whether you requested the CSV-format (PATSTAT's standard format) or the MS Access format.

Name	Type	Compressed size	Password p...	Size	Ratio	Date modified
summary.txt	TXT File	1 KB	No	1 KB	49%	22-12-2015 09:28
tls200_appln_origin.csv	Microsoft Excel Comma S...	81 KB	No	611 KB	87%	22-12-2015 09:28
tls201_appln.csv	Microsoft Excel Comma S...	1.057 KB	No	4.178 KB	75%	22-12-2015 09:28
tls204_appln_prior.csv	Microsoft Excel Comma S...	211 KB	No	682 KB	70%	22-12-2015 09:28
tls206_person.csv	Microsoft Excel Comma S...	2.443 KB	No	9.907 KB	76%	22-12-2015 09:28
tls207_pers_appln.csv	Microsoft Excel Comma S...	593 KB	No	2.213 KB	74%	22-12-2015 09:28
tls209_appln_ipc.csv	Microsoft Excel Comma S...	435 KB	No	3.537 KB	88%	22-12-2015 09:28

Figure 61: Content of the zip file when downloading files in PATSTAT's CSV format

Name	Type	Compressed size	Password p...	Size	Ratio	Date modified
patstatsubset.accdb	Microsoft Access Database	170.911 KB	No	862.016 KB	81%	22-12-2015 08:44
summary.txt	TXT File	1 KB	No	1 KB	47%	22-12-2015 08:44

Figure 62: Content of the zip file when downloading files in MS Access format

- File `summary.txt`

```

Untitled - Notepad
File Edit Format View Help
Date: 2015/12/22 - 08:44
Query: select * from tls201_appln where appln_auth = 'AT' and ipr_type = 'PI' a
Exported tables:
    tls200_appln_origin - 794 839 rows
    tls201_appln - 794 839 rows
    tls204_appln_prior - 685 291 rows
    tls206_person - 1 531 655 rows
    tls207_pers_appln - 2 733 466 rows
    tls209_appln_ipc - 2 980 889 rows
Number of applications which match the query: 28 407 rows
Number of applications included by family expansion: 187 437 rows
Number of applications included by citation expansion: 578 995 rows

```

As shown in the image above, the (`summary.txt`) file is always included and contains:

- your short description, if any
 - the date and time of the download
 - your query, which defined the original result set
 - for every table you selected: its name and the number of rows
 - the number of applications in the original result set
 - the number of additional applications included by family expansion
 - the number of additional applications included by citation expansion
- A table `tls200_appln_origin` is included if a family expansion and/or a citation expansion has been applied. This file is either packaged as a file `tls200_appln_origin.csv` or included into the MS Access file.

```

054941032,"Family
054944149,"Original"
054951745,"Family "
054952438,"Family "
054953389,"Family "
054981040,"Citation"
054981085,"Citation"
054981627,"Family "

```

Figure 63: Excerpt of the file `tls200_appln_origin.txt`

It is a two column table indicating for each application in the downloaded set whether

- the application was in the **original** result set (i.e. retrieved by the query the user executed prior to the download)
 - the application has been added because **family** expansion was requested or
 - the application has been added because **citation** expansion was requested
- The tables selected by the user.
These tables are either packaged in a CSV file each, or are all included in an .accdb file which can be used directly by MS Access.

11.5. Download a result list

You can initiate the preparation of a download containing all or only parts of the result list using this form:




Figure 64: Prepare download for the result list

You can select the queries to be downloaded:

- Select 1 or more rows
- Download all rows
- Specify a range of line numbers

When the download format is PDF, HTML or XLS, then a header can be requested to add the information on the PATSTAT edition currently in use, the query and the number of applications the query retrieved.

11.6. Download an application

You can initiate the preparation of a download containing all or only some of the applications using this form:

Prepare download

What: Application ▼

Format: ☐ PDF ☐ RTF ☒ XML
☐ Concatenate
☐ Include a header

Range: ☒ Selection
☐ All
☐ From: to:

OK Cancel

Figure 65: Prepare download for applications

You can select the queries to be downloaded:

- Select 1 or more rows
- Download all rows
- Specify a range of line numbers

When opting for the PDF download format, a header can be requested. This header will give information on the PATSTAT edition currently in use, the query and the number of applications the query retrieved.

When opting for the PDF download format, you can retrieve all data in a **single** PDF file by selecting the “Concatenate” option to avoid downloading separate PDF files for each application.

12. Print

This function can be accessed from the user interface top toolbar.





Figure 66: Print button in the user interface top toolbar

The Print function is available from all windows. However, the type of data you can print is context specific and depends on the window that you are in.

Context	Data to print	Comment
Search window	query history	Print all or print a range of entries in the query history
Table window	--	not available
Application window	result list	Print current, all, selected or a range of entries in the result list
	Application	Print current application
Chart window*	chart	Print current chart

* In the Chart window, the print function can also be invoked by the  icon. See also Section 9.7 .

13. Help

This function can be accessed from the user interface top toolbar.




Figure 67: Help menu in the user interface top toolbar

- **Database help:**
A link to the EPO website where you will find a short description of the database. Additional information is available in the User Manual, the Data Catalog and several further documents.
- **About...:**
Clicking on this line will display the version number of PATSTAT Online

14. Annex I: References

[1] "PATSTAT's Data Catalog", and the "EP Register for PATSTAT Data Catalog" are available at the PATSTAT page

<https://www.epo.org/patstat>

[2] This user manual, the Data Catalog, sample queries, FAQs and more helpful information as well as request for test access are available at

<https://www.epo.org/patstat>

[3] PATSTAT related training can be found at

<https://www.epo.org/en/learning>

15. Annex II: Glossary

CPC	Cooperative Patent Classification; An extension of IPC and which is used by the EPO, the US office and some other offices. It replaced ECLA from 2013 onwards.
CSV	Comma separated values: A file with CSV format can be opened in any text editor and can be loaded into MS Excel, too
DOCDB	EPO's master database for worldwide bibliographic data
DOCDB family	see entry "family"
EPO	European Patent Office
family	https://www.epo.org/searching-for-patents/helpful-resources/first-time-here/patent-families.html
INPADOC family	see entry "family"
INPADOC legal event	Events during the lifetime of a patent, collected by the EPO on a worldwide scale
IPC	International Patent Classification
PISE	Patent Information Services for Experts: The search platform of the EPO which hosts a variety of databases https://data.epo.org/expert-services/
SQL	Structured Query Language: The de facto standard query language for relational databases
UI	User Interface
WIPO	World Intellectual Property Organization

16. Annex III: Theoretical foundation of Patent Indicator

Harhoff, D., Scherer, F. M., Vogel, K., 2002. Citations, family size, opposition and the value of patent rights. *Research Policy* 32 (2003), 1343–1363.

Ernst H., Omland, N., 2010. The Patent Asset Index - A new approach to benchmark patent portfolios. *World Patent Information* 33 (2011), 34-41

Lanjouw, J. O., Schankermann, M., 2002. Research Productivity and Patent Quality: Measurement with Multiple Indicators. LSE STICERD Research Paper No. EI 32 (2002). 1-47

van Zeebroeck, N., 2009. The puzzle of patent value indicators. CEB Working Paper N° 07/023. April 2009

Webb, C., Dernis, H., Harhoff, D., Hoisl, K, 2005. ANALYSING EUROPEAN AND INTERNATIONAL PATENT CITATIONS: A SET OF EPO PATENT DATABASE BUILDING BLOCKS. *DSTI/DOC(2005)9*. 1-30

Bosworth, D. L., 2004. THE ANCESTRAL TREE OF IPC C12S: A PRELIMINARY EXPLORATION BASED ON A SAMPLE OF TWO. Paper to be presented to the Oxford Intellectual Property Research Centre Seminar Series, 27th January 2004. 1-36

Michel, J., Bettels, B., 2001. Patent citation analysis: A closer look at the basic input data from patent search reports. Jointly published by Kluwer Academic Publishers, Dordrecht, and Akadémiai Kiadó, Budapest *Scientometric* Vol. 51, No. 1 (2001) 185–201

van Pottelsberghe de la Potterie, B., van Zeebroeck, N., 2008. Filing strategies and patent value. March 2008. 1-45

17. Annex IV: Name types

- Original Name:
This is the name as provided by the patent offices.
- DOCDB standardized name:
Name variations of the same name are standardized. This is done manually by the EPO in the framework of the DOCDB database maintenance.
- PATSTAT Standardized Name (PSN):
This is the result of another approach to name-standardization (<https://www.ecoom.be/en>). It is done in an automated way with some additional manual refinements.
- OECD HAN Harmonized Applicant Name:
These names have been taken from the OECD HAN database (cf. <https://www.oecd.org/sti/innovationinsciencetechnologyandindustry/oecdpatentdatabases.htm>).
Please note that the OECD HAN database is provided for research and analytical work. When publishing the results of your analysis, make sure it is quoted as: "OECD, HAN database, <Month, Year>".